

# MISP Objects

# MISP Objects

Introduction	1
Funding and Support	2
MISP objects	3
ail-leak	3
android-permission	4
annotation	6
asn	7
av-signature	8
bank-account	9
cap-alert	11
cap-info	14
cap-resource	17
coin-address	18
cookie	19
course-of-action	20
cowrie	21
credential	23
credit-card	24
ddos	25
diameter-attack	26
domain-ip	27
elf	27
elf-section	30
email	32
fail2ban	34
file	34
geolocation	36
gtp-attack	37
http-request	38
ip-port	40
ja3	40
legal-entity	41
macho	42
macho-section	42
microblog	43
mutex	44
netflow	45
network-connection	46

network-socket	47
passive-dns	51
paste	52
pe	53
pe-section	55
person	56
phone	58
process	60
r2graphity	61
regex	63
registry-key	64
report	66
rtir	66
sandbox-report	67
sb-signature	68
ss7-attack	68
stix2-pattern	71
suricata	71
target-system	72
timecode	72
timesketch-timeline	73
timestamp	73
tor-node	74
transaction	75
url	77
victim	78
virustotal-report	80
vulnerability	80
whois	82
x509	83
yabin	84
yara	85
Relationships	85

# Introduction



The MISP threat sharing platform is a free and open source software helping information sharing of threat intelligence including cyber security indicators, financial fraud or counter-terrorism information. The MISP project includes multiple sub-projects to support the operational requirements of analysts and improve the overall quality of information shared.

MISP objects are used in MISP (starting from version 2.4.80) system and can be used by other information sharing tool. MISP objects are in addition to MISP attributes to allow advanced combinations of attributes. The creation of these objects and their associated attributes are based on real cyber security use-cases and existing practices in information sharing. The objects are just shared like any other attributes in MISP even if the other MISP instances don't have the template of the object. The following document is generated from the machine-readable JSON describing the [MISP objects](#).

# Funding and Support

The MISP project is financially and resource supported by [CIRCL Computer Incident Response Center Luxembourg](#).



A CEF (Connecting Europe Facility) funding under CEF-TC-2016-3 - Cyber Security has been granted from 1st September 2017 until 31th August 2019 as **Improving MISP as building blocks for next-generation information sharing**.



**Co-financed by the European Union**  
Connecting Europe Facility

If you are interested to co-fund projects around MISP, feel free to get in touch with us.

# MISP objects

## ail-leak

An information leak as defined by the AIL Analysis Information Leak framework..



ail-leak is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
origin	text	The link where the leak is (or was) accessible at first-seen.	—
first-seen	datetime	When the leak has been accessible or seen for the first time.	✓
sensor	text	The AIL sensor uuid where the leak was processed and analysed.	—
last-seen	datetime	When the leak has been accessible or seen for the last time.	✓
raw-data	attachment	Raw data as received by the AIL sensor compressed and encoded in Base64.	✓
duplicate	text	Duplicate of the existing leaks.	—
text	text	A description of the leak which could include the potential victim(s) or description of the leak.	✓
duplicate_number	counter	Number of known duplicates.	—

Object attribute	MISP attribute type	Description	Disable correlation
type	text	Type of information leak as discovered and classified by an AIL module. ['Credential', 'CreditCards', 'Mail', 'Onion', 'Phone', 'Keys']	—
original-date	datetime	When the information available in the leak was created. It's usually before the first-seen.	✓

## android-permission

A set of android permissions - one or more permission(s) which can be linked to other objects (e.g. malware, app)..



android-permission is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
comment	comment	Comment about the set of android permission(s)	—

Object attribute	MISP attribute type	Description	Disable correlation
permission	text	Android permission ['ACCESS_CHECKIN_PROPERTIES', 'ACCESS_COARSE_LOCATION', 'ACCESS_FINE_LOCATION', 'ACCESS_LOCATION_EXTRA_COMMANDS', 'ACCESS_NETWORK_STATE', 'ACCESS_NOTIFICATION_POLICY', 'ACCESS_WIFI_STATE', 'ACCOUNT_MANAGER', 'ADD_VOICEMAIL', 'ANSWER_PHONE_CALLS', 'BATTERY_STATS', 'BIND_ACCESSIBILITY_SERVICE', 'BIND_APPWIDGET', 'BIND_AUTOFILL_SERVICE', 'BIND_CARRIER_MESSAGING_SERVICE', 'BIND_CHOOSER_TARGET_SERVICE', 'BIND_CONDITION_PROVIDER_SERVICE', 'BIND_DEVICE_ADMIN', 'BIND_DREAM_SERVICE', 'BIND_INCALL_SERVICE', 'BIND_INPUT_METHOD', ', 'BIND_MIDI_DEVICE_SERVICE', 'BIND_NFC_SERVICE', 'BIND_NOTIFICATION_LISTENER_SERVICE', 'BIND_PRINT_SERVICE', 'BIND_QUICK_SETTINGS_TILE', 'BIND_REMOTEVIEWS', 'BIND_SCREENING_SERVICE', 'BIND_TELECOM_CONN	-



# annotation

An annotation object allowing analysts to add annotations, comments, executive summary to a MISP event, objects or attributes..



annotation is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

'ACTION\_SERVICE',  
'BIND\_TEXT\_SERVICE',  
'BIND\_TV\_INPUT',  
'BIND\_VISUAL\_VOICEM  
ALL\_SERVICE',  
'BIND\_VOICE\_INTERAC  
TION',

Object attribute	MISP attribute type	Description	Disable correlation
creation-date	datetime	Initial creation of the annotation	—
modification-date	datetime	Last update of the annotation	—
format	text	Format of the annotation ['text', 'markdown', 'asciidoc', 'MultiMarkdown', 'GFM', 'pandoc', 'Fountain', 'CommonWork', 'kramdown-rfc2629', 'rfc7328', 'Extra']	✓
text	text	Raw text of the annotation	—
type	text	Type of the annotation ['Annotation', 'Executive Summary', 'Introduction', 'Conclusion', 'Disclaimer', 'Keywords', 'Acknowledgement', 'Other', 'Copyright', 'Authors', 'Logo']	✓
ref	link	Reference(s) to the annotation	—

'DIAGNOSTIC',  
'DISABLE\_KEYGUARD',  
'DUMP',  
'EXPAND\_STATUS\_BAR',  
'FACTORY\_TEST',

# asn

Autonomous system object describing an autonomous system which can include one or more network operators management an entity (e.g. ISP) along with their routing policy, routing prefixes or alike..



asn is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
subnet-announced	ip-src	Subnet announced	—
mp-export	text	This attribute performs the same function as the export attribute above. The difference is that mp-export allows both IPv4 and IPv6 address families to be specified. The export is described in RFC 4012 – Routing Policy Specification Language next generation (RPSLNg), section 4.5. format	—
asn	AS	Autonomous System Number	—
last-seen	datetime	Last time the ASN was seen	✓
first-seen	datetime	First time the ASN was seen	✓
export	text	The outbound routing policy of the AS in RFC 2622 – Routing Policy Specification Language (RPSL) format	—

Object attribute	MISP attribute type	Description	Disable correlation
mp-import	text	The inbound IPv4 or IPv6 routing policy of the AS in RFC 4012 – Routing Policy Specification Language next generation (RPSLng), section 4.5. format	–
description	text	Description of the autonomous system	–
country	text	Country code of the main location of the autonomous system	–
import	text	The inbound IPv4 routing policy of the AS in RFC 2622 – Routing Policy Specification Language (RPSL) format	–

## av-signature

Antivirus detection signature.



av-signature is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation
datetime	datetime	Datetime	✓
text	text	Free text value to attach to the file	✓
software	text	Name of antivirus software	✓
signature	text	Name of detection signature	–

'MODIFY\_AUDIO\_SETTINGS',  
'MODIFY\_PHONE\_STATE',  
'MOUNT\_FORMAT\_FILESYSTEMS',  
'MOUNT\_FORMAT\_FILESYSTEMS',  
'PACKAGE\_USAGE\_STATS',  
'READ\_PHONE\_NUMBERS',  
'READ\_PHONE\_STATE',

# bank-account

An object describing bank account information based on account description from goAML 4.0..



bank-account is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
currency-code	text	Currency of the account. ['USD', 'EUR']	✓
report-code	text	Report code of the bank account. ['CTR Cash Transaction Report', 'STR Suspicious Transaction Report', 'EFT Electronic Funds Transfer', 'IFT International Funds Transfer', 'TFR Terror Financing Report', 'BCR Border Cash Report', 'UTR Unusual Transaction Report', 'AIF Additional Information File – Can be used for example to get full disclosure of transactions of an account for a period of time without reporting it as a CTR.', 'IRI Incoming Request for Information – International', 'ORI Outgoing Request for Information – International', 'IRD Incoming Request for Information – Domestic', 'ORD Outgoing Request for Information – Domestic']	✓

Object attribute	MISP attribute type	Description	Disable correlation
institution-code	text	Institution code of the bank.	✓
beneficiary	text	Final beneficiary of the bank account.	✓
iban	iban	IBAN of the bank account.	—
beneficiary-comment	text	Comment about the final beneficiary.	✓
balance	text	The balance of the account after the suspicious transaction was processed.	✓
aba-rtn	aba-rtn	ABA routing transit number	—
institution-name	text	Name of the bank or financial organisation.	✓
comments	text	Comments about the bank account.	✓
account-name	text	A field to freely describe the bank account details.	—
non-banking-institution	boolean	A flag to define if this account belong to a non-banking organisation. If set to true, it's a non-banking organisation.	✓
account	bank-account-nr	Account number	—
text	text	A description of the bank account.	✓

SYSTEM\_ALERT\_WINDOW', 'TRANSMIT\_IR', 'UNINSTALL\_SHORTCUT', 'UPDATE\_DEVICE\_STAT

Object attribute	MISP attribute type	Description	Disable correlation
status-code	text	Account status at the time of the transaction processed. ['A - Active', 'B - Inactive', 'C - Dormant']	✓
closed	datetime	When the account was closed.	✓
swift	bic	SWIFT or BIC as defined in ISO 9362.	✓
client-number	text	Client number as seen by the bank.	—
personal-account-type	text	Account type. ['A - Business', 'B - Personal Current', 'C - Savings', 'D - Trust Account', 'E - Trading Account', 'O - Other']	✓
date-balance	datetime	When the balance was reported.	✓
opened	datetime	When the account was opened.	✓
branch	text	Branch code or name	✓

## cap-alert

Common Alerting Protocol Version (CAP) alert object.



cap-alert is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
code	text	The code denoting the special handling of the alert message.	✓

<b>Object attribute</b>	<b>MISP attribute type</b>	<b>Description</b>	<b>Disable correlation</b>
msgType	text	The code denoting the nature of the alert message. ['Alert', 'Update', 'Cancel', 'Ack', 'Error']	✓
scope	text	The code denoting the intended distribution of the alert message. ['Public', 'Restricted', 'Private']	✓
source	text	The text identifying the source of the alert message. The particular source of this alert; e.g., an operator or a specific device.	✓
identifier	text	The identifier of the alert message in a number or string uniquely identifying this message, assigned by the sender.	✓
references	text	The group listing identifying earlier message(s) referenced by the alert message. (1) The extended message identifier(s) (in the form sender,identifier,sent) of an earlier CAP message or messages referenced by this one. (2) If multiple messages are referenced, they SHALL be separated by whitespace.	✓

Object attribute	MISP attribute type	Description	Disable correlation
incident	text	The group listing naming the referent incident(s) of the alert message. (1) Used to collate multiple messages referring to different aspects of the same incident. (2) If multiple incident identifiers are referenced, they SHALL be separated by whitespace. Incident names including whitespace SHALL be surrounded by double-quotes.	✓
status	text	The code denoting the appropriate handling of the alert message. ['Actual', 'Exercise', 'System', 'Test', 'Draft']	—
sender	text	The identifier of the sender of the alert message which identifies the originator of this alert. Guaranteed by assigner to be unique globally; e.g., may be based on an Internet domain name.	✓
sent	datetime	The time and date of the origination of the alert message.	✓
note	text	The text describing the purpose or significance of the alert message.	✓



Object attribute	MISP attribute type	Description	Disable correlation
restriction	text	The text describing the rule for limiting distribution of the restricted alert message.	✓
addresses	text	The group listing of intended recipients of the alert message. (1) Required when <scope> is “Private”, optional when <scope> is “Public” or “Restricted”. (2) Each recipient SHALL be identified by an identifier or an address. (3) Multiple space-delimited addresses MAY be included. Addresses including whitespace MUST be enclosed in double-quotes.	✓

## cap-info

Common Alerting Protocol Version (CAP) info object.



cap-info is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
expires	datetime	The expiry time of the information of the alert message.	✓
audience	text	The text describing the intended audience of the alert message.	✓

<b>Object attribute</b>	<b>MISP attribute type</b>	<b>Description</b>	<b>Disable correlation</b>
parameter	text	A system-specific additional parameter associated with the alert message.	✓
headline	text	The text headline of the alert message.	✓
contact	text	The text describing the contact for follow-up and confirmation of the alert message.	✓
event	text	The text denoting the type of the subject event of the alert message.	✓
certainty	text	The code denoting the certainty of the subject event of the alert message. For backward compatibility with CAP 1.0, the deprecated value of “Very Likely” SHOULD be treated as equivalent to “Likely”. ['Likely', 'Possible', 'Unlikely', 'Unknown']	✓
effective	datetime	The effective time of the information of the alert message.	✓
instruction	text	The text describing the recommended action to be taken by recipients of the alert message.	✓

<b>Object attribute</b>	<b>MISP attribute type</b>	<b>Description</b>	<b>Disable correlation</b>
severity	text	The code denoting the severity of the subject event of the alert message. ['Extreme', 'Severe', 'Moderate', 'Minor', 'Unknown']	✓
language	text	The code denoting the language of the info sub-element of the alert message.	✓
category	text	The code denoting the category of the subject event of the alert message. ['Geo', 'Met', 'Safety', 'Security', 'Rescue', 'Fire', 'Health', 'Env', 'Transport', 'Infra', 'CBRNE', 'Other']	✓
senderName	text	The text naming the originator of the alert message.	✓
description	text	The text describing the subject event of the alert message.	✓
web	link	The identifier of the hyperlink associating additional information with the alert message.	✓
urgency	text	The code denoting the urgency of the subject event of the alert message. ['Immediate', 'Expected', 'Future', 'Past', 'Unknown']	✓

Object attribute	MISP attribute type	Description	Disable correlation
onset	datetime	The expected time of the beginning of the subject event of the alert message.	✓
eventCode	text	A system-specific code identifying the event type of the alert message.	✓
responseType	text	The code denoting the type of action recommended for the target audience. ['Shelter', 'Evacuate', 'Prepare', 'Execute', 'Avoid', 'Monitor', 'Assess', 'AllClear', 'None']	✓

## cap-resource

Common Alerting Protocol Version (CAP) resource object.



cap-resource is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
derefUri	attachment	The base-64 encoded data content of the resource file.	✓
uri	link	The identifier of the hyperlink for the resource file.	—
size	text	The integer indicating the size of the resource file.	✓

Object attribute	MISP attribute type	Description	Disable correlation
digest	sha1	The code representing the digital digest (“hash”) computed from the resource file (OPTIONAL).	—
mimeType	mime-type	The identifier of the MIME content type and sub-type describing the resource file.	✓
resourceDesc	text	The text describing the type and content of the resource file.	✓

## coin-address

An address used in a cryptocurrency.



coin-address is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
first-seen	datetime	First time this payment destination address has been seen	✓
text	text	Free text value	✓
address	btc	Address used as a payment destination in a cryptocurrency	—

Object attribute	MISP attribute type	Description	Disable correlation
symbol	text	The (uppercase) symbol of the cryptocurrency used. Symbol should be from <a href="https://coinmarketcap.com/all/views/all/">https://coinmarketcap.com/all/views/all/</a> ['BTC', 'ETH', 'BCH', 'XRP', 'MIOTA', 'DASH', 'BTG', 'LTC', 'ADA', 'XMR', 'ETC', 'NEO', 'NEM', 'EOS', 'XLM', 'BCC', 'LSK', 'OMG', 'QTUM', 'ZEC', 'USDT', 'HSR', 'STRAT', 'WAVES', 'PPT']	✓
last-seen	datetime	Last time this payment destination address has been seen	✓

## cookie

An HTTP cookie (web cookie, browser cookie) is a small piece of data that a server sends to the user's web browser. The browser may store it and send it back with the next request to the same server. Typically, it's used to tell if two requests came from the same browser — keeping a user logged-in, for example. It remembers stateful information for the stateless HTTP protocol. (as defined by the Mozilla foundation..



cookie is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
cookie-value	text	Value of the cookie (if splitted)	—
text	text	A description of the cookie.	✓

Object attribute	MISP attribute type	Description	Disable correlation
type	text	Type of cookie and how it's used in this specific object. ['Session management', 'Personalization', 'Tracking', 'Exfiltration', 'Malicious Payload', 'Beaconing']	—
cookie-name	text	Name of the cookie (if splitted)	—
cookie	cookie	Full cookie	—

## course-of-action

An object describing a specific measure taken to prevent or respond to an attack..



course-of-action is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
impact	text	The estimated impact of applying the course of action. ['High', 'Medium', 'Low', 'None', 'Unknown']	✓
name	text	The name used to identify the course of action.	✓
cost	text	The estimated cost of applying the course of action. ['High', 'Medium', 'Low', 'None', 'Unknown']	✓
objective	text	The objective of the course of action.	✓

Object attribute	MISP attribute type	Description	Disable correlation
type	text	The type of the course of action. ['Perimeter Blocking', 'Internal Blocking', 'Redirection', 'Redirection (Honey Pot)', 'Hardening', 'Patching', 'Eradication', 'Rebuilding', 'Training', 'Monitoring', 'Physical Access Restrictions', 'Logical Access Restrictions', 'Public Disclosure', 'Diplomatic Actions', 'Policy Actions', 'Other']	✓
stage	text	The stage of the threat management lifecycle that the course of action is applicable to. ['Remedy', 'Response']	✓
efficacy	text	The estimated efficacy of applying the course of action. ['High', 'Medium', 'Low', 'None', 'Unknown']	✓
description	text	A description of the course of action.	✓

## cowrie

Cowrie honeypot object template.



cowrie is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
src_ip	ip-src	Source IP address of the session	—



Object attribute	MISP attribute type	Description	Disable correlation
sensor	text	Cowrie sensor name	✓
src_port	port	Source port of the session	✓
password	text	Password	-
eventid	text	Eventid of the session in the cowrie honeypot	✓
dst_port	port	Destination port of the session	✓
keyAlgs	text	SSH public-key algorithm supported in the session	✓
encCS	text	SSH symmetric encryption algorithm supported in the session	✓
dst_ip	ip-dst	Destination IP address of the session	✓
system	text	System origin in cowrie honeypot	✓
session	text	Session id	-
compCS	text	SSH compression algorithm supported in the session	✓
username	text	Username related to the password(s)	-
input	text	Input of the session	-
protocol	text	Protocol used in the cowrie honeypot	✓

Object attribute	MISP attribute type	Description	Disable correlation
message	text	Message of the cowrie honeypot	✓
timestamp	datetime	When the event happened	✓
macCS	text	SSH MAC supported in the session	✓
isError	text	isError	✓

## credential

Credential describes one or more credential(s) including password(s), api key(s) or decryption key(s)..



credential is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
origin	text	Origin of the credential(s) ['bruteforce-scanning', 'malware-analysis', 'memory-analysis', 'network-analysis', 'leak', 'unknown']	—
username	text	Username related to the password(s)	—
password	text	Password	—
notification	text	Mention of any notification(s) towards the potential owner(s) of the credential(s) ['victim-notified', 'service-notified', 'none']	—

Object attribute	MISP attribute type	Description	Disable correlation
format	text	Format of the password(s) ['clear-text', 'hashed', 'encrypted', 'unknown']	—
text	text	A description of the credential(s)	✓
type	text	Type of password(s) ['password', 'api-key', 'encryption-key', 'unknown']	—

## credit-card

A payment card like credit card, debit card or any similar cards which can be used for financial transactions..



credit-card is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
version	text	Version of the card.	—
issued	datetime	Initial date of validity or issued date.	—
cc-number	cc-number	credit-card number as encoded on the card.	—
name	text	Name of the card owner.	—
expiration	datetime	Maximum date of validity	—
comment	comment	A description of the card.	—

Object attribute	MISP attribute type	Description	Disable correlation
card-security-code	text	Card security code (CSC, CVD, CVV, CVC and SPC) as embossed or printed on the card.	—

## ddos

DDoS object describes a current DDoS activity from a specific or/and to a specific target. Type of DDoS can be attached to the object as a taxonomy.



ddos is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
protocol	text	Protocol used for the attack ['TCP', 'UDP', 'ICMP', 'IP']	—
domain-dst	domain	Destination domain (victim)	—
last-seen	datetime	End of the attack	✓
src-port	port	Port originating the attack	—
ip-src	ip-src	IP address originating the attack	—
total-bps	counter	Bits per second	—
first-seen	datetime	Beginning of the attack	✓
text	text	Description of the DDoS	✓
dst-port	port	Destination port of the attack	—
total-pps	counter	Packets per second	—
ip-dst	ip-dst	Destination IP (victim)	—

# diameter-attack

Attack as seen on diameter authentication against a GSM, UMTS or LTE network.



diameter-attack is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
Username	text	Username (in this case, usually the IMSI).	—
Origin-Realm	text	Origin-Realm.	—
IdrFlags	text	IDR-Flags.	✓
text	text	A description of the attack seen.	✓
CmdCode	text	A decimal representation of the diameter Command Code.	✓
category	text	Category. ['Cat0', 'Cat1', 'Cat2', 'Cat3', 'CatSMS']	✓
first-seen	datetime	When the attack has been seen for the first time.	✓
Origin-Host	text	Origin-Host.	—
Destination-Realm	text	Destination-Realm.	—
ApplicationId	text	Application-ID is used to identify for which Diameter application the message is applicable. Application-ID is a decimal representation.	—
SessionId	text	Session-ID.	—

Object attribute	MISP attribute type	Description	Disable correlation
Destination-Host	text	Destination-Host.	—

## domain-ip

A domain and IP address seen as a tuple in a specific time frame..



domain-ip is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
first-seen	datetime	First time the tuple has been seen	✓
text	text	A description of the tuple	✓
domain	domain	Domain name	—
last-seen	datetime	Last time the tuple has been seen	✓
ip	ip-dst	IP Address	—

## elf

Object describing a Executable and Linkable Format.



elf is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
entrypoint-address	text	Address of the entry point	✓
number-sections	counter	Number of sections	✓
text	text	Free text value to attach to the ELF	✓

Object attribute	MISP attribute type	Description	Disable correlation
os_abi	text	Header operating system application binary interface (ABI) ['AIX', 'ARM', 'AROS', 'C6000_ELFABI', 'C6000_LINUX', 'CLOUDABI', 'FENIXOS', 'FREEBSD', 'GNU', 'HPUX', 'HURD', 'IRIX', 'MODESTO', 'NETBSD', 'NSK', 'OPENBSD', 'OPENVMS', 'SOLARIS', 'STANDALONE', 'SYSTEMV', 'TRU64']	✓
type	text	Type of ELF ['CORE', 'DYNAMIC', 'EXECUTABLE', 'HIPROC', 'LOPROC', 'NONE', 'RELOCATABLE']	-

Object attribute	MISP attribute type	Description	Disable correlation
arch	text	Architecture of the ELF file ['None', 'M32', 'SPARC', 'i386', 'ARCH_68K', 'ARCH_88K', 'IAMCU', 'ARCH_860', 'MIPS', 'S370', 'MIPS_RS3_LE', 'PARISC', 'VPP500', 'SPARC32PLUS', 'ARCH_960', 'PPC', 'PPC64', 'S390', 'SPU', 'V800', 'FR20', 'RH32', 'RCE', 'ARM', 'ALPHA', 'SH', 'SPARCV9', 'TRICORE', 'ARC', 'H8_300', 'H8_300H', 'H8S', 'H8_500', 'IA_64', 'MIPS_X', 'COLDFIRE', 'ARCH_68HC12', 'MMA', 'PCP', 'NCPU', 'NDR1', 'STARCORE', 'ME16', 'ST100', 'TINYJ', 'x86_64', 'PDSP', 'PDP10', 'PDP11', 'FX66', 'ST9PLUS', 'ST7', 'ARCH_68HC16', 'ARCH_68HC11', 'ARCH_68HC08', 'ARCH_68HC05', 'SVX', 'ST19', 'VAX', 'CRIS', 'JAVELIN', 'FIREPATH', 'ZSP', 'MMIX', 'HUANY', 'PRISM', 'AVR', 'FR30', 'D10V', 'D30V', 'V850', 'M32R', 'MN10300', 'MN10200', 'PJ', 'OPENRISC', 'ARC_COMPACT', 'XTENSA', 'VIDEOCORE', 'TMM_GPP', 'NS32K', 'TPC', 'SNP1K', 'ST200', 'IP2K', 'MAX', 'CR', 'F2MC16', 'MSP430', 'BLACKFIN', 'SE_C33', 'SEP', 'ARCA', 'UNICORE', 'EXCESS', 'DXP', 'ALTERA_NIOS2', 'CRX', 'XGATE', 'C166',	✓



# elf-section

Object describing a section of an Executable and Linkable Format



elf-section is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

'M16C', 'DSPIC30F', 'CE',  
'M33C', 'TSK3000',  
'RS08', 'SHARC',  
'ECOG8', 'SCORE7',  
'DSP24', 'VIDEOCORE3',  
'LATTICEMICO32',

Object attribute	MISP attribute type	Description	Disable correlation
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—
name	text	Name of the section	✓
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH)	—
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—
text	text	Free text value to attach to the section	✓
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—

'COREA\_2ND',  
'ARC\_COMPACT2',  
'OPEN8', 'RL78',  
'VIDEOCORE5',  
'ARCH\_78KOR',  
'ARCH\_56800EX', 'BA1',  
'BA2', 'XCORE',  
'MCHP\_PIC', 'INTEL205',  
'INTEL206', 'INTEL207',  
'INTEL208', 'INTEL209',  
'KM32', 'KMX32',  
'KMX16', 'KMX8',  
'KVARC', 'CDP', 'COGE',  
'COOL', 'NORC',  
'CSR\_KALIMBA',  
'AMDGPU']

Object attribute	MISP attribute type	Description	Disable correlation
type	text	Type of the section ['NULL', 'PROGBITS', 'SYMTAB', 'STRTAB', 'RELA', 'HASH', 'DYNAMIC', 'NOTE', 'NOBITS', 'REL', 'SHLIB', 'DYNSYM', 'INIT_ARRAY', 'FINI_ARRAY', 'PREINIT_ARRAY', 'GROUP', 'SYMTAB_SHNDX', 'LOOS', 'GNU_ATTRIBUTES', 'GNU_HASH', 'GNU_VERDEF', 'GNU_VERNEED', 'GNU_VERSYM', 'HIOS', 'LOPROC', 'ARM_EXIDX', 'ARM_PREEMPTMAP', 'HEX_ORDERED', 'X86_64_UNWIND', 'MIPS_REGINFO', 'MIPS_OPTIONS', 'MIPS_ABIFLAGS', 'HIPROC', 'LOUSER', 'HIUSER']	✓
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—
md5	md5	[Insecure] MD5 hash (128 bits)	—

Object attribute	MISP attribute type	Description	Disable correlation
flag	text	Flag of the section ['ALLOC', 'EXCLUDE', 'EXECINSTR', 'GROUP', 'HEX_GPREL', 'INFO_LINK', 'LINK_ORDER', 'MASKOS', 'MASKPROC', 'MERGE', 'MIPS_ADDR', 'MIPS_LOCAL', 'MIPS_MERGE', 'MIPS_NAMES', 'MIPS_NODUPES', 'MIPS_NOSTRIP', 'NONE', 'OS_NONCONFORMING', 'STRINGS', 'TLS', 'WRITE', 'XCORE_SHF_CP_SECTION']	✓
size-in-bytes	size-in-bytes	Size of the section, in bytes	✓
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—
entropy	float	Entropy of the whole section	✓

## email

Email object describing an email with meta-information.



email is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
attachment	email-attachment	Attachment	—

Object attribute	MISP attribute type	Description	Disable correlation
from	email-src	Sender email address	—
eml	attachment	Full EML	✓
subject	email-subject	Subject	—
thread-index	email-thread-index	Identifies a particular conversation thread	✓
from-display-name	email-src-display-name	Display name of the sender	—
email-body	email-body	Body of the email	✓
return-path	email-src	Message return path	—
to-display-name	email-dst-display-name	Display name of the receiver	—
header	email-header	Full headers	✓
cc	email-dst	Carbon copy	✓
user-agent	text	User Agent of the sender	✓
to	email-dst	Destination email address	✓
x-mailer	email-x-mailer	X-Mailer generally tells the program that was used to draft and send the original email	✓
message-id	email-message-id	Message ID	✓
mime-boundary	email-mime-boundary	MIME Boundary	✓
reply-to	email-reply-to	Email address the reply will be sent to	—
screenshot	attachment	Screenshot of email	✓

Object attribute	MISP attribute type	Description	Disable correlation
send-date	datetime	Date the email has been sent	✓

## fail2ban

Fail2ban event.



fail2ban is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
processing-timestamp	datetime	Timestamp of the report	✓
sensor	text	Identifier of the sensor	✓
failures	counter	Amount of failures that lead to the ban.	✓
banned-ip	ip-src	IP Address banned by fail2ban	—
victim	text	Identifier of the victim	✓
attack-type	text	Type of the attack	✓
logline	text	Example log line that caused the ban.	✓
logfile	attachment	Full logfile related to the attack.	✓

## file

File object describing a file with meta-information.



file is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—
malware-sample	malware-sample	The file itself (binary)	—
authentihash	authentihash	Authenticode executable signature hash	—
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH)	—
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—
text	text	Free text value to attach to the file	✓
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—
state	text	State of the file ['Malicious', 'Harmless', 'Signed', 'Revoked', 'Expired', 'Trusted']	✓
certificate	x509-fingerprint-sha1	Certificate value if the binary is signed with another authentication scheme than authenticode	—
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—
path	text	Path of the filename complete or partial	✓
pattern-in-file	pattern-in-file	Pattern that can be found in the file	—

Object attribute	MISP attribute type	Description	Disable correlation
tlsh	tlsh	Fuzzy hash by Trend Micro: Locality Sensitive Hash	—
mimetype	mime-type	Mime type	✓
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—
md5	md5	[Insecure] MD5 hash (128 bits)	—
entropy	float	Entropy of the whole file	✓
size-in-bytes	size-in-bytes	Size of the file, in bytes	✓
filename	filename	Filename on disk	✓
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—

## geolocation

An object to describe a geographic location..



geolocation is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
region	text	Region.	—
latitude	float	The latitude is the decimal value of the latitude in the World Geodetic System 84 (WGS84) reference.	✓
address	text	Address.	—

Object attribute	MISP attribute type	Description	Disable correlation
city	text	City.	—
country	text	Country.	—
last-seen	datetime	When the location was seen for the last time.	✓
zipcode	text	Zip Code.	—
first-seen	datetime	When the location was seen for the first time.	✓
text	text	A generic description of the location.	✓
longitude	float	The longitude is the decimal value of the longitude in the World Geodetic System 84 (WGS84) reference	✓
altitude	float	The altitude is the decimal value of the altitude in the World Geodetic System 84 (WGS84) reference.	—

## gtp-attack

GTP attack object as seen on a GSM, UMTS or LTE network.



gtp-attack is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
ipSrc	ip-src	IP source address.	—
PortDest	text	Destination port.	✓
GtpServingNetwork	text	GTP Serving Network.	✓



Object attribute	MISP attribute type	Description	Disable correlation
GtpMessageType	text	GTP defines a set of messages between two associated GSNs or an SGSN and an RNC. Message type is described as a decimal value.	✓
ipDest	ip-dst	IP destination address.	—
PortSrc	port	Source port.	✓
GtpImei	text	GTP IMEI (International Mobile Equipment Identity).	—
first-seen	datetime	When the attack has been seen for the first time.	✓
GtpInterface	text	GTP interface. ['S5', 'S11', 'S10', 'S8', 'Gn', 'Gp']	✓
GtpImsi	text	GTP IMSI (International mobile subscriber identity).	—
GtpMsisdn	text	GTP MSISDN.	—
text	text	A description of the GTP attack.	✓
GtpVersion	text	GTP version ['0', '1', '2']	✓

## http-request

A single HTTP request header.



http-request is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
proxy-user	text	HTTP Proxy Username	—
basicauth-user	text	HTTP Basic Authentication Username	—
proxy-password	text	HTTP Proxy Password	—
text	text	HTTP Request comment	✓
host	hostname	The domain name of the server	—
user-agent	user-agent	The user agent string of the user agent	—
basicauth-password	text	HTTP Basic Authentication Password	—
uri	uri	Request URI	—
content-type	other	The MIME type of the body of the request	—
cookie	text	An HTTP cookie previously sent by the server with Set-Cookie	—
method	http-method	HTTP Method invoked (one of GET, POST, PUT, HEAD, DELETE, OPTIONS, CONNECT)	✓
referer	other	This is the address of the previous web page from which a link to the currently requested page was followed	—
url	url	Full HTTP Request URL	—

# ip-port

An IP address (or domain or hostname) and a port seen as a tuple (or as a triple) in a specific time frame..



ip-port is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
src-port	port	Source port	—
last-seen	datetime	Last time the tuple has been seen	✓
dst-port	port	Destination port	✓
first-seen	datetime	First time the tuple has been seen	✓
text	text	Description of the tuple	✓
ip	ip-dst	IP Address	—
hostname	hostname	Hostname	—
domain	domain	Domain	—

# ja3

JA3 is a new technique for creating SSL client fingerprints that are easy to produce and can be easily shared for threat intelligence. Fingerprints are composed of Client Hello packet; SSL Version, Accepted Ciphers, List of Extensions, Elliptic Curves, and Elliptic Curve Formats. <https://github.com/salesforce/ja3>.



ja3 is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
last-seen	datetime	Last seen of the SSL/TLS handshake	✓
ip-src	ip-src	Source IP Address	—

Object attribute	MISP attribute type	Description	Disable correlation
first-seen	datetime	First seen of the SSL/TLS handshake	✓
ja3-fingerprint-md5	md5	Hash identifying source	—
description	text	Type of detected software ie software, malware	—
ip-dst	ip-dst	Destination IP address	—

## legal-entity

An object to describe a legal entity..



legal-entity is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
legal-form	text	Legal form of an entity.	—
phone-number	phone-number	Phone number of an entity.	—
name	text	Name of an entity.	—
commercial-name	text	Commercial name of an entity.	—
registration-number	text	Registration number of an entity in the relevant authority.	—
text	text	A description of the entity.	✓
business	text	Business area of an entity.	—

# macho

Object describing a file in Mach-O format..



macho is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
text	text	Free text value to attach to the Mach-O file	✓
entrypoint-address	text	Address of the entry point	✓
type	text	Type of Mach-O ['BUNDLE', 'CORE', 'DSYM', 'DYLIB', 'DYLIB_STUB', 'DYLINKER', 'EXECUTE', 'FVMLIB', 'KEXT_BUNDLE', 'OBJECT', 'PRELOAD']	—
name	text	Binary's name	—
number-sections	counter	Number of sections	✓

# macho-section

Object describing a section of a file in Mach-O format..



macho-section is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—
name	text	Name of the section	✓

Object attribute	MISP attribute type	Description	Disable correlation
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH)	—
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—
text	text	Free text value to attach to the section	✓
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—
md5	md5	[Insecure] MD5 hash (128 bits)	—
size-in-bytes	size-in-bytes	Size of the section, in bytes	✓
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—
entropy	float	Entropy of the whole section	✓

## microblog

Microblog post like a Twitter tweet or a post on a Facebook wall..



microblog is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
creation-date	datetime	Initial creation of the microblog post	—
username	text	Username who posted the microblog post	—
link	url	Link into the microblog post	—
username-quoted	text	Username who are quoted into the microblog post	—
post	text	Raw post	—
modification-date	datetime	Last update of the microblog post	—
removal-date	datetime	When the microblog post was removed	—
type	text	Type of the microblog post ['Twitter', 'Facebook', 'LinkedIn', 'Reddit', 'Google+', 'Instagram', 'Forum', 'Other']	✓
url	url	Original URL location of the microblog post	—

## mutex

Object to describe mutual exclusion locks (mutex) as seen in memory or computer program.



mutex is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
name	text	name of the mutex	—
description	text	Description	—

Object attribute	MISP attribute type	Description	Disable correlation
operating-system	text	Operating system where the mutex has been seen ['Windows', 'Unix']	—

## netflow

Netflow object describes an network object based on the Netflowv5/v9 minimal definition.



netflow is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
src-as	AS	Source AS number for this flow	—
packet-count	counter	Packets counted in this flow	✓
direction	text	Direction of this flow ['Ingress', 'Egress']	✓
ip_version	counter	IP version of this flow	✓
ip-src	ip-src	IP address source of the netflow	—
last-packet-seen	datetime	Last packet seen in this flow	—
dst-port	port	Destination port of the netflow	—
first-packet-seen	datetime	First packet seen in this flow	—
byte-count	counter	Bytes counted in this flow	✓
icmp-type	text	ICMP type of the flow (if the traffic is ICMP)	✓



Object attribute	MISP attribute type	Description	Disable correlation
src-port	port	Source port of the netflow	—
protocol	text	Protocol used for this flow ['TCP', 'UDP', 'ICMP', 'IP']	—
ip-protocol-number	size-in-bytes	IP protocol number of this flow	✓
flow-count	counter	Flows counted in this flow	✓
tcp-flags	text	TCP flags of the flow	✓
dst-as	AS	Destination AS number for this flow	—
ip-dst	ip-dst	IP address destination of the netflow	—

## network-connection

A local or remote network connection..



network-connection is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
hostname-dst	hostname	Destination hostname of the network connection.	—
first-packet-seen	datetime	Datetime of the first packet seen.	—
src-port	port	Source port of the network connection.	—
ip-src	ip-src	Source IP address of the network connection.	—

Object attribute	MISP attribute type	Description	Disable correlation
dst-port	port	Destination port of the network connection.	—
layer4-protocol	text	Layer 4 protocol of the network connection. ['TCP', 'UDP']	—
layer3-protocol	text	Layer 3 protocol of the network connection. ['IP', 'ICMP', 'ARP']	—
hostname-src	hostname	Source hostname of the network connection.	—
layer7-protocol	text	Layer 7 protocol of the network connection. ['HTTP', 'HTTPS', 'FTP']	—
ip-dst	ip-dst	Destination IP address of the network connection.	—

## network-socket

Network socket object describes a local or remote network connections based on the socket data structure..



network-socket is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
protocol	text	Protocol used by the network socket. ['TCP', 'UDP', 'ICMP', 'IP']	—
ip-src	ip-src	Source (local) IP address of the network socket connection.	—
option	text	Option on the socket connection.	—

<b>Object attribute</b>	<b>MISP attribute type</b>	<b>Description</b>	<b>Disable correlation</b>
src-port	port	Source (local) port of the network socket connection.	—
hostname-dst	hostname	Destination hostname of the network socket connection.	—
dst-port	port	Destination port of the network socket connection.	—

Object attribute	MISP attribute type	Description	Disable correlation
domain-family	text	Domain family who specifies the communication domain (PF_*) of the socket connection. ['PF_UNSPEC', 'PF_LOCAL', 'PF_UNIX', 'PF_FILE', 'PF_INET', 'PF_AX25', 'PF_IPX', 'PF_APPLETALK', 'PF_NETROM', 'PF_BRIDGE', 'PF_ATMPVC', 'PF_X25', 'PF_INET6', 'PF_ROSE', 'PF_DECnet', 'PF_NETBEUI', 'PF_SECURITY', 'PF_KEY', 'PF_NETLINK', 'PF_ROUTE', 'PF_PACKET', 'PF_ASH', 'PF_ECONET', 'PF_ATMSVC', 'PF_RDS', 'PF_SNA', 'PF_IRDA', 'PF_PPPOX', 'PF_WANPIPE', 'PF_LLC', 'PF_IB', 'PF_MPLS', 'PF_CAN', 'PF_TIPC', 'PF_BLUETOOTH', 'PF_IUCV', 'PF_RXRPC', 'PF_ISDN', 'PF_PHONET', 'PF_IEEE802154', 'PF_CAIF', 'PF_ALG', 'PF_NFC', 'PF_VSOCK', 'PF_KCM', 'PF_MAX']	-
state	text	State of the socket connection. ['blocking', 'listening']	-

Object attribute	MISP attribute type	Description	Disable correlation
hostname-src	hostname	Source (local) hostname of the network socket connection.	—
address-family	text	Address family who specifies the address family type (AF_*) of the socket connection. [AF_UNSPEC, 'AF_LOCAL', 'AF_UNIX', 'AF_FILE', 'AF_INET', 'AF_AX25', 'AF_IPX', 'AF_APPLETALK', 'AF_NETROM', 'AF_BRIDGE', 'AF_ATMPVC', 'AF_X25', 'AF_INET6', 'AF_ROSE', 'AF_DECnet', 'AF_NETBEUI', 'AF_SECURITY', 'AF_KEY', 'AF_NETLINK', 'AF_ROUTE', 'AF_PACKET', 'AF_ASH', 'AF_ECONET', 'AF_ATMSVC', 'AF_RDS', 'AF_SNA', 'AF_IRDA', 'AF_PPPOX', 'AF_WANPIPE', 'AF_LLC', 'AF_IB', 'AF_MPLS', 'AF_CAN', 'AF_TIPC', 'AF_BLUETOOTH', 'AF_IUCV', 'AF_RXRPC', 'AF_ISDN', 'AF_PHONET', 'AF_IEEE802154', 'AF_CAIF', 'AF_ALG', 'AF_NFC', 'AF_VSOCK', 'AF_KCM', 'AF_MAX']	—
ip-dst	ip-dst	Destination IP address of the network socket connection.	—

# passive-dns

Passive DNS records as expressed in draft-dulaunoy-dnsop-passive-dns-cof-01.



passive-dns is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
origin	text	Origin of the Passive DNS response	✓
zone_time_last	datetime	Last time that the unique tuple (rrname, rrtype, rdata) record has been seen via master file import.	✓
time_first	datetime	First time that the unique tuple (rrname, rrtype, rdata) has been seen by the passive DNS	✓
sensor_id	text	Sensor information where the record was seen	✓
text	text	Description of the passive DNS record.	✓
zone_time_first	datetime	First time that the unique tuple (rrname, rrtype, rdata) record has been seen via master file import	✓
rdata	text	Resource records of the queried resource	—
rrname	text	Resource Record name of the queried resource.	—

Object attribute	MISP attribute type	Description	Disable correlation
time_last	datetime	Last time that the unique tuple (rrname, rrtype, rdata) record has been seen by the passive DNS	✓
count	counter	How many authoritative DNS answers were received at the Passive DNS Server's collectors with exactly the given set of values as answers.	✓
bailiwick	text	Best estimate of the apex of the zone where this data is authoritative	✓
rrtype	text	Resource Record type as seen by the passive DNS. ['A', 'AAAA', 'CNAME', 'PTR', 'SOA', 'TXT', 'DNAME', 'NS', 'SRV', 'RP', 'NAPTR', 'HINFO', 'A6']	✓

## paste

Paste or similar post from a website allowing to share privately or publicly posts..



paste is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
origin	text	Original source of the paste or post. ['pastebin.com', 'pastebin.com_pro', 'pastie.org', 'slexy.org', 'gist.github.com', 'codepad.org', 'safebin.net', 'hastebin.com', 'ghostbin.com']	—
last-seen	datetime	When the paste has been accessible or seen for the last time.	✓
title	text	Title of the paste or post.	—
first-seen	datetime	When the paste has been accessible or seen for the first time.	✓
paste	text	Raw text of the paste or post	—
url	url	Link to the original source of the paste or post.	—

## pe

Object describing a Portable Executable.



pe is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).



Object attribute	MISP attribute type	Description	Disable correlation
pehash	pehash	Hash of the structural information about a sample. See <a href="https://www.usenix.org/legacy/event/leet09/tech/full_papers/wicherski/wicherski_html/">https://www.usenix.org/legacy/event/leet09/tech/full_papers/wicherski/wicherski_html/</a>	—
company-name	text	CompanyName in the resources	✓
text	text	Free text value to attach to the PE	✓
product-version	text	ProductVersion in the resources	✓
type	text	Type of PE ['exe', 'dll', 'driver', 'unknown']	✓
lang-id	text	Lang ID in the resources	✓
product-name	text	ProductName in the resources	✓
entrypoint-address	text	Address of the entry point	✓
number-sections	counter	Number of sections	✓
file-version	text	FileVersion in the resources	✓
impfuzzy	impfuzzy	Fuzzy Hash (ssdeep) calculated from the import table	—
original-filename	filename	OriginalFilename in the resources	✓

Object attribute	MISP attribute type	Description	Disable correlation
internal-filename	filename	InternalFilename in the resources	✓
compilation-timestamp	datetime	Compilation timestamp defined in the PE header	—
entrypoint-section-at-position	text	Name of the section and position of the section in the PE	✓
file-description	text	FileDescription in the resources	✓
legal-copyright	text	LegalCopyright in the resources	✓
imphash	imphash	Hash (md5) calculated from the import table	—

## pe-section

Object describing a section of a Portable Executable.



pe-section is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—
name	text	Name of the section ['.rsrc', '.reloc', '.rdata', '.data', '.text']	✓
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH)	—

Object attribute	MISP attribute type	Description	Disable correlation
characteristic	text	Characteristic of the section ['read', 'write', 'executable']	—
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—
text	text	Free text value to attach to the section	✓
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—
md5	md5	[Insecure] MD5 hash (128 bits)	—
size-in-bytes	size-in-bytes	Size of the section, in bytes	✓
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—
entropy	float	Entropy of the whole section	✓

## person

An object which describes a person or an identity..



person is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

<b>Object attribute</b>	<b>MISP attribute type</b>	<b>Description</b>	<b>Disable correlation</b>
middle-name	middle-name	Middle name of a natural person.	–
social-security-number	text	Social security number	–
passport-country	passport-country	The country in which the passport was issued.	✓
redress-number	redress-number	The Redress Control Number is the record identifier for people who apply for redress through the DHS Travel Redress Inquiry Program (DHS TRIP). DHS TRIP is for travelers who have been repeatedly identified for additional screening and who want to file an inquiry to have erroneous information corrected in DHS systems.	–
nationality	nationality	The nationality of a natural person.	✓
text	text	A description of the person or identity.	✓
passport-expiration	passport-expiration	The expiration date of a passport.	✓
alias	text	Alias name or known as.	–
first-name	first-name	First name of a natural person.	✓
last-name	last-name	Last name of a natural person.	–

Object attribute	MISP attribute type	Description	Disable correlation
passport-number	passport-number	The passport number of a natural person.	—
place-of-birth	place-of-birth	Place of birth of a natural person.	✓
title	text	Title of the natural person such as Dr. or equivalent.	✓
gender	gender	The gender of a natural person. ['Male', 'Female', 'Other', 'Prefer not to say']	✓
date-of-birth	date-of-birth	Date of birth of a natural person (in YYYY-MM-DD format).	—
identity-card-number	identity-card-number	The identity card number of a natural person.	—
mothers-name	text	Mother name, father, second name or other names following country's regulation.	—

## phone

A phone or mobile phone object which describe a phone..



phone is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
msisdn	text	MSISDN (pronounced as /'em es ai es di en/ or misden) is a number uniquely identifying a subscription in a GSM or a UMTS mobile network. Simply put, it is the mapping of the telephone number to the SIM card in a mobile/cellular phone. This abbreviation has a several interpretations, the most common one being Mobile Station International Subscriber Directory Number.	—
tmsi	text	Temporary Mobile Subscriber Identities (TMSI) to visiting mobile subscribers can be allocated.	—
serial-number	text	Serial Number.	—
imsi	text	A usually unique International Mobile Subscriber Identity (IMSI) is allocated to each mobile subscriber in the GSM/UMTS/EPS system. IMSI can also refer to International Mobile Station Identity in the ITU nomenclature.	—
last-seen	datetime	When the phone has been accessible or seen for the last time.	✓

Object attribute	MISP attribute type	Description	Disable correlation
first-seen	datetime	When the phone has been accessible or seen for the first time.	✓
text	text	A description of the phone.	✓
guti	text	Globally Unique Temporary UE Identity (GUTI) is a temporary identification to not reveal the phone (user equipment in 3GPP jargon) composed of GUMMEI and the M-TMSI.	—
imei	text	International Mobile Equipment Identity (IMEI) is a number, usually unique, to identify 3GPP and iDEN mobile phones, as well as some satellite phones.	—
gummei	text	Globally Unique MME Identifier (GUMMEI) is composed from MCC, MNC and MME Identifier (MMEI).	—

## process

Object describing a system process..



process is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
pid	text	Process ID of the process.	—

Object attribute	MISP attribute type	Description	Disable correlation
start-time	datetime	Local date/time at which the process was started.	✓
name	text	Name of the process	—
creation-time	datetime	Local date/time at which the process was created.	✓
port	src-port	Port(s) owned by the process.	—
parent_pid	text	Process ID of the parent process.	—
child-pid	text	Process ID of the child(ren) process.	—

## r2graphity

Indicators extracted from files using radare2 and graphml.



r2graphity is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
shortest-path-to-create-thread	counter	Shortest path to the first time the binary calls CreateThread	✓
dangling-strings	counter	Amount of dangling strings (string with a code cross reference, that is not within a function. Radare2 failed to detect that function.)	✓
ratio-string	float	Ratio: amount of referenced strings per kilobyte of code section	✓



Object attribute	MISP attribute type	Description	Disable correlation
callbacks	counter	Amount of callbacks (functions started as thread)	✓
local-references	counter	Amount of API calls inside a code section	✓
total-api	counter	Total amount of API calls	✓
refsglobalvar	counter	Amount of API calls outside of code section (glob var, dynamic API)	✓
get-proc-address	counter	Amount of calls to GetProcAddress	✓
miss-api	counter	Amount of API call reference that does not resolve to a function offset	✓
memory-allocations	counter	Amount of memory allocations	✓
text	text	Description of the r2graphity object	✓
ratio-api	float	Ratio: amount of API calls per kilobyte of code section	✓
gml	attachment	Graph export in Graph Modelling Language format	✓
r2-commit-version	text	Radare2 commit ID used to generate this object	✓
create-thread	counter	Amount of calls to CreateThread	✓

Object attribute	MISP attribute type	Description	Disable correlation
unknown-references	counter	Amount of API calls not ending in a function (Radare2 bug, probalby)	✓
not-referenced-strings	counter	Amount of not referenced strings	✓
total-functions	counter	Total amount of functions in the file.	✓
referenced-strings	counter	Amount of referenced strings	✓
ratio-functions	float	Ratio: amount of functions per kilobyte of code section	✓
callback-largest	counter	Largest callback	✓
callback-average	counter	Average size of a callback	✓

## regexp

An object describing a regular expression (regex or regexp). The object can be linked via a relationship to other attributes or objects to describe how it can be represented as a regular expression..



regexp is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
type	text	Specify which type corresponds to this regex. ['hostname', 'domain', 'email-src', 'email-dst', 'email-subject', 'url', 'user-agent', 'regkey', 'cookie', 'uri', 'filename', 'windows-service-name', 'windows-scheduled-task']	✓
comment	comment	A description of the regular expression.	—
regexp-type	text	Type of the regular expression syntax. ['PCRE', 'PCRE2', 'POSIX BRE', 'POSIX ERE']	✓
regexp	text	regexp	—

## registry-key

Registry key object describing a Windows registry key with value and last-modified timestamp.



registry-key is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
name	text	Name of the registry key	—
key	regkey	Full key path	—

Object attribute	MISP attribute type	Description	Disable correlation
root-keys	text	Root key of the Windows registry (extracted from the key) ['HKCC', 'HKCR', 'HKCU', 'HKDD', 'HKEY_CLASSES_ROOT', 'HKEY_CURRENT_CONFIG', 'HKEY_CURRENT_USER', 'HKEY_DYN_DATA', 'HKEY_LOCAL_MACHINE', 'HKEY_PERFORMANCE_DATA', 'HKEY_USERS', 'HKLM', 'HKPD', 'HKU']	✓
last-modified	datetime	Last time the registry key has been modified	—
data-type	text	Registry value type ['REG_NONE', 'REG_SZ', 'REG_EXPAND_SZ', 'REG_BINARY', 'REG_DWORD', 'REG_DWORD_LITTLE_ENDIAN', 'REG_DWORD_BIG_ENDIAN', 'REG_LINK', 'REG_MULTI_SZ', 'REG_RESOURCE_LIST', 'REG_FULL_RESOURCE_DESCRIPTOR', 'REG_RESOURCE_REQUIREMENTS_LIST', 'REG_QWORD', 'REG_QWORD_LITTLE_ENDIAN']	✓
data	text	Data stored in the registry key	—
hive	text	Hive used to store the registry key (file on disk)	✓

# report

Metadata used to generate an executive level report.



report is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
summary	text	Free text summary of the report	—
case-number	text	Case number	—

# rtir

RTIR - Request Tracker for Incident Response.



rtir is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
classification	text	Classification of the RTIR ticket	—
subject	text	Subject of the RTIR ticket	—
constituency	text	Constituency of the RTIR ticket	—
status	text	Status of the RTIR ticket ['new', 'open', 'stalled', 'resolved', 'rejected', 'deleted']	—
queue	text	Queue of the RTIR ticket ['incident', 'investigations', 'blocks', 'incident reports']	—
ticket-number	text	ticket-number of the RTIR ticket	—

Object attribute	MISP attribute type	Description	Disable correlation
ip	ip-dst	IPs automatically extracted from the RTIR ticket	—

## sandbox-report

Sandbox report.



sandbox-report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
sandbox-type	text	The type of sandbox used ['on-premise', 'web', 'saas']	✓
permalink	link	Permalink reference	—
raw-report	text	Raw report from sandbox	✓
score	text	Score	✓
saas-sandbox	text	A non-on-premise sandbox, also results are not publicly available ['forticloud-sandbox', 'joe-sandbox-cloud', 'symantec-cas-cloud']	✓
results	text	Freetext result values	✓

Object attribute	MISP attribute type	Description	Disable correlation
on-premise-sandbox	text	The on-premise sandbox used ['cuckoo', 'symantec-cas-on-premise', 'bluecoat-maa', 'trendmicro-deep-discovery-analyzer', 'fireeye-ax', 'vmray', 'joe-sandbox-on-premise']	✓
web-sandbox	text	A web sandbox where results are publicly available via an URL ['malwr', 'hybrid-analysis']	✓

## sb-signature

Sandbox detection signature.



sb-signature is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
datetime	datetime	Datetime	✓
text	text	Additional signature description	✓
software	text	Name of Sandbox software	✓
signature	text	Name of detection signature - set the description of the detection signature as a comment	—

## ss7-attack

SS7 object of an attack seen on a GSM, UMTS or LTE network via SS7 logging..



ss7-attack is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
MapOpCode	text	MAP operation codes - Decimal value between 0-99.	✓
MapSmsTypeNumber	text	MAP SMS TypeNumber.	✓
MapGsmScfGT	text	MAP GSMSCF GT. Phone number.	—
SccpCdGT	text	Signaling Connection Control Part (SCCP) CdGT - Phone number.	—
SccpCdSSN	text	Signaling Connection Control Part (SCCP) - Decimal value between 0-255.	✓
MapUssdContent	text	MAP USSD Content.	—
MapSmsTP-DCS	text	MAP SMS TP-DCS.	✓
Category	text	Category ['Cat0', 'Cat1', 'Cat2.1', 'Cat2.2', 'Cat3.1', 'Cat3.2', 'Cat3.3', 'CatSMS', 'CatSpoofing']	✓
MapSmsText	text	MAP SMS Text. Important indicators in SMS text.	—
MapVersion	text	Map version. ['1', '2', '3']	✓
SccpCgSSN	text	Signaling Connection Control Part (SCCP) - Decimal value between 0-255.	✓
MapUssdCoding	text	MAP USSD Content.	✓



Object attribute	MISP attribute type	Description	Disable correlation
MapImsi	text	MAP IMSI. Phone number starting with MCC/MNC.	—
MapMsisdn	text	MAP MSISDN. Phone number.	—
MapApplicationContext	text	MAP application context in OID format.	✓
SccpCgGT	text	Signaling Connection Control Part (SCCP) CgGT - Phone number.	—
MapGmlc	text	MAP GMLC. Phone number.	—
SccpCdPC	text	Signaling Connection Control Part (SCCP) CdPC - Phone number.	—
MapMscGT	text	MAP MSC GT. Phone number.	—
MapVlrGT	text	MAP VLR GT. Phone number.	—
first-seen	datetime	When the attack has been seen for the first time.	✓
MapSmscGT	text	MAP SMSC. Phone number.	—
MapSmsTP-OA	text	MAP SMS TP-OA. Phone number.	—
text	text	A description of the attack seen via SS7 logging.	✓
MapSmsTP-PID	text	MAP SMS TP-PID.	✓

Object attribute	MISP attribute type	Description	Disable correlation
SccpCgPC	text	Signaling Connection Control Part (SCCP) CgPC - Phone number.	—

## stix2-pattern

An object describing a STIX pattern. The object can be linked via a relationship to other attributes or objects to describe how it can be represented as a STIX pattern..



stix2-pattern is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
version	text	Version of STIX 2 pattern. ['stix 2.0']	—
comment	comment	A description of the stix2-pattern.	—
stix2-pattern	stix2-pattern	STIX 2 pattern	—

## suricata

An object describing a Suricata rule along with its version and context.



suricata is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
suricata	suricata	Suricata rule.	—
version	text	Version of the Suricata rule depending where the suricata rule is known to work as expected.	—
comment	comment	A description of the Suricata rule.	—

Object attribute	MISP attribute type	Description	Disable correlation
ref	link	Reference to the Suricata rule such as origin of the rule or alike.	—

## target-system

Description about an targeted system, this could potentially be a compromised internal system.



target-system is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
targeted_machine	target-machine	Targeted system	✓
timestamp_seen	datetime	Registered date and time	✓
targeted_ip_of_system	ip-src	Targeted system IP address	✓

## timecode

Timecode object to describe a start of video sequence (e.g. CCTV evidence) and the end of the video sequence..



timecode is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
start-timecode	text	Start marker timecode in the format hh:mm:ss.mms	—
end-timecode	text	End marker timecode in the format hh:mm:ss.mms	—
recording-date	datetime	Date of recording of the video sequence	—

Object attribute	MISP attribute type	Description	Disable correlation
start-marker-timecode	text	Start marker timecode in the format hh:mm:ss;ff	—
description	text	Description of the video sequence	—
end-marker-timecode	text	End marker timecode in the format hh:mm:ss;ff	—

## timesketch-timeline

A timesketch timeline object based on mandatory field in timesketch to describe a log entry..



timesketch-timeline is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
message	text	Informative message of the event	—
timestamp	timestamp-microsec	When the log entry was seen in microseconds since Unix epoch	—
timestamp_desc	text	Text explaining what type of timestamp is it	—
datetime	datetime	When the log entry was seen	—

## timestamp

A generic timestamp object to represent time including first time and last time seen. Relationship will then define the kind of time relationship..



timestamp is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
first-seen	datetime	First time that the linked object or attribute has been seen.	✓
text	text	Description of the time object.	✓
last-seen	datetime	First time that the linked object or attribute has been seen.	✓
precision	text	Timestamp precision represents the precision given to first_seen and/or last_seen in this object. ['year', 'month', 'day', 'hour', 'minute', 'full']	✓

## tor-node

Tor node (which protects your privacy on the internet by hiding the connection between users Internet address and the services used by the users) description which are part of the Tor network at a time..



tor-node is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
fingerprint	text	router's fingerprint.	—
first-seen	datetime	When the Tor node designed by the IP address has been seen for the first time.	✓
text	text	Tor node comment.	✓
nickname	text	router's nickname.	—

Object attribute	MISP attribute type	Description	Disable correlation
published	datetime	router's publication time. This can be different from first-seen and last-seen.	✓
flags	text	list of flag associated with the node.	—
version_line	text	versioning information reported by the node.	—
version	text	parsed version of tor, this is None if the relay's using a new versioning scheme.	—
document	text	Raw document from the consensus.	✓
last-seen	datetime	When the Tor node designed by the IP address has been seen for the last time.	✓
address	ip-src	IP address of the Tor node seen.	—
description	text	Tor node description.	✓

## transaction

An object to describe a financial transaction..



transaction is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
authorized	text	Person who authorized the transaction.	—

<b>Object attribute</b>	<b>MISP attribute type</b>	<b>Description</b>	<b>Disable correlation</b>
transaction-number	text	A unique number identifying a transaction.	—
to-funds-code	text	Type of funds used to finalize a transaction. [A Deposit', 'C Currency exchange', 'D Casino chips', 'E Bank draft', 'F Money order', 'G Traveler's cheques', 'H Life insurance policy', 'I Real estate', 'J Securities', 'K Cash', 'O Other', 'P Cheque']	✓
date	datetime	Date and time of the transaction.	—
transmode-comment	text	Comment describing transmode-code, if needed.	—
from-funds-code	text	Type of funds used to initiate a transaction. [A Deposit', 'C Currency exchange', 'D Casino chips', 'E Bank draft', 'F Money order', 'G Traveler's cheques', 'H Life insurance policy', 'I Real estate', 'J Securities', 'K Cash', 'O Other', 'P Cheque']	✓
transmode-code	text	How the transaction was conducted.	—
amount	text	The value of the transaction in local currency.	—
location	text	Location where the transaction took place.	—

Object attribute	MISP attribute type	Description	Disable correlation
to-country	text	Target country of a transaction.	—
from-country	text	Origin country of a transaction.	—
text	text	A description of the transaction.	✓
date-posting	datetime	Date of posting, if different from date of transaction.	—
teller	text	Person who conducted the transaction.	—

## url

url object describes an url along with its normalized field (like extracted using faup parsing library) and its metadata..



url is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
port	port	Port number	✓
domain_without_tld	text	Domain without Top-Level Domain	—
domain	domain	Full domain	—
credential	text	Credential (username, password)	—
first-seen	datetime	First time this URL has been seen	✓
text	text	Description of the URL	—
host	hostname	Full hostname	—



Object attribute	MISP attribute type	Description	Disable correlation
subdomain	text	Subdomain	✓
query_string	text	Query (after path, preceded by '?')	—
tld	text	Top-Level Domain	✓
scheme	text	Scheme ['http', 'https', 'ftp', 'gopher', 'sip']	✓
last-seen	datetime	Last time this URL has been seen	✓
fragment	text	Fragment identifier is a short string of characters that refers to a resource that is subordinate to another, primary resource.	—
resource_path	text	Path (between hostname:port and query)	—
url	url	Full URL	—

## victim

Victim object describes the target of an attack or abuse..



victim is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
name	target-org	The name of the department(s) or organisation(s) targeted.	—
ip-address	ip-dst	IP address(es) of the node targeted.	—

Object attribute	MISP attribute type	Description	Disable correlation
roles	text	The list of roles targeted within the victim.	—
sectors	text	The list of sectors that the victim belong to ['agriculture', 'aerospace', 'automotive', 'communications', 'construction', 'defence', 'education', 'energy', 'engineering', 'entertainment', 'financial services', 'government national', 'government regional', 'government local', 'government public services', 'healthcare', 'hospitality leisure', 'infrastructure', 'insurance', 'manufacturing', 'mining', 'non profit', 'pharmaceuticals', 'retail', 'technology', 'telecommunications', 'transportation', 'utilities']	—
classification	text	The type of entity being targeted. ['individual', 'group', 'organization', 'class', 'unknown']	✓
node	target-machine	Name(s) of node that was targeted.	—
external	target-external	External target organisations affected by this attack.	—

Object attribute	MISP attribute type	Description	Disable correlation
regions	target-location	The list of regions or locations from the victim targeted. ISO 3166 should be used.	—
description	text	Description of the victim	—
user	target-user	The username(s) of the user targeted.	—
email	target-email	The email address(es) of the user targeted.	—

## virustotal-report

VirusTotal report.



virustotal-report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
first-submission	datetime	First Submission	—
detection-ratio	text	Detection Ratio	✓
permalink	link	Permalink Reference	—
community-score	text	Community Score	✓
comment	text	Comment related to this hash	—
last-submission	datetime	Last Submission	—

## vulnerability

Vulnerability object describing a common vulnerability enumeration which can describe unpublished, under review or embargo vulnerability for software, equipments or hardware..



vulnerability is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
created	datetime	First time when the vulnerability was discovered	✓
summary	text	Summary of the vulnerability	—
references	link	External references	—
state	text	State of the vulnerability. A vulnerability can have multiple states depending of the current actions performed. ['Published', 'Embargo', 'Reviewed', 'Vulnerability ID Assigned', 'Reported', 'Fixed']	✓
modified	datetime	Last modification date	✓
text	text	Description of the vulnerability	—
id	vulnerability	Vulnerability ID (generally CVE, but not necessarily). The id is not required as the object itself has an UUID and the CVE id can updated later.	—
published	datetime	Initial publication date	✓
vulnerable_configuration	text	The vulnerable configuration is described in CPE format	—

# whois

Whois records information for a domain name or an IP address..



whois is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
creation-date	datetime	Initial creation of the whois entry	✓
comment	text	Comment of the whois entry	—
registrant-phone	whois-registrant-phone	Registrant phone number	—
domain	domain	Domain of the whois entry	—
modification-date	datetime	Last update of the whois entry	✓
text	text	Full whois entry	✓
registrant-org	whois-registrant-org	Registrant organisation	—
nameserver	hostname	Nameserver	✓
registrant-email	whois-registrant-email	Registrant email address	—
registrar	whois-registrar	Registrar of the whois entry	—
ip-address	ip-src	IP address of the whois entry	—
registrant-name	whois-registrant-name	Registrant name	—
expiration-date	datetime	Expiration of the whois entry	✓

# x509

x509 object describing a X.509 certificate.



x509 is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
self_signed	boolean	Self-signed certificate	—
x509-fingerprint-sha256	x509-fingerprint-sha256	Secure Hash Algorithm 2 (256 bits)	—
pubkey-info-algorithm	text	Algorithm of the public key	—
serial-number	text	Serial number of the certificate	—
subject	text	Subject of the certificate	—
raw-base64	text	Raw certificate base64 encoded (DER format)	—
text	text	Free text description of the certificate	—
x509-fingerprint-sha1	x509-fingerprint-sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—
pem	text	Raw certificate in PEM format (Unix-like newlines)	—
pubkey-info-modulus	text	Modulus of the public key	—
dns_names	text	DNS names	—
version	text	Version of the certificate	—

Object attribute	MISP attribute type	Description	Disable correlation
pubkey-info-size	text	Length of the public key (in bits)	—
validity-not-after	datetime	Certificate invalid after that date	—
x509-fingerprint-md5	x509-fingerprint-md5	[Insecure] MD5 hash (128 bits)	—
validity-not-before	datetime	Certificate invalid before that date	—
issuer	text	Issuer of the certificate	—
pubkey-info-exponent	text	Exponent of the public key	—
is_ca	boolean	CA certificate	—

## yabin

yabin.py generates Yara rules from function prologs, for matching and hunting binaries. ref: <https://github.com/AlienVault-OTX/yabin>.



yabin is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
yara-hunt	yara	Wide yara rule generated from -yh.	✓
version	comment	yabin.py and regex.txt version used for the generation of the yara rules.	—
comment	comment	A description of Yara rule generated.	—
yara	yara	Yara rule generated from -y.	✓

Object attribute	MISP attribute type	Description	Disable correlation
whitelist	comment	Whitelist name used to generate the rules.	—

## yara

An object describing a YARA rule along with its version..



yara is a MISP object available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation
version	text	Version of the YARA rule depending where the yara rule is known to work as expected. ['3.7.1']	—
comment	comment	A description of the YARA rule.	—
yara	yara	YARA rule.	—
context	text	Context where the YARA rule can be applied ['all', 'disk', 'memory', 'network']	—

## Relationships

Default type of relationships in MISP objects.

Relationships are part of MISP object and available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Name of relationship	Description	Format
derived-from	The information in the target object is based on information from the source object.	['misp', 'stix-2.0']
duplicate-of	The referenced source and target objects are semantically duplicates of each other.	['misp', 'stix-2.0']



<b>Name of relationship</b>	<b>Description</b>	<b>Format</b>
related-to	The referenced source is related to the target object.	['misp', 'stix-2.0']
connected-to	The referenced source is connected to the target object.	['misp', 'stix-1.1']
contains	The references source is containing the target object.	['misp', 'stix-1.1']
resolved-to	The referenced source is resolved to the target object.	['misp', 'stix-1.1']
attributed-to	This referenced source is attributed to the target object.	['misp', 'stix-2.0']
targets	This relationship describes that the source object targets the target object.	['misp', 'stix-2.0']
uses	This relationship describes the use by the source object of the target object.	['misp', 'stix-2.0']
indicates	This relationships describes that the source object indicates the target object.	['misp', 'stix-2.0']
mitigates	This relationship describes a source object which mitigates the target object.	['misp', 'stix-2.0']
variant-of	This relationship describes a source object which is a variant of the target object	['misp', 'stix-2.0']
impersonates	This relationship describe a source object which impersonates the target object	['misp', 'stix-2.0']
authored-by	This relationship describes the author of a specific object.	['misp']
located	This relationship describes the location (of any type) of a specific object.	['misp']
included-in	This relationship describes an object included in another object.	['misp']
analysed-with	This relationship describes an object analysed by another object.	['misp']
claimed-by	This relationship describes an object claimed by another object.	['misp']

<b>Name of relationship</b>	<b>Description</b>	<b>Format</b>
communicates-with	This relationship describes an object communicating with another object.	['misp']
dropped-by	This relationship describes an object dropped by another object.	['misp']
drops	This relationship describes an object which drops another object	['misp']
executed-by	This relationship describes an object executed by another object.	['misp']
affects	This relationship describes an object affected by another object.	['misp']
beacons-to	This relationship describes an object beaconing to another object.	['misp']
abuses	This relationship describes an object which abuses another object.	['misp']
exfiltrates-to	This relationship describes an object exfiltrating to another object.	['misp']
identifies	This relationship describes an object which identifies another object.	['misp']
intercepts	This relationship describes an object which intercepts another object.	['misp']
calls	This relationship describes an object which calls another objects.	['misp']
detected-as	This relationship describes an object which is detected as another object.	['misp']
followed-by	This relationship describes an object which is followed by another object. This can be used when a time reference is missing but a sequence is known.	['misp']

<b>Name of relationship</b>	<b>Description</b>	<b>Format</b>
preceding-by	This relationship describes an object which is preceded by another object. This can be used when a time reference is missing but a sequence is known.	['misp']
triggers	This relationship describes an object which triggers another object.	['misp']
vulnerability-of	This relationship describes an object which is a vulnerability of another object.	['cert-eu']
works-like	This relationship describes an object which works like another object.	['cert-eu']
seller-of	This relationship describes an object which is selling another object.	['cert-eu']
seller-on	This relationship describes an object which is selling on another object.	['cert-eu']
trying-to-obtain-the-exploit	This relationship describes an object which is trying to obtain the exploit described by another object	['cert-eu']
used-by	This relationship describes an object which is used by another object.	['cert-eu']
affiliated	This relationship describes an object which is affiliated with another object.	['cert-eu']
alleged-founder-of	This relationship describes an object which is the alleged founder of another object.	['cert-eu']
attacking-other-group	This relationship describes an object which attacks another object.	['cert-eu']
belongs-to	This relationship describes an object which belongs to another object.	['cert-eu']
business-relations	This relationship describes an object which has business relations with another object.	['cert-eu']

<b>Name of relationship</b>	<b>Description</b>	<b>Format</b>
claims-to-be-the-founder-of	This relationship describes an object which claims to be the founder of another object.	['cert-eu']
cooperates-with	This relationship describes an object which cooperates with another object.	['cert-eu']
former-member-of	This relationship describes an object which is a former member of another object.	['cert-eu']
successor-of	This relationship describes an object which is a successor of another object.	['cert-eu']
has-joined	This relationship describes an object which has joined another object.	['cert-eu']
member-of	This relationship describes an object which is a member of another object.	['cert-eu']
primary-member-of	This relationship describes an object which is a primary member of another object.	['cert-eu']
administrator-of	This relationship describes an object which is an administrator of another object.	['cert-eu']
is-in-relation-with	This relationship describes an object which is in relation with another object,	['cert-eu']
provide-support-to	This relationship describes an object which provides support to another object.	['cert-eu']
regional-branch	This relationship describes an object which is a regional branch of another object.	['cert-eu']
similar	This relationship describes an object which is similar to another object.	['cert-eu']
subgroup	This relationship describes an object which is a subgroup of another object.	['cert-eu']
suspected-link	This relationship describes an object which is suspected to be linked with another object.	['misp']
same-as	This relationship describes an object which is the same as another object.	['misp']

<b>Name of relationship</b>	<b>Description</b>	<b>Format</b>
creator-of	This relationship describes an object which is the creator of another object.	['cert-eu']
developer-of	This relationship describes an object which is a developer of another object.	['cert-eu']
uses-for-recon	This relationship describes an object which uses another object for recon.	['cert-eu']
operator-of	This relationship describes an object which is an operator of another object.	['cert-eu']
overlaps	This relationship describes an object which overlaps another object.	['cert-eu']
owner-of	This relationship describes an object which owns another object.	['cert-eu']
publishes-method-for	This relationship describes an object which publishes method for another object.	['cert-eu']
recommends-use-of	This relationship describes an object which recommends the use of another object.	['cert-eu']
released-source-code	This relationship describes an object which released source code of another object.	['cert-eu']
released	This relationship describes an object which release another object.	['cert-eu']