

# MISP Galaxy Clusters

# MISP Galaxy Cluster

Android	1
Banker	85
Cert EU GovSector	96
Exploit-Kit	97
Microsoft Activity Group actor	110
Attack Pattern	114
Course of Action	227
intrusion Set	260
Malware	280
Tool	321
Preventive Measure	332
Ransomware	335
RAT	467
Sector	514
TDS	521
Threat actor	522
Tool	562



MISP galaxy is a simple method to express a large object called cluster that can be attached to MISP events or attributes. A cluster can be composed of one or more elements. Elements are expressed as key-values. There are default vocabularies available in MISP galaxy but those can be overwritten, replaced or updated as you wish. Existing clusters and vocabularies can be used as-is or as a template. MISP distribution can be applied to each cluster to permit a limited or broader distribution scheme.

## Android

Android malware galaxy based on multiple open sources..



Android is a cluster galaxy available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

Unknown

## CopyCat

CopyCat is a fully developed malware with vast capabilities, including rooting devices, establishing persistency, and injecting code into Zygote – a daemon responsible for launching apps in the Android operating system – that allows the malware to control any activity on the device.

*Table 1. Table References*

Links
<a href="https://blog.checkpoint.com/2017/07/06/how-the-copycat-malware-infected-android-devices-around-the-world/">https://blog.checkpoint.com/2017/07/06/how-the-copycat-malware-infected-android-devices-around-the-world/</a>

## Andr/Dropr-FH

Andr/Dropr-FH can silently record audio and video, monitor texts and calls, modify files, and ultimately spawn ransomware.

Andr/Dropr-FH is also known as:

- GhostCtrl

Table 2. Table References

Links
<a href="https://nakedsecurity.sophos.com/2017/07/21/watch-out-for-the-android-malware-that-snoops-on-your-phone/">https://nakedsecurity.sophos.com/2017/07/21/watch-out-for-the-android-malware-that-snoops-on-your-phone/</a>
<a href="https://www.neowin.net/news/the-ghostctrl-android-malware-can-silently-record-your-audio-and-steal-sensitive-data">https://www.neowin.net/news/the-ghostctrl-android-malware-can-silently-record-your-audio-and-steal-sensitive-data</a>

## Judy

The malware, dubbed Judy, is an auto-clicking adware which was found on 41 apps developed by a Korean company. The malware uses infected devices to generate large amounts of fraudulent clicks on advertisements, generating revenues for the perpetrators behind it.

Table 3. Table References

Links
<a href="http://fortune.com/2017/05/28/android-malware-judy/">http://fortune.com/2017/05/28/android-malware-judy/</a>
<a href="https://blog.checkpoint.com/2017/05/25/judy-malware-possibly-largest-malware-campaign-found-google-play/">https://blog.checkpoint.com/2017/05/25/judy-malware-possibly-largest-malware-campaign-found-google-play/</a>

## RedAlert2

The trojan waits in hiding until the user opens a banking or social media app. When this happens, the trojan shows an HTML-based overlay on top of the original app, alerting the user of an error, and asking to reauthenticate. Red Alert then collects the user's credentials and sends them to its C&C server.

Table 4. Table References

Links
<a href="https://www.bleepingcomputer.com/news/security/researchers-discover-new-android-banking-trojan/">https://www.bleepingcomputer.com/news/security/researchers-discover-new-android-banking-trojan/</a>

## DoubleLocker

DoubleLocker can change the device's PIN, preventing victims from accessing their devices, and also encrypts the data requesting a ransom. It will misuse accessibility services after being installed by impersonating the Adobe Flash player - similar to BankBot.

Table 5. Table References

Links
<a href="https://www.welivesecurity.com/2017/10/13/doublelocker-innovative-android-malware/">https://www.welivesecurity.com/2017/10/13/doublelocker-innovative-android-malware/</a>

# Svpeng

Svpeng is a Banking trojan which acts as a keylogger. If the Android device is not Russian, Svpeng will ask for permission to use accessibility services. In abusing this service it will gain administrator rights allowing it to draw over other apps, send and receive SMS and take screenshots when keys are pressed.

Svpeng is also known as:

- Invisible Man

Table 6. Table References

Links
<a href="https://securelist.com/a-new-era-in-mobile-banking-trojans/79198/">https://securelist.com/a-new-era-in-mobile-banking-trojans/79198/</a>
<a href="https://www.theregister.co.uk/2017/08/02/banking_android_malware_in_uk/">https://www.theregister.co.uk/2017/08/02/banking_android_malware_in_uk/</a>

# LokiBot

LokiBot is a banking trojan for Android 4.0 and higher. It can steal the information and send SMS messages. It has the ability to start web browsers, and banking applications, along with showing notifications impersonating other apps. Upon attempt to remove it will encrypt the devices' external storage requiring Bitcoins to decrypt files.

Table 7. Table References

Links
<a href="https://clientsidedetection.com/lokibot_the_first_hybrid_android_malware.html">https://clientsidedetection.com/lokibot_the_first_hybrid_android_malware.html</a> <a href="https://clientsidedetection.com/lokibot_the_first_hybrid_android_malware.html">[https://clientsidedetection.com/lokibot_the_first_hybrid_android_malware.html]</a>

# BankBot

The main goal of this malware is to steal banking credentials from the victim's device. It usually impersonates flash player updaters, android system tools, or other legitimate applications.

Table 8. Table References

Links
<a href="https://blog.fortinet.com/2017/09/19/a-look-into-the-new-strain-of-bankbot">https://blog.fortinet.com/2017/09/19/a-look-into-the-new-strain-of-bankbot</a>
<a href="https://forensics.spreitzenbarth.de/android-malware/">https://forensics.spreitzenbarth.de/android-malware/</a>

# Viking Horde

In rooted devices, Viking Horde installs software and executes code remotely to get access to the mobile data.

Table 9. Table References

Links
-------

<a href="http://www.alwayson-network.com/worst-types-android-malware-2016/">http://www.alwayson-network.com/worst-types-android-malware-2016/</a>
---

## HummingBad

A Chinese advertising company has developed this malware. The malware has the power to take control of devices; it forces users to click advertisements and download apps. The malware uses a multistage attack chain.

*Table 10. Table References*

Links
-------

<a href="http://www.alwayson-network.com/worst-types-android-malware-2016/">http://www.alwayson-network.com/worst-types-android-malware-2016/</a>
---

<a href="http://blog.checkpoint.com/wp-content/uploads/2016/07/HummingBad-Research-report_FINAL-62916.pdf">http://blog.checkpoint.com/wp-content/uploads/2016/07/HummingBad-Research-report_FINAL-62916.pdf</a>
---

## Ackposts

Ackposts is a Trojan horse for Android devices that steals the Contacts information from the compromised device and sends it to a predetermined location.

*Table 11. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-072302-3943-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-072302-3943-99</a>
---

## Wirex

Wirex is a Trojan horse for Android devices that opens a backdoor on the compromised device which then joins a botnet for conducting click fraud.

*Table 12. Table References*

Links
-------

<a href="https://krebsonsecurity.com/2017/08/tech-firms-team-up-to-take-down-wirex-android-ddos-botnet/">https://krebsonsecurity.com/2017/08/tech-firms-team-up-to-take-down-wirex-android-ddos-botnet/</a>
---

<a href="http://www.zdnet.com/article/wirex-ddos-malware-given-udp-flood-capabilities/">http://www.zdnet.com/article/wirex-ddos-malware-given-udp-flood-capabilities/</a>
---

## WannaLocker

WannaLocker is a strain of ransomware for Android devices that encrypts files on the device's external storage and demands a payment to decrypt them.

*Table 13. Table References*

Links
-------

<a href="https://fossbytes.com/wannalocker-ransomware-wannacry-android/">https://fossbytes.com/wannalocker-ransomware-wannacry-android/</a>
---

# Switcher

Switcher is a Trojan horse for Android devices that modifies Wi-Fi router DNS settings. Switcher attempts to infiltrate a router's admin interface on the devices' WIFI network by using brute force techniques. If the attack succeeds, Switcher alters the DNS settings of the router, making it possible to reroute DNS queries to a network controlled by the malicious actors.

Table 14. Table References

Links
<a href="http://www.zdnet.com/article/this-android-infecting-trojan-malware-uses-your-phone-to-attack-your-router/">http://www.zdnet.com/article/this-android-infecting-trojan-malware-uses-your-phone-to-attack-your-router/</a>
<a href="https://www.theregister.co.uk/2017/01/03/android_trojan_targets_routers/">https://www.theregister.co.uk/2017/01/03/android_trojan_targets_routers/</a>
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2017-090410-0547-99">https://www.symantec.com/security_response/writeup.jsp?docid=2017-090410-0547-99</a>

# Vibleaker

Vibleaker was an app available on the Google Play Store named Beaver Gang Counter that contained malicious code that after specific orders from its maker would scan the user's phone for the Viber app, and then steal photos and videos recorded or sent through the app.

Table 15. Table References

Links
<a href="http://news.softpedia.com/news/malicious-android-app-steals-viber-photos-and-videos-505758.shtml">http://news.softpedia.com/news/malicious-android-app-steals-viber-photos-and-videos-505758.shtml</a>

# ExpensiveWall

ExpensiveWall is Android malware that sends fraudulent premium SMS messages and charges users accounts for fake services without their knowledge

Table 16. Table References

Links
<a href="https://blog.checkpoint.com/2017/09/14/expensivewall-dangerous-packed-malware-google-play-will-hit-wallet/">https://blog.checkpoint.com/2017/09/14/expensivewall-dangerous-packed-malware-google-play-will-hit-wallet/</a>
<a href="http://fortune.com/2017/09/14/google-play-android-malware/">http://fortune.com/2017/09/14/google-play-android-malware/</a>

# Cepsohord

Cepsohord is a Trojan horse for Android devices that uses compromised devices to commit click fraud, modify DNS settings, randomly delete essential files, and download additional malware such as ransomware.

Table 17. Table References

Links
-------

## Fakem Rat

Fakem RAT makes their network traffic look like well-known protocols (e.g. Messenger traffic, HTML pages).

Table 18. Table References

Links
<a href="https://www.trendmicro.de/cloud-content/us/pdfs/security-intelligence/white-papers/wp-fakem-rat.pdf">https://www.trendmicro.de/cloud-content/us/pdfs/security-intelligence/white-papers/wp-fakem-rat.pdf</a>
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2016-012608-1538-99">https://www.symantec.com/security_response/writeup.jsp?docid=2016-012608-1538-99</a>

## GM Bot

GM Bot – also known as Acecard, SlemBunk, or Bankosy – scams people into giving up their banking log-in credentials and other personal data by displaying overlays that look nearly identical to banking apps log-in pages. Subsequently, the malware intercepts SMS to obtain two-factor authentication PINs, giving cybercriminals full access to bank accounts.

GM Bot is also known as:

- Acecard
- SlemBunk
- Bankosy

Table 19. Table References

Links
<a href="https://blog.avast.com/android-trojan-gm-bot-is-evolving-and-targeting-more-than-50-banks-worldwide">https://blog.avast.com/android-trojan-gm-bot-is-evolving-and-targeting-more-than-50-banks-worldwide</a>

## Moplus

The Wormhole vulnerability in the Moplus SDK could be exploited by hackers to open an unsecured and unauthenticated HTTP server connection on the user's device, and this connection is established in the background without the user's knowledge.

Table 20. Table References

Links
<a href="http://securityaffairs.co/wordpress/41681/hacking/100m-android-device-baidu-moplus-sdk.html">http://securityaffairs.co/wordpress/41681/hacking/100m-android-device-baidu-moplus-sdk.html</a>

## Adwind

Adwind is a backdoor written purely in Java that targets system supporting the Java runtime



environment. Commands that can be used, among other things, to display messages on the system, open URLs, update the malware, download/execute files, and download/load plugins. According to the author, the backdoor component can run on Windows, Mac OS, Linux and Android platforms providing rich capabilities for remote control, data gathering, data exfiltration and lateral movement.

Adwind is also known as:

- AlienSpy
- Frutas
- Unrecom
- Sockrat
- Jsocket
- jRat
- Backdoor:Java/Adwind

*Table 21. Table References*

Links
<a href="https://securelist.com/adwind-faq/73660/">https://securelist.com/adwind-faq/73660/</a>

## AdSms

Adsms is a Trojan horse that may send SMS messages from Android devices.

*Table 22. Table References*

Links
<a href="https://www.fortiguard.com/encyclopedia/virus/7389670">https://www.fortiguard.com/encyclopedia/virus/7389670</a>
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-051313-4039-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-051313-4039-99</a>

## Airpush

Airpush is a very aggressive Ad - Network

Airpush is also known as:

- StopSMS

*Table 23. Table References*

Links
<a href="https://crypto.stanford.edu/cs155old/cs155-spring16/lectures/18-mobile-malware.pdf">https://crypto.stanford.edu/cs155old/cs155-spring16/lectures/18-mobile-malware.pdf</a>

# BeanBot

BeanBot forwards device's data to a remote server and sends out premium-rate SMS messages from the infected device.

Table 24. Table References

Links
<a href="https://www.f-secure.com/v-descs/trojan_android_beanbot.shtml">https://www.f-secure.com/v-descs/trojan_android_beanbot.shtml</a>

# Kemoge

Kemoge is adware that disguises itself as popular apps via repackaging, then allows for a complete takeover of the users Android device.

Table 25. Table References

Links
<a href="https://www.fireeye.com/blog/threat-research/2015/10/kemoge_another_mobi.html">https://www.fireeye.com/blog/threat-research/2015/10/kemoge_another_mobi.html</a>
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-101207-3555-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-101207-3555-99</a>

# Ghost Push

Ghost Push is a family of malware that infects the Android OS by automatically gaining root access, downloading malicious software, masquerading as a system app, and then losing root access, which then makes it virtually impossible to remove the infection even by factory reset unless the firmware is reflashed.

Table 26. Table References

Links
<a href="https://en.wikipedia.org/wiki/Ghost_Push">https://en.wikipedia.org/wiki/Ghost_Push</a>
<a href="https://blog.avast.com/how-to-protect-your-android-device-from-ghost-push">https://blog.avast.com/how-to-protect-your-android-device-from-ghost-push</a>

# BeNews

The BeNews app is a backdoor app that uses the name of defunct news site BeNews to appear legitimate. After installation it bypasses restrictions and downloads additional threats to the compromised device.

Table 27. Table References

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/fake-news-app-in-hacking-team-dump-designed-to-bypass-google-play/">http://blog.trendmicro.com/trendlabs-security-intelligence/fake-news-app-in-hacking-team-dump-designed-to-bypass-google-play/</a>

## Accstealer

Accstealer is a Trojan horse for Android devices that steals information from the compromised device.

Table 28. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-012711-1159-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-012711-1159-99</a>

## Acnetdoor

Acnetdoor is a detection for Trojan horses on the Android platform that open a back door on the compromised device.

Table 29. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-051611-4258-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-051611-4258-99</a>

## Acnetsteal

Acnetsteal is a detection for Trojan horses on the Android platform that steal information from the compromised device.

Table 30. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-051612-0505-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-051612-0505-99</a>

## Actech

Actech is a Trojan horse for Android devices that steals information and sends it to a remote location.

Table 31. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-080111-3948-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-080111-3948-99</a>

## AdChina

AdChina is an advertisement library that is bundled with certain Android applications.

Table 32. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-032814-2947-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-032814-2947-99</a>

## Adfonic

Adfonic is an advertisement library that is bundled with certain Android applications.

*Table 33. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052615-0024-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052615-0024-99</a>

## AdInfo

AdInfo is an advertisement library that is bundled with certain Android applications.

*Table 34. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-2433-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-2433-99</a>

## Adknowledge

Adknowledge is an advertisement library that is bundled with certain Android applications.

*Table 35. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052822-1033-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052822-1033-99</a>

## AdMarvel

AdMarvel is an advertisement library that is bundled with certain Android applications.

*Table 36. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-060621-2450-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-060621-2450-99</a>

## AdMob

AdMob is an advertisement library that is bundled with certain Android applications.

*Table 37. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052822-3437-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052822-3437-99</a>

## Adrd

Adrd is a Trojan horse that steals information from Android devices.

Table 38. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-021514-4954-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-021514-4954-99</a>

## Aduru

Aduru is an advertisement library that is bundled with certain Android applications.

Table 39. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052618-2419-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052618-2419-99</a>

## Adwhirl

Adwhirl is an advertisement library that is bundled with certain Android applications.

Table 40. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052918-1414-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052918-1414-99</a>

## Adwlauncher

Adwlauncher is a Trojan horse for Android devices that steals information from the compromised device.

Table 41. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-082308-1823-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-082308-1823-99</a>

## Adwo

Adwo is an advertisement library that is bundled with certain Android applications.

Table 42. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-032814-5806-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-032814-5806-99</a>

## Airad

Airad is an advertisement library that is bundled with certain Android applications.

Table 43. Table References

Links
-------

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-032815-1704-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-032815-1704-99)

## Alienspy

Alienspy is a Trojan horse for Android devices that steals information from the compromised device. It may also download potentially malicious files.

*Table 44. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2015-042714-5942-99](https://www.symantec.com/security_response/writeup.jsp?docid=2015-042714-5942-99)

## AmazonAds

AmazonAds is an advertisement library that is bundled with certain Android applications.

*Table 45. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-052618-5002-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-052618-5002-99)

## Answerbot

Answerbot is a Trojan horse that opens a back door on Android devices.

*Table 46. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2011-100711-2129-99](https://www.symantec.com/security_response/writeup.jsp?docid=2011-100711-2129-99)

## Antammi

Antammi is a Trojan horse that steals information from Android devices.

*Table 47. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-032106-5211-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-032106-5211-99)

## Apkmore

Apkmore is an advertisement library that is bundled with certain Android applications.

*Table 48. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-040113-4813-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-040113-4813-99)

## Aplog

Aplog is a Trojan horse for Android devices that steals information from the device.

*Table 49. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-100911-1023-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-100911-1023-99</a>

## Appenda

Appenda is an advertisement library that is bundled with certain Android applications.

*Table 50. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-062812-0516-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-062812-0516-99</a>

## Apperhand

Apperhand is an advertisement library that is bundled with certain Android applications.

*Table 51. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-032815-5637-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-032815-5637-99</a>

## Appleservice

Appleservice is a Trojan horse for Android devices that may steal information from the compromised device.

*Table 52. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-031011-4321-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-031011-4321-99</a>

## AppLovin

AppLovin is an advertisement library that is bundled with certain Android applications.

*Table 53. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040112-1739-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040112-1739-99</a>

## Arspam

Arspam is a Trojan horse for Android devices that sends spam SMS messages to contacts on the compromised device.

*Table 54. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-121915-3251-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-121915-3251-99</a>

## Aurecord

Aurecord is a spyware application for Android devices that allows the device it is installed on to be monitored.

*Table 55. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-031914-2310-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-031914-2310-99</a>

## Backapp

Backapp is a Trojan horse for Android devices that steals information from the compromised device.

*Table 56. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-092708-5017-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-092708-5017-99</a>

## Backdexter

Backdexter is a Trojan horse for Android devices that may send premium-rate SMS messages from the compromised device.

*Table 57. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-121812-2502-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-121812-2502-99</a>

## Backflash

Backflash is a Trojan horse for Android devices that opens a back door and steals information from the compromised device.

*Table 58. Table References*

Links
-------



[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-091714-0427-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-091714-0427-99)

## Backscript

Backscript is a Trojan horse for Android devices that downloads files onto the compromised device.

*Table 59. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-090704-3639-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-090704-3639-99)

## Badaccents

Badaccents is a Trojan horse for Android devices that may download apps on the compromised device.

*Table 60. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-123015-3618-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-123015-3618-99)

## Badpush

Badpush is an advertisement library that is bundled with certain Android applications.

*Table 61. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-040311-4133-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-040311-4133-99)

## Ballonpop

Ballonpop is a Trojan horse for Android devices that steals information from the compromised device.

*Table 62. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-120911-1731-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-120911-1731-99)

## Bankosy

Bankosy is a Trojan horse for Android devices that steals information from the compromised device.

*Table 63. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-072316-5249-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-072316-5249-99)

## Bankun

Bankun is a Trojan horse for Android devices that replaces certain banking applications on the compromised device.

*Table 64. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-072318-4143-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-072318-4143-99)

## Basebridge

Basebridge is a Trojan horse that attempts to send premium-rate SMS messages to predetermined numbers.

*Table 65. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2011-060915-4938-99](https://www.symantec.com/security_response/writeup.jsp?docid=2011-060915-4938-99)

## Basedao

Basedao is a Trojan horse for Android devices that steals information from the compromised device.

*Table 66. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-061715-3303-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-061715-3303-99)

## Batterydoctor

Batterydoctor is Trojan that makes exaggerated claims about the device's ability to recharge the battery, as well as steal information.

*Table 67. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2011-101916-0847-99](https://www.symantec.com/security_response/writeup.jsp?docid=2011-101916-0847-99)

## Beaglespy

Beaglespy is an Android mobile detection for the Beagle spyware program as well as its associated client application.

*Table 68. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-091010-0627-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-091010-0627-99</a>
---

## Becuro

Becuro is a Trojan horse for Android devices that downloads potentially malicious files onto the compromised device.

*Table 69. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-051410-3348-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-051410-3348-99</a>
---

## Beita

Beita is a Trojan horse for Android devices that steals information from the compromised device.

*Table 70. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-110111-1829-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-110111-1829-99</a>
---

## Bgserv

Bgserv is a Trojan that opens a back door and transmits information from the device to a remote location.

*Table 71. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-031005-2918-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-031005-2918-99</a>
---

## Biigespy

Biigespy is an Android mobile detection for the Biige spyware program as well as its associated client application.

*Table 72. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-091012-0526-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-091012-0526-99</a>
---

## Bmaster

Bmaster is a Trojan horse on the Android platform that opens a back door, downloads files and steals potentially confidential information from the compromised device.

*Table 73. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-020609-3003-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-020609-3003-99</a>
---

## Bossefiv

Bossefiv is a Trojan horse for Android devices that steals information.

*Table 74. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-061520-4322-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-061520-4322-99</a>
---

## Boxpush

Boxpush is an advertisement library that is bundled with certain Android applications.

*Table 75. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040207-4613-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040207-4613-99</a>
---

## Burstly

Burstly is an advertisement library that is bundled with certain Android applications.

*Table 76. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052918-1443-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052918-1443-99</a>
---

## Buzzcity

Buzzcity is an advertisement library that is bundled with certain Android applications.

*Table 77. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052918-1454-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052918-1454-99</a>
---

## ByPush

ByPush is an advertisement library that is bundled with certain Android applications.

*Table 78. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040315-4708-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040315-4708-99</a>
---

# Cajino

Cajino is a Trojan horse for Android devices that opens a back door on the compromised device.

Table 79. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-040210-3746-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-040210-3746-99</a>

# Casee

Casee is an advertisement library that is bundled with certain Android applications.

Table 80. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052919-3501-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052919-3501-99</a>

# Catchtoken

Catchtoken is a Trojan horse for Android devices that intercepts SMS messages and opens a back door on the compromised device.

Table 81. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-121619-0548-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-121619-0548-99</a>

# Cauly

Cauly is an advertisement library that is bundled with certain Android applications.

Table 82. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052919-3454-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052919-3454-99</a>

# Cellshark

Cellshark is a spyware application for Android devices that periodically gathers information from the device and uploads it to a predetermined location.

Table 83. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-111611-0914-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-111611-0914-99</a>

## Centero

Centero is a Trojan horse for Android devices that displays advertisements on the compromised device.

*Table 84. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-053006-2502-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-053006-2502-99</a>

## Chuli

Chuli is a Trojan horse for Android devices that opens a back door and may steal information from the compromised device.

*Table 85. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-032617-1604-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-032617-1604-99</a>

## Citmo

Citmo is a Trojan horse for Android devices that steals information from the compromised device.

*Table 86. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-030715-5012-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-030715-5012-99</a>

## Claco

Claco is a Trojan horse for Android devices that steals information from the compromised device.

*Table 87. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-020415-5600-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-020415-5600-99</a>

## Clevernet

Clevernet is an advertisement library that is bundled with certain Android applications.

*Table 88. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040107-5257-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040107-5257-99</a>

# Cnappbox

Cnappbox is an advertisement library that is bundled with certain Android applications.

Table 89. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040215-1141-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040215-1141-99</a>

# Cobblersone

Cobblersone is a spyware application for Android devices that can track the phone's location and remotely erase the device.

Table 90. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-111514-3846-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-111514-3846-99</a>

# Coolpaperleak

Coolpaperleak is a Trojan horse for Android devices that steals information and sends it to a remote location.

Table 91. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-080211-5757-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-080211-5757-99</a>

# Coolreaper

Coolreaper is a Trojan horse for Android devices that opens a back door on the compromised device. It may also steal information and download potentially malicious files.

Table 92. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-011220-3211-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-011220-3211-99</a>

# Cosha

Cosha is a spyware program for Android devices that monitors and sends certain information to a remote location.

Table 93. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-081712-5231-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-081712-5231-99</a>

# Counterclank

Counterclank is a Trojan horse for Android devices that steals information.

Table 94. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-012709-4046-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-012709-4046-99</a>

# Crazymedia

Crazymedia is an advertisement library that is bundled with certain Android applications.

Table 95. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040312-2547-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040312-2547-99</a>

# Crisis

Crisis is a Trojan horse for Android devices that opens a back door and steals information from the compromised device.

Table 96. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-071409-0636-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-071409-0636-99</a>

# Crusewind

Crusewind is a Trojan horse for Android devices that sends SMS messages to a premium-rate number.

Table 97. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-070301-5702-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-070301-5702-99</a>

# Dandro

Dandro is a Trojan horse for Android devices that allows a remote attacker to gain control over the device and steal information from it.

Table 98. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-012916-2128-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-012916-2128-99</a>



## Daoyoudao

Daoyoudao is an advertisement library that is bundled with certain Android applications.

*Table 99. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040214-5018-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040214-5018-99</a>

## Deathring

Deathring is a Trojan horse for Android devices that may perform malicious activities on the compromised device.

*Table 100. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-121116-4547-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-121116-4547-99</a>

## Deeveemap

Deeveemap is a Trojan horse for Android devices that downloads potentially malicious files onto the compromised device.

*Table 101. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2017-060907-5221-99">https://www.symantec.com/security_response/writeup.jsp?docid=2017-060907-5221-99</a>

## Dendoroid

Dendoroid is a Trojan horse for Android devices that opens a back door, steals information, and may perform other malicious activities on the compromised device.

*Table 102. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-030418-2633-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-030418-2633-99</a>

## Dengaru

Dengaru is a Trojan horse for Android devices that performs click-fraud from the compromised device.

*Table 103. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-051113-4819-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-051113-4819-99</a>

## Diandong

Diandong is an advertisement library that is bundled with certain Android applications.

Table 104. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040207-2453-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040207-2453-99</a>

## Dianjin

Dianjin is an advertisement library that is bundled with certain Android applications.

Table 105. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040107-0313-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040107-0313-99</a>

## Dogowar

Dogowar is a Trojan horse on the Android platform that sends SMS texts to all contacts on the device. It is a repackaged version of a game application called Dog Wars, which can be downloaded from a third party market and must be manually installed.

Table 106. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-081510-4323-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-081510-4323-99</a>

## Domob

Domob is an advertisement library that is bundled with certain Android applications.

Table 107. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-4235-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-4235-99</a>

## Dougalek

Dougalek is a Trojan horse for Android devices that steals information from the compromised device. The threat is typically disguised to display a video.

Table 108. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-041601-3400-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-041601-3400-99</a>

## Dowgin

Dowgin is an advertisement library that is bundled with certain Android applications.

*Table 109. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-033108-4723-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-033108-4723-99</a>

## Droidsheep

Droidsheep is a hacktool for Android devices that hijacks social networking accounts on compromised devices.

*Table 110. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-031014-3628-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-031014-3628-99</a>

## Dropdialer

Dropdialer is a Trojan horse for Android devices that sends SMS messages to a premium-rate phone number.

*Table 111. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-070909-0726-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-070909-0726-99</a>

## Dupvert

Dupvert is a Trojan horse for Android devices that opens a back door and steals information from the compromised device. It may also perform other malicious activities.

*Table 112. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-072313-1959-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-072313-1959-99</a>

## Dynamicit

Dynamicit is an advertisement library that is bundled with certain Android applications.

*Table 113. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040407-1346-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040407-1346-99</a>

## Ecardgrabber

Ecardgrabber is an application that attempts to read details from NFC enabled credit cards. It attempts to read information from NFC enabled credit cards that are in close proximity.

Table 114. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-062215-0939-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-062215-0939-99</a>

## Ecobatry

Ecobatry is a Trojan horse for Android devices that steals information and sends it to a remote location.

Table 115. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-080606-4102-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-080606-4102-99</a>

## Enesoluty

Enesoluty is a Trojan horse for Android devices that steals information and sends it to a remote location.

Table 116. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-090607-0807-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-090607-0807-99</a>

## Everbadge

Everbadge is an advertisement library that is bundled with certain Android applications.

Table 117. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-3736-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-3736-99</a>

## Ewalls

Ewalls is a Trojan horse for the Android operating system that steals information from the mobile device.

Table 118. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2010-073014-0854-99">https://www.symantec.com/security_response/writeup.jsp?docid=2010-073014-0854-99</a>

## Exprespam

Exprespam is a Trojan horse for Android devices that displays a fake message and steals personal information stored on the compromised device.

Table 119. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-010705-2324-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-010705-2324-99</a>

## Fakealbums

Fakealbums is a Trojan horse for Android devices that monitors and forwards received messages from the compromised device.

Table 120. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-071819-0636-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-071819-0636-99</a>

## Fakeangry

Fakeangry is a Trojan horse on the Android platform that opens a back door, downloads files, and steals potentially confidential information from the compromised device.

Table 121. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-022823-4233-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-022823-4233-99</a>

## Fakeapp

Fakeapp is a Trojan horse for Android devices that downloads configuration files to display advertisements and collects information from the compromised device.

Table 122. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-022805-4318-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-022805-4318-99</a>

## Fakebanco

Fakebanco is a Trojan horse for Android devices that redirects users to a phishing page in order to steal their information.

Table 123. Table References

Links
-------

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-112109-5329-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-112109-5329-99)

## Fakebank

Fakebank is a Trojan horse that steals information from the compromised device.

*Table 124. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-071813-2448-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-071813-2448-99)

## Fakebank.B

Fakebank.B is a Trojan horse for Android devices that opens a back door and steals information from the compromised device.

*Table 125. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-101114-5645-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-101114-5645-99)

## Fakebok

Fakebok is a Trojan horse for Android devices that sends SMS messages to premium phone numbers.

*Table 126. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-021115-5153-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-021115-5153-99)

## Fakedaum

Fakedaum is a Trojan horse for Android devices that steals information from the compromised device.

*Table 127. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-061813-3630-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-061813-3630-99)

## Fakedefender

Fakedefender is a Trojan horse for Android devices that displays fake security alerts in an attempt to convince the user to purchase an app in order to remove non-existent malware or security risks from the device.

*Table 128. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-060301-4418-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-060301-4418-99</a>
---

## Fakedefender.B

Fakedefender.B is a Trojan horse for Android devices that displays fake security alerts in an attempt to convince the user to purchase an app in order to remove non-existent malware or security risks from the device.

*Table 129. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-091013-3953-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-091013-3953-99</a>
---

## Fakedown

Fakedown is a Trojan horse for Android devices that downloads more malicious apps onto the compromised device.

*Table 130. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-041803-5918-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-041803-5918-99</a>
---

## Fakeflash

Fakeflash is a Trojan horse for Android devices that installs a fake Flash application in order to direct users to a website.

*Table 131. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-070318-2122-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-070318-2122-99</a>
---

## Fakegame

Fakegame is a Trojan horse for Android devices that displays advertisements and steals information from the compromised device.

*Table 132. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-040808-2922-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-040808-2922-99</a>
---

## Fakeguard

Fakeguard is a Trojan horse for Android devices that steals information from the compromised

device.

*Table 133. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-102908-3526-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-102908-3526-99</a>

## Fakejob

Fakejob is a Trojan horse for Android devices that redirects users to scam websites.

*Table 134. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-030721-3048-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-030721-3048-99</a>

## Fakekakao

Fakekakao is a Trojan horse for Android devices sends SMS messages to contacts stored on the compromised device.

*Table 135. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-071617-2031-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-071617-2031-99</a>

## Fakelemon

Fakelemon is a Trojan horse for Android devices that blocks certain SMS messages and may subscribe to services without the user's consent.

*Table 136. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-120609-3608-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-120609-3608-99</a>

## Fakelicense

Fakelicense is a Trojan horse that displays advertisements on the compromised device.

*Table 137. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-062709-1437-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-062709-1437-99</a>

## Fakelogin

Fakelogin is a Trojan horse for Android devices that steals information from the compromised



device.

*Table 138. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-102108-5457-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-102108-5457-99</a>

## FakeLookout

FakeLookout is a Trojan horse for Android devices that opens a back door and steals information on the compromised device.

*Table 139. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-101919-2128-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-101919-2128-99</a>

## FakeMart

FakeMart is a Trojan horse for Android devices that may send SMS messages to premium rate numbers. It may also block incoming messages and steal information from the compromised device.

*Table 140. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-081217-1428-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-081217-1428-99</a>

## Fakemini

Fakemini is a Trojan horse for Android devices that disguises itself as an installation for the Opera Mini browser and sends premium-rate SMS messages to a predetermined number.

*Table 141. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-110410-5958-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-110410-5958-99</a>

## Fakemrat

Fakemrat is a Trojan horse for Android devices that opens a back door and steals information from the compromised device.

*Table 142. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2016-012608-1538-99">https://www.symantec.com/security_response/writeup.jsp?docid=2016-012608-1538-99</a>

## Fakeneflic

Fakeneflic is a Trojan horse that steals information from Android devices.

*Table 143. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-101105-0518-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-101105-0518-99</a>

## Fakenotify

Fakenotify is a Trojan horse for Android devices that sends SMS messages to premium-rate phone numbers, collects and sends information, and periodically displays Web pages. It also downloads legitimate apps onto the compromised device.

*Table 144. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-011302-3052-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-011302-3052-99</a>

## Fakepatch

Fakepatch is a Trojan horse for Android devices that downloads more files on to the device.

*Table 145. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-062811-2820-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-062811-2820-99</a>

## Fakeplay

Fakeplay is a Trojan horse for Android devices that steals information from the compromised device and sends it to a predetermined email address.

*Table 146. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-100917-3825-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-100917-3825-99</a>

## Fakescarav

Fakescarav is a Trojan horse for Android devices that displays fake security alerts in an attempt to convince the user to pay in order to remove non-existent malware or security risks from the device.

*Table 147. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-012809-1901-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-012809-1901-99</a>

## Fakesecsuit

Fakesecsuit is a Trojan horse for Android devices that steals information from the compromised device.

Table 148. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-060514-1301-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-060514-1301-99</a>

## Fakesucon

Fakesucon is a Trojan horse program for Android devices that sends SMS messages to premium-rate phone numbers.

Table 149. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-120915-2524-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-120915-2524-99</a>

## Faketaobao

Faketaobao is a Trojan horse for Android devices that steals information from the compromised device.

Table 150. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-062518-4057-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-062518-4057-99</a>

## Faketaobao.B

Faketaobao.B is a Trojan horse for Android devices that intercepts and sends incoming SMS messages to a remote attacker.

Table 151. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-012106-4013-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-012106-4013-99</a>

## Faketoken

Faketoken is a Trojan horse that opens a back door on the compromised device.

Table 152. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-032211-2048-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-032211-2048-99</a>

## Fakeupdate

Fakeupdate is a Trojan horse for Android devices that downloads other applications onto the compromised device.

*Table 153. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-081914-5637-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-081914-5637-99)

## Fakevoice

Fakevoice is a Trojan horse for Android devices that dials a premium-rate phone number.

*Table 154. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-040510-3249-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-040510-3249-99)

## Farmbaby

Farmbaby is a spyware application for Android devices that logs certain information and sends SMS messages to a predetermined phone number.

*Table 155. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-090715-3641-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-090715-3641-99)

## Fauxtocopy

Fauxtocopy is a spyware application for Android devices that gathers photos from the device and sends them to a predetermined email address.

*Table 156. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2011-111515-3940-99](https://www.symantec.com/security_response/writeup.jsp?docid=2011-111515-3940-99)

## Feiwo

Feiwo is an advertisement library that is bundled with certain Android applications.

*Table 157. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-040107-4038-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-040107-4038-99)

## FindAndCall

FindAndCall is a Potentially Unwanted Application for Android devices that may leak information.

*Table 158. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-031020-2906-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-031020-2906-99)

## Finfish

Finfish is a Trojan horse for Android devices that opens a back door and steals information from the compromised device.

*Table 159. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-083016-0032-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-083016-0032-99)

## Fireleaker

Fireleaker is a Trojan horse for Android devices that steals information from the compromised device.

*Table 160. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-031814-5207-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-031814-5207-99)

## Fitikser

Fitikser is a Trojan horse for Android devices that steals information from the compromised device.

*Table 161. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-093015-2830-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-093015-2830-99)

## Flexispy

Flexispy is a Spyware application for Android devices that logs the device's activity and sends it to a predetermined website.

*Table 162. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2011-122006-4805-99](https://www.symantec.com/security_response/writeup.jsp?docid=2011-122006-4805-99)

## Fokonge

Fokonge is a Trojan horse that steals information from Android devices.

*Table 163. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2011-071802-0727-99](https://www.symantec.com/security_response/writeup.jsp?docid=2011-071802-0727-99)

## FoncySMS

FoncySMS is a Trojan horse for Android devices that sends SMS messages to premium-rate phone numbers. It may also connect to an IRC server and execute any received shell commands.

*Table 164. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-011502-2651-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-011502-2651-99)

## Frogonal

Frogonal is a Trojan horse for Android devices that steals information from the compromised device.

*Table 165. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-062205-2312-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-062205-2312-99)

## Ftad

Ftad is an advertisement library that is bundled with certain Android applications.

*Table 166. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-040114-2020-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-040114-2020-99)

## Fantasy

Fantasy is a Trojan horse for Android devices that subscribes the user to premium SMS services.

*Table 167. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-092519-5811-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-092519-5811-99)

## GallMe

GallMe is an advertisement library that is bundled with certain Android applications.

*Table 168. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040312-1336-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040312-1336-99</a>

## GameX

GameX is a Trojan horse for Android devices that downloads further threats.

*Table 169. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-051015-1808-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-051015-1808-99</a>

## Gappusin

Gappusin is a Trojan horse for Android devices that downloads applications and disguises them as system updates.

*Table 170. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-022007-2013-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-022007-2013-99</a>

## Gazon

Gazon is a worm for Android devices that spreads through SMS messages.

*Table 171. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-030320-1436-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-030320-1436-99</a>

## Geinimi

Geinimi is a Trojan that opens a back door and transmits information from the device to a remote location.

*Table 172. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-010111-5403-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-010111-5403-99</a>

## Generisk

Generisk is a generic detection for Android applications that may pose a privacy, security, or stability risk to the user or user's Android device.

Table 173. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-062622-1559-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-062622-1559-99</a>

## Genheur

Genheur is a generic detection for many individual but varied Trojans for Android devices for which specific definitions have not been created. A generic detection is used because it protects against many Trojans that share similar characteristics.

Table 174. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-032613-0848-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-032613-0848-99</a>

## Genpush

Genpush is an advertisement library that is bundled with certain Android applications.

Table 175. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-033109-0426-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-033109-0426-99</a>

## GeoFake

GeoFake is a Trojan horse for Android devices that sends SMS messages to premium-rate numbers.

Table 176. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-040217-3232-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-040217-3232-99</a>

## Geplook

Geplook is a Trojan horse for Android devices that downloads additional apps onto the compromised device.

Table 177. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-121814-0917-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-121814-0917-99</a>



# Getadpush

Getadpush is an advertisement library that is bundled with certain Android applications.

Table 178. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040112-0957-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040112-0957-99</a>

# Ggtracker

Ggtracker is a Trojan horse for Android devices that sends SMS messages to a premium-rate number. It may also steal information from the device.

Table 179. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-062208-5013-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-062208-5013-99</a>

# Ghostpush

Ghostpush is a Trojan horse for Android devices that roots the compromised device. It may then perform malicious activities on the compromised device.

Table 180. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-100215-3718-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-100215-3718-99</a>

# Gmaster

Gmaster is a Trojan horse on the Android platform that steals potentially confidential information from the compromised device.

Table 181. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-082404-5049-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-082404-5049-99</a>

# Godwon

Godwon is a Trojan horse for Android devices that steals information.

Table 182. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-091017-1833-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-091017-1833-99</a>

## Golddream

Golddream is a Trojan horse that steals information from Android devices.

*Table 183. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-070608-4139-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-070608-4139-99</a>

## Goldeneagle

Goldeneagle is a Trojan horse that steals information from Android devices.

*Table 184. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-090110-3712-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-090110-3712-99</a>

## Golocker

Golocker is a Trojan horse for Android devices that steals information from the compromised device.

*Table 185. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-062003-3214-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-062003-3214-99</a>

## Gomal

Gomal is a Trojan horse for Android devices that steals information from the compromised device.

*Table 186. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-101312-1047-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-101312-1047-99</a>

## Gonesixty

Gonesixty is a Trojan horse that steals information from Android devices.

*Table 187. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-093001-2649-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-093001-2649-99</a>

# Gonfu

Gonfu is a Trojan horse that steals information from Android devices.

*Table 188. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-060610-3953-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-060610-3953-99</a>

# Gonfu.B

Gonfu.B is a Trojan horse that steals information from Android devices.

*Table 189. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-030811-5215-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-030811-5215-99</a>

# Gonfu.C

Gonfu.C is a Trojan horse for Android devices that may download additional threats on the compromised device.

*Table 190. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-031817-3639-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-031817-3639-99</a>

# Gonfu.D

Gonfu.D is a Trojan horse that opens a back door on Android devices.

*Table 191. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-040414-1158-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-040414-1158-99</a>

# Gooboot

Gooboot is a Trojan horse for Android devices that may send text messages to premium rate numbers.

*Table 192. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-031818-3034-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-031818-3034-99</a>

# Goodadpush

Goodadpush is an advertisement library that is bundled with certain Android applications.

Table 193. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040108-0913-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040108-0913-99</a>

# Greystripe

Greystripe is an advertisement library that is bundled with certain Android applications.

Table 194. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052919-2643-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052919-2643-99</a>

# Gugespy

Gugespy is a spyware program for Android devices that logs the device's activity and sends it to a predetermined email address.

Table 195. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-071822-2515-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-071822-2515-99</a>

# Gugespy.B

Gugespy.B is a spyware program for Android devices that monitors and sends certain information to a remote location.

Table 196. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-070511-5038-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-070511-5038-99</a>

# Gupno

Gupno is a Trojan horse for Android devices that poses as a legitimate app and attempts to charge users for features that are normally free. It may also display advertisements on the compromised device.

Table 197. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-072211-5533-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-072211-5533-99</a>

## Habey

Habey is a Trojan horse for Android devices that may attempt to delete files and send SMS messages from the compromised device.

Table 198. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-100608-4512-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-100608-4512-99</a>

## Handyclient

Handyclient is an advertisement library that is bundled with certain Android applications.

Table 199. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040307-5027-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040307-5027-99</a>

## Hehe

Hehe is a Trojan horse for Android devices that blocks incoming calls and SMS messages from specific numbers. The Trojan also steals information from the compromised device.

Table 200. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-012211-0020-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-012211-0020-99</a>

## Hesperbot

Hesperbot is a Trojan horse for Android devices that opens a back door on the compromised device and may steal information.

Table 201. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-121010-1120-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-121010-1120-99</a>

## Hippo

Hippo is a Trojan horse that sends SMS messages to premium-rate phone numbers.

Table 202. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-071215-3547-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-071215-3547-99</a>

## Hippo.B

Hippo.B is a Trojan horse that sends SMS messages to premium-rate phone numbers.

*Table 203. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-031915-0151-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-031915-0151-99</a>

## IadPush

IadPush is an advertisement library that is bundled with certain Android applications.

*Table 204. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040315-4104-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040315-4104-99</a>

## iBanking

iBanking is a Trojan horse for Android devices that opens a back door on the compromised device and may steal information.

*Table 205. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-030713-0559-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-030713-0559-99</a>

## Iconosis

Iconosis is a Trojan horse for Android devices that steals information from the compromised device.

*Table 206. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-062107-3327-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-062107-3327-99</a>

## Iconosys

Iconosys is a Trojan horse for Android devices that steals information from the compromised device.

*Table 207. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-081309-0341-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-081309-0341-99</a>

## Igexin

Igexin is an advertisement library that is bundled with certain Android applications.

*Table 208. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-032606-5519-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-032606-5519-99</a>

## ImAdPush

ImAdPush is an advertisement library that is bundled with certain Android applications.

*Table 209. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040323-0218-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040323-0218-99</a>

## InMobi

InMobi is an advertisement library that is bundled with certain Android applications.

*Table 210. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052713-1527-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052713-1527-99</a>

## Jifake

Jifake is a Trojan horse for Android devices that sends SMS messages to premium-rate phone numbers.

*Table 211. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-073021-4247-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-073021-4247-99</a>

## Jollyserv

Jollyserv is a Trojan horse for Android devices that sends SMS messages and steals information from the compromised device.

*Table 212. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-090311-4533-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-090311-4533-99</a>

## Jsmshider

Jsmshider is a Trojan horse that opens a back door on Android devices.

*Table 213. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-062114-0857-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-062114-0857-99</a>

## Ju6

Ju6 is an advertisement library that is bundled with certain Android applications.

*Table 214. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-2428-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-2428-99</a>

## Jumptap

Jumptap is an advertisement library that is bundled with certain Android applications.

*Table 215. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052713-0859-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052713-0859-99</a>

## Jzmob

Jzmob is an advertisement library that is bundled with certain Android applications.

*Table 216. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040207-1703-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040207-1703-99</a>

## Kabstamper

Kabstamper is a Trojan horse for Android devices that corrupts images found on the compromised device.

*Table 217. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-060706-2305-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-060706-2305-99</a>



## Kidlogger

Kidlogger is a Spyware application for Android devices that logs the device's activity and sends it to a predetermined website.

Table 218. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-122014-1927-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-122014-1927-99</a>

## Kielog

Kielog is a Trojan horse for Android devices that logs keystrokes and sends the stolen information to the remote attacker.

Table 219. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-040205-4035-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-040205-4035-99</a>

## Kituri

Kituri is a Trojan horse for Android devices that blocks certain SMS messages from being received by the device. It may also send SMS messages to a premium-rate number.

Table 220. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-061111-5350-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-061111-5350-99</a>

## Kranxpay

Kranxpay is a Trojan horse for Android devices that downloads other apps onto the device.

Table 221. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-071009-0809-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-071009-0809-99</a>

## Krysanec

Krysanec is a Trojan horse for Android devices that opens a back door on the compromised device.

Table 222. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-090113-4128-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-090113-4128-99</a>

## Kuaidian360

Kuaidian360 is an advertisement library that is bundled with certain Android applications.

Table 223. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040109-2415-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040109-2415-99</a>

## Kuguo

Kuguo is an advertisement library that is bundled with certain Android applications.

Table 224. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040315-5215-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040315-5215-99</a>

## Lastacloud

Lastacloud is a Trojan horse for Android devices that steals information from the compromised device.

Table 225. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-121216-4334-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-121216-4334-99</a>

## Laucassspy

Laucassspy is a spyware program for Android devices that steals information and sends it to a remote location.

Table 226. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-092409-1822-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-092409-1822-99</a>

## Lifemonspy

Lifemonspy is a spyware application for Android devices that can track the phone's location, download SMS messages, and erase certain data from the device.

Table 227. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-111516-5540-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-111516-5540-99</a>

## Lightdd

Lightdd is a Trojan horse that steals information from Android devices.

Table 228. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-053114-2342-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-053114-2342-99</a>

## Loaderpush

Loaderpush is an advertisement library that is bundled with certain Android applications.

Table 229. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040108-0244-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040108-0244-99</a>

## Locaspy

Locaspy is a Potentially Unwanted Application for Android devices that tracks the location of the compromised device.

Table 230. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-030720-3500-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-030720-3500-99</a>

## Lockdroid.E

Lockdroid.E is a Trojan horse for Android devices that locks the screen and displays a ransom demand on the compromised device.

Table 231. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-103005-2209-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-103005-2209-99</a>

## Lockdroid.F

Lockdroid.F is a Trojan horse for Android devices that locks the screen and displays a ransom demand on the compromised device.

Table 232. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-102215-4346-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-102215-4346-99</a>

## Lockdroid.G

Lockdroid.G is a Trojan horse for Android devices that may display a ransom demand on the compromised device.

*Table 233. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-050610-2450-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-050610-2450-99</a>

## Lockdroid.H

Lockdroid.H is a Trojan horse for Android devices that locks the screen and displays a ransom demand on the compromised device.

*Table 234. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2016-031621-1349-99">https://www.symantec.com/security_response/writeup.jsp?docid=2016-031621-1349-99</a>

## Lockscreen

Lockscreen is a Trojan horse for Android devices that locks the compromised device from use.

*Table 235. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-032409-0743-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-032409-0743-99</a>

## LogiaAd

LogiaAd is an advertisement library that is bundled with certain Android applications.

*Table 236. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052713-0348-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052713-0348-99</a>

## Loicdos

Loicdos is an Android application that provides an interface to a website in order to perform a denial of service (DoS) attack against a computer.

*Table 237. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-022002-2431-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-022002-2431-99</a>

## Loozfon

Loozfon is a Trojan horse for Android devices that steals information from the compromised device.

*Table 238. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-082005-5451-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-082005-5451-99</a>

## Lotoor

Lotoor is a generic detection for hack tools that exploit vulnerabilities in order to gain root privileges on compromised Android devices.

*Table 239. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-091922-4449-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-091922-4449-99</a>

## Lovespy

Lovespy is a Trojan horse for Android devices that steals information from the device.

*Table 240. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-071814-3805-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-071814-3805-99</a>

## Lovetrap

Lovetrap is a Trojan horse that sends SMS messages to premium-rate phone numbers.

*Table 241. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-072806-2905-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-072806-2905-99</a>

## Luckycat

Luckycat is a Trojan horse for Android devices that opens a back door and steals information on the compromised device.

*Table 242. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-080617-5343-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-080617-5343-99</a>

## Machinleak

Machinleak is a Trojan horse for Android devices that steals information from the compromised device.

*Table 243. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-120311-2440-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-120311-2440-99</a>

## Maistealer

Maistealer is a Trojan that steals information from Android devices.

*Table 244. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-072411-4350-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-072411-4350-99</a>

## Malapp

Malapp is a generic detection for many individual but varied threats on Android devices that share similar characteristics.

*Table 245. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-073014-3354-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-073014-3354-99</a>

## Malebook

Malebook is a Trojan horse for Android devices that steals information from the compromised device.

*Table 246. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-071206-3403-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-071206-3403-99</a>

## Malhome

Malhome is a Trojan horse for Android devices that steals information from the compromised device.

*Table 247. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-071118-0441-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-071118-0441-99</a>

## Malminer

Malminer is a Trojan horse for Android devices that mines cryptocurrencies on the compromised device.

*Table 248. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-032712-3709-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-032712-3709-99</a>

## Mania

Mania is a Trojan horse for Android devices that sends SMS messages to a premium-rate phone number.

*Table 249. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-070623-1520-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-070623-1520-99</a>

## Maxit

Maxit is a Trojan horse for Android devices that opens a back door on the compromised device. It also steals certain information and uploads it to a remote location.

*Table 250. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-120411-2511-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-120411-2511-99</a>

## MdotM

MdotM is an advertisement library that is bundled with certain Android applications.

*Table 251. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052712-5824-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052712-5824-99</a>

## Medialets

Medialets is an advertisement library that is bundled with certain Android applications.

*Table 252. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052712-5222-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052712-5222-99</a>

## Meshidden

Meshidden is a spyware application for Android devices that allows the device it is installed on to be monitored.

Table 253. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-031913-5257-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-031913-5257-99</a>

## Mesexploit

Mesexploit is a tool for Android devices used to create applications that exploit the Android Fake ID vulnerability.

Table 254. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-032014-2847-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-032014-2847-99</a>

## Mesprank

Mesprank is a Trojan horse for Android devices that opens a back door on the compromised device.

Table 255. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-030717-1933-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-030717-1933-99</a>

## Meswatcherbox

Meswatcherbox is a spyware application for Android devices that forwards SMS messages without the user knowing.

Table 256. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-111612-2736-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-111612-2736-99</a>

## Miji

Miji is an advertisement library that is bundled with certain Android applications.

Table 257. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-032815-4720-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-032815-4720-99</a>



## Milipnot

Milipnot is a Trojan horse for Android devices that steals information from the compromised device.

Table 258. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-070414-0941-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-070414-0941-99</a>

## MillennialMedia

MillennialMedia is an advertisement library that is bundled with certain Android applications.

Table 259. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052712-4602-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052712-4602-99</a>

## Mitcad

Mitcad is an advertisement library that is bundled with certain Android applications.

Table 260. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040212-0528-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040212-0528-99</a>

## MobClix

MobClix is an advertisement library that is bundled with certain Android applications.

Table 261. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052712-4011-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052712-4011-99</a>

## MobFox

MobFox is an advertisement library that is bundled with certain Android applications.

Table 262. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052712-3050-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052712-3050-99</a>

## Mobidisplay

Mobidisplay is an advertisement library that is bundled with certain Android applications.

Table 263. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040312-0435-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040312-0435-99</a>

## Mobigapp

Mobigapp is a Trojan horse for Android devices that downloads applications disguised as system updates.

Table 264. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-062520-5802-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-062520-5802-99</a>

## MobileBackup

MobileBackup is a spyware application for Android devices that monitors the affected device.

Table 265. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-031020-0040-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-031020-0040-99</a>

## Mobilespy

Mobilespy is a Trojan horse that steals information from Android devices.

Table 266. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-071512-0653-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-071512-0653-99</a>

## Mobiletx

Mobiletx is a Trojan horse for Android devices that steals information from the compromised device. It may also send SMS messages to a premium-rate number.

Table 267. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-052807-4439-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-052807-4439-99</a>

## Mobinaspy

Mobinaspy is a spyware application for Android devices that can track the device's location.

Table 268. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-111516-0511-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-111516-0511-99</a>

## Mobus

Mobus is an advertisement library that is bundled with certain Android applications.

Table 269. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-2006-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-2006-99</a>

## MobWin

MobWin is an advertisement library that is bundled with certain Android applications.

Table 270. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-1522-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-1522-99</a>

## Mocore

Mocore is an advertisement library that is bundled with certain Android applications.

Table 271. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-092112-4603-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-092112-4603-99</a>

## Moghava

Moghava is a Trojan horse for Android devices that modifies images that are stored on the device.

Table 272. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-022712-2822-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-022712-2822-99</a>

## Momark

Momark is an advertisement library that is bundled with certain Android applications.

Table 273. Table References

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-040113-5529-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-040113-5529-99)

## Monitorello

Monitorello is a spyware application for Android devices that allows the device it is installed on to be monitored.

Table 274. Table References

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-031914-4737-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-031914-4737-99)

## Moolah

Moolah is an advertisement library that is bundled with certain Android applications.

Table 275. Table References

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-040416-1007-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-040416-1007-99)

## MoPub

MoPub is an advertisement library that is bundled with certain Android applications.

Table 276. Table References

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-052712-2456-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-052712-2456-99)

## Morepaks

Morepaks is a Trojan horse for Android devices that downloads remote files and may display advertisements on the compromised device.

Table 277. Table References

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-071204-1130-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-071204-1130-99)

## Nandrobox

Nandrobox is a Trojan horse for Android devices that steals information from the compromised device. It also deletes certain SMS messages from the device.

Table 278. Table References

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-070212-2132-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-070212-2132-99)

## Netisend

Netisend is a Trojan horse that steals information from Android devices.

Table 279. Table References

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2011-080207-1139-99](https://www.symantec.com/security_response/writeup.jsp?docid=2011-080207-1139-99)

## Nickispy

Nickispy is a Trojan horse that steals information from Android devices.

Table 280. Table References

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2011-072714-3613-99](https://www.symantec.com/security_response/writeup.jsp?docid=2011-072714-3613-99)

## Notcompatible

Notcompatible is a Trojan horse for Android devices that acts as a proxy.

Table 281. Table References

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-050307-2712-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-050307-2712-99)

## Nuhaz

Nuhaz is a Trojan horse for Android devices that may intercept text messages on the compromised device.

Table 282. Table References

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-031814-3416-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-031814-3416-99)

## Nyearleaker

Nyearleaker is a Trojan horse program for Android devices that steals information.

Table 283. Table References

Links

## Obad

Obad is a Trojan horse for Android devices that opens a back door, steals information, and downloads files. It also sends SMS messages to premium-rate numbers and spreads malware to Bluetooth-enabled devices.

*Table 284. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-060411-4146-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-060411-4146-99)

## Oneclickfraud

Oneclickfraud is a Trojan horse for Android devices that attempts to coerce a user into paying for a pornographic service.

*Table 285. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-011205-4412-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-011205-4412-99)

## Opfake

Opfake is a detection for Trojan horses on the Android platform that send SMS texts to premium-rate numbers.

*Table 286. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-012709-2732-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-012709-2732-99)

## Opfake.B

Opfake.B is a Trojan horse for the Android platform that may receive commands from a remote attacker to perform various functions.

*Table 287. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-022406-1309-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-022406-1309-99)

## Ozotshielder

Ozotshielder is a Trojan horse that steals information from Android devices.

*Table 288. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-091505-3230-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-091505-3230-99</a>
---

## Pafloat

Pafloat is an advertisement library that is bundled with certain Android applications.

*Table 289. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040215-2015-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040215-2015-99</a>
---

## PandaAds

PandaAds is an advertisement library that is bundled with certain Android applications.

*Table 290. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040312-1959-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040312-1959-99</a>
---

## Pandbot

Pandbot is a Trojan horse for Android devices that may download more files onto the device.

*Table 291. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-071215-1454-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-071215-1454-99</a>
---

## Pdaspy

Pdaspy is a spyware application for Android devices that periodically gathers information from the device and uploads it to a predetermined location.

*Table 292. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-111612-0749-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-111612-0749-99</a>
---

## Penetho

Penetho is a hacktool for Android devices that can be used to crack the WiFi password of the router that the device is using.

*Table 293. Table References*

Links
-------

## Perkel

Perkel is a Trojan horse for Android devices that may steal information from the compromised device.

*Table 294. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-082811-4213-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-082811-4213-99)

## Phindropper

Phindropper is a Trojan horse for Android devices that sends and intercepts incoming SMS messages.

*Table 295. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-021002-2943-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-021002-2943-99)

## Phospy

Phospy is a Trojan horse for Android devices that steals confidential information from the compromised device.

*Table 296. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-060706-4803-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-060706-4803-99)

## Piddialer

Piddialer is a Trojan horse for Android devices that dials premium-rate numbers from the compromised device.

*Table 297. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-111020-2247-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-111020-2247-99)

## Pikspam

Pikspam is a Trojan horse for Android devices that sends spam SMS messages from the compromised device.

*Table 298. Table References*



Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-121815-0336-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-121815-0336-99</a>
---

## Pincer

Pincer is a Trojan horse for Android devices that steals confidential information and opens a back door on the compromised device.

*Table 299. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-052307-3530-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-052307-3530-99</a>
---

## Pirator

Pirator is a Trojan horse on the Android platform that downloads files and steals potentially confidential information from the compromised device.

*Table 300. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-021609-5740-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-021609-5740-99</a>
---

## Pjapps

Pjapps is a Trojan horse that has been embedded on third party applications and opens a back door on the compromised device. It retrieves commands from a remote command and control server.

*Table 301. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-022303-3344-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-022303-3344-99</a>
---

## Pjapps.B

Pjapps.B is a Trojan horse for Android devices that opens a back door on the compromised device.

*Table 302. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-032014-1624-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-032014-1624-99</a>
---

## Pletora

Pletora is a Trojan horse for Android devices that may lock the compromised device. It then asks the user to pay in order to unlock the device.

*Table 303. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-061217-4345-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-061217-4345-99</a>
---

## Poisoncake

Poisoncake is a Trojan horse for Android devices that opens a back door on the compromised device. It may also download potentially malicious files and steal information.

*Table 304. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-010610-0726-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-010610-0726-99</a>
---

## Pontiflex

Pontiflex is an advertisement library that is bundled with certain Android applications.

*Table 305. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052618-0946-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052618-0946-99</a>
---

## Positmob

Positmob is a Trojan horse program for Android devices that sends SMS messages to premium rate phone numbers.

*Table 306. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-111409-1556-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-111409-1556-99</a>
---

## Premiumtext

Premiumtext is a detection for Trojan horses on the Android platform that send SMS texts to premium-rate numbers. These Trojans will often be repackaged versions of genuine Android software packages, often distributed outside the Android Marketplace.

*Table 307. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-080213-5308-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-080213-5308-99</a>
---

## Pris

Pris is a Trojan horse for Android devices that silently downloads a malicious application and attempts to open a back door on the compromised device.

Table 308. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-061820-5638-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-061820-5638-99</a>

## Qdplugin

Qdplugin is a Trojan horse for Android devices that opens a back door and steals information from the compromised device.

Table 309. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-102510-3330-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-102510-3330-99</a>

## Qicsomos

Qicsomos is a Trojan horse for Android devices that sends SMS messages to a premium-rate phone number.

Table 310. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-011007-2223-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-011007-2223-99</a>

## Qitmo

Qitmo is a Trojan horse for Android devices that steals information from the compromised device.

Table 311. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-030716-4923-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-030716-4923-99</a>

## Rabbhome

Rabbhome is a Trojan horse for Android devices that steals information from the compromised device.

Table 312. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-053007-3750-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-053007-3750-99</a>

## Repane

Repane is a Trojan horse for Android devices that steals information and sends SMS messages from the compromised device.

Table 313. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-090411-5052-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-090411-5052-99</a>

## Reputation.1

Reputation.1 is a detection for Android files based on analysis performed by Norton Mobile Insight.

Table 314. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-022612-2619-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-022612-2619-99</a>

## Reputation.2

Reputation.2 is a detection for Android files based on analysis performed by Norton Mobile Insight.

Table 315. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-022613-2629-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-022613-2629-99</a>

## Reputation.3

Reputation.3 is a detection for Android files based on analysis performed by Norton Mobile Insight.

Table 316. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-022613-3126-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-022613-3126-99</a>

## RevMob

RevMob is an advertisement library that is bundled with certain Android applications.

Table 317. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040308-0502-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040308-0502-99</a>

## Roidsec

Roidsec is a Trojan horse for Android devices that steals confidential information.

Table 318. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-052022-1227-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-052022-1227-99</a>

## Rootcager

Rootcager is a Trojan horse that steals information from Android devices.

*Table 319. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-030212-1438-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-030212-1438-99</a>

## Rootnik

Rootnik is a Trojan horse for Android devices that steals information and downloads additional apps.

*Table 320. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2016-062710-0328-99">https://www.symantec.com/security_response/writeup.jsp?docid=2016-062710-0328-99</a>

## Rufraud

Rufraud is a Trojan horse for Android devices that sends SMS messages to premium-rate phone numbers.

*Table 321. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-121306-2304-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-121306-2304-99</a>

## Rusms

Rusms is a Trojan horse for Android devices that sends SMS messages and steals information from the compromised device.

*Table 322. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-061711-5009-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-061711-5009-99</a>

## Samsapo

Samsapo is a worm for Android devices that spreads by sending SMS messages to all contacts stored on the compromised device. It also opens a back door and downloads files.

*Table 323. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-050111-1908-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-050111-1908-99</a>

## Sandorat

Sandorat is a Trojan horse for Android devices that opens a back door on the compromised device. It also steals information.

Table 324. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-110720-2146-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-110720-2146-99</a>

## Sberick

Sberick is a Trojan horse for Android devices that steals information from the compromised device.

Table 325. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-071014-2146-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-071014-2146-99</a>

## Scartibro

Scartibro is a Trojan horse for Android devices that locks the compromised device and asks the user to pay in order to unlock it.

Table 326. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-080718-2038-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-080718-2038-99</a>

## Scipiox

Scipiox is a Trojan horse for Android devices that steals information from the compromised device.

Table 327. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-100814-4702-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-100814-4702-99</a>

## Selfmite

Selfmite is a worm for Android devices that spreads through SMS messages.

Table 328. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-070111-5857-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-070111-5857-99</a>

## Selfmite.B

Selfmite.B is a worm for Android devices that displays ads on the compromised device. It spreads through SMS messages.

Table 329. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-101013-4717-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-101013-4717-99</a>

## SellARing

SellARing is an advertisement library that is bundled with certain Android applications.

Table 330. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040407-3157-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040407-3157-99</a>

## SendDroid

SendDroid is an advertisement library that is bundled with certain Android applications.

Table 331. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040311-2111-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040311-2111-99</a>

## Simhosy

Simhosy is a Trojan horse for Android devices that steals information from the compromised device.

Table 332. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-061013-3955-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-061013-3955-99</a>

## Simplocker

Simplocker is a Trojan horse for Android devices that may encrypt files on the compromised device. It then asks the user to pay in order to decrypt these files.

Table 333. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-060610-5533-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-060610-5533-99</a>

# Simplocker.B

Simplocker.B is a Trojan horse for Android devices that may encrypt files on the compromised device. It then asks the user to pay in order to decrypt these files.

Table 334. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-072317-1950-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-072317-1950-99</a>

# Skullkey

Skullkey is a Trojan horse for Android devices that gives the attacker remote control of the compromised device to perform malicious activity.

Table 335. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-072322-5422-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-072322-5422-99</a>

# Smaato

Smaato is an advertisement library that is bundled with certain Android applications.

Table 336. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052622-1755-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052622-1755-99</a>

# Smbcheck

Smbcheck is a hacktool for Android devices that can trigger a Server Message Block version 2 (SMBv2) vulnerability and may cause the target computer to crash.

Table 337. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-032613-5634-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-032613-5634-99</a>

# Smsblocker

Smsblocker is a generic detection for threats on Android devices that block the transmission of SMS messages.

Table 338. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-081607-4001-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-081607-4001-99</a>



# Smsbomber

Smsbomber is a program that can be used to send messages to contacts on the device.

Table 339. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-112611-5837-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-112611-5837-99</a>

# Smslink

Smslink is a Trojan horse for Android devices that may send malicious SMS messages from the compromised device. It may also display advertisements.

Table 340. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-112600-3035-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-112600-3035-99</a>

# Smspacem

Smspacem is a Trojan horse that may send SMS messages from Android devices.

Table 341. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-052310-1322-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-052310-1322-99</a>

# SMSReplicator

SMSReplicator is a spying utility that will secretly transmit incoming SMS messages to another phone of the installer's choice.

Table 342. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2010-110214-1252-99">https://www.symantec.com/security_response/writeup.jsp?docid=2010-110214-1252-99</a>

# Smsniffer

Smsniffer is a Trojan horse that intercepts SMS messages on Android devices.

Table 343. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-071108-3626-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-071108-3626-99</a>

## Smsstealer

Smsstealer is a Trojan horse for Android devices that steals information from the compromised device.

*Table 344. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-121514-0214-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-121514-0214-99</a>

## Smstibook

Smstibook is a Trojan horse that attempts to send premium-rate SMS messages to predetermined numbers.

*Table 345. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-051207-4833-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-051207-4833-99</a>

## Smszombie

Smszombie is a Trojan horse for Android devices that steals information from the compromised device.

*Table 346. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-082011-0922-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-082011-0922-99</a>

## Snadapps

Snadapps is a Trojan horse that steals information from Android devices.

*Table 347. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-071807-3111-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-071807-3111-99</a>

## Sockbot

Sockbot is a Trojan horse for Android devices that creates a SOCKS proxy on the compromised device.

*Table 348. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2017-101314-1353-99">https://www.symantec.com/security_response/writeup.jsp?docid=2017-101314-1353-99</a>

# Sokrat

Sokrat is a Trojan horse for Android devices that opens a back door and steals information from the compromised device.

Table 349. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2015-110509-4646-99">https://www.symantec.com/security_response/writeup.jsp?docid=2015-110509-4646-99</a>

# Sofacy

Sofacy is a Trojan horse for Android devices that steals information from the compromised device.

Table 350. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2017-010508-5201-99">https://www.symantec.com/security_response/writeup.jsp?docid=2017-010508-5201-99</a>

# Sosceo

Sosceo is an advertisement library that is bundled with certain Android applications.

Table 351. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040408-0609-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040408-0609-99</a>

# Spitmo

Spitmo is a Trojan horse that steals information from Android devices.

Table 352. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-091407-1435-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-091407-1435-99</a>

# Spitmo.B

Spitmo.B is a Trojan horse for Android devices that steals information from the compromised device.

Table 353. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-030715-0445-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-030715-0445-99</a>

## Spyagent

Spyagent is a spyware application for Android devices that logs certain information and sends SMS messages to a predetermined phone number.

*Table 354. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-090710-1836-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-090710-1836-99</a>

## Spybubble

Spybubble is a Spyware application for Android devices that logs the device's activity and sends it to a predetermined website.

*Table 355. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-121917-0335-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-121917-0335-99</a>

## Spydafon

Spydafon is a Potentially Unwanted Application for Android devices that monitors the affected device.

*Table 356. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-030722-4740-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-030722-4740-99</a>

## Spymple

Spymple is a spyware application for Android devices that allows the device it is installed on to be monitored.

*Table 357. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-031914-5403-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-031914-5403-99</a>

## Spyoo

Spyoo is a spyware program for Android devices that records and sends certain information to a remote location.

*Table 358. Table References*

Links
-------

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-081709-0457-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-081709-0457-99)

## Spyteckcell

Spyteckcell is a spyware program for Android devices that monitors and sends certain information to a remote location.

*Table 359. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-121021-0730-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-121021-0730-99)

## Spytrack

Spytrack is a spyware program for Android devices that periodically sends certain information to a remote location.

*Table 360. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-080109-5710-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-080109-5710-99)

## Spywaller

Spywaller is a Trojan horse for Android devices that steals information from the compromised device.

*Table 361. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2015-121807-0203-99](https://www.symantec.com/security_response/writeup.jsp?docid=2015-121807-0203-99)

## Stealthgenie

Stealthgenie is a Trojan horse for Android devices that steals information from the compromised device.

*Table 362. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-111416-1306-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-111416-1306-99)

## Steek

Steek is a potentially unwanted application that is placed on a download website for Android applications and disguised as popular applications.

*Table 363. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-010911-3142-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-010911-3142-99</a>
---

## Stels

Stels is a Trojan horse for Android devices that opens a back door and steals information from the compromised device.

*Table 364. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-032910-0254-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-032910-0254-99</a>
---

## Stiniter

Stiniter is a Trojan horse for Android devices that sends SMS messages to a premium-rate phone number.

*Table 365. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-030903-5228-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-030903-5228-99</a>
---

## Sumzand

Sumzand is a Trojan horse for Android devices that steals information and sends it to a remote location.

*Table 366. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-080308-2851-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-080308-2851-99</a>
---

## Sysecsms

Sysecsms is a Trojan horse for Android devices that steals information from the compromised device.

*Table 367. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-122714-5228-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-122714-5228-99</a>
---

## Tanci

Tanci is an advertisement library that is bundled with certain Android applications.

*Table 368. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-032815-4108-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-032815-4108-99</a>
---

## Tapjoy

Tapjoy is an advertisement library that is bundled with certain Android applications.

*Table 369. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052619-4702-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052619-4702-99</a>
---

## Tapsnake

Tapsnake is a Trojan horse for Android phones that is embedded into a game. It tracks the phone's location and posts it to a remote web service.

*Table 370. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2010-081214-2657-99">https://www.symantec.com/security_response/writeup.jsp?docid=2010-081214-2657-99</a>
---

## Tascudap

Tascudap is a Trojan horse for Android devices that uses the compromised device in denial of service attacks.

*Table 371. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-121312-4547-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-121312-4547-99</a>
---

## Teelog

Teelog is a Trojan horse for Android devices that opens a back door and steals information from the compromised device.

*Table 372. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-040215-2736-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-040215-2736-99</a>
---

## Temai

Temai is a Trojan horse for Android applications that opens a back door and downloads malicious files onto the compromised device.

*Table 373. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-091722-4052-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-091722-4052-99</a>
---

## Tetus

Tetus is a Trojan horse for Android devices that steals information from the compromised device.

*Table 374. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-012409-4705-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-012409-4705-99</a>
---

## Tgpush

Tgpush is an advertisement library that is bundled with certain Android applications.

*Table 375. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-032816-0259-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-032816-0259-99</a>
---

## Tigerbot

Tigerbot is a Trojan horse for Android devices that opens a back door on the compromised device.

*Table 376. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-041010-2221-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-041010-2221-99</a>
---

## Tonclank

Tonclank is a Trojan horse that steals information and may open a back door on Android devices.

*Table 377. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-061012-4545-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-061012-4545-99</a>
---

## Trogle

Trogle is a worm for Android devices that may steal information from the compromised device.

*Table 378. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-081213-5553-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-081213-5553-99</a>
---



## Twikabot

Twikabot is a Trojan horse for Android devices that attempts to steal information.

*Table 379. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-062614-5813-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-062614-5813-99</a>

## Uapush

Uapush is a Trojan horse for Android devices that steals information from the compromised device. It may also display advertisements and send SMS messages from the compromised device.

*Table 380. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-040114-2910-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-040114-2910-99</a>

## Umeng

Umeng is an advertisement library that is bundled with certain Android applications.

*Table 381. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040307-5749-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040307-5749-99</a>

## Updtbot

Updtbot is a Trojan horse for Android devices that may arrive through SMS messages. It may then open a back door on the compromised device.

*Table 382. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-041611-4136-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-041611-4136-99</a>

## Upush

Upush is an advertisement library that is bundled with certain Android applications.

*Table 383. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040207-0733-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040207-0733-99</a>

## Uracto

Uracto is a Trojan horse for Android devices that steals personal information and sends spam SMS messages to contacts found on the compromised device.

*Table 384. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-031805-2722-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-031805-2722-99</a>

## Uranico

Uranico is a Trojan horse for Android devices that steals information from the compromised device.

*Table 385. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-052803-3835-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-052803-3835-99</a>

## Usbcleaver

Usbcleaver is a Trojan horse for Android devices that steals information from the compromised device.

*Table 386. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-062010-1818-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-062010-1818-99</a>

## Utchi

Utchi is an advertisement library that is bundled with certain Android applications.

*Table 387. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040107-2536-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040107-2536-99</a>

## Uten

Uten is a Trojan horse for Android devices that may send, block, and delete SMS messages on a compromised device. It may also download and install additional applications and attempt to gain root privileges.

*Table 388. Table References*

Links
-------

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2013-092316-4752-99](https://www.symantec.com/security_response/writeup.jsp?docid=2013-092316-4752-99)

## Uupay

Uupay is a Trojan horse for Android devices that steals information from the compromised device. It may also download additional malware.

*Table 389. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-061714-1550-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-061714-1550-99)

## Uxipp

Uxipp is a Trojan horse that attempts to send premium-rate SMS messages to predetermined numbers.

*Table 390. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2011-060910-5804-99](https://www.symantec.com/security_response/writeup.jsp?docid=2011-060910-5804-99)

## Vdloader

Vdloader is a Trojan horse for Android devices that opens a back door on the compromised device and steals confidential information.

*Table 391. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-080209-1420-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-080209-1420-99)

## VDopia

VDopia is an advertisement library that is bundled with certain Android applications.

*Table 392. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2014-052712-1559-99](https://www.symantec.com/security_response/writeup.jsp?docid=2014-052712-1559-99)

## Virusshield

Virusshield is a Trojan horse for Android devices that claims to scan apps and protect personal information, but has no real functionality.

*Table 393. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040810-5457-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040810-5457-99</a>
---

## VServ

VServ is an advertisement library that is bundled with certain Android applications.

*Table 394. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-052619-3117-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-052619-3117-99</a>
---

## Walkinwat

Walkinwat is a Trojan horse that steals information from the compromised device.

*Table 395. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-033008-4831-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-033008-4831-99</a>
---

## Waps

Waps is an advertisement library that is bundled with certain Android applications.

*Table 396. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040406-5437-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040406-5437-99</a>
---

## Waren

Waren is an advertisement library that is bundled with certain Android applications.

*Table 397. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-032815-5501-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-032815-5501-99</a>
---

## Windseeker

Windseeker is a Trojan horse for Android devices that steals information from the compromised device.

*Table 398. Table References*

Links
-------

<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-101519-0720-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-101519-0720-99</a>
---

## Wiyun

Wiyun is an advertisement library that is bundled with certain Android applications.

*Table 399. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040207-5646-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040207-5646-99</a>

## Wooboo

Wooboo is an advertisement library that is bundled with certain Android applications.

*Table 400. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040407-5829-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040407-5829-99</a>

## Wqmobile

Wqmobile is an advertisement library that is bundled with certain Android applications.

*Table 401. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040407-4926-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040407-4926-99</a>

## YahooAds

YahooAds is an advertisement library that is bundled with certain Android applications.

*Table 402. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-060621-3229-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-060621-3229-99</a>

## Yatoot

Yatoot is a Trojan horse for Android devices that steals information from the compromised device.

*Table 403. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-031408-4748-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-031408-4748-99</a>

## Yinhan

Yinhan is an advertisement library that is bundled with certain Android applications.

Table 404. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040107-3350-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040107-3350-99</a>

## Youmi

Youmi is an advertisement library that is bundled with certain Android applications.

Table 405. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-040407-4318-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-040407-4318-99</a>

## YuMe

YuMe is an advertisement library that is bundled with certain Android applications.

Table 406. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2014-060621-0322-99">https://www.symantec.com/security_response/writeup.jsp?docid=2014-060621-0322-99</a>

## Zeahache

Zeahache is a Trojan horse that elevates privileges on the compromised device.

Table 407. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2011-032309-5042-99">https://www.symantec.com/security_response/writeup.jsp?docid=2011-032309-5042-99</a>

## ZertSecurity

ZertSecurity is a Trojan horse for Android devices that steals information and sends it to a remote attacker.

Table 408. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2013-050820-4100-99">https://www.symantec.com/security_response/writeup.jsp?docid=2013-050820-4100-99</a>

## ZestAdz

ZestAdz is an advertisement library that is bundled with certain Android applications.

Table 409. Table References

Links
-------

## Zeusmitmo

Zeusmitmo is a Trojan horse for Android devices that opens a back door and steals information from the compromised device.

*Table 410. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2012-080818-0448-99](https://www.symantec.com/security_response/writeup.jsp?docid=2012-080818-0448-99)

## Banker

A list of banker malware..



Banker is a cluster galaxy available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

Unknown

## Zeus

Zeus is a trojan horse that is primarily delivered via drive-by-downloads, malvertising, exploit kits and malspam campaigns. It uses man-in-the-browser keystroke logging and form grabbing to steal information from victims. Source was leaked in 2011.

Zeus is also known as:

- Zbot

*Table 411. Table References*

Links

<https://usa.kaspersky.com/resource-center/threats/zeus-virus>

## Vawtrak

Delivered primarily by exploit kits as well as malspam campaigns utilizing macro based Microsoft Office documents as attachments. Vawtrak/Neverquest is a modularized banking trojan designed to steal credentials through harvesting, keylogging, Man-In-The-Browser, etc.

Vawtrak is also known as:

- Neverquest

*Table 412. Table References*

## Links

<https://www.kaspersky.com/blog/neverquest-trojan-built-to-steal-from-hundreds-of-banks/3247/>

<https://www.fidelissecurity.com/threatgeek/2016/05/vawtrak-trojan-bank-it-evolving>

<https://www.proofpoint.com/us/threat-insight/post/In-The-Shadows>

<https://www.botconf.eu/wp-content/uploads/2016/11/2016-Vawtrak-technical-report.pdf>

## Dridex

Dridex leverages redirection attacks designed to send victims to malicious replicas of the banking sites they think they're visiting.

Dridex is also known as:

- Feodo Version D

*Table 413. Table References*

## Links

<https://blog.malwarebytes.com/detections/trojan-dridex/>

<https://feodotracker.abuse.ch/>

## Gozi

Banking trojan delivered primarily via email (typically malspam) and exploit kits. Gozi 1.0 source leaked in 2010

Gozi is also known as:

- Ursnif
- CRM
- Snifula
- Papras

*Table 414. Table References*

## Links

<https://www.secureworks.com/research/gozi>

<https://www.gdatasoftware.com/blog/2016/11/29325-analysis-ursnif-spying-on-your-data-since-2007>

[https://lokalhost.pl/gozi\\_tree.txt](https://lokalhost.pl/gozi_tree.txt)

## GoziV2

Banking trojan attributed to Project Blitzkrieg targeting U.S. Financial institutions.



Goziv2 is also known as:

- Prinimalka

Table 415. Table References

Links
<a href="https://krebsonsecurity.com/tag/gozi-prinimalka/">https://krebsonsecurity.com/tag/gozi-prinimalka/</a>
<a href="https://securityintelligence.com/project-blitzkrieg-how-to-block-the-planned-prinimalka-gozi-trojan-attack/">https://securityintelligence.com/project-blitzkrieg-how-to-block-the-planned-prinimalka-gozi-trojan-attack/</a>
<a href="https://lokalhost.pl/gozi_tree.txt">https://lokalhost.pl/gozi_tree.txt</a>

## Gozi ISFB

Banking trojan based on Gozi source. Features include web injects for the victims' browsers, screenshotting, video recording, transparent redirections, etc. Source leaked ~ end of 2015.

Table 416. Table References

Links
<a href="https://www.govcert.admin.ch/blog/18/gozi-isfb-when-a-bug-really-is-a-feature">https://www.govcert.admin.ch/blog/18/gozi-isfb-when-a-bug-really-is-a-feature</a>
<a href="https://blog.malwarebytes.com/threat-analysis/2017/04/binary-options-malvertising-campaign-drops-isfb-banking-trojan/">https://blog.malwarebytes.com/threat-analysis/2017/04/binary-options-malvertising-campaign-drops-isfb-banking-trojan/</a>
<a href="https://info.phishlabs.com/blog/the-unrelenting-evolution-of-vawtrak">https://info.phishlabs.com/blog/the-unrelenting-evolution-of-vawtrak</a>
<a href="https://lokalhost.pl/gozi_tree.txt">https://lokalhost.pl/gozi_tree.txt</a>

## Dreambot

Dreambot is a variant of Gozi ISFB that is spread via numerous exploit kits as well as through malspam email attachments and links.

Table 417. Table References

Links
<a href="https://blog.malwarebytes.com/threat-analysis/2017/04/binary-options-malvertising-campaign-drops-isfb-banking-trojan/">https://blog.malwarebytes.com/threat-analysis/2017/04/binary-options-malvertising-campaign-drops-isfb-banking-trojan/</a>
<a href="https://www.proofpoint.com/us/threat-insight/post/ursnif-variant-dreambot-adds-tor-functionality">https://www.proofpoint.com/us/threat-insight/post/ursnif-variant-dreambot-adds-tor-functionality</a>
<a href="https://lokalhost.pl/gozi_tree.txt">https://lokalhost.pl/gozi_tree.txt</a>

## IAP

Gozi ISFB variant

Table 418. Table References

Links
<a href="https://lokalhost.pl/gozi_tree.txt">https://lokalhost.pl/gozi_tree.txt</a>

## GozNym

GozNym hybrid takes the best of both the Nymaim and Gozi ISFB. From the Nymaim malware, it leverages the dropper's stealth and persistence; the Gozi ISFB parts add the banking Trojan's capabilities to facilitate fraud via infected Internet browsers.

*Table 419. Table References*

Links
<a href="https://securityintelligence.com/meet-goznym-the-banking-malware-offspring-of-gozi-isfb-and-nymaim/">https://securityintelligence.com/meet-goznym-the-banking-malware-offspring-of-gozi-isfb-and-nymaim/</a>
<a href="https://lokalhost.pl/gozi_tree.txt">https://lokalhost.pl/gozi_tree.txt</a>

## Zloader Zeus

Zloader is a loader that loads different payloads, one of which is a Zeus module. Delivered via exploit kits and malspam emails.

Zloader Zeus is also known as:

- Zeus Terdot

*Table 420. Table References*

Links
<a href="https://blog.threatstop.com/zloader/terdot-that-man-in-the-middle">https://blog.threatstop.com/zloader/terdot-that-man-in-the-middle</a>
<a href="https://www.scmagazine.com/terdot-zloaderzbot-combo-abuses-certificate-app-to-pull-off-mitm-browser-attacks/article/634443/">https://www.scmagazine.com/terdot-zloaderzbot-combo-abuses-certificate-app-to-pull-off-mitm-browser-attacks/article/634443/</a>

## Zeus VM

Zeus variant that utilizes steganography in image files to retrieve configuration file.

Zeus VM is also known as:

- VM Zeus

*Table 421. Table References*

Links
<a href="https://blog.malwarebytes.com/threat-analysis/2014/02/hiding-in-plain-sight-a-story-about-a-sneaky-banking-trojan/">https://blog.malwarebytes.com/threat-analysis/2014/02/hiding-in-plain-sight-a-story-about-a-sneaky-banking-trojan/</a>
<a href="https://securityintelligence.com/new-zberp-trojan-discovered-zeus-zbot-carberp/">https://securityintelligence.com/new-zberp-trojan-discovered-zeus-zbot-carberp/</a>

## Zeus Sphinx

Sphinx is a modular banking trojan that is a commercial offering sold to cybercriminals via underground fraudster boards.

Table 422. Table References

Links
<a href="https://securityintelligence.com/brazil-cant-catch-a-break-after-panda-comes-the-sphinx/">https://securityintelligence.com/brazil-cant-catch-a-break-after-panda-comes-the-sphinx/</a>

## Panda Banker

Zeus like banking trojan that is delivered primarily through malspam emails and exploit kits.

Panda Banker is also known as:

- Zeus Panda

Table 423. Table References

Links
<a href="https://www.proofpoint.com/us/threat-insight/post/panda-banker-new-banking-trojan-hits-the-market">https://www.proofpoint.com/us/threat-insight/post/panda-banker-new-banking-trojan-hits-the-market</a>
<a href="https://cyberwtf.files.wordpress.com/2017/07/panda-whitepaper.pdf">https://cyberwtf.files.wordpress.com/2017/07/panda-whitepaper.pdf</a>

## Zeus KINS

Zeus KINS is a modified version of Zeus 2.0.8.9. It contains an encrypted version of it's config in the registry.

Zeus KINS is also known as:

- Kasper Internet Non-Security
- Maple

Table 424. Table References

Links
<a href="https://securityintelligence.com/zeus-maple-variant-targets-canadian-online-banking-customers/">https://securityintelligence.com/zeus-maple-variant-targets-canadian-online-banking-customers/</a>
<a href="https://github.com/nyx0/KINS">https://github.com/nyx0/KINS</a>

## Chthonic

Chthonic according to Kaspersky is an evolution of Zeus VM. It uses the same encryptor as Andromeda bot, the same encryption scheme as Zeus AES and Zeus V2 Trojans, and a virtual machine similar to that used in ZeusVM and KINS malware.

Table 425. Table References

## Links

<https://www.proofpoint.com/us/threat-insight/post/threat-actors-using-legitimate-paypal-accounts-to-distribute-chthonic-banking-trojan>

<https://securelist.com/chthonic-a-new-modification-of-zeus/68176/>

# Trickbot

Trickbot is a bot that is delivered via exploit kits and malspam campaigns. The bot is capable of downloading modules, including a banker module. Trickbot also shares roots with the Dyre banking trojan

Trickbot is also known as:

- Trickster
- Trickloader

*Table 426. Table References*

## Links

<https://blog.malwarebytes.com/threat-analysis/2016/10/trick-bot-dyrezas-successor/>

<https://blog.malwarebytes.com/threat-analysis/2017/08/trickbot-comes-with-new-tricks-attacking-outlook-and-browsing-data/>

<http://www.pwc.co.uk/issues/cyber-security-data-privacy/research/trickbots-bag-of-tricks.html>

<https://www.flashpoint-intel.com/blog/new-version-trickbot-adds-worm-propagation-module/>

# Dyre

Dyre is a banking trojan distributed via exploit kits and malspam emails primarily. It has a modular architecture and utilizes man-in-the-browser functionality. It also leverages a backconnect server that allows threat actors to connect to a bank website through the victim's computer.

Dyre is also known as:

- Dyreza

*Table 427. Table References*

## Links

<https://www.secureworks.com/research/dyre-banking-trojan>

<https://blog.malwarebytes.com/threat-analysis/2015/11/a-technical-look-at-dyreza/>

# Tinba

Tinba is a very small banking trojan that hooks into browsers and steals login data and sniffs on network traffic. It also uses Man in The Browser (MiTB) and webinjects. Tinba is primarily delivered via exploit kits, malvertising and malspam email campaigns.

Tinba is also known as:

- Zusy
- TinyBanker
- illi

Table 428. Table References

Links
<a href="https://securityblog.switch.ch/2015/06/18/so-long-and-thanks-for-all-the-domains/">https://securityblog.switch.ch/2015/06/18/so-long-and-thanks-for-all-the-domains/</a>
<a href="http://securityintelligence.com/tinba-malware-reloaded-and-attacking-banks-around-the-world/">http://securityintelligence.com/tinba-malware-reloaded-and-attacking-banks-around-the-world/</a>
<a href="https://blog.avast.com/2014/09/15/tiny-banker-trojan-targets-customers-of-major-banks-worldwide/">https://blog.avast.com/2014/09/15/tiny-banker-trojan-targets-customers-of-major-banks-worldwide/</a>
<a href="http://my.infotex.com/tiny-banker-trojan/">http://my.infotex.com/tiny-banker-trojan/</a>

## Geodo

Geodo is a banking trojan delivered primarily through malspam emails. It is capable of sniffing network activity to steal information by hooking certain network API calls.

Geodo is also known as:

- Feodo Version C
- Emotet

Table 429. Table References

Links
<a href="https://feodotracker.abuse.ch/">https://feodotracker.abuse.ch/</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/new-banking-malware-uses-network-sniffing-for-data-theft/">http://blog.trendmicro.com/trendlabs-security-intelligence/new-banking-malware-uses-network-sniffing-for-data-theft/</a>

## Feodo

Feodo is a banking trojan that utilizes web injects and is also capable of monitoring & manipulating cookies. Version A = Port 8080, Version B = Port 80 It is delivered primarily via exploit kits and malspam emails.

Feodo is also known as:

- Bugat
- Cridex

Table 430. Table References

Links
<a href="https://securelist.com/dridex-a-history-of-evolution/78531/">https://securelist.com/dridex-a-history-of-evolution/78531/</a>
<a href="https://feodotracker.abuse.ch/">https://feodotracker.abuse.ch/</a>

## Ramnit

Originally not a banking trojan in 2010, Ramnit became a banking trojan after the Zeus source code leak. It is capable of performing Man-in-the-Browser attacks. Distributed primarily via exploit kits.

Ramnit is also known as:

- Nimnul

Table 431. Table References

Links
<a href="https://www.cert.pl/en/news/single/ramnit-in-depth-analysis/">https://www.cert.pl/en/news/single/ramnit-in-depth-analysis/</a>

## Qakbot

Qakbot is a banking trojan that leverages webinjects to steal banking information from victims. It also utilizes DGA for command and control. It is primarily delivered via exploit kits.

Qakbot is also known as:

- Qbot
- Pinkslipbot

Table 432. Table References

Links
<a href="https://securityintelligence.com/qakbot-banking-trojan-causes-massive-active-directory-lockouts/">https://securityintelligence.com/qakbot-banking-trojan-causes-massive-active-directory-lockouts/</a>
<a href="https://www.johannesbader.ch/2016/02/the-dga-of-qakbot/">https://www.johannesbader.ch/2016/02/the-dga-of-qakbot/</a>
<a href="https://www.virusbulletin.com/uploads/pdf/magazine/2016/VB2016-Karve-et-al.pdf">https://www.virusbulletin.com/uploads/pdf/magazine/2016/VB2016-Karve-et-al.pdf</a>

## Corebot

Corebot is a modular trojan that leverages a banking module that can perform browser hooking, form grabbing, MitM, webinjection to steal financial information from victims. Distributed primarily via malspam emails and exploit kits.

Table 433. Table References

Links
<a href="https://securityintelligence.com/an-overnight-sensation-corebot-returns-as-a-full-fledged-financial-malware/">https://securityintelligence.com/an-overnight-sensation-corebot-returns-as-a-full-fledged-financial-malware/</a>
<a href="https://www.arbornetworks.com/blog/asert/wp-content/uploads/2016/02/ASERT-Threat-Intelligence-Brief-2016-02-Corebot-1.pdf">https://www.arbornetworks.com/blog/asert/wp-content/uploads/2016/02/ASERT-Threat-Intelligence-Brief-2016-02-Corebot-1.pdf</a>

<https://malwarebreakdown.com/2017/09/11/re-details-malspam-downloads-corebot-banking-trojan/>

## TinyNuke

TinyNuke is a modular banking trojan that includes a HiddenDesktop/VNC server and reverse SOCKS 4 server. It's main functionality is to make web injections into specific pages to steal user data. Distributed primarily via malspam emails and exploit kits.

TinyNuke is also known as:

- NukeBot
- Nuclear Bot
- MicroBankingTrojan
- Xbot

Table 434. Table References

Links
<a href="https://securelist.com/the-nukebot-banking-trojan-from-rough-drafts-to-real-threats/78957/">https://securelist.com/the-nukebot-banking-trojan-from-rough-drafts-to-real-threats/78957/</a>
<a href="https://www.arbornetworks.com/blog/asert/dismantling-nuclear-bot/">https://www.arbornetworks.com/blog/asert/dismantling-nuclear-bot/</a>
<a href="https://securityintelligence.com/the-nukebot-trojan-a-bruised-ego-and-a-surprising-source-code-leak/">https://securityintelligence.com/the-nukebot-trojan-a-bruised-ego-and-a-surprising-source-code-leak/</a>
<a href="http://www.kernelmode.info/forum/viewtopic.php?f=16&amp;t=4596">http://www.kernelmode.info/forum/viewtopic.php?f=16&amp;t=4596</a>
<a href="https://benkowlab.blogspot.ca/2017/08/quick-look-at-another-alina-fork-xbot.html">https://benkowlab.blogspot.ca/2017/08/quick-look-at-another-alina-fork-xbot.html</a>

## Retefe

Retefe is a banking trojan that is distributed by what SWITCH CERT calls the Retefe gang or Operation Emmental. It uses geolocation based targeting. It also leverages fake root certificate and changes the DNS server for domain name resolution in order to display fake banking websites to victims. It is spread primarily through malspam emails.

Retefe is also known as:

- Tsukuba
- Werdlod

Table 435. Table References

Links
<a href="https://www.govcert.admin.ch/blog/33/the-retefe-saga">https://www.govcert.admin.ch/blog/33/the-retefe-saga</a>
<a href="https://threatpost.com/eternalblue-exploit-used-in-retefe-banking-trojan-campaign/128103/">https://threatpost.com/eternalblue-exploit-used-in-retefe-banking-trojan-campaign/128103/</a>
<a href="https://countuponsecurity.com/2016/02/29/retefe-banking-trojan/">https://countuponsecurity.com/2016/02/29/retefe-banking-trojan/</a>
<a href="https://securityblog.switch.ch/2014/11/05/retefe-with-a-new-twist/">https://securityblog.switch.ch/2014/11/05/retefe-with-a-new-twist/</a>

## ReactorBot

ReactorBot is sometimes mistakenly tagged as Rovnix. ReactorBot is a full fledged modular bot that includes a banking module that has roots with the Carberp banking trojan. Distributed primarily via malspam emails.

Table 436. Table References

Links
<a href="http://www.malwaredigger.com/2015/06/rovnix-payload-and-plugin-analysis.html">http://www.malwaredigger.com/2015/06/rovnix-payload-and-plugin-analysis.html</a>
<a href="https://www.symantec.com/connect/blogs/new-carberp-variant-heads-down-under">https://www.symantec.com/connect/blogs/new-carberp-variant-heads-down-under</a>
<a href="http://www.malwaredigger.com/2015/05/rovnix-dropper-analysis.html">http://www.malwaredigger.com/2015/05/rovnix-dropper-analysis.html</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/rovnix-infects-systems-with-password-protected-macros/">http://blog.trendmicro.com/trendlabs-security-intelligence/rovnix-infects-systems-with-password-protected-macros/</a>

## Matrix Banker

Matrix Banker is named accordingly because of the Matrix reference in it's C2 panel. Distributed primarily via malspam emails.

Table 437. Table References

Links
<a href="https://www.arbornetworks.com/blog/asert/another-banker-enters-matrix/">https://www.arbornetworks.com/blog/asert/another-banker-enters-matrix/</a>

## Zeus Gameover

Zeus Gameover captures banking credentials from infected computers, then use those credentials to initiate or re-direct wire transfers to accounts overseas that are controlled by the criminals. GameOver has a decentralized, peer-to-peer command and control infrastructure rather than centralized points of origin. Distributed primarily via malspam emails and exploit kits.

Table 438. Table References

Links
<a href="https://heimdalsecurity.com/blog/zeus-gameover/">https://heimdalsecurity.com/blog/zeus-gameover/</a>
<a href="https://www.us-cert.gov/ncas/alerts/TA14-150A">https://www.us-cert.gov/ncas/alerts/TA14-150A</a>

## SpyEye

SpyEye is a similar to the Zeus botnet banking trojan. It utilizes a web control panel for C2 and can perform form grabbing, autofill credit card modules, ftp grabber, pop3 grabber and HTTP basic access authorization grabber. It also contained a Kill Zeus feature which would remove any Zeus infections if SpyEye was on the system. Distributed primarily via exploit kits and malspam emails.



Table 439. Table References

Links
<a href="https://www.ioactive.com/pdfs/ZeusSpyEyeBankingTrojanAnalysis.pdf">https://www.ioactive.com/pdfs/ZeusSpyEyeBankingTrojanAnalysis.pdf</a>
<a href="https://www.computerworld.com/article/2509482/security0/spyeye-trojan-defeating-online-banking-defenses.html">https://www.computerworld.com/article/2509482/security0/spyeye-trojan-defeating-online-banking-defenses.html</a>
<a href="https://www.symantec.com/connect/blogs/spyeye-bot-versus-zeus-bot">https://www.symantec.com/connect/blogs/spyeye-bot-versus-zeus-bot</a>

## Citadel

Citadel is an offspring of the Zeus banking trojan. Delivered primarily via exploit kits.

Table 440. Table References

Links
<a href="https://blog.malwarebytes.com/threat-analysis/2012/11/citadel-a-cyber-criminals-ultimate-weapon/">https://blog.malwarebytes.com/threat-analysis/2012/11/citadel-a-cyber-criminals-ultimate-weapon/</a>
<a href="https://krebsonsecurity.com/tag/citadel-trojan/">https://krebsonsecurity.com/tag/citadel-trojan/</a>
<a href="https://securityintelligence.com/cybercriminals-use-citadel-compromise-password-management-authentication-solutions/">https://securityintelligence.com/cybercriminals-use-citadel-compromise-password-management-authentication-solutions/</a>

## Atmos

Atmos is derived from the Citadel banking trojan. Delivered primarily via exploit kits and malspam emails.

Table 441. Table References

Links
<a href="https://heimdalsecurity.com/blog/security-alert-citadel-trojan-resurfaces-atmos-zeus-legacy/">https://heimdalsecurity.com/blog/security-alert-citadel-trojan-resurfaces-atmos-zeus-legacy/</a>
<a href="http://www.xylibox.com/2016/02/citadel-0011-atmos.html">http://www.xylibox.com/2016/02/citadel-0011-atmos.html</a>

## Ice IX

Ice IX is a bot created using the source code of Zeus 2.0.8.9. No major improvements compared to Zeus 2.0.8.9.

Table 442. Table References

Links
<a href="https://securelist.com/ice-ix-not-cool-at-all/29111/">https://securelist.com/ice-ix-not-cool-at-all/29111/</a> [ <a href="https://securelist.com/ice-ix-not-cool-at-all/29111/">https://securelist.com/ice-ix-not-cool-at-all/29111/</a> ]

## Zitmo

Zeus in the mobile. Banking trojan developed for mobile devices such as Windows Mobile, Blackberry and Android.

Table 443. Table References

Links
<a href="https://securelist.com/zeus-in-the-mobile-for-android-10/29258/">https://securelist.com/zeus-in-the-mobile-for-android-10/29258/</a>

## Licat

Banking trojan based on Zeus V2. Murofet is a newer version of Licat found ~end of 2011

Licat is also known as:

- Murofet

Table 444. Table References

Links
<a href="https://johannesbader.ch/2015/09/three-variants-of-murofets-dga/">https://johannesbader.ch/2015/09/three-variants-of-murofets-dga/</a>
<a href="https://www.trendmicro.com/vinfo/us/threat-encyclopedia/malware/PE_LICAT.A">https://www.trendmicro.com/vinfo/us/threat-encyclopedia/malware/PE_LICAT.A</a>
<a href="https://www.microsoft.com/en-us/wdsi/threats/malware-encyclopedia-description?Name=Virus%3aWin32%2fMurofet.A">https://www.microsoft.com/en-us/wdsi/threats/malware-encyclopedia-description?Name=Virus%3aWin32%2fMurofet.A</a>

## Skynet

Skynet is a Tor-powered trojan with DDoS, Bitcoin mining and Banking capabilities. Spread via USENET as per rapid7.

Table 445. Table References

Links
<a href="https://blog.rapid7.com/2012/12/06/skynet-a-tor-powered-botnet-straight-from-reddit/">https://blog.rapid7.com/2012/12/06/skynet-a-tor-powered-botnet-straight-from-reddit/</a>

## Cert EU GovSector

Cert EU GovSector.



Cert EU GovSector is a cluster galaxy available in JSON format at [https://github.com/MISP/misp-galaxy/blob/master/clusters/cert\\_eu\\_govsector.json](https://github.com/MISP/misp-galaxy/blob/master/clusters/cert_eu_govsector.json)[**this location**] The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

Various

## Constituency

## EU-Centric

## EU-nearby

## World-class

## Unknown

## Outside World

## Exploit-Kit

Exploit-Kit is an enumeration of some exploitation kits used by adversaries. The list includes document, browser and router exploit kits. It's not meant to be totally exhaustive but aim at covering the most seen in the past 5 years.



Exploit-Kit is a cluster galaxy available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

Kafeine - Will Metcalf - KahuSecurity

## Astrum

Astrum Exploit Kit is a private Exploit Kit used in massive scale malvertising campaigns. It's notable by its use of Steganography

Astrum is also known as:

- Stegano EK

Table 446. Table References

Links
<a href="http://malware.dontneedcoffee.com/2014/09/astrum-ek.html">http://malware.dontneedcoffee.com/2014/09/astrum-ek.html</a>
<a href="http://www.welivesecurity.com/2016/12/06/readers-popular-websites-targeted-stealthy-stegano-exploit-kit-hiding-pixels-malicious-ads/">http://www.welivesecurity.com/2016/12/06/readers-popular-websites-targeted-stealthy-stegano-exploit-kit-hiding-pixels-malicious-ads/</a>

## Bingo

Bingo EK is the name chosen by the defense for a Fiesta-ish EK first spotted in March 2017 and targeting at that times mostly Russia

# Terror EK

Terror EK is built on Hunter, Sundown and RIG EK code

Terror EK is also known as:

- Blaze EK
- Neptune EK

Table 447. Table References

Links
<a href="https://www.trustwave.com/Resources/SpiderLabs-Blog/Terror-Exploit-Kit—More-like-Error-Exploit-Kit/">https://www.trustwave.com/Resources/SpiderLabs-Blog/Terror-Exploit-Kit—More-like-Error-Exploit-Kit/</a>

# DealersChoice

DealersChoice is a Flash Player Exploit platform triggered by RTF

DealersChoice is also known as:

- Sednit RTF EK

Table 448. Table References

Links
<a href="http://researchcenter.paloaltonetworks.com/2016/10/unit42-dealerschoice-sofacys-flash-player-exploit-platform/">http://researchcenter.paloaltonetworks.com/2016/10/unit42-dealerschoice-sofacys-flash-player-exploit-platform/</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/pawn-storm-ramps-up-spear-phishing-before-zero-days-get-patched/">http://blog.trendmicro.com/trendlabs-security-intelligence/pawn-storm-ramps-up-spear-phishing-before-zero-days-get-patched/</a>

# DNSChanger

DNSChanger Exploit Kit is an exploit kit targeting Routers via the browser

DNSChanger is also known as:

- RouterEK

Table 449. Table References

Links
<a href="http://malware.dontneedcoffee.com/2015/05/an-exploit-kit-dedicated-to-csrf.html">http://malware.dontneedcoffee.com/2015/05/an-exploit-kit-dedicated-to-csrf.html</a>
<a href="https://www.proofpoint.com/us/threat-insight/post/home-routers-under-attack-malvertising-windows-android-devices">https://www.proofpoint.com/us/threat-insight/post/home-routers-under-attack-malvertising-windows-android-devices</a>

# Disdain

Disdain EK has been introduced on underground forum on 2017-08-07. The panel is stolen from Sundown, the pattern are Terror alike and the obfuscation reminds Nebula

Table 450. Table References

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/new-disdain-exploit-kit-detected-wild/">http://blog.trendmicro.com/trendlabs-security-intelligence/new-disdain-exploit-kit-detected-wild/</a>

# Kaixin

Kaixin is an exploit kit mainly seen behind compromised website in Asia

Kaixin is also known as:

- CK vip

Table 451. Table References

Links
<a href="http://www.kahusecurity.com/2013/deobfuscating-the-ck-exploit-kit/">http://www.kahusecurity.com/2013/deobfuscating-the-ck-exploit-kit/</a>
<a href="http://www.kahusecurity.com/2012/new-chinese-exploit-pack/">http://www.kahusecurity.com/2012/new-chinese-exploit-pack/</a>

# Magnitude

Magnitude EK

Magnitude is also known as:

- Popads EK
- TopExp

Table 452. Table References

Links
<a href="http://malware.dontneedcoffee.com/2013/10/Magnitude.html">http://malware.dontneedcoffee.com/2013/10/Magnitude.html</a>
<a href="https://www.trustwave.com/Resources/SpiderLabs-Blog/A-Peek-Into-the-Lion-s-Den-%E2%80%93-The-Magnitude—aka-PopAds—Exploit-Kit/">https://www.trustwave.com/Resources/SpiderLabs-Blog/A-Peek-Into-the-Lion-s-Den-%E2%80%93-The-Magnitude—aka-PopAds—Exploit-Kit/</a>
<a href="http://malware.dontneedcoffee.com/2014/02/and-real-name-of-magnitude-is.html">http://malware.dontneedcoffee.com/2014/02/and-real-name-of-magnitude-is.html</a>
<a href="https://community.rsa.com/community/products/netwitness/blog/2017/02/09/magnitude-exploit-kit-under-the-hood">https://community.rsa.com/community/products/netwitness/blog/2017/02/09/magnitude-exploit-kit-under-the-hood</a>

# MWI

Microsoft Word Intruder is an exploit kit focused on Word and embedded flash exploits. The author wants to avoid their customer to use it in mass spam campaign, so it's most often connected to

semi-targeted attacks

Table 453. Table References

Links
<a href="https://www.fireeye.com/blog/threat-research/2015/04/a_new_word_document.html">https://www.fireeye.com/blog/threat-research/2015/04/a_new_word_document.html</a>
<a href="https://www.sophos.com/en-us/medialibrary/PDFs/technical%20papers/sophos-microsoft-word-intruder-revealed.pdf">https://www.sophos.com/en-us/medialibrary/PDFs/technical%20papers/sophos-microsoft-word-intruder-revealed.pdf</a>

## RIG

RIG is an exploit kit that takes its source in Infinity EK itself an evolution of Redkit. It became dominant after the fall of Angler, Nuclear Pack and the end of public access to Neutrino. RIG-v is the name given to RIG 4 when it was only accessible by "vip" customers and when RIG 3 was still in use.

RIG is also known as:

- RIG 3
- RIG-v
- RIG 4
- Meadgive

Table 454. Table References

Links
<a href="http://www.kahusecurity.com/2014/rig-exploit-pack/">http://www.kahusecurity.com/2014/rig-exploit-pack/</a>
<a href="https://www.trustwave.com/Resources/SpiderLabs-Blog/RIG-Reloaded---Examining-the-Architecture-of-RIG-Exploit-Kit-3-0/">https://www.trustwave.com/Resources/SpiderLabs-Blog/RIG-Reloaded---Examining-the-Architecture-of-RIG-Exploit-Kit-3-0/</a>
<a href="https://www.trustwave.com/Resources/SpiderLabs-Blog/RIG-Exploit-Kit-%E2%80%93-Diving-Deeper-into-the-Infrastructure/">https://www.trustwave.com/Resources/SpiderLabs-Blog/RIG-Exploit-Kit-%E2%80%93-Diving-Deeper-into-the-Infrastructure/</a>
<a href="http://malware.dontneedcoffee.com/2016/10/rig-evolves-neutrino-waves-goodbye.html">http://malware.dontneedcoffee.com/2016/10/rig-evolves-neutrino-waves-goodbye.html</a>

## Sednit EK

Sednit EK is the exploit kit used by APT28

Table 455. Table References

Links
<a href="http://www.welivesecurity.com/2014/10/08/sednit-espionage-group-now-using-custom-exploit-kit/">http://www.welivesecurity.com/2014/10/08/sednit-espionage-group-now-using-custom-exploit-kit/</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/new-adobe-flash-zero-day-used-in-pawn-storm-campaign/">http://blog.trendmicro.com/trendlabs-security-intelligence/new-adobe-flash-zero-day-used-in-pawn-storm-campaign/</a>

## Sundown-P

Sundown-P/Sundown-Pirate is a rip of Sundown seen used in a private way (One group using it only) - First spotted at the end of June 2017, branded as CaptainBlack in August 2017

Sundown-P is also known as:

- Sundown-Pirate
- CaptainBlack

*Table 456. Table References*

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/promediads-malvertising-sundown-pirate-exploit-kit/">http://blog.trendmicro.com/trendlabs-security-intelligence/promediads-malvertising-sundown-pirate-exploit-kit/</a>

## Bizarro Sundown

Bizarro Sundown appears to be a fork of Sundown with added anti-analysis features

Bizarro Sundown is also known as:

- Sundown-b

*Table 457. Table References*

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/new-bizarro-sundown-exploit-kit-spreads-locky/">http://blog.trendmicro.com/trendlabs-security-intelligence/new-bizarro-sundown-exploit-kit-spreads-locky/</a>
<a href="https://blog.malwarebytes.com/cybercrime/exploits/2016/10/yet-another-sundown-ek-variant/">https://blog.malwarebytes.com/cybercrime/exploits/2016/10/yet-another-sundown-ek-variant/</a>

## Hunter

Hunter EK is an evolution of 3Ros EK

Hunter is also known as:

- 3ROS Exploit Kit

*Table 458. Table References*

Links
<a href="https://www.proofpoint.com/us/threat-insight/post/Hunter-Exploit-Kit-Targets-Brazilian-Banking-Customers">https://www.proofpoint.com/us/threat-insight/post/Hunter-Exploit-Kit-Targets-Brazilian-Banking-Customers</a>

## GreenFlash Sundown

GreenFlash Sundown is a variation of Bizarro Sundown without landing

GreenFlash Sundown is also known as:

- Sundown-GF

Table 459. Table References

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/new-bizarro-sundown-exploit-kit-spreads-locky/">http://blog.trendmicro.com/trendlabs-security-intelligence/new-bizarro-sundown-exploit-kit-spreads-locky/</a>

## Angler

The Angler Exploit Kit has been the most popular and evolved exploit kit from 2014 to middle of 2016. There was several variation. The historical "indexm" variant was used to spread Lurk. A vip version used notably to spread Poweliks, the "standard" commercial version, and a declinaison tied to load selling (mostly bankers) that can be associated to EmpirePPC

Angler is also known as:

- XXX
- AEK
- Axpergle

Table 460. Table References

Links
<a href="https://blogs.sophos.com/2015/07/21/a-closer-look-at-the-angler-exploit-kit/">https://blogs.sophos.com/2015/07/21/a-closer-look-at-the-angler-exploit-kit/</a>
<a href="http://malware.dontneedcoffee.com/2015/12/xxx-is-angler-ek.html">http://malware.dontneedcoffee.com/2015/12/xxx-is-angler-ek.html</a>
<a href="http://malware.dontneedcoffee.com/2016/06/is-it-end-of-angler.html">http://malware.dontneedcoffee.com/2016/06/is-it-end-of-angler.html</a>

## Archie

Archie EK

Table 461. Table References

Links
<a href="https://www.alienvault.com/blogs/labs-research/archie-just-another-exploit-kit">https://www.alienvault.com/blogs/labs-research/archie-just-another-exploit-kit</a>

## BlackHole

The BlackHole Exploit Kit has been the most popular exploit kit from 2011 to 2013. Its activity stopped with Paunch's arrest (all activity since then is anecdotal and based on an old leak)

BlackHole is also known as:

- BHEK



Table 462. Table References

Links
<a href="https://www.trustwave.com/Resources/SpiderLabs-Blog/Blackhole-Exploit-Kit-v2/">https://www.trustwave.com/Resources/SpiderLabs-Blog/Blackhole-Exploit-Kit-v2/</a>
<a href="https://nakedsecurity.sophos.com/exploring-the-blackhole-exploit-kit/">https://nakedsecurity.sophos.com/exploring-the-blackhole-exploit-kit/</a>

## Bleeding Life

Bleeding Life is an exploit kit that became open source with its version 2

Bleeding Life is also known as:

- BL
- BL2

Table 463. Table References

Links
<a href="http://www.kahusecurity.com/2011/flash-used-in-idol-malvertisement/">http://www.kahusecurity.com/2011/flash-used-in-idol-malvertisement/</a>
<a href="http://thehackernews.com/2011/10/bleeding-life-2-exploit-pack-released.html">http://thehackernews.com/2011/10/bleeding-life-2-exploit-pack-released.html</a>

## Cool

The Cool Exploit Kit was a kind of BlackHole VIP in 2012/2013

Cool is also known as:

- CEK
- Styxy Cool

Table 464. Table References

Links
<a href="http://malware.dontneedcoffee.com/2012/10/newcoolek.html">http://malware.dontneedcoffee.com/2012/10/newcoolek.html</a>
<a href="http://malware.dontneedcoffee.com/2013/07/a-styxy-cool-ek.html">http://malware.dontneedcoffee.com/2013/07/a-styxy-cool-ek.html</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/styx-exploit-pack-how-it-works/">http://blog.trendmicro.com/trendlabs-security-intelligence/styx-exploit-pack-how-it-works/</a>

## Fiesta

Fiesta Exploit Kit

Fiesta is also known as:

- NeoSploit
- Fiexp

Table 465. Table References

Links
<a href="http://blog.0x3a.com/post/110052845124/an-in-depth-analysis-of-the-fiesta-exploit-kit-an">http://blog.0x3a.com/post/110052845124/an-in-depth-analysis-of-the-fiesta-exploit-kit-an</a>
<a href="http://www.kahusecurity.com/2011/neosploit-is-back/">http://www.kahusecurity.com/2011/neosploit-is-back/</a>

## Empire

The Empire Pack is a variation of RIG operated by a load seller. It's being fed by many traffic actors

Empire is also known as:

- RIG-E

*Table 466. Table References*

Links
<a href="http://malware.dontneedcoffee.com/2016/10/rig-evolves-neutrino-waves-goodbye.html">http://malware.dontneedcoffee.com/2016/10/rig-evolves-neutrino-waves-goodbye.html</a>

## FlashPack

FlashPack EK got multiple fork. The most common variant seen was the standalone Flash version

FlashPack is also known as:

- FlashEK
- SafePack
- CritXPack
- Vintage Pack

*Table 467. Table References*

Links
<a href="http://malware.dontneedcoffee.com/2012/11/meet-critxpack-previously-vintage-pack.html">http://malware.dontneedcoffee.com/2012/11/meet-critxpack-previously-vintage-pack.html</a>
<a href="http://malware.dontneedcoffee.com/2013/04/meet-safe-pack-v20-again.html">http://malware.dontneedcoffee.com/2013/04/meet-safe-pack-v20-again.html</a>

## GrandSoft

GrandSoft Exploit Kit was a quite common exploit kit used in 2012/2013

GrandSoft is also known as:

- StampEK
- SofosFO

*Table 468. Table References*

Links
<a href="http://malware.dontneedcoffee.com/2013/09/FinallyGrandSoft.html">http://malware.dontneedcoffee.com/2013/09/FinallyGrandSoft.html</a>

<http://malware.dontneedcoffee.com/2012/10/neosploit-now-showing-bh-ek-20-like.html>

<https://nakedsecurity.sophos.com/2012/08/24/sophos-sucks-malware/>

## HanJuan

HanJuan EK was a one actor fed variation of Angler EK used in evolved malvertising chain targeting USA. It has been using a 0day (CVE-2015-0313) from beginning of December 2014 till beginning of February 2015

*Table 469. Table References*

Links
<a href="http://www.malwaresigs.com/2013/10/14/unknown-ek/">http://www.malwaresigs.com/2013/10/14/unknown-ek/</a>
<a href="https://blog.malwarebytes.com/threat-analysis/2014/08/shining-some-light-on-the-unknown-exploit-kit/">https://blog.malwarebytes.com/threat-analysis/2014/08/shining-some-light-on-the-unknown-exploit-kit/</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/a-closer-look-at-the-exploit-kit-in-cve-2015-0313-attack">http://blog.trendmicro.com/trendlabs-security-intelligence/a-closer-look-at-the-exploit-kit-in-cve-2015-0313-attack</a>
<a href="https://twitter.com/kafeine/status/562575744501428226">https://twitter.com/kafeine/status/562575744501428226</a>

## Himan

Himan Exploit Kit

Himan is also known as:

- High Load

*Table 470. Table References*

Links
<a href="http://malware.dontneedcoffee.com/2013/10/HiMan.html">http://malware.dontneedcoffee.com/2013/10/HiMan.html</a>

## Impact

Impact EK

*Table 471. Table References*

Links
<a href="http://malware.dontneedcoffee.com/2012/12/inside-impact-exploit-kit-back-on-track.html">http://malware.dontneedcoffee.com/2012/12/inside-impact-exploit-kit-back-on-track.html</a>

## Infinity

Infinity is an evolution of Redkit

Infinity is also known as:

- Redkit v2.0
- Goon

Table 472. Table References

Links
<a href="http://blog.talosintel.com/2013/11/im-calling-this-goon-exploit-kit-for-now.html">http://blog.talosintel.com/2013/11/im-calling-this-goon-exploit-kit-for-now.html</a>
<a href="http://www.kahusecurity.com/2014/the-resurrection-of-redkit/">http://www.kahusecurity.com/2014/the-resurrection-of-redkit/</a>

## Lightsout

Lightsout Exploit Kit has been used in Watering Hole attack performed by the APT Group havex

Table 473. Table References

Links
<a href="http://blog.talosintel.com/2014/03/hello-new-exploit-kit.html">http://blog.talosintel.com/2014/03/hello-new-exploit-kit.html</a>
<a href="http://blog.talosintel.com/2014/05/continued-analysis-of-lightsout-exploit.html">http://blog.talosintel.com/2014/05/continued-analysis-of-lightsout-exploit.html</a>
<a href="http://malwageddon.blogspot.fr/2013/09/unknown-ek-by-way-how-much-is-fish.html">http://malwageddon.blogspot.fr/2013/09/unknown-ek-by-way-how-much-is-fish.html</a>

## Nebula

Nebula Exploit Kit has been built on Sundown source and features an internal TDS

Table 474. Table References

Links
<a href="http://malware.dontneedcoffee.com/2017/03/nebula-exploit-kit.html">http://malware.dontneedcoffee.com/2017/03/nebula-exploit-kit.html</a>

## Neutrino

Neutrino Exploit Kit has been one of the major exploit kit from its launch in 2013 till september 2016 when it become private (defense name for this variation is Neutrino-v). This EK vanished from march 2014 till november 2014.

Neutrino is also known as:

- Job314
- Neutrino Rebooted
- Neutrino-v

Table 475. Table References

Links
<a href="http://malware.dontneedcoffee.com/2013/03/hello-neutrino-just-one-more-exploit-kit.html">http://malware.dontneedcoffee.com/2013/03/hello-neutrino-just-one-more-exploit-kit.html</a>
<a href="http://malware.dontneedcoffee.com/2014/11/neutrino-come-back.html">http://malware.dontneedcoffee.com/2014/11/neutrino-come-back.html</a>

# Niteris

Niteris was used mainly to target Russian.

Niteris is also known as:

- CottonCastle

*Table 476. Table References*

Links
<a href="http://malware.dontneedcoffee.com/2014/06/cottoncastle.html">http://malware.dontneedcoffee.com/2014/06/cottoncastle.html</a>
<a href="http://malware.dontneedcoffee.com/2015/05/another-look-at-niteris-post.html">http://malware.dontneedcoffee.com/2015/05/another-look-at-niteris-post.html</a>

# Nuclear

The Nuclear Pack appeared in 2009 and has been one of the longer living one. Spartan EK was a landing less variation of Nuclear Pack

Nuclear is also known as:

- NEK
- Nuclear Pack
- Spartan
- Neclu

*Table 477. Table References*

Links
<a href="http://blog.checkpoint.com/2016/05/17/inside-nuclears-core-unraveling-a-ransomware-as-a-service-infrastructure/">http://blog.checkpoint.com/2016/05/17/inside-nuclears-core-unraveling-a-ransomware-as-a-service-infrastructure/</a>

# Phoenix

Phoenix Exploit Kit

Phoenix is also known as:

- PEK

*Table 478. Table References*

Links
<a href="http://malwareint.blogspot.fr/2010/09/phoenix-exploits-kit-v21-inside.html">http://malwareint.blogspot.fr/2010/09/phoenix-exploits-kit-v21-inside.html</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/now-exploiting-phoenix-exploit-kit-version-2-5/">http://blog.trendmicro.com/trendlabs-security-intelligence/now-exploiting-phoenix-exploit-kit-version-2-5/</a>

# Private Exploit Pack

Private Exploit Pack

Private Exploit Pack is also known as:

- PEP

*Table 479. Table References*

Links
<a href="http://malware.dontneedcoffee.com/2013/07/pep-new-bep.html">http://malware.dontneedcoffee.com/2013/07/pep-new-bep.html</a>
<a href="http://malwageddon.blogspot.fr/2013/07/unknown-ek-well-hey-hey-i-wanna-be.html">http://malwageddon.blogspot.fr/2013/07/unknown-ek-well-hey-hey-i-wanna-be.html</a>

## Redkit

Redkit has been a major exploit kit in 2012. One of its specific features was to allow its access against a share of a percentage of the customer's traffic

*Table 480. Table References*

Links
<a href="https://www.trustwave.com/Resources/SpiderLabs-Blog/A-Wild-Exploit-Kit-Appears----Meet-RedKit/">https://www.trustwave.com/Resources/SpiderLabs-Blog/A-Wild-Exploit-Kit-Appears----Meet-RedKit/</a>
<a href="http://malware.dontneedcoffee.com/2012/05/inside-redkit.html">http://malware.dontneedcoffee.com/2012/05/inside-redkit.html</a>
<a href="https://nakedsecurity.sophos.com/2013/05/09/redkit-exploit-kit-part-2/">https://nakedsecurity.sophos.com/2013/05/09/redkit-exploit-kit-part-2/</a>

## Sakura

Description Here

*Table 481. Table References*

Links
<a href="http://www.xylibox.com/2012/01/sakura-exploit-pack-10.html">http://www.xylibox.com/2012/01/sakura-exploit-pack-10.html</a>

## Sundown

Sundown Exploit Kit is mainly built out of stolen code from other exploit kits

Sundown is also known as:

- Beps
- Xer
- Beta

*Table 482. Table References*

Links
-------

<http://malware.dontneedcoffee.com/2015/06/fast-look-at-sundown-ek.html>

<https://www.virusbulletin.com/virusbulletin/2015/06/beta-exploit-pack-one-more-piece-crimeware-infection-road>

## Sweet-Orange

Sweet Orange

Sweet-Orange is also known as:

- SWO
- Anogre

*Table 483. Table References*

Links

<http://malware.dontneedcoffee.com/2012/12/juice-sweet-orange-2012-12.html>

## Styx

Styx Exploit Kit

*Table 484. Table References*

Links

<http://malware.dontneedcoffee.com/2012/12/crossing-styx-styx-splloit-pack-20-cve.html>

<https://krebsonsecurity.com/2013/07/styx-exploit-pack-domo-arigato-pc-roboto/>

<http://malware.dontneedcoffee.com/2013/05/inside-styx-2013-05.html>

## WhiteHole

WhiteHole Exploit Kit appeared in January 2013 in the tail of the CVE-2013-0422

*Table 485. Table References*

Links

<http://malware.dontneedcoffee.com/2013/02/briefly-wave-whitehole-exploit-kit-hello.html>

## Unknown

Unknown Exploit Kit. This is a place holder for any undocumented Exploit Kit. If you use this tag, we will be more than happy to give the associated EK a deep look.

*Table 486. Table References*

Links

<https://twitter.com/kafeine>

<https://twitter.com/node5>

<https://twitter.com/kahusecurity>

## Microsoft Activity Group actor

Activity groups as described by Microsoft.



Microsoft Activity Group actor is a cluster galaxy available in JSON format at <https://github.com/MISP/misp-galaxy/blob/master/clusters/microsoft> activity group actor.json[**this location**] The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

Various

## PROMETHIUM

PROMETHIUM is an activity group that has been active as early as 2012. The group primarily uses Truvasys, a first-stage malware that has been in circulation for several years. Truvasys has been involved in several attack campaigns, where it has masqueraded as one of server common computer utilities, including WinUtils, TrueCrypt, WinRAR, or SanDisk. In each of the campaigns, Truvasys malware evolved with additional features—this shows a close relationship between the activity groups behind the campaigns and the developers of the malware.

*Table 487. Table References*

### Links

<https://blogs.technet.microsoft.com/mmpc/2016/12/14/twin-zero-day-attacks-promethium-and-neodymium-target-individuals-in-europe/>

## NEODYMIUM

NEODYMIUM is an activity group that is known to use a backdoor malware detected by Microsoft as Wingbird. This backdoor's characteristics closely match FinFisher, a government-grade commercial surveillance package. Data about Wingbird activity indicate that it is typically used to attack individual computers instead of networks.

*Table 488. Table References*

### Links

<https://blogs.technet.microsoft.com/mmpc/2016/12/14/twin-zero-day-attacks-promethium-and-neodymium-target-individuals-in-europe/>

## TERBIUM

Microsoft Threat Intelligence identified similarities between this recent attack and previous 2012



attacks against tens of thousands of computers belonging to organizations in the energy sector. Microsoft Threat Intelligence refers to the activity group behind these attacks as TERBIUM, following our internal practice of assigning rogue actors chemical element names.

Table 489. Table References

Links
<a href="https://blogs.technet.microsoft.com/mmmpc/2016/12/09/windows-10-protection-detection-and-response-against-recent-attacks/">https://blogs.technet.microsoft.com/mmmpc/2016/12/09/windows-10-protection-detection-and-response-against-recent-attacks/</a>

## STRONTIUM

STRONTIUM has been active since at least 2007. Whereas most modern untargeted malware is ultimately profit-oriented, STRONTIUM mainly seeks sensitive information. Its primary institutional targets have included government bodies, diplomatic institutions, and military forces and installations in NATO member states and certain Eastern European countries. Additional targets have included journalists, political advisors, and organizations associated with political activism in central Asia. STRONTIUM is an activity group that usually targets government agencies, diplomatic institutions, and military organizations, as well as affiliated private sector organizations such as defense contractors and public policy research institutes. Microsoft has attributed more 0-day exploits to STRONTIUM than any other tracked group in 2016. STRONTIUM frequently uses compromised e-mail accounts from one victim to send malicious e-mails to a second victim and will persistently pursue specific targets for months until they are successful in compromising the victims' computer.

STRONTIUM is also known as:

- APT 28
- APT28
- Pawn Storm
- Fancy Bear
- Sednit
- TsarTeam
- TG-4127
- Group-4127
- Sofacy
- Grey-Cloud

Table 490. Table References

Links
<a href="https://blogs.technet.microsoft.com/mmmpc/2016/11/01/our-commitment-to-our-customers-security/">https://blogs.technet.microsoft.com/mmmpc/2016/11/01/our-commitment-to-our-customers-security/</a>
<a href="http://download.microsoft.com/download/4/4/C/44CDEF0E-7924-4787-A56A-16261691ACE3/Microsoft_Security_Intelligence_Report_Volume_19_A_Profile_Of_A_Persistent_Adversary_English.pdf">http://download.microsoft.com/download/4/4/C/44CDEF0E-7924-4787-A56A-16261691ACE3/Microsoft_Security_Intelligence_Report_Volume_19_A_Profile_Of_A_Persistent_Adversary_English.pdf</a>

<https://blogs.technet.microsoft.com/mmpc/2015/11/16/microsoft-security-intelligence-report-strontium/>

## DUBNIUM

DUBNIUM (which shares indicators with what Kaspersky researchers have called DarkHotel) is one of the activity groups that has been very active in recent years, and has many distinctive features.

DUBNIUM is also known as:

- darkhotel

*Table 491. Table References*

Links
<a href="https://securelist.com/blog/research/71713/darkhotels-attacks-in-2015/">https://securelist.com/blog/research/71713/darkhotels-attacks-in-2015/</a>
<a href="https://blogs.technet.microsoft.com/mmpc/2016/06/09/reverse-engineering-dubnium-2">https://blogs.technet.microsoft.com/mmpc/2016/06/09/reverse-engineering-dubnium-2</a>
<a href="https://blogs.technet.microsoft.com/mmpc/2016/06/20/reverse-engineering-dubniums-flash-targeting-exploit/">https://blogs.technet.microsoft.com/mmpc/2016/06/20/reverse-engineering-dubniums-flash-targeting-exploit/</a>
<a href="https://blogs.technet.microsoft.com/mmpc/2016/07/14/reverse-engineering-dubnium-stage-2-payload-analysis/">https://blogs.technet.microsoft.com/mmpc/2016/07/14/reverse-engineering-dubnium-stage-2-payload-analysis/</a>

## PLATINUM

PLATINUM has been targeting its victims since at least as early as 2009, and may have been active for several years prior. Its activities are distinctly different not only from those typically seen in untargeted attacks, but from many targeted attacks as well. A large share of targeted attacks can be characterized as opportunistic: the activity group changes its target profiles and attack geographies based on geopolitical seasons, and may attack institutions all over the world. Like many such groups, PLATINUM seeks to steal sensitive intellectual property related to government interests, but its range of preferred targets is consistently limited to specific governmental organizations, defense institutes, intelligence agencies, diplomatic institutions, and telecommunication providers in South and Southeast Asia. The group's persistent use of spear phishing tactics (phishing attempts aimed at specific individuals) and access to previously undiscovered zero-day exploits have made it a highly resilient threat.

*Table 492. Table References*

Links
<a href="https://blogs.technet.microsoft.com/mmpc/2016/04/26/digging-deep-for-platinum/">https://blogs.technet.microsoft.com/mmpc/2016/04/26/digging-deep-for-platinum/</a>
<a href="http://download.microsoft.com/download/2/2/5/225BFE3E-E1DE-4F5B-A77B-71200928D209/Platinum%20feature%20article%20-%20Targeted%20attacks%20in%20South%20and%20Southeast%20Asia%20April%202016.pdf">http://download.microsoft.com/download/2/2/5/225BFE3E-E1DE-4F5B-A77B-71200928D209/Platinum%20feature%20article%20-%20Targeted%20attacks%20in%20South%20and%20Southeast%20Asia%20April%202016.pdf</a>

## BARIUM

Microsoft Threat Intelligence associates Winnti with multiple activity groups—collections of

malware, supporting infrastructure, online personas, victimology, and other attack artifacts that the Microsoft intelligent security graph uses to categorize and attribute threat activity. Microsoft labels activity groups using code names derived from elements in the periodic table. In the case of this malware, the activity groups strongly associated with Winnti are BARIUM and LEAD. But even though they share the use of Winnti, the BARIUM and LEAD activity groups are involved in very different intrusion scenarios. BARIUM begins its attacks by cultivating relationships with potential victims—particularly those working in Business Development or Human Resources—on various social media platforms. Once BARIUM has established rapport, they spear-phish the victim using a variety of unsophisticated malware installation vectors, including malicious shortcut (.lnk) files with hidden payloads, compiled HTML help (.chm) files, or Microsoft Office documents containing macros or exploits. Initial intrusion stages feature the Win32/Barlaiy implant— notable for its use of social network profiles, collaborative document editing sites, and blogs for C&C. Later stages of the intrusions rely upon Winnti for persistent access. The majority of victims recorded to date have been in electronic gaming, multimedia, and Internet content industries, although occasional intrusions against technology companies have occurred.

*Table 493. Table References*

Links
<a href="https://blogs.technet.microsoft.com/mmpc/2017/01/25/detecting-threat-actors-in-recent-german-industrial-attacks-with-windows-defender-atp/">https://blogs.technet.microsoft.com/mmpc/2017/01/25/detecting-threat-actors-in-recent-german-industrial-attacks-with-windows-defender-atp/</a>

## LEAD

In contrast, LEAD has established a far greater reputation for industrial espionage. In the past few years, LEAD's victims have included: Multinational, multi-industry companies involved in the manufacture of textiles, chemicals, and electronics Pharmaceutical companies A company in the chemical industry University faculty specializing in aeronautical engineering and research A company involved in the design and manufacture of motor vehicles A cybersecurity company focusing on protecting industrial control systems During these intrusions, LEAD's objective was to steal sensitive data, including research materials, process documents, and project plans. LEAD also steals code-signing certificates to sign its malware in subsequent attacks. In most cases, LEAD's attacks do not feature any advanced exploit techniques. The group also does not make special effort to cultivate victims prior to an attack. Instead, the group often simply emails a Winnti installer to potential victims, relying on basic social engineering tactics to convince recipients to run the attached malware. In some other cases, LEAD gains access to a target by brute-forcing remote access login credentials, performing SQL injection, or exploiting unpatched web servers, and then they copy the Winnti installer directly to compromised machines.

*Table 494. Table References*

Links
<a href="https://blogs.technet.microsoft.com/mmpc/2017/01/25/detecting-threat-actors-in-recent-german-industrial-attacks-with-windows-defender-atp/">https://blogs.technet.microsoft.com/mmpc/2017/01/25/detecting-threat-actors-in-recent-german-industrial-attacks-with-windows-defender-atp/</a>

## ZIRCONIUM

In addition to strengthening generic detection of EoP exploits, Microsoft security researchers are

actively gathering threat intelligence and indicators attributable to ZIRCONIUM, the activity group using the CVE-2017-0005 exploit.

Table 495. Table References

Links
<a href="https://blogs.technet.microsoft.com/mmpc/2017/03/27/detecting-and-mitigating-elevation-of-privilege-exploit-for-cve-2017-0005/">https://blogs.technet.microsoft.com/mmpc/2017/03/27/detecting-and-mitigating-elevation-of-privilege-exploit-for-cve-2017-0005/</a>

## Attack Pattern

ATT&CK tactic.



Attack Pattern is a cluster galaxy available in JSON format at <https://github.com/MISP/misp-galaxy/blob/master/clusters/attack> pattern.json[**this location**] The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

MITRE

## Exfiltration Over Alternative Protocol

Data exfiltration is performed with a different protocol from the main command and control protocol or channel. The data is likely to be sent to an alternate network location from the main command and control server. Alternate protocols include FTP, SMTP, HTTP/S, DNS, or some other network protocol. Different channels could include Internet Web services such as cloud storage.

Detection: Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: User interface, Process monitoring, Process use of network, Packet capture, Netflow/Enclave netflow, Network protocol analysis

Table 496. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1048">https://attack.mitre.org/wiki/Technique/T1048</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>

# Standard Application Layer Protocol

Adversaries may communicate using a common, standardized application layer protocol such as HTTP, HTTPS, SMTP, or DNS to avoid detection by blending in with existing traffic. Commands to the remote system, and often the results of those commands, will be embedded within the protocol traffic between the client and server.

For connections that occur internally within an enclave (such as those between a proxy or pivot node and other nodes), commonly used protocols are RPC, SSH, or RDP.

Detection: Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect application layer protocols that do not follow the expected protocol for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Packet capture, Netflow/Enclave netflow, Process use of network, Malware reverse engineering, Process monitoring

Table 497. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1071">https://attack.mitre.org/wiki/Technique/T1071</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>

## Launch Agent

Per Apple's developer documentation, when a user logs in, a per-user launchd process is started which loads the parameters for each launch-on-demand user agent from the property list (plist) files found in `<code>/System/Library/LaunchAgents</code>`, `<code>/Library/LaunchAgents</code>`, and `<code>$HOME/Library/LaunchAgents</code>` [[Citation: AppleDocs Launch Agent Daemons]] [[Citation: OSX Keydnep malware]] [[Citation: Antiquated Mac Malware]]. These launch agents have property list files which point to the executables that will be launched [[Citation: OSX.Dok Malware]].

Adversaries may install a new launch agent that can be configured to execute at login by using launchd or launchctl to load a plist into the appropriate directories [[Citation: Sofacy Komplex Trojan]] [[Citation: Methods of Mac Malware Persistence]]. The agent name may be disguised by using a name from a related operating system or benign software. Launch Agents are created with user level privileges and are executed with the privileges of the user when they log in [[Citation: OSX Malware Detection]] [[Citation: OceanLotus for OS X]]. They can be set up to execute when a specific user logs in (in the specific user's directory structure) or when any user logs in (which requires administrator privileges).

Detection: Monitor Launch Agent creation through additional plist files and utilities such as

Objective-See's KnockKnock application. Launch Agents also require files on disk for persistence which can also be monitored via other file monitoring applications.

Platforms: MacOS, OS X

Data Sources: File monitoring, Process Monitoring

Table 498. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1159">https://attack.mitre.org/wiki/Technique/T1159</a>
<a href="https://blog.malwarebytes.com/threat-analysis/2017/04/new-osx-dok-malware-intercepts-web-traffic/">https://blog.malwarebytes.com/threat-analysis/2017/04/new-osx-dok-malware-intercepts-web-traffic/</a>
<a href="https://blog.malwarebytes.com/threat-analysis/2017/01/new-mac-backdoor-using-antiquated-code/">https://blog.malwarebytes.com/threat-analysis/2017/01/new-mac-backdoor-using-antiquated-code/</a>
<a href="https://developer.apple.com/library/content/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/CreatingLaunchdJobs.html">https://developer.apple.com/library/content/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/CreatingLaunchdJobs.html</a>
<a href="https://www.welivesecurity.com/2016/07/06/new-osxkeydnep-malware-hungry-credentials/">https://www.welivesecurity.com/2016/07/06/new-osxkeydnep-malware-hungry-credentials/</a>
<a href="https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf">https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf</a>
<a href="https://researchcenter.paloaltonetworks.com/2016/09/unit42-sofacys-komplex-os-x-trojan/">https://researchcenter.paloaltonetworks.com/2016/09/unit42-sofacys-komplex-os-x-trojan/</a>
<a href="https://www.alienvault.com/blogs/labs-research/oceanlotus-for-os-x-an-application-bundle-pretending-to-be-an-adobe-flash-update">https://www.alienvault.com/blogs/labs-research/oceanlotus-for-os-x-an-application-bundle-pretending-to-be-an-adobe-flash-update</a>
<a href="https://www.synack.com/wp-content/uploads/2016/03/RSA%20OSX%20Malware.pdf">https://www.synack.com/wp-content/uploads/2016/03/RSA%20OSX%20Malware.pdf</a>

## Communication Through Removable Media

Adversaries can perform command and control between compromised hosts on potentially disconnected networks using removable media to transfer commands from system to system. Both systems would need to be compromised, with the likelihood that an Internet-connected system was compromised first and the second through lateral movement by Replication Through Removable Media. Commands and files would be relayed from the disconnected system to the Internet-connected system to which the adversary has direct access.

Detection: Monitor file access on removable media. Detect processes that execute when removable media is mounted.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: File monitoring, Data loss prevention

Table 499. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1092">https://attack.mitre.org/wiki/Technique/T1092</a>

# Access Token Manipulation

Windows uses access tokens to determine the ownership of a running process. A user can manipulate access tokens to make a running process appear as though it belongs to someone other than the user that started the process. When this occurs, the process also takes on the security context associated with the new token. For example, Microsoft promotes the use of access tokens as a security best practice. Administrators should log in as a standard user but run their tools with administrator privileges using the built-in access token manipulation command `runas`. [[Citation: Microsoft runas]]

Adversaries may use access tokens to operate under a different user or system security context to perform actions and evade detection. An adversary can use built-in Windows API functions to copy access tokens from existing processes; this is known as token stealing. An adversary must already be in a privileged user context (i.e. administrator) to steal a token. However, adversaries commonly use token stealing to elevate their security context from the administrator level to the SYSTEM level. [[Citation: Pentestlab Token Manipulation]]

Adversaries can also create spoofed access tokens if they know the credentials of a user. Any standard user can use the `runas` command, and the Windows API functions, to do this; it does not require access to an administrator account.

Lastly, an adversary can use a spoofed token to authenticate to a remote system as the account for that token if the account has appropriate permissions on the remote system.

Metasploit's Meterpreter payload allows arbitrary token stealing and uses token stealing to escalate privileges. [[Citation: Metasploit access token]] The Cobalt Strike beacon payload allows arbitrary token stealing and can also create tokens. [[Citation: Cobalt Strike Access Token]]

Detection: If an adversary is using a standard command-line shell, analysts can detect token manipulation by auditing command-line activity. Specifically, analysts should look for use of the `runas` command. Detailed command-line logging is not enabled by default in Windows. [[Citation: Microsoft Command-line Logging]]

If an adversary is using a payload that calls the Windows token APIs directly, analysts can detect token manipulation only through careful analysis of user network activity, examination of running processes, and correlation with other endpoint and network behavior.

There are many Windows API calls a payload can take advantage of to manipulate access tokens (e.g., `LogonUser` [[Citation: Microsoft LogonUser]], `DuplicateTokenEx` [[Citation: Microsoft DuplicateTokenEx]], and `ImpersonateLoggedOnUser` [[Citation: Microsoft ImpersonateLoggedOnUser]]). Please see the referenced Windows API pages for more information.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Effective Permissions: SYSTEM

Contributors: Tom Ueltschi @c\_APT\_ure

Table 500. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1134">https://attack.mitre.org/wiki/Technique/T1134</a>
<a href="https://technet.microsoft.com/en-us/windows-server-docs/identity/ad-ds/manage/component-updates/command-line-process-auditing">https://technet.microsoft.com/en-us/windows-server-docs/identity/ad-ds/manage/component-updates/command-line-process-auditing</a>
<a href="https://blog.cobaltstrike.com/2015/12/16/windows-access-tokens-and-alternate-credentials/">https://blog.cobaltstrike.com/2015/12/16/windows-access-tokens-and-alternate-credentials/</a>
<a href="https://msdn.microsoft.com/en-us/library/windows/desktop/aa446617(v=vs.85).aspx">https://msdn.microsoft.com/en-us/library/windows/desktop/aa446617(v=vs.85).aspx</a>
<a href="https://www.offensive-security.com/metasploit-unleashed/fun-incognito/">https://www.offensive-security.com/metasploit-unleashed/fun-incognito/</a>
<a href="https://technet.microsoft.com/en-us/library/bb490994.aspx">https://technet.microsoft.com/en-us/library/bb490994.aspx</a>
<a href="https://pentestlab.blog/2017/04/03/token-manipulation/">https://pentestlab.blog/2017/04/03/token-manipulation/</a>
<a href="https://msdn.microsoft.com/en-us/library/windows/desktop/aa378612(v=vs.85).aspx">https://msdn.microsoft.com/en-us/library/windows/desktop/aa378612(v=vs.85).aspx</a>
<a href="https://msdn.microsoft.com/en-us/library/windows/desktop/aa378184(v=vs.85).aspx">https://msdn.microsoft.com/en-us/library/windows/desktop/aa378184(v=vs.85).aspx</a>

## Custom Command and Control Protocol

Adversaries may communicate using a custom command and control protocol instead of using existing Standard Application Layer Protocol to encapsulate commands. Implementations could mimic well-known protocols.

Detection: Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Packet capture, Netflow/Enclave netflow, Process use of network, Process monitoring

Table 501. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1094">https://attack.mitre.org/wiki/Technique/T1094</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>

## File System Permissions Weakness

Processes may automatically execute specific binaries as part of their functionality or to perform other actions. If the permissions on the file system directory containing a target binary, or permissions on the binary itself, are improperly set, then the target binary may be overwritten with another binary using user-level permissions and executed by the original process. If the original process and thread are running under a higher permissions level, then the replaced binary will also execute under higher-level permissions, which could include SYSTEM.



Adversaries may use this technique to replace legitimate binaries with malicious ones as a means of executing code at a higher permissions level. If the executing process is set to run at a specific time or during a certain event (e.g., system bootup) then this technique can also be used for persistence.

#### ===Services===

Manipulation of Windows service binaries is one variation of this technique. Adversaries may replace a legitimate service executable with their own executable to gain persistence and/or privilege escalation to the account context the service is set to execute under (local/domain account, SYSTEM, LocalService, or NetworkService). Once the service is started, either directly by the user (if appropriate access is available) or through some other means, such as a system restart if the service starts on bootup, the replaced executable will run instead of the original service executable.

#### ===Executable Installers===

Another variation of this technique can be performed by taking advantage of a weakness that is common in executable, self-extracting installers. During the installation process, it is common for installers to use a subdirectory within the `%TEMP%` directory to unpack binaries such as DLLs, EXEs, or other payloads. When installers create subdirectories and files they often do not set appropriate permissions to restrict write access, which allows for execution of untrusted code placed in the subdirectories or overwriting of binaries used in the installation process. This behavior is related to and may take advantage of DLL Search Order Hijacking. Some installers may also require elevated privileges that will result in privilege escalation when executing adversary controlled code. This behavior is related to Bypass User Account Control. Several examples of this weakness in existing common installers have been reported to software vendors. [[Citation: Mozilla Firefox Installer DLL Hijack]] [[Citation: Seclists Kanthak 7zip Installer]]

Detection: Look for changes to binaries and service executables that may normally occur during software updates. If an executable is written, renamed, and/or moved to match an existing service executable, it could be detected and correlated with other suspicious behavior. Hashing of binaries and service executables could be used to detect replacement against historical data.

Look for abnormal process call trees from typical processes and services and for execution of other commands that could relate to or other adversary techniques.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: File monitoring, Services, Process command-line parameters

Effective Permissions: SYSTEM, User, Administrator

Contributors: Stefan Kanthak

#### Table 502. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1044">https://attack.mitre.org/wiki/Technique/T1044</a>

<https://www.mozilla.org/en-US/security/advisories/mfsa2012-98/>

<http://seclists.org/fulldisclosure/2015/Dec/34>

## Process Hollowing

Process hollowing occurs when a process is created in a suspended state and the process's memory is replaced with the code of a second program so that the second program runs instead of the original program. Windows and process monitoring tools believe the original process is running, whereas the actual program running is different. DLL Injection to evade defenses and detection analysis of malicious process execution by launching adversary-controlled code under the context of a legitimate process.

Detection: Monitoring API calls may generate a significant amount of data and may not be directly useful for defense unless collected under specific circumstances for known bad sequences of calls, since benign use of API functions may be common and difficult to distinguish from malicious behavior.

Analyze process behavior to determine if a process is performing actions it usually does not, such as opening network connections, reading files, or other suspicious actions that could relate to post-compromise behavior.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Process monitoring, API monitoring

*Table 503. Table References*

Links

<https://attack.mitre.org/wiki/Technique/T1093>

<http://www.autosectools.com/process-hollowing.pdf>

## Scripting

Adversaries may use scripts to aid in operations and perform multiple actions that would otherwise be manual. Scripting is useful for speeding up operational tasks and reducing the time required to gain access to critical resources. Some scripting languages may be used to bypass process monitoring mechanisms by directly interacting with the operating system at an API level instead of calling other programs. Common scripting languages for Windows include VBScript and PowerShell but could also be in the form of command-line batch scripts.

Many popular offensive frameworks exist which use forms of scripting for security testers and adversaries alike. Metasploit[[Citation: Metasploit]], Veil[[Citation: Veil]], and PowerSploit[[Citation: Powersploit]] are three examples that are popular among penetration testers for exploit and post-compromise operations and include many features for evading defenses. Some adversaries are known to use PowerShell. [[Citation: Alperovitch 2014]]

Detection: Scripting may be common on admin, developer, or power user systems, depending on job function. If scripting is restricted for normal users, then any attempts to enable scripts running on a system would be considered suspicious. If scripts are not commonly used on a system, but enabled, scripts running out of cycle from patching or other administrator functions are suspicious. Scripts should be captured from the file system when possible to determine their actions and intent.

Scripts are likely to perform actions with various effects on a system that may generate events, depending on the types of monitoring used. Monitor processes and command-line arguments for script execution and subsequent behavior. Actions may be related to network and system information, , or other scriptable post-compromise behaviors and could be used as indicators of detection leading back to the source script.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: Process monitoring, File monitoring, Process command-line parameters

Table 504. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1064">https://attack.mitre.org/wiki/Technique/T1064</a>
<a href="http://www.metasploit.com">http://www.metasploit.com</a>
<a href="http://blog.crowdstrike.com/deep-thought-chinese-targeting-national-security-think-tanks/">http://blog.crowdstrike.com/deep-thought-chinese-targeting-national-security-think-tanks/</a>
<a href="https://www.veil-framework.com/framework/">https://www.veil-framework.com/framework/</a>
<a href="https://github.com/mattifestation/PowerSploit">https://github.com/mattifestation/PowerSploit</a>

## Data from Removable Media

Sensitive data can be collected from any removable media (optical disk drive, USB memory, etc.) connected to the compromised system prior to cmd may be used to gather information. Some adversaries may also use Automated Collection on removable media.

Detection: Monitor processes and command-line arguments for actions that could be taken to collect files from a system's connected removable media. Remote access tools with built-in features may interact directly with the Windows API to gather data. Data may also be acquired through Windows system management tools such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process command-line parameters

Table 505. Table References

Links
-------

## Code Signing

Code signing provides a level of authenticity on a binary from the developer and a guarantee that the binary has not been tampered with. [[Citation: Wikipedia Code Signing]] However, adversaries are known to use code signing certificates to masquerade malware and tools as legitimate binaries [[Citation: Janicab]]. The certificates used during an operation may be created, forged, or stolen by the adversary. [[Citation: Securelist Digital Certificates]] [[Citation: Symantec Digital Certificates]]

Code signing to verify software on first run can be used on modern Windows and MacOS/OS X systems. It is not used on Linux due to the decentralized nature of the platform. [[Citation: Wikipedia Code Signing]]

Code signing certificates may be used to bypass security policies that require signed code to execute on a system.

Detection: Collect and analyze signing certificate metadata on software that executes within the environment to look for unusual certificate characteristics and outliers.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, MacOS, OS X

Data Sources: Binary file metadata

Table 506. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1116">https://attack.mitre.org/wiki/Technique/T1116</a>
<a href="http://www.symantec.com/connect/blogs/how-attackers-steal-private-keys-digital-certificates">http://www.symantec.com/connect/blogs/how-attackers-steal-private-keys-digital-certificates</a>
<a href="https://securelist.com/blog/security-policies/68593/why-you-shouldnt-completely-trust-files-signed-with-digital-certificates/">https://securelist.com/blog/security-policies/68593/why-you-shouldnt-completely-trust-files-signed-with-digital-certificates/</a>
<a href="http://www.thesafemac.com/new-signed-malware-called-janicab/">http://www.thesafemac.com/new-signed-malware-called-janicab/</a>
<a href="https://en.wikipedia.org/wiki/Code%20signing">https://en.wikipedia.org/wiki/Code%20signing</a>

## Hidden Window

The configurations for how applications run on macOS and OS X are listed in property list (plist) files. One of the tags in these files can be `<code>apple.awt.UIElement</code>`, which allows for Java applications to prevent the application's icon from appearing in the Dock. A common use for this is when applications run in the system tray, but don't also want to show up in the Dock. However, adversaries can abuse this feature and hide their running window [[Citation: Antiquated Mac Malware]].

Detection: Plist files are ASCII text files with a specific format, so they're relatively easy to parse. File monitoring can check for the `<code>apple.awt.UIElement</code>` or any other suspicious plist

tag in plist files and flag them.

Platforms: MacOS, OS X

Data Sources: File monitoring

Table 507. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1143">https://attack.mitre.org/wiki/Technique/T1143</a>
<a href="https://blog.malwarebytes.com/threat-analysis/2017/01/new-mac-backdoor-using-antiquated-code/">https://blog.malwarebytes.com/threat-analysis/2017/01/new-mac-backdoor-using-antiquated-code/</a>

## Rootkit

Rootkits are programs that hide the existence of malware by intercepting and modifying operating system API calls that supply system information. Rootkits or rootkit enabling functionality may reside at the user or kernel level in the operating system or lower, to include a Hypervisor, Master Boot Record, or the System Firmware. [[Citation: Wikipedia Rootkit]]

Adversaries may use rootkits to hide the presence of programs, files, network connections, services, drivers, and other system components.

Detection: Some rootkit protections may be built into anti-virus or operating system software. There are dedicated rootkit detection tools that look for specific types of rootkit behavior. Monitor for the existence of unrecognized DLLs, devices, services, and changes to the MBR. [[Citation: Wikipedia Rootkit]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: BIOS, MBR, System calls

Table 508. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1014">https://attack.mitre.org/wiki/Technique/T1014</a>
<a href="https://en.wikipedia.org/wiki/Rootkit">https://en.wikipedia.org/wiki/Rootkit</a>

## Startup Items

Per Apple's documentation, startup items execute during the final phase of the boot process and contain shell scripts or other executable files along with configuration information used by the system to determine the execution order for all startup items [[Citation: Startup Items]]. This is technically a deprecated version (superseded by Launch Daemons), and thus the appropriate folder, `/Library/StartupItems` isn't guaranteed to exist on the system by default, but does appear to exist by default on macOS Sierra. A startup item is a directory whose executable and configuration property list (plist), `StartupParameters.plist`, reside in the top-level directory.

An adversary can create the appropriate folders/files in the StartupItems directory to register their own persistence mechanism[[Citation: Methods of Mac Malware Persistence]]. Additionally, since StartupItems run during the bootup phase of macOS, they will run as root. If an adversary is able to modify an existing Startup Item, then they will be able to Privilege Escalate as well.

Detection: The `/Library/StartupItems` folder can be monitored for changes. Similarly, the programs that are actually executed from this mechanism should be checked against a whitelist. Monitor processes that are executed during the bootup process to check for unusual or unknown applications and behavior.

Platforms: MacOS, OS X

Data Sources: File monitoring, Process Monitoring

Effective Permissions: root

Table 509. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1165">https://attack.mitre.org/wiki/Technique/T1165</a>
<a href="https://developer.apple.com/library/content/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/StartupItems.html">https://developer.apple.com/library/content/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/StartupItems.html</a>
<a href="https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf">https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf</a>

## Command-Line Interface

Command-line interfaces provide a way of interacting with computer systems and is a common feature across many types of operating system platforms.cmd, which can be used to perform a number of tasks including execution of other software. Command-line interfaces can be interacted with locally or remotely via a remote desktop application, reverse shell session, etc. Commands that are executed run with the current permission level of the command-line interface process unless the command includes process invocation that changes permissions context for that execution (e.g. Scheduled Task).

Adversaries may use command-line interfaces to interact with systems and execute other software during the course of an operation.

Detection: Command-line interface activities can be captured through proper logging of process execution with command-line arguments. This information can be useful in gaining additional insight to adversaries' actions through how they use native processes or custom tools.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Process monitoring, Process command-line parameters

Table 510. Table References

Links
-------

<https://attack.mitre.org/wiki/Technique/T1059>

<https://en.wikipedia.org/wiki/Command-line%20interface>

## Exfiltration Over Command and Control Channel

Data exfiltration is performed over the [[Command and Control]] channel. Data is encoded into the normal communications channel using the same protocol as command and control communications.

Detection: Detection for command and control applies. Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: User interface, Process monitoring

*Table 511. Table References*

Links

<https://attack.mitre.org/wiki/Technique/T1041>

<https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf>

## Multi-Stage Channels

Adversaries may create multiple stages for command and control that are employed under different conditions or for certain functions. Use of multiple stages may obfuscate the command and control channel to make detection more difficult.

Remote access tools will call back to the first-stage command and control server for instructions. The first stage may have automated capabilities to collect basic host information, update tools, and upload additional files. A second remote access tool (RAT) could be uploaded at that point to redirect the host to the second-stage command and control server. The second stage will likely be more fully featured and allow the adversary to interact with the system through a reverse shell and additional RAT features.

The different stages will likely be hosted separately with no overlapping infrastructure. The loader may also have backup first-stage callbacks or Fallback Channels in case the original first-stage communication path is discovered and blocked.

Detection: Host data that can relate unknown or suspicious process activity using a network connection is important to supplement any existing indicators of compromise based on malware command and control signatures and infrastructure. Relating subsequent actions that may result from of the system and network information or [[Lateral Movement]] to the originating process

may also yield useful data.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Netflow/Enclave netflow, Network device logs, Network protocol analysis, Packet capture, Process use of network

Table 512. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1104">https://attack.mitre.org/wiki/Technique/T1104</a>

## Keychain

Keychains are the built-in way for macOS to keep track of users' passwords and credentials for many services and features such as WiFi passwords, websites, secure notes, certificates, and Kerberos. Keychain files are located in `~/Library/Keychains/`, `/Library/Keychains/`, and `/Network/Library/Keychains/`.<sup>[[Citation: Wikipedia keychain]]</sup> The `security` command-line utility, which is built into macOS by default, provides a useful way to manage these credentials.

To manage their credentials, users have to use additional credentials to access their keychain. If an adversary knows the credentials for the login keychain, then they can get access to all the other credentials stored in this vault.<sup>[[Citation: External to DA, the OS X Way]]</sup> By default, the passphrase for the keychain is the user's logon credentials.

Detection: Unlocking the keychain and using passwords from it is a very common process, so there is likely to be a lot of noise in any detection technique. Monitoring of system calls to the keychain can help determine if there is a suspicious process trying to access it.

Platforms: MacOS, OS X

Data Sources: System calls, Process Monitoring

Table 513. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1142">https://attack.mitre.org/wiki/Technique/T1142</a>
<a href="http://www.slideshare.net/StephanBorosh/external-to-da-the-os-x-way">http://www.slideshare.net/StephanBorosh/external-to-da-the-os-x-way</a>
<a href="https://en.wikipedia.org/wiki/Keychain%20(software)">https://en.wikipedia.org/wiki/Keychain%20(software)</a>

## Input Capture

Adversaries can use methods of capturing user input for obtaining credentials for Valid Accounts and information Credential Dumping efforts are not effective, and may require an adversary to remain passive on a system for a period of time before an opportunity arises.



Adversaries may also install code on externally facing portals, such as a VPN login page, to capture and transmit credentials of users who attempt to log into the service. This variation on input capture may be conducted post-compromise using legitimate administrative access as a backup measure to maintain network access through External Remote Services and Valid Accounts or as part of the initial compromise by exploitation of the externally facing web service. Valid Accounts in use by adversaries may help to catch the result of user input interception if new techniques are used.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: Windows Registry, Kernel drivers, Process monitoring, API monitoring

Contributors: John Lambert, Microsoft Threat Intelligence Center

Table 514. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1056">https://attack.mitre.org/wiki/Technique/T1056</a>
<a href="http://blog.leetsys.com/2012/01/02/capturing-windows-7-credentials-at-logon-using-custom-credential-provider/">http://blog.leetsys.com/2012/01/02/capturing-windows-7-credentials-at-logon-using-custom-credential-provider/</a>
<a href="https://www.volexity.com/blog/2015/10/07/virtual-private-keylogging-cisco-web-vpns-leveraged-for-access-and-persistence/">https://www.volexity.com/blog/2015/10/07/virtual-private-keylogging-cisco-web-vpns-leveraged-for-access-and-persistence/</a>

## Regsvcs/Regasm

Regsvcs and Regasm are Windows command-line utilities that are used to register .NET Component Object Model (COM) assemblies. Both are digitally signed by Microsoft. [[Citation: MSDN Regsvcs]] [[Citation: MSDN Regasm]]

Adversaries can use Regsvcs and Regasm to proxy execution of code through a trusted Windows utility. Both utilities may be used to bypass process whitelisting through use of attributes within the binary to specify code that should be run before registration or unregistration: `[ComRegisterFunction]` or `[ComUnregisterFunction]` respectively. The code with the registration and unregistration attributes will be executed even if the process is run under insufficient privileges and fails to execute. [[Citation: SubTee GitHub All The Things Application Whitelisting Bypass]]

Detection: Use process monitoring to monitor the execution and arguments of Regsvcs.exe and Regasm.exe. Compare recent invocations of Regsvcs.exe and Regasm.exe with prior history of known good arguments and executed binaries to determine anomalous and potentially adversarial activity. Command arguments used before and after Regsvcs.exe or Regasm.exe invocation may also be useful in determining the origin and purpose of the binary being executed.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Process monitoring, Process command-line parameters

Contributors: Casey Smith

Table 515. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1121">https://attack.mitre.org/wiki/Technique/T1121</a>
<a href="https://msdn.microsoft.com/en-us/library/04za0hca.aspx">https://msdn.microsoft.com/en-us/library/04za0hca.aspx</a>
<a href="https://msdn.microsoft.com/en-us/library/tzat5yw6.aspx">https://msdn.microsoft.com/en-us/library/tzat5yw6.aspx</a>
<a href="https://github.com/subTee/AllTheThings">https://github.com/subTee/AllTheThings</a>

## Trusted Developer Utilities

There are many utilities used for software development related tasks that can be used to execute code in various forms to assist in development, debugging, and reverse engineering. These utilities may often be signed with legitimate certificates that allow them to execute on a system and proxy execution of malicious code through a trusted process that effectively bypasses application whitelisting defensive solutions.

===MSBuild===

MSBuild.exe (Microsoft Build Engine) is a software build platform used by Visual Studio. It takes XML formatted project files that define requirements for building various platforms and configurations. [[Citation: MSDN MSBuild]]

Adversaries can use MSBuild to proxy execution of code through a trusted Windows utility. The inline task capability of MSBuild that was introduced in .NET version 4 allows for C# code to be inserted into the XML project file. [[Citation: MSDN MSBuild Inline Tasks]] MSBuild will compile and execute the inline task. MSBuild.exe is a signed Microsoft binary, so when it is used this way it can execute arbitrary code and bypass application whitelisting defenses that are configured to allow MSBuild.exe execution. [[Citation: SubTee GitHub All The Things Application Whitelisting Bypass]]

===DNX===

The .NET Execution Environment (DNX), dnx.exe, is a software development kit packaged with Visual Studio Enterprise. It was retired in favor of .NET Core CLI in 2016. [[Citation: Microsoft Migrating from DNX]] DNX is not present on standard builds of Windows and may only be present on developer workstations using older versions of .NET Core and ASP.NET Core 1.0. The dnx.exe executable is signed by Microsoft.

An adversary can use dnx.exe to proxy execution of arbitrary code to bypass application whitelist policies that do not account for DNX. [[Citation: engima0x3 DNX Bypass]]

===RCSI===

The rcsi.exe utility is a non-interactive command-line interface for C# that is similar to csi.exe. It was provided within an early version of the Roslyn .NET Compiler Platform but has since been deprecated for an integrated solution. [[Citation: Microsoft Roslyn CPT RCSI]] The rcsi.exe binary is

signed by Microsoft. [[Citation: engima0x3 RCSI Bypass]]

C# .csx script files can be written and executed with rcsi.exe at the command-line. An adversary can use rcsi.exe to proxy execution of arbitrary code to bypass application whitelisting policies that do not account for execution of rcsi.exe. [[Citation: engima0x3 RCSI Bypass]]

===WinDbg/CDB===

WinDbg is a Microsoft Windows kernel and user-mode debugging utility. The Microsoft Console Debugger (CDB) cdb.exe is also user-mode debugger. Both utilities are included in Windows software development kits and can be used as standalone tools. [[Citation: Microsoft Debugging Tools for Windows]] They are commonly used in software development and reverse engineering and may not be found on typical Windows systems. Both WinDbg.exe and cdb.exe binaries are signed by Microsoft.

An adversary can use WinDbg.exe and cdb.exe to proxy execution of arbitrary code to bypass application whitelist policies that do not account for execution of those utilities. [[Citation: Exploit Monday WinDbg]]

It is likely possible to use other debuggers for similar purposes, such as the kernel-mode debugger kd.exe, which is also signed by Microsoft.

Detection: The presence of these or other utilities that enable proxy execution that are typically used for development, debugging, and reverse engineering on a system that is not used for these purposes may be suspicious.

Use process monitoring to monitor the execution and arguments of MSBuild.exe, dnx.exe, rcsi.exe, WinDbg.exe, and cdb.exe. Compare recent invocations of those binaries with prior history of known good arguments and executed binaries to determine anomalous and potentially adversarial activity. It is likely that these utilities will be used by software developers or for other software development related tasks, so if it exists and is used outside of that context, then the event may be suspicious. Command arguments used before and after invocation of the utilities may also be useful in determining the origin and purpose of the binary being executed.

Platforms: Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Process monitoring

Contributors: Casey Smith

Table 516. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1127">https://attack.mitre.org/wiki/Technique/T1127</a>
<a href="https://enigma0x3.net/2016/11/17/bypassing-application-whitelisting-by-using-dnx-exe/">https://enigma0x3.net/2016/11/17/bypassing-application-whitelisting-by-using-dnx-exe/</a>
<a href="https://msdn.microsoft.com/library/dd722601.aspx">https://msdn.microsoft.com/library/dd722601.aspx</a>
<a href="https://blogs.msdn.microsoft.com/visualstudio/2011/10/19/introducing-the-microsoft-roslyn-ctp/">https://blogs.msdn.microsoft.com/visualstudio/2011/10/19/introducing-the-microsoft-roslyn-ctp/</a>
<a href="https://docs.microsoft.com/en-us/windows-hardware/drivers/debugger/index">https://docs.microsoft.com/en-us/windows-hardware/drivers/debugger/index</a>

<https://github.com/subTee/AllTheThings>

<https://msdn.microsoft.com/library/dd393574.aspx>

<http://www.exploit-monday.com/2016/08/windbg-cdb-shellcode-runner.html>

<https://enigma0x3.net/2016/11/21/bypassing-application-whitelisting-by-using-rcsi-exe/>

<https://docs.microsoft.com/en-us/dotnet/core/migration/from-dnx>

## System Network Configuration Discovery

Adversaries will likely look for details about the network configuration and settings of systems they access or through information discovery of remote systems. Several operating system administration utilities exist that can be used to gather this information. Examples include Arp, ipconfig/ifconfig, nbtstat, and route.

Detection: System and network discovery techniques normally occur throughout an operation as an adversary learns the environment. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: Process monitoring, Process command-line parameters

*Table 517. Table References*

Links

<https://attack.mitre.org/wiki/Technique/T1016>

## Scheduled Task

Utilities such as at and schtasks, along with the Windows Task Scheduler, can be used to schedule programs or scripts to be executed at a date and time. The account used to create the task must be in the Administrators group on the local system. A task can also be scheduled on a remote system, provided the proper authentication is met to use RPC and file and printer sharing is turned on. Windows Management Instrumentation and PowerShell, so additional logging may need to be configured to gather the appropriate data.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: File monitoring, Process monitoring, Process command-line parameters

Effective Permissions: SYSTEM, Administrator

*Table 518. Table References*

## Links

<https://attack.mitre.org/wiki/Technique/T1053>

<https://technet.microsoft.com/en-us/sysinternals/bb963902>

<https://technet.microsoft.com/en-us/library/cc785125.aspx>

# Application Shimming

The Microsoft Windows Application Compatibility Infrastructure/Framework (Application Shim) was created to allow compatibility of programs as Windows updates and changes its code. For example, application shimming feature that allows programs that were created for Windows XP to work with Windows 10. Within the framework, shims are created to act as a buffer between the program (or more specifically, the Import Address Table) and the Windows OS. When a program is executed, the shim cache is referenced to determine if the program requires the use of the shim database (.sdb). If so, the shim database uses API hooking to redirect the code as necessary in order to communicate with the OS. A list of all shims currently installed by the default Windows installer (sdbinst.exe) is kept in:

- `%WINDIR%\AppPatch\sysmain.sdb`
- `hkml\software\microsoft\windows nt\currentversion\appcompatflags\installedsdb`

Custom databases are stored in:

- `%WINDIR%\AppPatch\custom & %WINDIR%\AppPatch\AppPatch64\Custom`
- `hkml\software\microsoft\windows nt\currentversion\appcompatflags\custom`

To keep shims secure, Windows designed them to run in user mode so they cannot modify the kernel and you must have administrator privileges to install a shim. However, certain shims can be used to Bypass User Account Control (UAC) (RedirectEXE), inject DLLs into processes (InjectDll), and intercept memory addresses (GetProcAddress). Utilizing these shims, an adversary can perform several malicious acts, such as elevate privileges, install backdoors, disable defenses like Windows Defender, etc.

Detection: There are several public tools available that will detect shims that are currently available[[Citation: Black Hat 2015 App Shim]]:

- Shim-Process-Scanner - checks memory of every running process for any Shim flags
- Shim-Detector-Lite - detects installation of custom shim databases
- Shim-Guard - monitors registry for any shim installations
- ShimScanner - forensic tool to find active shims in memory
- ShimCacheMem - Volatility plug-in that pulls shim cache from memory (note: shims are only cached after reboot)

Monitor process execution for sdbinst.exe and command-line arguments for potential indications of application shim abuse.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Loaded DLLs, System calls, Windows Registry, Process Monitoring, Process command-line parameters

Table 519. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1138">https://attack.mitre.org/wiki/Technique/T1138</a>
<a href="https://www.blackhat.com/docs/eu-15/materials/eu-15-Pierce-Defending-Against-Malicious-Application-Compatibility-Shims-wp.pdf">https://www.blackhat.com/docs/eu-15/materials/eu-15-Pierce-Defending-Against-Malicious-Application-Compatibility-Shims-wp.pdf</a>

## Windows Management Instrumentation

Windows Management Instrumentation (WMI) is a Windows administration feature that provides a uniform environment for local and remote access to Windows system components. It relies on the WMI service for local and remote access and the server message block (SMB)[[Citation: Wikipedia SMB]] and Remote Procedure Call Service (RPCS)[[Citation: TechNet RPC]] for remote access. RPCS operates over port 135.[[Citation: MSDN WMI]]

An adversary can use WMI to interact with local and remote systems and use it as a means to perform many tactic functions, such as gathering information for and remote of files as part of [[Lateral Movement]].[[Citation: FireEye WMI 2015]]

Detection: Monitor network traffic for WMI connections; the use of WMI in environments that do not typically use WMI may be suspect. Perform process monitoring to capture command-line arguments of "wmic" and detect commands that are used to perform remote behavior.[[Citation: FireEye WMI 2015]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Authentication logs, Netflow/Enclave netflow, Process monitoring, Process command-line parameters

Table 520. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1047">https://attack.mitre.org/wiki/Technique/T1047</a>
<a href="https://msdn.microsoft.com/en-us/library/aa394582.aspx">https://msdn.microsoft.com/en-us/library/aa394582.aspx</a>
<a href="https://en.wikipedia.org/wiki/Server%20Message%20Block">https://en.wikipedia.org/wiki/Server%20Message%20Block</a>
<a href="https://technet.microsoft.com/en-us/library/cc787851.aspx">https://technet.microsoft.com/en-us/library/cc787851.aspx</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/wp-windows-management-instrumentation.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/wp-windows-management-instrumentation.pdf</a>

## NTFS Extended Attributes

Data or executables may be stored in New Technology File System (NTFS) partition metadata instead of directly in files. This may be done to evade some defenses, such as static indicator scanning tools and anti-virus. [[Citation: Journey into IR ZeroAccess NTFS EA]]

The NTFS format has a feature called Extended Attributes (EA), which allows data to be stored as an attribute of a file or folder. [[Citation: Microsoft File Streams]]

Detection: Forensic techniques exist to identify information stored in EA. [[Citation: Journey into IR ZeroAccess NTFS EA]] It may be possible to monitor NTFS for writes or reads to NTFS EA or to regularly scan for the presence of modified information.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: File monitoring, Kernel drivers

*Table 521. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1096">https://attack.mitre.org/wiki/Technique/T1096</a>
<a href="http://journeyintoir.blogspot.com/2012/12/extracting-zeroaccess-from-ntfs.html">http://journeyintoir.blogspot.com/2012/12/extracting-zeroaccess-from-ntfs.html</a>
<a href="http://msdn.microsoft.com/en-us/library/aa364404">http://msdn.microsoft.com/en-us/library/aa364404</a>

## Launch Daemon

Per Apple's developer documentation, when macOS and OS X boot up, launchd is run to finish system initialization. This process loads the parameters for each launch-on-demand system-level daemon from the property list (plist) files found in `/System/Library/LaunchDaemons` and `/Library/LaunchDaemons` [[Citation: AppleDocs Launch Agent Daemons]]. These LaunchDaemons have property list files which point to the executables that will be launched [[Citation: Methods of Mac Malware Persistence]].

Adversaries may install a new launch daemon that can be configured to execute at startup by using launchd or launchctl to load a plist into the appropriate directories [[Citation: OSX Malware Detection]]. The daemon name may be disguised by using a name from a related operating system or benign software [[Citation: WireLurker]]. Launch Daemons may be created with administrator privileges, but are executed under root privileges, so an adversary may also use a service to escalate privileges from administrator to root.

The plist file permissions must be root:wheel, but the script or program that it points to has no such requirement. So, it is possible for poor configurations to allow an adversary to modify a current Launch Daemon's executable and gain persistence or Privilege Escalation.

Detection: Monitor Launch Daemon creation through additional plist files and utilities such as Objective-See's Knock Knock application.

Platforms: MacOS, OS X

Data Sources: Process Monitoring, File monitoring

Effective Permissions: root

Table 522. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1160">https://attack.mitre.org/wiki/Technique/T1160</a>
<a href="https://developer.apple.com/library/content/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/CreatingLaunchdJobs.html">https://developer.apple.com/library/content/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/CreatingLaunchdJobs.html</a>
<a href="https://www.paloaltonetworks.com/content/dam/pan/en%20US/assets/pdf/reports/Unit%2042/unit42-wirelurker.pdf">https://www.paloaltonetworks.com/content/dam/pan/en%20US/assets/pdf/reports/Unit%2042/unit42-wirelurker.pdf</a>
<a href="https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf">https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf</a>
<a href="https://www.synack.com/wp-content/uploads/2016/03/RSA%20OSX%20Malware.pdf">https://www.synack.com/wp-content/uploads/2016/03/RSA%20OSX%20Malware.pdf</a>

## Process Discovery

Adversaries may attempt to get information about running processes on a system. Information obtained could be used to gain an understanding of common software running on systems within the network.

===Windows===

An example command that would obtain details on processes is "tasklist" using the Tasklist utility.

===Mac and Linux===

In Mac and Linux, this is accomplished with the `ps` command.

Detection: System and network discovery techniques normally occur throughout an operation as an adversary learns the environment. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Process monitoring, Process command-line parameters

Table 523. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1057">https://attack.mitre.org/wiki/Technique/T1057</a>



# System Firmware

The BIOS (Basic Input/Output System) and The Unified Extensible Firmware Interface (UEFI) or Extensible Firmware Interface (EFI) are examples of system firmware that operate as the software interface between the operating system and hardware of a computer. [[Citation: Wikipedia BIOS]] [[Citation: Wikipedia UEFI]] [[Citation: About UEFI]]

System firmware like BIOS and (U)EFI underly the functionality of a computer and may be modified by an adversary to perform or assist in malicious activity. Capabilities exist to overwrite the system firmware, which may give sophisticated adversaries a means to install malicious firmware updates as a means of persistence on a system that may be difficult to detect.

Detection: System firmware manipulation may be detected. [[Citation: MITRE Trustworthy Firmware Measurement]] Dump and inspect BIOS images on vulnerable systems and compare against known good images. [[Citation: MITRE Copernicus]] Analyze differences to determine if malicious changes have occurred. Log attempts to read/write to BIOS and compare against known patching behavior.

Likewise, EFI modules can be collected and compared against a known-clean list of EFI executable binaries to detect potentially malicious modules. The CHIPSEC framework can be used for analysis to determine if firmware modifications have been performed. [[Citation: McAfee CHIPSEC Blog]] [[Citation: Github CHIPSEC]] [[Citation: Intel HackingTeam UEFI Rootkit]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: API monitoring, BIOS, EFI

Contributors: Ryan Becwar

Table 524. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1019">https://attack.mitre.org/wiki/Technique/T1019</a>
<a href="https://en.wikipedia.org/wiki/Unified%20Extensible%20Firmware%20Interface">https://en.wikipedia.org/wiki/Unified%20Extensible%20Firmware%20Interface</a>
<a href="http://www.intelsecurity.com/advanced-threat-research/content/data/HT-UEFI-rootkit.html">http://www.intelsecurity.com/advanced-threat-research/content/data/HT-UEFI-rootkit.html</a>
<a href="http://www.uefi.org/about">http://www.uefi.org/about</a>
<a href="http://www.mitre.org/publications/project-stories/going-deep-into-the-bios-with-mitre-firmware-security-research">http://www.mitre.org/publications/project-stories/going-deep-into-the-bios-with-mitre-firmware-security-research</a>
<a href="http://www.mitre.org/capabilities/cybersecurity/overview/cybersecurity-blog/copernicus-question-your-assumptions-about">http://www.mitre.org/capabilities/cybersecurity/overview/cybersecurity-blog/copernicus-question-your-assumptions-about</a>
<a href="https://en.wikipedia.org/wiki/BIOS">https://en.wikipedia.org/wiki/BIOS</a>
<a href="https://github.com/chipsec/chipsec">https://github.com/chipsec/chipsec</a>
<a href="https://securingtomorrow.mcafee.com/business/chipsec-support-vault-7-disclosure-scanning/">https://securingtomorrow.mcafee.com/business/chipsec-support-vault-7-disclosure-scanning/</a>

# Registry Run Keys / Start Folder

Adding an entry to the "run keys" in the Registry or startup folder will cause the program referenced to be executed when a user logs in. Masquerading to make the Registry entries look as if they are associated with legitimate programs.

Detection: Monitor Registry for changes to run keys that do not correlate with known software, patch cycles, etc. Monitor the start folder for additions or changes. Tools such as Sysinternals Autoruns may also be used to detect system changes that could be attempts at persistence, including listing the run keys' Registry locations and startup folders. [[Citation: TechNet Autoruns]] Suspicious program execution as startup programs may show up as outlier processes that have not been seen before when compared against historical data.

Changes to these locations typically happen under normal conditions when legitimate software is installed. To increase confidence of malicious activity, data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as network connections made for [[Command and Control]], learning details about the environment through , and [[Lateral Movement]].

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Windows Registry, File monitoring

Table 525. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1060">https://attack.mitre.org/wiki/Technique/T1060</a>
<a href="https://technet.microsoft.com/en-us/sysinternals/bb963902">https://technet.microsoft.com/en-us/sysinternals/bb963902</a>
<a href="http://msdn.microsoft.com/en-us/library/aa376977">http://msdn.microsoft.com/en-us/library/aa376977</a>

## Service Execution

Adversaries may execute a binary, command, or script via a method that interacts with Windows services, such as the Service Control Manager. This can be done by either creating a new service or modifying an existing service. This technique is the execution used in conjunction with New Service and Modify Existing Service during service persistence or privilege escalation.

Detection: Changes to service Registry entries and command-line invocation of tools capable of modifying services that do not correlate with known software, patch cycles, etc., may be suspicious. If a service is used only to execute a binary or script and not to persist, then it will likely be changed back to its original form shortly after the service is restarted so the service is not left broken, as is the case with the common administrator tool PsExec.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Windows Registry, Process monitoring, Process command-line parameters

Table 526. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1035">https://attack.mitre.org/wiki/Technique/T1035</a>

## Uncommonly Used Port

Adversaries may conduct C2 communications over a non-standard port to bypass proxies and firewalls that have been improperly configured.

Detection: Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Netflow/Enclave netflow, Process use of network, Process monitoring

Table 527. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1065">https://attack.mitre.org/wiki/Technique/T1065</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>

## Deobfuscate/Decode Files or Information

Adversaries may use Obfuscated Files or Information to hide artifacts of an intrusion from analysis. They may require separate mechanisms to decode or deobfuscate that information depending on how they intend to use it. Methods for doing that include built-in functionality of malware, Scripting, PowerShell, or by using utilities present on the system.

One such example is use of certutil to decode a remote access tool portable executable file that has been hidden inside a certificate file.certutil.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: File monitoring, Process Monitoring, Process command-line parameters

Contributors: Matthew Demaske, Adaptforward

Table 528. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1140">https://attack.mitre.org/wiki/Technique/T1140</a>
<a href="https://blog.malwarebytes.com/cybercrime/social-engineering-cybercrime/2017/03/new-targeted-attack-saudi-arabia-government/">https://blog.malwarebytes.com/cybercrime/social-engineering-cybercrime/2017/03/new-targeted-attack-saudi-arabia-government/</a>

## Create Account

Adversaries with a sufficient level of access may create a local system or domain account. Such accounts may be used for persistence that do not require persistent remote access tools to be deployed on the system.

The `net user` commands can be used to create a local or domain account.

Detection: Collect data on account creation within a network. Event ID 4720 is generated when a user account is created on a Windows system and domain controller. [[Citation: Microsoft User Creation Event]] Perform regular audits of domain and local system accounts to detect suspicious accounts that may have been created by an adversary.

Platforms: Windows 10, Windows Server 2012, Windows 7, Windows 8, Windows Server 2008 R2, Windows Server 2012 R2, Windows 8.1, Windows Server 2003, Windows Server 2008, Windows XP, Windows Server 2003 R2, Windows Vista, Linux, MacOS, OS X

Data Sources: Process Monitoring, Process command-line parameters, Authentication logs, Windows event logs

Table 529. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1136">https://attack.mitre.org/wiki/Technique/T1136</a>
<a href="https://docs.microsoft.com/windows/device-security/auditing/event-4720">https://docs.microsoft.com/windows/device-security/auditing/event-4720</a>

## Data Staged

Collected data is staged in a central location or directory prior to Data Compressed or Data Encrypted.

Interactive command shells may be used, and common functionality within cmd and bash may be used to copy data into a staging location.

Detection: Processes that appear to be reading files from disparate locations and writing them to the same directory or file may be an indication of data being staged, especially if they are suspected of performing encryption or compression on the files.

Monitor processes and command-line arguments for actions that could be taken to collect and combine files. Remote access tools with built-in features may interact directly with the Windows API to gather and copy to a location. Data may also be acquired and staged through Windows system management tools such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process command-line parameters

Table 530. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1074">https://attack.mitre.org/wiki/Technique/T1074</a>

## Rc.common

During the boot process, macOS and Linux both execute `source /etc/rc.common`, which is a shell script containing various utility functions. This file also defines routines for processing command-line arguments and for gathering system settings, and is thus recommended to include in the start of Startup Item Scripts[[Citation: Startup Items]]. In macOS and OS X, this is now a deprecated technique in favor of launch agents and launch daemons, but is currently still used.

Adversaries can use the rc.common file as a way to hide code for persistence that will execute on each reboot as the root user[[Citation: Methods of Mac Malware Persistence]].

Detection: The `/etc/rc.common` file can be monitored to detect changes from the company policy. Monitor process execution resulting from the rc.common script for unusual or unknown applications or behavior.

Platforms: Linux, MacOS, OS X

Data Sources: File monitoring, Process Monitoring

Table 531. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1163">https://attack.mitre.org/wiki/Technique/T1163</a>
<a href="https://developer.apple.com/library/content/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/StartupItems.html">https://developer.apple.com/library/content/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/StartupItems.html</a>
<a href="https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf">https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf</a>

## Securityd Memory

In OS X prior to El Capitan, users with root access can read plaintext keychain passwords of logged-in users because Apple's keychain implementation allows these credentials to be cached so that users are not repeatedly prompted for passwords. [[Citation: OS X Keychain]] [[Citation: External to DA, the OS X Way]] Apple's securityd utility takes the user's logon password, encrypts it with PBKDF2, and stores this master key in memory. Apple also uses a set of keys and algorithms to encrypt the user's password, but once the master key is found, an attacker need only iterate over the other values to unlock the final password. [[Citation: OS X Keychain]]

If an adversary can obtain root access (allowing them to read securityd's memory), then they can scan through memory to find the correct sequence of keys in relatively few tries to decrypt the user's logon keychain. This provides the adversary with all the plaintext passwords for users, WiFi, mail, browsers, certificates, secure notes, etc. [[Citation: OS X Keychain]] [[Citation: OSX Keydnep malware]]

Platforms: OS X

Data Sources: Process Monitoring

Table 532. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1167">https://attack.mitre.org/wiki/Technique/T1167</a>
<a href="https://www.welivesecurity.com/2016/07/06/new-osxkeydnep-malware-hungry-credentials/">https://www.welivesecurity.com/2016/07/06/new-osxkeydnep-malware-hungry-credentials/</a>
<a href="http://www.slideshare.net/StephanBorosh/external-to-da-the-os-x-way">http://www.slideshare.net/StephanBorosh/external-to-da-the-os-x-way</a>
<a href="http://juusosalonen.com/post/30923743427/breaking-into-the-os-x-keychain">http://juusosalonen.com/post/30923743427/breaking-into-the-os-x-keychain</a>

## New Service

When operating systems boot up, they can start programs or applications called services that perform background system functions. Masquerading. Services may be created with administrator privileges but are executed under SYSTEM privileges, so an adversary may also use a service to escalate privileges from administrator to SYSTEM. Adversaries may also directly start services through Service Execution.

Detection: Monitor service creation through changes in the Registry and common utilities using command-line invocation. New, benign services may be created during installation of new software. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as network connections made for Windows Management Instrumentation and PowerShell, so additional logging may need to be configured to gather the appropriate data.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Windows Registry, Process monitoring, Process command-line parameters

Effective Permissions: SYSTEM

Table 533. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1050">https://attack.mitre.org/wiki/Technique/T1050</a>
<a href="https://technet.microsoft.com/en-us/sysinternals/bb963902">https://technet.microsoft.com/en-us/sysinternals/bb963902</a>
<a href="https://technet.microsoft.com/en-us/library/cc772408.aspx">https://technet.microsoft.com/en-us/library/cc772408.aspx</a>

# Network Share Connection Removal

Windows shared drive and Windows Admin Shares connections can be removed when no longer needed. Net is an example utility that can be used to remove network share connections with the `net use \\system\share /delete` command. Windows Admin Shares. SMB traffic between systems may also be captured and decoded to look for related network share session and file transfer activity. Windows authentication logs are also useful in determining when authenticated network shares are established and by which account, and can be used to correlate network share activity to other events to investigate potentially malicious activity.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Process monitoring, Process command-line parameters, Packet capture, Authentication logs

Table 534. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1126">https://attack.mitre.org/wiki/Technique/T1126</a>
<a href="https://technet.microsoft.com/bb490717.aspx">https://technet.microsoft.com/bb490717.aspx</a>

## DLL Injection

DLL injection is used to run code in the context of another process by causing the other process to load and execute code. Running code in the context of another process provides adversaries many benefits, such as access to the process's memory and permissions. It also allows adversaries to mask their actions under a legitimate process. A more sophisticated kind of DLL injection, reflective DLL injection, loads code without calling the normal Windows API calls, potentially bypassing DLL load monitoring. Numerous methods of DLL injection exist on Windows, including modifying the Registry, creating remote threads, Windows hooking APIs, and DLL pre-loading. PowerShell with tools such as PowerSploit,[[Citation: Powersploit]] so additional PowerShell monitoring may be required to cover known implementations of this behavior.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: API monitoring, Windows Registry, File monitoring, Process monitoring

Effective Permissions: User, Administrator, SYSTEM

Table 535. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1055">https://attack.mitre.org/wiki/Technique/T1055</a>
<a href="http://www.codeproject.com/Articles/4610/Three-Ways-to-Inject-Your-Code-into-Another-Process">http://www.codeproject.com/Articles/4610/Three-Ways-to-Inject-Your-Code-into-Another-Process</a>

<http://en.wikipedia.org/wiki/DLL%20injection>

<https://github.com/mattifestation/PowerSploit>

## Hidden Files and Directories

To prevent normal users from accidentally changing special files on a system, most operating systems have the concept of a 'hidden' file. These files don't show up when a user browses the file system with a GUI or when using normal commands on the command line. Users must explicitly ask to show the hidden files either via a series of Graphical User Interface (GUI) prompts or with command line switches (`dir /a` for Windows and `ls -a` for Linux and macOS).

===Windows===

Users can mark specific files as hidden by using the `attrib.exe` binary. Simply do `attrib +h filename` to mark a file or folder as hidden. Similarly, the "+s" marks a file as a system file and the "+r" flag marks the file as read only. Like most windows binaries, the `attrib.exe` binary provides the ability to apply these changes recursively "/S".

===Linux/Mac===

Users can mark specific files as hidden simply by putting a "." as the first character in the file or folder name [[Citation: Sofacy Komplex Trojan]][[Citation: Antiquated Mac Malware]]. Files and folder that start with a period, '.', are by default hidden from being viewed in the Finder application and standard command-line utilities like "ls". Users must specifically change settings to have these files viewable. For command line usages, there is typically a flag to see all files (including hidden ones). To view these files in the Finder Application, the following command must be executed: `defaults write com.apple.finder AppleShowAllFiles YES`, and then relaunch the Finder Application.

===Mac===

Files on macOS can be marked with the `UF_HIDDEN` flag which prevents them from being seen in `Finder.app`, but still allows them to be seen in `Terminal.app`[[Citation: WireLurker]]. Many applications create these hidden files and folders to store information so that it doesn't clutter up the user's workspace. For example, SSH utilities create a `.ssh` folder that's hidden and contains the user's known hosts and keys.

Adversaries can use this to their advantage to hide files and folders anywhere on the system for persistence and evading a typical user or system analysis that does not incorporate investigation of hidden files.

Detection: Monitor the file system and shell commands for files being created with a leading "." and the Windows command-line use of `attrib.exe` to add the hidden attribute.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X



Table 536. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1158">https://attack.mitre.org/wiki/Technique/T1158</a>
<a href="https://www.paloaltonetworks.com/content/dam/pan/en%20US/assets/pdf/reports/Unit%2042/unit42-wirelurker.pdf">https://www.paloaltonetworks.com/content/dam/pan/en%20US/assets/pdf/reports/Unit%2042/unit42-wirelurker.pdf</a>
<a href="https://researchcenter.paloaltonetworks.com/2016/09/unit42-sofacys-komplex-os-x-trojan/">https://researchcenter.paloaltonetworks.com/2016/09/unit42-sofacys-komplex-os-x-trojan/</a>
<a href="https://blog.malwarebytes.com/threat-analysis/2017/01/new-mac-backdoor-using-antiquated-code/">https://blog.malwarebytes.com/threat-analysis/2017/01/new-mac-backdoor-using-antiquated-code/</a>

## Authentication Package

Windows Authentication Package DLLs are loaded by the Local Security Authority (LSA) process at system start. They provide support for multiple logon processes and multiple security protocols to the operating system. [[Citation: MSDN Authentication Packages]]

Adversaries can use the autostart mechanism provided by LSA Authentication Packages for persistence by placing a reference to a binary in the Windows Registry location `HKLM\SYSTEM\CurrentControlSet\Control\Lsa` with the key value of `"Authentication Packages"=<target binary>`. The binary will then be executed by the system when the authentication packages are loaded.

Detection: Monitor the Registry for changes to the LSA Registry keys. Monitor the LSA process for DLL loads. Windows 8.1 and Windows Server 2012 R2 may generate events when unsigned DLLs try to load into the LSA by setting the Registry key `HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\LSASS.exe` with `AuditLevel = 8`. [[Citation: Graeber 2014]] [[Citation: Microsoft Configure LSA]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: DLL monitoring, Windows Registry, Loaded DLLs

Table 537. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1131">https://attack.mitre.org/wiki/Technique/T1131</a>
<a href="https://msdn.microsoft.com/library/windows/desktop/aa374733.aspx">https://msdn.microsoft.com/library/windows/desktop/aa374733.aspx</a>
<a href="https://technet.microsoft.com/en-us/library/dn408187.aspx">https://technet.microsoft.com/en-us/library/dn408187.aspx</a>
<a href="http://docplayer.net/20839173-Analysis-of-malicious-security-support-provider-dlls.html">http://docplayer.net/20839173-Analysis-of-malicious-security-support-provider-dlls.html</a>

## Multilayer Encryption

An adversary performs C2 communications using multiple layers of encryption, typically (but not exclusively) tunneling a custom encryption scheme within a protocol encryption scheme such as

HTTPS or SMTPS.

Detection: If malware uses Standard Cryptographic Protocol, SSL/TLS inspection can be used to detect command and control traffic within some encrypted communication channels. Custom Cryptographic Protocol, if malware uses encryption with symmetric keys, it may be possible to obtain the algorithm and key from samples and use them to decode network traffic to detect malware communications signatures. [[Citation: Fidelis DarkComet]]

In general, analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Packet capture, Process use of network, Malware reverse engineering, Process monitoring

Table 538. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1079">https://attack.mitre.org/wiki/Technique/T1079</a>
<a href="https://www.fidelissecurity.com/sites/default/files/FTA%201018%20looking%20at%20the%20sky%20for%20a%20dark%20comet.pdf">https://www.fidelissecurity.com/sites/default/files/FTA%201018%20looking%20at%20the%20sky%20for%20a%20dark%20comet.pdf</a>
<a href="http://www.sans.org/reading-room/whitepapers/analyst/finding-hidden-threats-decrypting-ssl-34840">http://www.sans.org/reading-room/whitepapers/analyst/finding-hidden-threats-decrypting-ssl-34840</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>
<a href="https://insights.sei.cmu.edu/cert/2015/03/the-risks-of-ssl-inspection.html">https://insights.sei.cmu.edu/cert/2015/03/the-risks-of-ssl-inspection.html</a>

## Component Firmware

Some adversaries may employ sophisticated means to compromise computer components and install malicious firmware that will execute adversary code outside of the operating system and main system firmware or BIOS. This technique may be similar to System Firmware but conducted upon other system components that may not have the same capability or level of integrity checking. Malicious device firmware could provide both a persistent level of access to systems despite potential typical failures to maintain access and hard disk re-images, as well as a way to evade host software-based defenses and integrity checks.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Table 539. Table References

Links
-------

## Cron Job

Per Apple's developer documentation, there are two supported methods for creating periodic background jobs: launchd and cron[[Citation: AppleDocs Scheduling Timed Jobs]].

===Launchd===

Each Launchd job is described by a different configuration property list (plist) file similar to Launch Daemons or Launch Agents, except there is an additional key called `StartCalendarInterval` with a dictionary of time values [[Citation: AppleDocs Scheduling Timed Jobs]]. This only works on macOS and OS X.

===cron===

System-wide cron jobs are installed by modifying `/etc/crontab` while per-user cron jobs are installed using `crontab` with specifically formatted crontab files [[Citation: AppleDocs Scheduling Timed Jobs]]. This works on Mac and Linux systems.

Both methods allow for commands or scripts to be executed at specific, periodic intervals in the background without user interaction. An adversary may use task scheduling to execute programs at system startup or on a scheduled basis for persistence[[Citation: Janicab]][[Citation: Methods of Mac Malware Persistence]][[Citation: Malware Persistence on OS X]], to conduct Execution as part of Lateral Movement, to gain root privileges, or to run a process under the context of a specific account.

Detection: Legitimate scheduled jobs may be created during installation of new software or through administration functions. Tasks scheduled with launchd and cron can be monitored from their respective utilities to list out detailed information about the jobs. Monitor process execution resulting from launchd and cron tasks to look for unusual or unknown applications and behavior.

Platforms: Linux, MacOS

Data Sources: File monitoring, Process Monitoring

Table 540. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1168">https://attack.mitre.org/wiki/Technique/T1168</a>
<a href="https://www.rsaconference.com/writable/presentations/file%20upload/ht-r03-malware-persistence-on-os-x-yosemite%20final.pdf">https://www.rsaconference.com/writable/presentations/file%20upload/ht-r03-malware-persistence-on-os-x-yosemite%20final.pdf</a>
<a href="http://www.thesafemac.com/new-signed-malware-called-janicab/">http://www.thesafemac.com/new-signed-malware-called-janicab/</a>
<a href="https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf">https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf</a>
<a href="https://developer.apple.com/library/content/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/ScheduledJobs.html">https://developer.apple.com/library/content/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/ScheduledJobs.html</a>

# Windows Management Instrumentation Event Subscription

Windows Management Instrumentation (WMI) can be used to install event filters, providers, consumers, and bindings that execute code when a defined event occurs. Adversaries may use the capabilities of WMI to subscribe to an event and execute arbitrary code when that event occurs, providing persistence on a system. Adversaries may attempt to evade detection of this technique by compiling WMI scripts. [[Citation: Dell WMI Persistence]] Examples of events that may be subscribed to are the wall clock time or the computer's uptime. [[Citation: Kazanciyan 2014]] Several threat groups have reportedly used this technique to maintain persistence. [[Citation: Mandiant M-Trends 2015]]

Detection: Monitor WMI event subscription entries, comparing current WMI event subscriptions to known good subscriptions for each host. Tools such as Sysinternals Autoruns may also be used to detect WMI changes that could be attempts at persistence. [[Citation: TechNet Autoruns]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: WMI Objects

Table 541. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1084">https://attack.mitre.org/wiki/Technique/T1084</a>
<a href="https://technet.microsoft.com/en-us/sysinternals/bb963902">https://technet.microsoft.com/en-us/sysinternals/bb963902</a>
<a href="https://www2.fireeye.com/rs/fireeye/images/rpt-m-trends-2015.pdf">https://www2.fireeye.com/rs/fireeye/images/rpt-m-trends-2015.pdf</a>
<a href="https://www.secureworks.com/blog/wmi-persistence">https://www.secureworks.com/blog/wmi-persistence</a>
<a href="https://www.defcon.org/images/defcon-22/dc-22-presentations/Kazanciyan-Hastings/DEFCON-22-Ryan-Kazanciyan-Matt-Hastings-Investigating-Powershell-Attacks.pdf">https://www.defcon.org/images/defcon-22/dc-22-presentations/Kazanciyan-Hastings/DEFCON-22-Ryan-Kazanciyan-Matt-Hastings-Investigating-Powershell-Attacks.pdf</a>

## Disabling Security Tools

Adversaries may disable security tools to avoid possible detection of their tools and activities. This can take the form of killing security software or event logging processes, deleting Registry keys so that tools do not start at run time, or other methods to interfere with security scanning or event reporting.

Detection: Monitor processes and command-line arguments to see if security tools are killed or stop running. Monitor Registry edits for modifications to services and startup programs that correspond to security tools. Lack of log or event file reporting may be suspicious.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: API monitoring, File monitoring, Services, Windows Registry, Process command-line parameters, Anti-virus

Table 542. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1089">https://attack.mitre.org/wiki/Technique/T1089</a>

## Peripheral Device Discovery

Adversaries may attempt to gather information about attached peripheral devices and components connected to a computer system. The information may be used to enhance their awareness of the system and network environment or may be used for further actions.

Detection: System and network discovery techniques normally occur throughout an operation as an adversary learns the environment. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities based on the information obtained.

Monitor processes and command-line arguments for actions that could be taken to gather system and network information. Remote access tools with built-in features may interact directly with the Windows API to gather information. Information may also be acquired through Windows system management tools such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Table 543. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1120">https://attack.mitre.org/wiki/Technique/T1120</a>

## Data Compressed

An adversary may compress data (e.g., sensitive documents) that is collected prior to exfiltration in order to make it portable and minimize the amount of data sent over the network. The compression is done separately from the exfiltration channel and is performed using a custom program or algorithm, or a more common compression library or utility such as 7zip, RAR, ZIP, or zlib.

Detection: Compression software and compressed files can be detected in many ways. Common utilities that may be present on the system or brought in by an adversary may be detectable through process monitoring and monitoring for command-line arguments for known compression utilities. This may yield a significant amount of benign events, depending on how systems in the environment are typically used.

If the communications channel is unencrypted, compressed files can be detected in transit during exfiltration with a network intrusion detection or data loss prevention system analyzing file headers. [[Citation: Wikipedia File Header Signatures]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process command-line parameters, Binary file metadata

Table 544. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1002">https://attack.mitre.org/wiki/Technique/T1002</a>
<a href="https://en.wikipedia.org/wiki/List%20of%20file%20signatures">https://en.wikipedia.org/wiki/List%20of%20file%20signatures</a>

## Account Discovery

Adversaries may attempt to get a listing of local system or domain accounts.

===Windows===

Example commands that can acquire this information are `net user`, `net group <groupname>`, and `net localgroup <groupname>` using the Net utility or through use of dsquery. If adversaries attempt to identify the primary user, currently logged in user, or set of users that commonly uses a system, System Owner/User Discovery may apply.

===Mac===

On Mac, groups can be enumerated through the `groups` and `id` commands. In mac specifically, `dscl . list /Groups` and `dscacheutil -q group` can also be used to enumerate groups and users.

===Linux===

On Linux, local users can be enumerated through the use of the `/etc/passwd` file which is world readable. In mac, this same file is only used in single-user mode in addition to the `/etc/master.passwd` file.

Also, groups can be enumerated through the `groups` and `id` commands. In mac specifically, `dscl . list /Groups` and `dscacheutil -q group` can also be used to enumerate groups and users.

Detection: System and network discovery techniques normally occur throughout an operation as an adversary learns the environment. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: API monitoring, Process monitoring, Process command-line parameters

Table 545. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1087">https://attack.mitre.org/wiki/Technique/T1087</a>

## Pass the Hash

Pass the hash (PtH)[[Citation: Aorato PTH]] is a method of authenticating as a user without having access to the user's cleartext password. This method bypasses standard authentication steps that require a cleartext password, moving directly into the portion of the authentication that uses the password hash. In this technique, valid password hashes for the account being used are captured using a [[Credential Access]] technique. Captured hashes are used with PtH to authenticate as that user. Once authenticated, PtH may be used to perform actions on local or remote systems.

Windows 7 and higher with KB2871997 require valid domain user credentials or RID 500 administrator hashes.[[Citation: NSA Spotting]]

Detection: Audit all logon and credential use events and review for discrepancies. Unusual remote logins that correlate with other suspicious activity (such as writing and executing binaries) may indicate malicious activity. NTLM LogonType 3 authentications that are not associated to a domain login and are not anonymous logins are suspicious.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Authentication logs

Table 546. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1075">https://attack.mitre.org/wiki/Technique/T1075</a>
<a href="http://www.nsa.gov/ia/%20files/app/spotting%20the%20adversary%20with%20windows%20event%20log%20monitoring.pdf">http://www.nsa.gov/ia/%20files/app/spotting%20the%20adversary%20with%20windows%20event%20log%20monitoring.pdf</a>
<a href="http://www.aorato.com/labs/pass-the-hash/">http://www.aorato.com/labs/pass-the-hash/</a>

## Clear Command History

macOS and Linux both keep track of the commands users type in their terminal so that users can easily remember what they've done. These logs can be accessed in a few different ways. While logged in, this command history is tracked in a file pointed to by the environment variable `HISTFILE`. When a user logs off a system, this information is flushed to a file in the user's home directory called `~/.bash_history`. The benefit of this is that it allows users to go back to commands they've used before in different sessions. Since everything typed on the command-line is saved, passwords passed in on the command line are also saved. Adversaries can abuse this by searching these files for cleartext passwords. Additionally, adversaries can use a variety of methods to prevent their own commands from appear in these logs such as `unset HISTFILE`, `export HISTFILESIZE=0`, `history -c`, `rm`

`~/.bash_history`.

Detection: User authentication, especially via remote terminal services like SSH, without new entries in that user's `~/.bash_history` is suspicious. Additionally, the modification of the HISTFILE and HISTFILESIZE environment variables or the removal/clearing of the `~/.bash_history` file are indicators of suspicious activity.

Platforms: Linux, MacOS, OS X

Data Sources: Authentication logs, File monitoring

Table 547. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1146">https://attack.mitre.org/wiki/Technique/T1146</a>

## Timestomp

Timestomping is a technique that modifies the timestamps of a file (the modify, access, create, and change times), often to mimic files that are in the same folder. This is done, for example, on files that have been modified or created by the adversary so that they do not appear conspicuous to forensic investigators or file analysis tools. Timestomping may be used along with file name Masquerading to hide malware and tools. [[Citation: WindowsIR Anti-Forensic Techniques]]

Detection: Forensic techniques exist to detect aspects of files that have had their timestamps modified. [[Citation: WindowsIR Anti-Forensic Techniques]] It may be possible to detect timestomping using file modification monitoring that collects information on file handle opens and can compare timestamp values.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10

Data Sources: File monitoring, Process monitoring, Process command-line parameters

Table 548. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1099">https://attack.mitre.org/wiki/Technique/T1099</a>
<a href="http://windowsir.blogspot.com/2013/07/howto-determinedetect-use-of-anti.html">http://windowsir.blogspot.com/2013/07/howto-determinedetect-use-of-anti.html</a>

## Setuid and Setgid

When the setuid or setgid bits are set on Linux or macOS for an application, this means that the application will run with the privileges of the owning user or group respectively. Normally an application is run in the current user's context, regardless of which user or group owns the application. There are instances where programs need to be executed in an elevated context to function properly, but the user running them doesn't need the elevated privileges. Instead of creating an entry in the sudoers file, which must be done by root, any user can specify the setuid or



setgid flag to be set for their own applications. These bits are indicated with an "s" instead of an "x" when viewing a file's attributes via `ls -l`. The `chmod` program can set these bits with via bitmasking, `chmod 4777 [file]` or via shorthand naming, `chmod u+s [file]`.

An adversary can take advantage of this to either do a shell escape or exploit a vulnerability in an application with the setsuid or setgid bits to get code running in a different user's context.

Detection: Monitor the file system for files that have the setuid or setgid bits set. Monitor for execution of utilities, like `chmod`, and their command-line arguments to look for setuid or setgid bits being set.

Platforms: Linux, MacOS, OS X

Data Sources: File monitoring, Process Monitoring, Process command-line parameters

Effective Permissions: Administrator, root

*Table 549. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1166">https://attack.mitre.org/wiki/Technique/T1166</a>

## Brute Force

Adversaries may use brute force techniques to attempt access to accounts when passwords are unknown or when password hashes are obtained.

Credential Dumping to obtain password hashes may only get an adversary so far when Pass the Hash is not an option. Techniques to systematically guess the passwords used to compute hashes are available, or the adversary may use a pre-computed rainbow table. Cracking hashes is usually done on adversary-controlled systems outside of the target network. Valid Accounts. If authentication failures are high, then there may be a brute force attempt to gain access to a system using legitimate credentials.

Also monitor for many failed authentication attempts across various accounts that may result from password spraying attempts.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: Authentication logs

Contributors: John Strand

*Table 550. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1110">https://attack.mitre.org/wiki/Technique/T1110</a>

<http://www.blackhillsinfosec.com/?p=4645>

<http://www.cylance.com/assets/Cleaver/Cylance%20Operation%20Cleaver%20Report.pdf>

<https://en.wikipedia.org/wiki/Password%20cracking>

## Modify Registry

Adversaries may interact with the Windows Registry to hide configuration information within Registry keys, remove information as part of cleaning up, or as part of other techniques to aid in Reg may be used for local or remote Registry modification. Valid Accounts are required, along with access to the remote system's Windows Admin Shares for RPC communication.

Detection: Modifications to the Registry are normal and occur throughout typical use of the Windows operating system. Changes to Registry entries that load software on Windows startup that do not correlate with known software, patch cycles, etc., are suspicious, as are additions or changes to files within the startup folder. Changes could also include new services and modification of existing binary paths to point to malicious files. If a change to a service-related entry occurs, then it will likely be followed by a local or remote service start or restart to execute the file.

Monitor processes and command-line arguments for actions that could be taken to change or delete information in the Registry. Remote access tools with built-in features may interact directly with the Windows API to gather information. Information may also be acquired through Windows system management tools such as Windows Management Instrumentation and PowerShell, which may require additional logging features to be configured in the operating system to collect necessary information for analysis.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Windows Registry, File monitoring, Process monitoring, Process command-line parameters

*Table 551. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1112">https://attack.mitre.org/wiki/Technique/T1112</a>
<a href="https://technet.microsoft.com/en-us/library/cc754820.aspx">https://technet.microsoft.com/en-us/library/cc754820.aspx</a>
<a href="https://technet.microsoft.com/en-us/library/cc732643.aspx">https://technet.microsoft.com/en-us/library/cc732643.aspx</a>

## Screen Capture

Adversaries may attempt to take screen captures of the desktop to gather information over the course of an operation. Screen capturing functionality may be included as a feature of a remote access tool used in post-compromise operations.

===Mac===

On OSX, the native command `screencapture` is used to capture screenshots.

===Linux===

On Linux, there is the native command `xwd`.<sup>[[Citation: Antiquated Mac Malware]]</sup>

Detection: Monitoring for screen capture behavior will depend on the method used to obtain data from the operating system and write output files. Detection methods could include collecting information from unusual processes using API calls used to obtain image data, and monitoring for image files written to disk. The sensor data may need to be correlated with other events to identify malicious activity, depending on the legitimacy of this behavior within a given network environment.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: API monitoring, Process monitoring, File monitoring

*Table 552. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1113">https://attack.mitre.org/wiki/Technique/T1113</a>
<a href="https://blog.malwarebytes.com/threat-analysis/2017/01/new-mac-backdoor-using-antiquated-code/">https://blog.malwarebytes.com/threat-analysis/2017/01/new-mac-backdoor-using-antiquated-code/</a>

## AppleScript

macOS and OS X applications send AppleEvent messages to each other for interprocess communications (IPC). These messages can be easily scripted with AppleScript for local or remote IPC. Osascript executes AppleScript and any other Open Scripting Architecture (OSA) language scripts. A list of OSA languages installed on a system can be found by using the `osalang` program. AppleEvent messages can be sent independently or as part of a script. These events can locate open windows, send keystrokes, and interact with almost any open application locally or remotely.

Adversaries can use this to interact with open SSH connection, move to remote machines, and even present users with fake dialog boxes. These events cannot start applications remotely (they can start them locally though), but can interact with applications if they're already running remotely. Since this is a scripting language, it can be used to launch more common techniques as well such as a reverse shell via python <sup>[[Citation: Macro Malware Targets Macs]]</sup>. Scripts can be run from the command line via `osascript /path/to/script` or `osascript -e "script here"`.

Detection: Monitor for execution of AppleScript through osascript that may be related to other suspicious behavior occurring on the system.

Platforms: MacOS, OS X

Data Sources: API monitoring, System calls, Process Monitoring, Process command-line parameters

*Table 553. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1155">https://attack.mitre.org/wiki/Technique/T1155</a>
<a href="https://securingtomorrow.mcafee.com/mcafee-labs/macro-malware-targets-macs/">https://securingtomorrow.mcafee.com/mcafee-labs/macro-malware-targets-macs/</a>

## Launchctl

Launchctl controls the macOS launchd process which handles things like launch agents and launch daemons, but can execute other commands or programs itself. Launchctl supports taking subcommands on the command-line, interactively, or even redirected from standard input. By loading or reloading launch agents or launch daemons, adversaries can install persistence or execute changes they made [[Citation: Sofacy Komplex Trojan]]. Running a command from launchctl is as simple as `launchctl submit -l <labelName> — /Path/to/thing/to/execute "arg" "arg" "arg"`. Loading, unloading, or reloading launch agents or launch daemons can require elevated privileges.

Adversaries can abuse this functionality to execute code or even bypass whitelisting if launchctl is an allowed process.

Detection: Knock Knock can be used to detect persistent programs such as those installed via launchctl as launch agents or launch daemons. Additionally, every launch agent or launch daemon must have a corresponding plist file on disk somewhere which can be monitored. Monitor process execution from launchctl/launchd for unusual or unknown processes.

Platforms: MacOS, OS X

Data Sources: File monitoring, Process Monitoring, Process command-line parameters

*Table 554. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1152">https://attack.mitre.org/wiki/Technique/T1152</a>
<a href="https://researchcenter.paloaltonetworks.com/2016/09/unit42-sofacys-komplex-os-x-trojan/">https://researchcenter.paloaltonetworks.com/2016/09/unit42-sofacys-komplex-os-x-trojan/</a>

## Indicator Removal from Tools

If a malicious tool is detected and quarantined or otherwise curtailed, an adversary may be able to determine why the malicious tool was detected (the indicator), modify the tool by removing the indicator, and use the updated version that is no longer detected by the target's defensive systems or subsequent targets that may use similar systems.

A good example of this is when malware is detected with a file signature and quarantined by anti-virus software. An adversary who can determine that the malware was quarantined because of its file signature may use Software Packing or otherwise modify the file so it has a different signature, and then re-use the malware.

Detection: The first detection of a malicious tool may trigger an anti-virus or other security tool alert. Similar events may also occur at the boundary through network IDS, email scanning appliance, etc. The initial detection should be treated as an indication of a potentially more invasive

intrusion. The alerting system should be thoroughly investigated beyond that initial alert for activity that was not detected. Adversaries may continue with an operation, assuming that individual events like an anti-virus detect will not be investigated or that an analyst will not be able to conclusively link that event to other activity occurring on the network.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: Process use of network, Process monitoring, Process command-line parameters, Anti-virus, Binary file metadata

*Table 555. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1066">https://attack.mitre.org/wiki/Technique/T1066</a>

## Dylib Hijacking

macOS and OS X use a common method to look for required dynamic libraries (dylib) to load into a program based on search paths. Adversaries can take advantage of ambiguous paths to plant dylibs to gain privilege escalation or persistence.

A common method is to see what dylibs an application uses, then plant a malicious version with the same name higher up in the search path. This typically results in the dylib being in the same folder as the application itself[[Citation: Writing Bad Malware for OSX]][[Citation: Malware Persistence on OS X]]. If the program is configured to run at a higher privilege level than the current user, then when the dylib is loaded into the application, the dylib will also run at that elevated level. This can be used by adversaries as a privilege escalation technique.

Detection: Objective-See's Dylib Hijacking Scanner can be used to detect potential cases of dylib hijacking. Monitor file systems for moving, renaming, replacing, or modifying dylibs. Changes in the set of dylibs that are loaded by a process (compared to past behavior) that do not correlate with known software, patches, etc., are suspicious. Check the system for multiple dylibs with the same name and monitor which versions have historically been loaded into a process.

Platforms: MacOS, OS X

Data Sources: File monitoring

Effective Permissions: Administrator, root

*Table 556. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1157">https://attack.mitre.org/wiki/Technique/T1157</a>
<a href="https://www.blackhat.com/docs/us-15/materials/us-15-Wardle-Writing-Bad-A-Malware-For-OS-X.pdf">https://www.blackhat.com/docs/us-15/materials/us-15-Wardle-Writing-Bad-A-Malware-For-OS-X.pdf</a>

## Change Default File Association

When a file is opened, the default program used to open the file (also called the file association or handler) is checked. File association selections are stored in the Windows Registry and can be edited by users, administrators, or programs that have Registry access. [[Citation: Microsoft Change Default Programs]] [[Citation: Microsoft File Handlers]] Applications can modify the file association for a given file extension to call an arbitrary program when a file with the given extension is opened.

Detection: Collect and analyze changes to Registry keys that associate file extensions to default applications for execution and correlate with unknown process launch activity or unusual file types for that process.

User file association preferences are stored under `[HKEY_CURRENT_USER]\Software\Microsoft\Windows\CurrentVersion\Explorer\FileExts` and override associations configured under `[HKEY_CLASSES_ROOT]`. Changes to a user's preference will occur under this entry's subkeys.

Also look for abnormal process call trees for execution of other commands that could relate to actions or other techniques.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Windows Registry, Process monitoring, Process command-line parameters

Contributors: Stefan Kanthak

*Table 557. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1042">https://attack.mitre.org/wiki/Technique/T1042</a>
<a href="http://msdn.microsoft.com/en-us/library/bb166549.aspx">http://msdn.microsoft.com/en-us/library/bb166549.aspx</a>
<a href="https://support.microsoft.com/en-us/help/18539/windows-7-change-default-programs">https://support.microsoft.com/en-us/help/18539/windows-7-change-default-programs</a>

## Space after Filename

Adversaries can hide a program's true filetype by changing the extension of a file. With certain file types (specifically this does not work with .app extensions), appending a space to the end of a filename will change how the file is processed by the operating system. For example, if there is a Mach-O executable file called evil.bin, when it is double clicked by a user, it will launch Terminal.app and execute. If this file is renamed to evil.txt, then when double clicked by a user, it will launch with the default text editing application (not executing the binary). However, if the file is renamed to "evil.txt " (note the space at the end), then when double clicked by a user, the true file

type is determined by the OS and handled appropriately and the binary will be executed[[Citation: Mac Backdoors are back]].

Adversaries can use this feature to trick users into double clicking benign-looking files of any format and ultimately executing something malicious.

Detection: It's not common for spaces to be at the end of filenames, so this is something that can easily be checked with file monitoring. From the user's perspective though, this is very hard to notice from within the Finder.app or on the command-line in Terminal.app. Processes executed from binaries containing non-standard extensions in the filename are suspicious.

Platforms: Linux, MacOS, OS X

Data Sources: File monitoring, Process Monitoring

*Table 558. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1151">https://attack.mitre.org/wiki/Technique/T1151</a>
<a href="https://arstechnica.com/security/2016/07/after-hiatus-in-the-wild-mac-backdoors-are-suddenly-back/">https://arstechnica.com/security/2016/07/after-hiatus-in-the-wild-mac-backdoors-are-suddenly-back/</a>

## Email Collection

Adversaries may target user email to collect sensitive information from a target.

Files containing email data can be acquired from a user's system, such as Outlook storage or cache files .pst and .ost.

Adversaries may leverage a user's credentials and interact directly with the Exchange server to acquire information from within a network.

Some adversaries may acquire user credentials and access externally facing webmail applications, such as Outlook Web Access.

Detection: There are likely a variety of ways an adversary could collect email from a target, each with a different mechanism for detection.

File access of local system email files for Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Authentication logs, File monitoring, Process monitoring, Process use of network

*Table 559. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1114">https://attack.mitre.org/wiki/Technique/T1114</a>

# System Information Discovery

An adversary may attempt to get detailed information about the operating system and hardware, including version, patches, hotfixes, service packs, and architecture.

===Windows===

Example commands and utilities that obtain this information include `ver`, Systeminfo, and `dir` within cmd for identifying information based on present files and directories.

===Mac===

On Mac, the `systemsetup` command gives a detailed breakdown of the system, but it requires administrative privileges. Additionally, the `system_profiler` gives a very detailed breakdown of configurations, firewall rules, mounted volumes, hardware, and many other things without needing elevated permissions.

Detection: System and network discovery techniques normally occur throughout an operation as an adversary learns the environment. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities based on the information obtained.

Monitor processes and command-line arguments for actions that could be taken to gather system and network information. Remote access tools with built-in features may interact directly with the Windows API to gather information. Information may also be acquired through Windows system management tools such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Process monitoring, Process command-line parameters

*Table 560. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1082">https://attack.mitre.org/wiki/Technique/T1082</a>

# System Network Connections Discovery

Adversaries may attempt to get a listing of network connections to or from the compromised system they are currently accessing or from remote systems by querying for information over the network.

===Windows===

Utilities and commands that acquire this information include netstat, "net use," and "net session" with Net.

===Mac and Linux===



In Mac and Linux, `netstat` and `lsof` can be used to list current connections. `who -a` and `w` can be used to show which users are currently logged in, similar to "net session".

Detection: System and network discovery techniques normally occur throughout an operation as an adversary learns the environment. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: Process monitoring, Process command-line parameters

*Table 561. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1049">https://attack.mitre.org/wiki/Technique/T1049</a>

## Two-Factor Authentication Interception

Use of two- or multifactor authentication is recommended and provides a higher level of security than user names and passwords alone, but organizations should be aware of techniques that could be used to intercept and bypass these security mechanisms. Adversaries may target authentication mechanisms, such as smart cards, to gain access to systems, services, and network resources.

If a smart card is used for two-factor authentication (2FA), then a keylogger will need to be used to obtain the password associated with a smart card during normal use. With both an inserted card and access to the smart card password, an adversary can connect to a network resource using the infected system to proxy the authentication with the inserted hardware token. [[Citation: Mandiant M Trends 2011]]

Other methods of 2FA may be intercepted and used by an adversary to authenticate. It is common for one-time codes to be sent via out-of-band communications (email, SMS). If the device and/or service is not secured, then it may be vulnerable to interception. Although primarily focused on by cyber criminals, these authentication mechanisms have been targeted by advanced actors. [[Citation: Operation Emmental]]

Other hardware tokens, such as RSA SecurID, require the adversary to have access to the physical device or the seed and algorithm in addition to the corresponding credentials.

Detection: Detecting use of proxied smart card connections by an adversary may be difficult because it requires the token to be inserted into a system; thus it is more likely to be in use by a legitimate user and blend in with other network behavior.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Contributors: John Lambert, Microsoft Threat Intelligence Center

Table 562. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1111">https://attack.mitre.org/wiki/Technique/T1111</a>
<a href="http://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp-finding-holes-operation-emmental.pdf">http://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp-finding-holes-operation-emmental.pdf</a>
<a href="https://dl.mandiant.com/EE/assets/PDF%20MTrends%202011.pdf">https://dl.mandiant.com/EE/assets/PDF%20MTrends%202011.pdf</a>

## Execution through API

Adversary tools may directly use the Windows application programming interface (API) to execute binaries. Functions such as the Windows API CreateProcess will allow programs and scripts to start other processes with proper path and argument parameters. [[Citation: Microsoft CreateProcess]]

Additional Windows API calls that can be used to execute binaries include: [[Citation: Kanthak Verifier]]

\*CreateProcessA() and CreateProcessW(), \*CreateProcessAsUserA() and CreateProcessAsUserW(), \*CreateProcessInternalA() and CreateProcessInternalW(), \*CreateProcessWithLogonW(), CreateProcessWithTokenW(), \*LoadLibraryA() and LoadLibraryW(), \*LoadLibraryExA() and LoadLibraryExW(), \*LoadModule(), \*LoadPackagedLibrary(), \*WinExec(), \*ShellExecuteA() and ShellExecuteW(), \*ShellExecuteExA() and ShellExecuteExW()

Detection: Monitoring API calls may generate a significant amount of data and may not be directly useful for defense unless collected under specific circumstances, since benign use of Windows API functions such as CreateProcess are common and difficult to distinguish from malicious behavior. Correlation of other events with behavior surrounding API function calls using API monitoring will provide additional context to an event that may assist in determining if it is due to malicious behavior. Correlation of activity by process lineage by process ID may be sufficient.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: API monitoring, Process monitoring

Contributors: Stefan Kanthak

Table 563. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1106">https://attack.mitre.org/wiki/Technique/T1106</a>
<a href="http://msdn.microsoft.com/en-us/library/ms682425">http://msdn.microsoft.com/en-us/library/ms682425</a>
<a href="https://skanthak.homepage.t-online.de/verifier.html">https://skanthak.homepage.t-online.de/verifier.html</a>

# Component Object Model Hijacking

The Microsoft Component Object Model (COM) is a system within Windows to enable interaction between software components through the operating system. [[Citation: Microsoft Component Object Model]] Adversaries can use this system to insert malicious code that can be executed in place of legitimate software through hijacking the COM references and relationships as a means for persistence. Hijacking a COM object requires a change in the Windows Registry to replace a reference to a legitimate system component which may cause that component to not work when executed. When that system component is executed through normal system operation the adversary's code will be executed instead. [[Citation: GDATA COM Hijacking]] An adversary is likely to hijack objects that are used frequently enough to maintain a consistent level of persistence, but are unlikely to break noticeable functionality within the system as to avoid system instability that could lead to detection.

Detection: There are opportunities to detect COM hijacking by searching for Registry references that have been replaced and through Registry operations replacing known binary paths with unknown paths. Even though some third party applications define user COM objects, the presence of objects within `HKEY_CURRENT_USER\Software\Classes\CLSID\` may be anomalous and should be investigated since user objects will be loaded prior to machine objects in `HKEY_LOCAL_MACHINE\SOFTWARE\Classes\CLSID\`. [[Citation: Endgame COM Hijacking]] Registry entries for existing COM objects may change infrequently. When an entry with a known good path and binary is replaced or changed to an unusual value to point to an unknown binary in a new location, then it may indicate suspicious behavior and should be investigated. Likewise, if software DLL loads are collected and analyzed, any unusual DLL load that can be correlated with a COM object Registry modification may indicate COM hijacking has been performed.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Windows Registry, DLL monitoring, Loaded DLLs

Contributors: ENDGAME

Table 564. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1122">https://attack.mitre.org/wiki/Technique/T1122</a>
<a href="https://blog.gdatasoftware.com/2014/10/23941-com-object-hijacking-the-discreet-way-of-persistence">https://blog.gdatasoftware.com/2014/10/23941-com-object-hijacking-the-discreet-way-of-persistence</a>
<a href="https://msdn.microsoft.com/library/ms694363.aspx">https://msdn.microsoft.com/library/ms694363.aspx</a>
<a href="https://www.endgame.com/blog/how-hunt-detecting-persistence-evasion-com">https://www.endgame.com/blog/how-hunt-detecting-persistence-evasion-com</a>

## Clipboard Data

Adversaries may collect data stored in the Windows clipboard from users copying information within or between applications.

===Windows===

Applications can access clipboard data by using the Windows API. [[Citation: MSDN Clipboard]]

===Mac===

OSX provides a native command, `pbpaste`, to grab clipboard contents [[Citation: Operating with EmPyre]].

Detection: Access to the clipboard is a legitimate function of many applications on a Windows system. If an organization chooses to monitor for this behavior, then the data will likely need to be correlated against other suspicious or non-user-driven activity.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: API monitoring

*Table 565. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1115">https://attack.mitre.org/wiki/Technique/T1115</a>
<a href="http://www.rvrsh3ll.net/blog/empyre/operating-with-empyre/">http://www.rvrsh3ll.net/blog/empyre/operating-with-empyre/</a>
<a href="https://msdn.microsoft.com/en-us/library/ms649012">https://msdn.microsoft.com/en-us/library/ms649012</a>

## InstallUtil

InstallUtil is a command-line utility that allows for installation and uninstallation of resources by executing specific installer components specified in .NET binaries. [[Citation: MSDN InstallUtil]] InstallUtil is located in the .NET directory on a Windows system: `C:\Windows\Microsoft.NET\Framework\v<version>\InstallUtil.exe`. InstallUtil.exe is digitally signed by Microsoft.

Adversaries may use InstallUtil to proxy execution of code through a trusted Windows utility. InstallUtil may also be used to bypass process whitelisting through use of attributes within the binary that execute the class decorated with the attribute `[System.ComponentModel.RunInstaller(true)]`. [[Citation: SubTee GitHub All The Things Application Whitelisting Bypass]]

Detection: Use process monitoring to monitor the execution and arguments of InstallUtil.exe. Compare recent invocations of InstallUtil.exe with prior history of known good arguments and executed binaries to determine anomalous and potentially adversarial activity. Command arguments used before and after the InstallUtil.exe invocation may also be useful in determining the origin and purpose of the binary being executed.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Process monitoring, Process command-line parameters

Contributors: Casey Smith

Table 566. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1118">https://attack.mitre.org/wiki/Technique/T1118</a>
<a href="https://msdn.microsoft.com/en-us/library/50614e95.aspx">https://msdn.microsoft.com/en-us/library/50614e95.aspx</a>
<a href="https://github.com/subTee/AllTheThings">https://github.com/subTee/AllTheThings</a>

## Data Obfuscation

Command and control (C2) communications are hidden (but not necessarily encrypted) in an attempt to make the content more difficult to discover or decipher and to make the communication less conspicuous and hide commands from being seen. This encompasses many methods, such as adding junk data to protocol traffic, using steganography, commingling legitimate traffic with C2 communications traffic, or using a non-standard data encoding system, such as a modified Base64 encoding for the message body of an HTTP request.

Detection: Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Packet capture, Process use of network, Process monitoring, Network protocol analysis

Table 567. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1001">https://attack.mitre.org/wiki/Technique/T1001</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>

## Shortcut Modification

Shortcuts or symbolic links are ways of referencing other files or programs that will be opened or executed when the shortcut is clicked or executed by a system startup process. Adversaries could use shortcuts to execute their tools for persistence. They may create a new shortcut as a means of indirection that may use Masquerading to look like a legitimate program. Adversaries could also edit the target path or entirely replace an existing shortcut so their tools will be executed instead of the intended legitimate program.

Detection: Since a shortcut's target path likely will not change, modifications to shortcut files that do not correlate with known software changes, patches, removal, etc., may be suspicious. Analysis should attempt to relate shortcut file change or creation events to other potentially suspicious events based on known adversary behavior such as process launches of unknown executables that make network connections.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: File monitoring, Process monitoring, Process command-line parameters

*Table 568. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1023">https://attack.mitre.org/wiki/Technique/T1023</a>

## Obfuscated Files or Information

Adversaries may attempt to make an executable or file difficult to discover or analyze by encrypting, encoding, or otherwise obfuscating its contents on the system.

Detection: Detection of file obfuscation is difficult unless artifacts are left behind by the obfuscation process that are uniquely detectable with a signature. If detection of the obfuscation itself is not possible, it may be possible to detect the malicious activity that caused the obfuscated file (for example, the method that was used to write, read, or modify the file on the file system).

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Network protocol analysis, Process use of network, File monitoring, Malware reverse engineering, Binary file metadata

*Table 569. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1027">https://attack.mitre.org/wiki/Technique/T1027</a>

## Video Capture

An adversary can leverage a computer's peripheral devices (e.g., integrated cameras or webcams) or applications (e.g., video call services) to capture video recordings for the purpose of gathering information. Images may also be captured from devices or applications, potentially in specified intervals, in lieu of video files.

Malware or scripts may be used to interact with the devices through an available API provided by the operating system or an application to capture video or images. Video or image files may be written to disk and exfiltrated later. This technique differs from Screen Capture due to use of

specific devices or applications for video recording rather than capturing the victim's screen.

Detection: Detection of this technique may be difficult due to the various APIs that may be used. Telemetry data regarding API use may not be useful depending on how a system is normally used, but may provide context to other potentially malicious activity occurring on a system.

Behavior that could indicate technique use include an unknown or unusual process accessing APIs associated with devices or software that interact with the video camera, recording devices, or recording software, and a process periodically writing files to disk that contain video or camera image data.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Process monitoring, File monitoring, API monitoring

*Table 570. Table References*

Links
-------

<a href="https://attack.mitre.org/wiki/Technique/T1125">https://attack.mitre.org/wiki/Technique/T1125</a>
---

## Gatekeeper Bypass

In macOS and OS X, when applications or programs are downloaded from the internet, there is a special attribute set on the file called `com.apple.quarantine`. This attribute is read by Apple's Gatekeeper defense program at execution time and provides a prompt to the user to allow or deny execution.

Apps loaded onto the system from USB flash drive, optical disk, external hard drive, or even from a drive shared over the local network won't set this flag. Additionally, other utilities or events like drive-by downloads don't necessarily set it either. This completely bypasses the built-in Gatekeeper check[[Citation: Methods of Mac Malware Persistence]]. The presence of the quarantine flag can be checked by the `xattr` command `xattr /path/to/MyApp.app` for `com.apple.quarantine`. Similarly, given sudo access or elevated permission, this attribute can be removed with `xattr` as well, `sudo xattr -r -d com.apple.quarantine /path/to/MyApp.app` [[Citation: Clearing quarantine attribute]][[Citation: OceanLotus for OS X]].

In typical operation, a file will be downloaded from the internet and given a quarantine flag before being saved to disk. When the user tries to open the file or application, macOS's gatekeeper will step in and check for the presence of this flag. If it exists, then macOS will then prompt the user to confirmation that they want to run the program and will even provide the url where the application came from. However, this is all based on the file being downloaded from a quarantine-savvy application [[Citation: Bypassing Gatekeeper]].

Detection: Monitoring for the removal of the `com.apple.quarantine` flag by a user instead of the operating system is a suspicious action and should be examined further.

Platforms: MacOS, OS X

Table 571. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1144">https://attack.mitre.org/wiki/Technique/T1144</a>
<a href="https://derflounder.wordpress.com/2012/11/20/clearing-the-quarantine-extended-attribute-from-downloaded-applications/">https://derflounder.wordpress.com/2012/11/20/clearing-the-quarantine-extended-attribute-from-downloaded-applications/</a>
<a href="https://blog.malwarebytes.com/cybercrime/2015/10/bypassing-apples-gatekeeper/">https://blog.malwarebytes.com/cybercrime/2015/10/bypassing-apples-gatekeeper/</a>
<a href="https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf">https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf</a>
<a href="https://www.alienvault.com/blogs/labs-research/oceanlotus-for-os-x-an-application-bundle-pretending-to-be-an-adobe-flash-update">https://www.alienvault.com/blogs/labs-research/oceanlotus-for-os-x-an-application-bundle-pretending-to-be-an-adobe-flash-update</a>

## Masquerading

Masquerading occurs when an executable, legitimate or malicious, is placed in a commonly trusted location (such as C:\Windows\System32) or named with a common name (such as "explorer.exe" or "svchost.exe") to bypass tools that trust executables by relying on file name or path. An adversary may even use a renamed copy of a legitimate utility, such as rundll32.exe. [[Citation: Endgame Masquerade Ball]] Masquerading also may be done to deceive defenders and system administrators into thinking a file is benign by associating the name with something that is thought to be legitimate.

Detection: Collect file hashes; file names that do not match their expected hash are suspect. Perform file monitoring; files with known names but in unusual locations are suspect. Likewise, files that are modified outside of an update or patch are suspect.

If file names are mismatched between the binary name on disk and the binary's resource section, this is a likely indicator that a binary was renamed after it was compiled. Collecting and comparing disk and resource filenames for binaries could provide useful leads, but may not always be indicative of malicious activity. [[Citation: Endgame Masquerade Ball]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Binary file metadata

Contributors: ENDGAME

Table 572. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1036">https://attack.mitre.org/wiki/Technique/T1036</a>
<a href="https://www.endgame.com/blog/how-hunt-masquerade-ball">https://www.endgame.com/blog/how-hunt-masquerade-ball</a>

## DLL Side-Loading

Programs may specify DLLs that are loaded at runtime. Programs that improperly or vaguely specify a required DLL may be open to a vulnerability in which an unintended DLL is loaded. Side-



loading vulnerabilities specifically occur when Windows Side-by-Side (WinSxS) manifests[[Citation: MSDN Manifests]] are not explicit enough about characteristics of the DLL to be loaded. Adversaries may take advantage of a legitimate program that is vulnerable to side-loading to load a malicious DLL.[[Citation: Stewart 2014]]

Adversaries likely use this technique as a means of masking actions they perform under a legitimate, trusted system or software process.

Detection: Monitor processes for unusual activity (e.g., a process that does not use the network begins to do so). Track DLL metadata, such as a hash, and compare DLLs that are loaded at process execution time against previous executions to detect differences that do not correlate with patching or updates.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Process use of network, Process monitoring, Loaded DLLs

Table 573. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1073">https://attack.mitre.org/wiki/Technique/T1073</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-dll-sideload.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-dll-sideload.pdf</a>
<a href="https://msdn.microsoft.com/en-us/library/aa375365">https://msdn.microsoft.com/en-us/library/aa375365</a>

## Automated Exfiltration

Data, such as sensitive documents, may be exfiltrated through the use of automated processing or Scripting after being gathered during Exfiltration Over Command and Control Channel and Exfiltration Over Alternative Protocol.

Detection: Monitor process file access patterns and network behavior. Unrecognized processes or scripts that appear to be traversing file systems and sending network traffic may be suspicious.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process use of network

Table 574. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1020">https://attack.mitre.org/wiki/Technique/T1020</a>

# Network Service Scanning

Adversaries may attempt to get a listing of services running on remote hosts, including those that may be vulnerable to remote software exploitation. Methods to acquire this information include port scans and vulnerability scans using tools that are brought onto a system.

Detection: System and network discovery techniques normally occur throughout an operation as an adversary learns the environment. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as [\[\[Lateral Movement\]\]](#), based on the information obtained.

Normal, benign system and network events from legitimate remote service scanning may be uncommon, depending on the environment and how they are used. Legitimate open port and vulnerability scanning may be conducted within the environment and will need to be deconflicted with any detection capabilities developed. Network intrusion detection systems can also be used to identify scanning activity. Monitor for process use of the networks and inspect intra-network flows to detect port scans.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Netflow/Enclave netflow, Network protocol analysis, Packet capture, Process use of network, Process command-line parameters

Table 575. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1046">https://attack.mitre.org/wiki/Technique/T1046</a>

## .bash\_profile and .bashrc

`~/bash_profile` and `~/bashrc` are executed in a user's context when a new shell opens or when a user logs in so that their environment is set correctly. `~/bash_profile` is executed for login shells and `~/bashrc` is executed for interactive non-login shells. This means that when a user logs in (via username and password) to the console (either locally or remotely via something like SSH), `~/bash_profile` is executed before the initial command prompt is returned to the user. After that, every time a new shell is opened, `~/bashrc` is executed. This allows users more fine grained control over when they want certain commands executed.

Mac's Terminal.app is a little different in that it runs a login shell by default each time a new terminal window is opened, thus calling `~/bash_profile` each time instead of `~/bashrc`.

These files are meant to be written to by the local user to configure their own environment; however, adversaries can also insert code into these files to gain persistence each time a user logs in or opens a new shell.

Detection: While users may customize their `~/.bashrc` and `~/.bash_profile` files, there are only certain types of commands that typically appear in these files. Monitor for abnormal commands such as execution of unknown programs, opening network sockets, or reaching out across the network when user profiles are loaded during the login process.

Platforms: Linux, MacOS, OS X

Data Sources: File monitoring, Process Monitoring, Process command-line parameters, Process use of network

*Table 576. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1156">https://attack.mitre.org/wiki/Technique/T1156</a>

## Bash History

Bash keeps track of the commands users type on the command-line with the "history" utility. Once a user logs out, the history is flushed to the user's `.bash_history` file. For each user, this file resides at the same location: `~/.bash_history`. Typically, this file keeps track of the user's last 500 commands. Users often type usernames and passwords on the command-line as parameters to programs, which then get saved to this file when they log out. Attackers can abuse this by looking through the file for potential credentials. [[Citation: External to DA, the OS X Way]]

Detection: Monitoring when the user's `.bash_history` is read can help alert to suspicious activity. While users do typically rely on their history of commands, they often access this history through other utilities like "history" instead of commands like `cat ~/.bash_history`.

Platforms: Linux, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process command-line parameters

*Table 577. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1139">https://attack.mitre.org/wiki/Technique/T1139</a>
<a href="http://www.slideshare.net/StephanBorosh/external-to-da-the-os-x-way">http://www.slideshare.net/StephanBorosh/external-to-da-the-os-x-way</a>

## Replication Through Removable Media

Adversaries may move to additional systems, possibly those on disconnected or air-gapped networks, by copying malware to removable media and taking advantage of Autorun features when the media is inserted into another system and executes. This may occur through modification of executable files stored on removable media or by copying malware and renaming it to look like a legitimate file to trick users into executing it on a separate system.

Detection: Monitor file access on removable media. Detect processes that execute from removable

media after it is mounted or when initiated by a user. If a remote access tool is used in this manner to move laterally, then additional actions are likely to occur after execution, such as opening network connections for [[Command and Control]] and system and network information .

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: File monitoring, Data loss prevention

Table 578. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1091">https://attack.mitre.org/wiki/Technique/T1091</a>

## Remote Desktop Protocol

Remote desktop is a common feature in operating systems. It allows a user to log into an interactive session with a system desktop graphical user interface on a remote system. Microsoft refers to its implementation of the Remote Desktop Protocol (RDP) as Remote Desktop Services (RDS). Remote Services similar to RDS.

Adversaries may connect to a remote system over RDP/RDS to expand access if the service is enabled and allows access to accounts with known credentials. Adversaries will likely use Accessibility Features technique for .[[Citation: Alperovitch Malware]]

Detection: Use of RDP may be legitimate, depending on the network environment and how it is used. Other factors, such as access patterns and activity that occurs after a remote login, may indicate suspicious or malicious behavior with RDP. Monitor for user accounts logged into systems they would not normally access or access patterns to multiple systems over a relatively short period of time.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Authentication logs, Netflow/Enclave netflow, Process monitoring

Table 579. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1076">https://attack.mitre.org/wiki/Technique/T1076</a>
<a href="https://technet.microsoft.com/en-us/windowsserver/ee236407.aspx">https://technet.microsoft.com/en-us/windowsserver/ee236407.aspx</a>
<a href="http://blog.crowdstrike.com/adversary-tricks-crowdstrike-treats/">http://blog.crowdstrike.com/adversary-tricks-crowdstrike-treats/</a>

## Scheduled Transfer

Data exfiltration may be performed only at certain times of day or at certain intervals. This could be done to blend traffic patterns with normal activity or availability.

When scheduled exfiltration is used, other exfiltration techniques likely apply as well to transfer the information out of the network, such as Exfiltration Over Command and Control Channel and Exfiltration Over Alternative Protocol.

Detection: Monitor process file access patterns and network behavior. Unrecognized processes or scripts that appear to be traversing file systems and sending network traffic may be suspicious. Network connections to the same destination that occur at the same time of day for multiple days are suspicious.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Netflow/Enclave netflow, Process use of network, Process monitoring

Table 580. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1029">https://attack.mitre.org/wiki/Technique/T1029</a>

## Bypass User Account Control

Windows User Account Control (UAC) allows a program to elevate its privileges to perform a task under administrator-level permissions by prompting the user for confirmation. The impact to the user ranges from denying the operation under high enforcement to allowing the user to perform the action if they are in the local administrators group and click through the prompt or allowing them to enter an administrator password to complete the action. DLL Injection and unusual loaded DLLs through DLL Search Order Hijacking, which indicate attempts to gain access to higher privileged processes.

Some UAC bypass methods rely on modifying specific, user-accessible Registry settings. For example:

- The `eventvwr.exe` bypass uses the `[HKEY_CURRENT_USER]\Software\Classes\mscfile\shell\open\command` Registry key. [[Citation: enigma0x3 Fileless UAC Bypass]]
- The `sdclt.exe` bypass uses the `[HKEY_CURRENT_USER]\Software\Microsoft\Windows\CurrentVersion\App Paths\control.exe` and `[HKEY_CURRENT_USER]\Software\Classes\exefile\shell\runas\command\isolatedCommand` Registry keys. [[Citation: enigma0x3 sdclt app paths]] [[Citation: enigma0x3 sdclt bypass]]

Analysts should monitor these Registry settings for unauthorized changes.

Platforms: Windows Server 2012, Windows 7, Windows 8, Windows Server 2008 R2, Windows Server 2012 R2, Windows 8.1, Windows 10

Data Sources: System calls, Process monitoring, Authentication logs, Process command-line

parameters

Effective Permissions: Administrator

Contributors: Stefan Kanthak, Casey Smith

Table 581. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1088">https://attack.mitre.org/wiki/Technique/T1088</a>
<a href="https://enigma0x3.net/2016/08/15/fileless-uac-bypass-using-eventvwr-exe-and-registry-hijacking/">https://enigma0x3.net/2016/08/15/fileless-uac-bypass-using-eventvwr-exe-and-registry-hijacking/</a>
<a href="https://github.com/hfiref0x/UACME">https://github.com/hfiref0x/UACME</a>
<a href="https://technet.microsoft.com/en-us/itpro/windows/keep-secure/how-user-account-control-works">https://technet.microsoft.com/en-us/itpro/windows/keep-secure/how-user-account-control-works</a>
<a href="https://enigma0x3.net/2017/03/14/bypassing-uac-using-app-paths/">https://enigma0x3.net/2017/03/14/bypassing-uac-using-app-paths/</a>
<a href="https://msdn.microsoft.com/en-us/library/ms679687.aspx">https://msdn.microsoft.com/en-us/library/ms679687.aspx</a>
<a href="https://enigma0x3.net/2017/03/17/fileless-uac-bypass-using-sdclt-exe/">https://enigma0x3.net/2017/03/17/fileless-uac-bypass-using-sdclt-exe/</a>
<a href="https://technet.microsoft.com/en-US/magazine/2009.07.uac.aspx">https://technet.microsoft.com/en-US/magazine/2009.07.uac.aspx</a>
<a href="http://www.pretentiousname.com/misc/win7%20uac%20whitelist2.html">http://www.pretentiousname.com/misc/win7%20uac%20whitelist2.html</a>
<a href="http://pen-testing.sans.org/blog/pen-testing/2013/08/08/psexec-uac-bypass">http://pen-testing.sans.org/blog/pen-testing/2013/08/08/psexec-uac-bypass</a>
<a href="https://blog.fortinet.com/2016/12/16/malicious-macro-bypasses-uac-to-elevate-privilege-for-fareit-malware">https://blog.fortinet.com/2016/12/16/malicious-macro-bypasses-uac-to-elevate-privilege-for-fareit-malware</a>

## Logon Scripts

===Windows===

Windows allows logon scripts to be run whenever a specific user or group of users log into a system. [[Citation: TechNet Logon Scripts]] The scripts can be used to perform administrative functions, which may often execute other programs or send information to an internal logging server.

If adversaries can access these scripts, they may insert additional code into the logon script to execute their tools when a user logs in. This code can allow them to maintain persistence on a single system, if it is a local script, or to move laterally within a network, if the script is stored on a central server and pushed to many systems. Depending on the access configuration of the logon scripts, either local credentials or an administrator account may be necessary.

===Mac===

Mac allows login and logoff hooks to be run as root whenever a specific user logs into or out of a system. A login hook tells Mac OS X to execute a certain script when a user logs in, but unlike startup items, a login hook executes as root [[Citation: creating login hook]]. There can only be one login hook at a time though. If adversaries can access these scripts, they can insert additional code to the script to execute their tools when a user logs in.

Detection: Monitor logon scripts for unusual access by abnormal users or at abnormal times. Look for files added or modified by unusual accounts outside of normal administration duties.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, MacOS, OS X

Data Sources: File monitoring, Process monitoring

Table 582. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1037">https://attack.mitre.org/wiki/Technique/T1037</a>
<a href="https://support.apple.com/de-at/HT2420">https://support.apple.com/de-at/HT2420</a>
<a href="https://technet.microsoft.com/en-us/library/cc758918(v=ws.10).aspx">https://technet.microsoft.com/en-us/library/cc758918(v=ws.10).aspx</a>

## Connection Proxy

A connection proxy is used to direct network traffic between systems or act as an intermediary for network communications. Many tools exist that enable traffic redirection through proxies or port redirection, including HTRAN, ZXProxy, and ZXPortMap. [[Citation: Trend Micro APT Attack Tools]]

The definition of a proxy can also be expanded out to encompass trust relationships between networks in peer-to-peer, mesh, or trusted connections between networks consisting of hosts or systems that regularly communicate with each other.

The network may be within a single organization or across organizations with trust relationships. Adversaries could use these types of relationships to manage command and control communications, to reduce the number of simultaneous outbound network connections, to provide resiliency in the face of connection loss, or to ride over existing trusted communications paths between victims to avoid suspicion.

Detection: Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Network activities disassociated from user-driven actions from processes that normally require user direction are suspicious.

Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server or between clients that should not or often do not communicate with one another). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Process use of network, Process monitoring, Netflow/Enclave netflow, Packet capture

Contributors: Walker Johnson

Table 583. Table References

## Links

<https://attack.mitre.org/wiki/Technique/T1090>

<http://blog.trendmicro.com/trendlabs-security-intelligence/in-depth-look-apt-attack-tools-of-the-trade/>

<https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf>

## Sudo

The sudoers file, `/etc/sudoers`, describes which users can run which commands and from which terminals. This also describes which commands users can run as other users or groups. This provides the idea of least privilege such that users are running in their lowest possible permissions for most of the time and only elevate to other users or permissions as needed, typically by prompting for a password. However, the sudoers file can also specify when to not prompt users for passwords with a line like `user1 ALL=(ALL) NOPASSWD: ALL`[[Citation: OSX.Dok Malware]].

Adversaries can take advantage of these configurations to execute commands as other users or spawn processes with higher privileges. You must have elevated privileges to edit this file though.

Detection: On Linux, auditd can alert every time a user's actual ID and effective ID are different (this is what happens when you sudo).

Platforms: Linux, MacOS, OS X

Data Sources: File monitoring

Effective Permissions: root

*Table 584. Table References*

## Links

<https://attack.mitre.org/wiki/Technique/T1169>

<https://blog.malwarebytes.com/threat-analysis/2017/04/new-osx-dok-malware-intercepts-web-traffic/>

## Office Application Startup

Microsoft Office is a fairly common application suite on Windows-based operating systems within an enterprise network. There are multiple mechanisms that can be used with Office for persistence when an Office-based application is started.

===Office Template Macros===

Microsoft Office contains templates that are part of common Office applications and are used to customize styles. The base templates within the application are used each time an application starts. [[Citation: Microsoft Change Normal Template]]

Office Visual Basic for Applications (VBA) macros [[Citation: MSDN VBA in Office]] can be inserted into



the base templated and used to execute code when the respective Office application starts in order to obtain persistence. Examples for both Word and Excel have been discovered and published. By default, Word has a Normal.dotm template created that can be modified to include a malicious macro. Excel does not have a template file created by default, but one can be added that will automatically be loaded. [[Citation: enigma0x3 normal.dotm]] [[Citation: Hexacorn Office Template Macros]]

Word Normal.dotm  
location: <code>C:\Users\(\username)\AppData\Roaming\Microsoft\Templates\Normal.dotm</code>

Excel Personal.xlsb  
location: <code>C:\Users\(\username)\AppData\Roaming\Microsoft\Excel\XLSTART\PERSONAL.XLSB</code>

An adversary may need to enable macros to execute unrestricted depending on the system or enterprise security policy on use of macros.

===Office Test===

A Registry location was found that when a DLL reference was placed within it the corresponding DLL pointed to by the binary path would be executed every time an Office application is started [[Citation: Hexacorn Office Test]]

<code>HKEY\_CURRENT\_USER\Software\Microsoft\Office test\Special\Perf</code>

===Add-ins===

Office add-ins can be used to add functionality to Office programs. [[Citation: Microsoft Office Add-ins]]

Add-ins can also be used to obtain persistence because they can be set to execute code when an Office application starts. There are different types of add-ins that can be used by the various Office products; including Word/Excel add-in Libraries (WLL/XLL), VBA add-ins, Office Component Object Model (COM) add-ins, automation add-ins, VBA Editor (VBE), and Visual Studio Tools for Office (VSTO) add-ins. [[Citation: MRWLabs Office Persistence Add-ins]]

Detection: Many Office-related persistence mechanisms require changes to the Registry and for binaries, files, or scripts to be written to disk or existing files modified to include malicious scripts. Collect events related to Registry key creation and modification for keys that could be used for Office-based persistence. Modification to base templated, like Normal.dotm, should also be investigated since the base templates should likely not contain VBA macros. Changes to the Office macro security settings should also be investigated.

Monitor and validate the Office trusted locations on the file system and audit the Registry entries relevant for enabling add-ins. [[Citation: MRWLabs Office Persistence Add-ins]]

Non-standard process execution trees may also indicate suspicious or malicious behavior. Collect process execution information including process IDs (PID) and parent process IDs (PPID) and look for abnormal chains of activity resulting from Office processes. If winword.exe is the parent process for suspicious processes and activity relating to other adversarial techniques, then it could

indicate that the application was used maliciously.

Platforms: Windows 10, Windows Server 2012, Windows 7, Windows 8, Windows Server 2008 R2, Windows Server 2012 R2, Windows 8.1, Windows XP, Windows Vista

Data Sources: Process monitoring, Process command-line parameters, Windows Registry, File monitoring

Contributors: Loic Jaquemet, Ricardo Dias

Table 585. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1137">https://attack.mitre.org/wiki/Technique/T1137</a>
<a href="https://msdn.microsoft.com/en-us/vba/office-shared-vba/articles/getting-started-with-vba-in-office">https://msdn.microsoft.com/en-us/vba/office-shared-vba/articles/getting-started-with-vba-in-office</a>
<a href="http://www.hexacorn.com/blog/2014/04/16/beyond-good-ol-run-key-part-10/">http://www.hexacorn.com/blog/2014/04/16/beyond-good-ol-run-key-part-10/</a>
<a href="https://enigma0x3.net/2014/01/23/maintaining-access-with-normal-dotm/comment-page-1/">https://enigma0x3.net/2014/01/23/maintaining-access-with-normal-dotm/comment-page-1/</a>
<a href="https://support.office.com/article/Add-or-remove-add-ins-0af570c4-5cf3-4fa9-9b88-403625a0b460">https://support.office.com/article/Add-or-remove-add-ins-0af570c4-5cf3-4fa9-9b88-403625a0b460</a>
<a href="https://labs.mwrinfosecurity.com/blog/add-in-opportunities-for-office-persistence/">https://labs.mwrinfosecurity.com/blog/add-in-opportunities-for-office-persistence/</a>
<a href="http://www.hexacorn.com/blog/2017/04/19/beyond-good-ol-run-key-part-62/">http://www.hexacorn.com/blog/2017/04/19/beyond-good-ol-run-key-part-62/</a>
<a href="https://support.office.com/article/Change-the-Normal-template-Normal-dotm-06de294b-d216-47f6-ab77-ccb5166f98ea">https://support.office.com/article/Change-the-Normal-template-Normal-dotm-06de294b-d216-47f6-ab77-ccb5166f98ea</a>

## Regsvr32

Regsvr32.exe is a command-line program used to register and unregister object linking and embedding controls, including dynamic link libraries (DLLs), on Windows systems. Regsvr32.exe can be used to execute arbitrary binaries. [[Citation: Microsoft Regsvr32]]

Adversaries may take advantage of this functionality to proxy execution of code to avoid triggering security tools that may not monitor execution of, and modules loaded by, the regsvr32.exe process because of whitelists or false positives from Windows using regsvr32.exe for normal operations. Regsvr32.exe is also a Microsoft signed binary.

Regsvr32.exe can also be used to specifically bypass process whitelisting using functionality to load COM scriptlets to execute DLLs under user permissions. Since regsvr32.exe is network and proxy aware, the scripts can be loaded by passing a uniform resource locator (URL) to file on an external Web server as an argument during invocation. This method makes no changes to the Registry as the COM object is not actually registered, only executed. [[Citation: SubTee Regsvr32 Whitelisting Bypass]] This variation of the technique has been used in campaigns targeting governments. [[Citation: FireEye Regsvr32 Targeting Mongolian Gov]]

Detection: Use process monitoring to monitor the execution and arguments of regsvr32.exe. Compare recent invocations of regsvr32.exe with prior history of known good arguments and loaded files to determine anomalous and potentially adversarial activity. Command arguments used before and after the regsvr32.exe invocation may also be useful in determining the origin and purpose of the script or DLL being loaded.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Loaded DLLs, Process monitoring, Windows Registry, Process command-line parameters

Contributors: Casey Smith

Table 586. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1117">https://attack.mitre.org/wiki/Technique/T1117</a>
<a href="https://support.microsoft.com/en-us/kb/249873">https://support.microsoft.com/en-us/kb/249873</a>
<a href="https://subt0x10.blogspot.com/2017/04/bypass-application-whitelisting-script.html">https://subt0x10.blogspot.com/2017/04/bypass-application-whitelisting-script.html</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/02/spear%20phishing%20techn.html">https://www.fireeye.com/blog/threat-research/2017/02/spear%20phishing%20techn.html</a>

## File and Directory Discovery

Adversaries may enumerate files and directories or may search in specific locations of a host or network share for certain information within a file system.

===Windows===

Example utilities used to obtain this information are `dir` and `tree`. Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process command-line parameters

Table 587. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1083">https://attack.mitre.org/wiki/Technique/T1083</a>
<a href="http://blog.jpccert.or.jp/2016/01/windows-commands-abused-by-attackers.html">http://blog.jpccert.or.jp/2016/01/windows-commands-abused-by-attackers.html</a>

## Commonly Used Port

Adversaries may communicate over a commonly used port to bypass firewalls or network detection systems and to blend with normal network activity to avoid more detailed inspection. They may use commonly open ports such as \* TCP:80 (HTTP) \* TCP:443 (HTTPS) \* TCP:25 (SMTP) \* TCP/UDP:53 (DNS)

They may use the protocol associated with the port or a completely different protocol.

For connections that occur internally within an enclave (such as those between a proxy or pivot

node and other nodes), examples of common ports are \* TCP/UDP:135 (RPC) \* TCP/UDP:22 (SSH) \* TCP/UDP:3389 (RDP)

Detection: Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Packet capture, Netflow/Enclave netflow, Process use of network, Process monitoring

Table 588. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1043">https://attack.mitre.org/wiki/Technique/T1043</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>

## Data Encoding

Command and control (C2) information is encoded using a standard data encoding system. Use of data encoding may be to adhere to existing protocol specifications and includes use of ASCII, Unicode, Base64, MIME, UTF-8, or other binary-to-text and character encoding systems. [[Citation: Wikipedia Binary-to-text Encoding]] [[Citation: Wikipedia Character Encoding]] Some data encoding systems may also result in data compression, such as gzip.

Detection: Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Packet capture, Process use of network, Process Monitoring, Network protocol analysis

Contributors: Itzik Kotler, SafeBreach

Table 589. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1132">https://attack.mitre.org/wiki/Technique/T1132</a>
<a href="https://en.wikipedia.org/wiki/Character%20encoding">https://en.wikipedia.org/wiki/Character%20encoding</a>

<https://en.wikipedia.org/wiki/Binary-to-text%20encoding>

<https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf>

## Credentials in Files

Adversaries may search local file systems and remote file shares for files containing passwords. These can be files created by users to store their own credentials, shared credential stores for a group of individuals, configuration files containing passwords for a system or service, or source code/binary files containing embedded passwords.

It is possible to extract passwords from backups or saved virtual machines through Credential Dumping. Valid Accounts for more information.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process command-line parameters

*Table 590. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1081">https://attack.mitre.org/wiki/Technique/T1081</a>
<a href="http://carnal0wnage.attackresearch.com/2014/05/mimikatz-against-virtual-machine-memory.html">http://carnal0wnage.attackresearch.com/2014/05/mimikatz-against-virtual-machine-memory.html</a>
<a href="http://blogs.technet.com/b/srd/archive/2014/05/13/ms14-025-an-update-for-group-policy-preferences.aspx">http://blogs.technet.com/b/srd/archive/2014/05/13/ms14-025-an-update-for-group-policy-preferences.aspx</a>

## PowerShell

PowerShell is a powerful interactive command-line interface and scripting environment included in the Windows operating system. [[Citation: TechNet PowerShell]] Adversaries can use PowerShell to perform a number of actions, including discovery of information and execution of code. Examples include the Start-Process cmdlet which can be used to run an executable and the Invoke-Command cmdlet which runs a command locally or on a remote computer.

PowerShell may also be used to download and run executables from the Internet, which can be executed from disk or in memory without touching disk.

Administrator permissions are required to use PowerShell to connect to remote systems.

A number of PowerShell-based offensive testing tools are available, including Empire, [[Citation: Github PowerShell Empire]] PowerSploit, [[Citation: Powersploit]] and PSAttack. [[Citation: Github PSAttack]]

Detection: If proper execution policy is set, adversaries will likely be able to define their own execution policy if they obtain administrator or system access, either through the Registry or at the command line. This change in policy on a system may be a way to detect malicious use of PowerShell. If PowerShell is not used in an environment, then simply looking for PowerShell

execution may detect malicious activity.

It is also beneficial to turn on PowerShell logging to gain increased fidelity in what occurs during execution. [[Citation: Malware Archaeology PowerShell Cheat Sheet]] PowerShell 5.0 introduced enhanced logging capabilities, and some of those features have since been added to PowerShell 4.0. Earlier versions of PowerShell do not have many logging features. [[Citation: FireEye PowerShell Logging 2016]] An organization can gather PowerShell execution details in a data analytic platform to supplement it with other data.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Windows Registry, File monitoring, Process monitoring, Process command-line parameters

Table 591. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1086">https://attack.mitre.org/wiki/Technique/T1086</a>
<a href="https://github.com/PowerShellEmpire/Empire">https://github.com/PowerShellEmpire/Empire</a>
<a href="http://www.malwarearchaeology.com/s/Windows-PowerShell-Logging-Cheat-Sheet-ver-June-2016-v2.pdf">http://www.malwarearchaeology.com/s/Windows-PowerShell-Logging-Cheat-Sheet-ver-June-2016-v2.pdf</a>
<a href="https://github.com/mattifestation/PowerSploit">https://github.com/mattifestation/PowerSploit</a>
<a href="https://github.com/jaredhaight/PSAttack">https://github.com/jaredhaight/PSAttack</a>
<a href="https://technet.microsoft.com/en-us/scriptcenter/dd742419.aspx">https://technet.microsoft.com/en-us/scriptcenter/dd742419.aspx</a>
<a href="https://www.fireeye.com/blog/threat-research/2016/02/greater%20visibility.html">https://www.fireeye.com/blog/threat-research/2016/02/greater%20visibility.html</a>

## Security Software Discovery

Adversaries may attempt to get a listing of security software, configurations, defensive tools, and sensors that are installed on the system. This may include things such as local firewall rules, anti-virus, and virtualization. These checks may be built into early-stage remote access tools.

===Windows===

Example commands that can be used to obtain security software information are netsh, `reg query` with Reg, `dir` with cmd, and Tasklist, but other indicators of discovery behavior may be more specific to the type of software or security system the adversary is looking for.

===Mac===

It's becoming more common to see macOS malware perform checks for LittleSnitch and KnockKnock software.

Detection: System and network discovery techniques normally occur throughout an operation as an adversary learns the environment. Data and events should not be viewed in isolation, but as part of

a chain of behavior that could lead to other activities, such as lateral movement, based on the information obtained.

Monitor processes and command-line arguments for actions that could be taken to gather system and network information. Remote access tools with built-in features may interact directly with the Windows API to gather information. Information may also be acquired through Windows system management tools such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process command-line parameters

Table 592. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1063">https://attack.mitre.org/wiki/Technique/T1063</a>

## Trap

The `trap` command allows programs and shells to specify commands that will be executed upon receiving interrupt signals. A common situation is a script allowing for graceful termination and handling of common keyboard interrupts like `ctrl+c` and `ctrl+d`. Adversaries can use this to register code to be executed when the shell encounters specific interrupts either to gain execution or as a persistence mechanism. Trap commands are of the following format `trap 'command list' signals` where "command list" will be executed when "signals" are received.

Detection: Trap commands must be registered for the shell or programs, so they appear in files. Monitoring files for suspicious or overly broad trap commands can narrow down suspicious behavior during an investigation. Monitor for suspicious processes executed through trap interrupts.

Platforms: Linux, MacOS, OS X

Data Sources: File monitoring, Process Monitoring, Process command-line parameters

Table 593. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1154">https://attack.mitre.org/wiki/Technique/T1154</a>

## Modify Existing Service

Windows service configuration information, including the file path to the service's executable, is stored in the Registry. Service configurations can be modified using utilities such as `sc.exe` and `Reg`.

Adversaries can modify an existing service to persist malware on a system by using system utilities or by using custom tools to interact with the Windows API. Use of existing services is a type of

Masquerading that may make detection analysis more challenging. Modifying existing services may interrupt their functionality or may enable services that are disabled or otherwise not commonly used.

Detection: Look for changes to service Registry entries that do not correlate with known software, patch cycles, etc. Changes to the binary path and the service startup type changed from manual or disabled to automatic, if it does not typically do so, may be suspicious. Tools such as Sysinternals Autoruns may also be used to detect system service changes that could be attempts at persistence.cmd commands or scripts.

Look for abnormal process call trees from known services and for execution of other commands that could relate to Windows Management Instrumentation and PowerShell, so additional logging may need to be configured to gather the appropriate data.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Windows Registry, File monitoring, Process monitoring, Process command-line parameters

Table 594. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1031">https://attack.mitre.org/wiki/Technique/T1031</a>
<a href="https://technet.microsoft.com/en-us/sysinternals/bb963902">https://technet.microsoft.com/en-us/sysinternals/bb963902</a>

## Standard Cryptographic Protocol

Adversaries use command and control over an encrypted channel using a known encryption protocol like HTTPS or SSL/TLS. The use of strong encryption makes it difficult for defenders to detect signatures within adversary command and control traffic.

Some adversaries may use other encryption protocols and algorithms with symmetric keys, such as RC4, that rely on encryption keys encoded into malware configuration files and not public key cryptography. Such keys may be obtained through malware reverse engineering.

Detection: SSL/TLS inspection is one way of detecting command and control traffic within some encrypted communication channels. [[Citation: SANS Decrypting SSL]] SSL/TLS inspection does come with certain risks that should be considered before implementing to avoid potential security issues such as incomplete certificate validation. [[Citation: SEI SSL Inspection Risks]]

If malware uses encryption with symmetric keys, it may be possible to obtain the algorithm and key from samples and use them to decode network traffic to detect malware communications signatures. [[Citation: Fidelis DarkComet]]

In general, analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to



detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Packet capture, Netflow/Enclave netflow, Malware reverse engineering, Process use of network, Process monitoring, SSL/TLS inspection

Table 595. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1032">https://attack.mitre.org/wiki/Technique/T1032</a>
<a href="https://www.fidelissecurity.com/sites/default/files/FTA%201018%20looking%20at%20the%20sky%20for%20a%20dark%20comet.pdf">https://www.fidelissecurity.com/sites/default/files/FTA%201018%20looking%20at%20the%20sky%20for%20a%20dark%20comet.pdf</a>
<a href="http://www.sans.org/reading-room/whitepapers/analyst/finding-hidden-threats-decrypting-ssl-34840">http://www.sans.org/reading-room/whitepapers/analyst/finding-hidden-threats-decrypting-ssl-34840</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>
<a href="https://insights.sei.cmu.edu/cert/2015/03/the-risks-of-ssl-inspection.html">https://insights.sei.cmu.edu/cert/2015/03/the-risks-of-ssl-inspection.html</a>

## Private Keys

Private cryptographic keys and certificates are used for authentication, encryption/decryption, and digital signatures. Remote Services like SSH or for use in decrypting other collected files such as email. Common key and certificate file extensions include: .key, .pgp, .gpg, .ppk., .p12, .pem, pfx, .cer, .p7b, .asc. Adversaries may also look in common key directories, such as `~/.ssh` for SSH keys on \*nix-based systems or `C:\Users\username\.ssh` on Windows.

Private keys should require a password or passphrase for operation, so an adversary may also use Input Capture for keylogging or attempt to Brute Force the passphrase off-line.

Adversary tools have been discovered that search compromised systems for file extensions relating to cryptographic keys and certificates. [[Citation: Kaspersky Careto]] [[Citation: Palo Alto Prince of Persia]]

Detection: Monitor access to files and directories related to cryptographic keys and certificates as a means for potentially detecting access patterns that may indicate collection and exfiltration activity. Collect authentication logs and look for potentially abnormal activity that may indicate improper use of keys or certificates for remote authentication.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: File monitoring

Contributors: Itzik Kotler, SafeBreach

Table 596. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1145">https://attack.mitre.org/wiki/Technique/T1145</a>
<a href="https://researchcenter.paloaltonetworks.com/2016/06/unit42-prince-of-persia-game-over/">https://researchcenter.paloaltonetworks.com/2016/06/unit42-prince-of-persia-game-over/</a>
<a href="https://kasperskycontenthub.com/wp-content/uploads/sites/43/vlpdfs/unveilingtheface%20v1.0.pdf">https://kasperskycontenthub.com/wp-content/uploads/sites/43/vlpdfs/unveilingtheface%20v1.0.pdf</a>
<a href="https://en.wikipedia.org/wiki/Public-key%20cryptography">https://en.wikipedia.org/wiki/Public-key%20cryptography</a>

## Valid Accounts

Adversaries may steal the credentials of a specific user or service account using [[Credential Access]] techniques. Compromised credentials may be used to bypass access controls placed on various resources on hosts and within the network and may even be used for persistent access to remote systems. Compromised credentials may also grant an adversary increased privilege to specific systems or access to restricted areas of the network. Adversaries may choose not to use malware or tools in conjunction with the legitimate access those credentials provide to make it harder to detect their presence.

Adversaries may also create accounts, sometimes using pre-defined account names and passwords, as a means for persistence through backup access in case other means are unsuccessful.

The overlap of credentials and permissions across a network of systems is of concern because the adversary may be able to pivot across accounts and systems to reach a high level of access (i.e., domain or enterprise administrator) to bypass access controls set within the enterprise. [[Citation: TechNet Credential Theft]]

Detection: Configure robust, consistent account activity audit policies across the enterprise. [[Citation: TechNet Audit Policy]] Look for suspicious account behavior across systems that share accounts, either user, admin, or service accounts. Examples: one account logged into multiple systems simultaneously; multiple accounts logged into the same machine simultaneously; accounts logged in at odd times or outside of business hours. Activity may be from interactive login sessions or process ownership from accounts being used to execute binaries on a remote system as a particular account. Correlate other security systems with login information (e.g., a user has an active login session but has not entered the building or does not have VPN access).

Perform regular audits of domain and local system accounts to detect accounts that may have been created by an adversary for persistence.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: Authentication logs, Process monitoring

Effective Permissions: User, Administrator

Table 597. Table References

#### Links

<https://attack.mitre.org/wiki/Technique/T1078>

<https://technet.microsoft.com/en-us/library/dn487457.aspx>

<https://technet.microsoft.com/en-us/library/dn535501.aspx>

## LC\_MAIN Hijacking

As of OS X 10.8, mach-O binaries introduced a new header called LC\_MAIN that points to the binary's entry point for execution. Previously, there were two headers to achieve this same effect: LC\_THREAD and LC\_UNIXTHREAD [[Citation: Prolific OSX Malware History]]. The entry point for a binary can be hijacked so that initial execution flows to a malicious addition (either another section or a code cave) and then goes back to the initial entry point so that the victim doesn't know anything was different [[Citation: Methods of Mac Malware Persistence]]. By modifying a binary in this way, application whitelisting can be bypassed because the file name or application path is still the same.

Detection: Determining the original entry point for a binary is difficult, but checksum and signature verification is very possible. Modifying the LC\_MAIN entry point or adding in an additional LC\_MAIN entry point invalidates the signature for the file and can be detected. Collect running process information and compare against known applications to look for suspicious behavior.

Platforms: MacOS, OS X

Data Sources: Binary file metadata, Malware reverse engineering, Process Monitoring

*Table 598. Table References*

#### Links

<https://attack.mitre.org/wiki/Technique/T1149>

<https://assets.documentcloud.org/documents/2459197/bit9-carbon-black-threat-research-report-2015.pdf>

<https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf>

## System Service Discovery

Adversaries may try to get information about registered services. Commands that may obtain information about services using operating system utilities are "sc," "tasklist /svc" using Tasklist, and "net start" using Net, but adversaries may also use other tools as well.

Detection: System and network discovery techniques normally occur throughout an operation as an adversary learns the environment. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Process monitoring, Process command-line parameters

Table 599. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1007">https://attack.mitre.org/wiki/Technique/T1007</a>

## System Owner/User Discovery

===Windows===

Adversaries may attempt to identify the primary user, currently logged in user, set of users that commonly uses a system, or whether a user is actively using the system. They may do this, for example, by retrieving account usernames or by using Credential Dumping. The information may be collected in a number of different ways using other Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process command-line parameters

Table 600. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1033">https://attack.mitre.org/wiki/Technique/T1033</a>

## Multiband Communication

Some adversaries may split communications between different protocols. There could be one protocol for inbound command and control and another for outbound data, allowing it to bypass certain firewall restrictions. The split could also be random to simply avoid data threshold alerts on any one communication.

Detection: Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]] Correlating alerts between multiple communication channels can further help identify command-and-control behavior.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Packet capture, Netflow/Enclave netflow, Process use of network, Malware reverse engineering, Process monitoring

Table 601. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1026">https://attack.mitre.org/wiki/Technique/T1026</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>

## Pass the Ticket

Pass the ticket (PtT) Valid Accounts are captured by Credential Dumping. A user's service tickets or ticket granting ticket (TGT) may be obtained, depending on the level of access. A service ticket allows for access to a particular resource, whereas a TGT can be used to request service tickets from the Ticket Granting Service (TGS) to access any resource the user has privileges to access. [[Citation: ADSecurity AD Kerberos Attacks]] [[Citation: GentilKiwi Pass the Ticket]]

Silver Tickets can be obtained for services that use Kerberos as an authentication mechanism and are used to generate tickets to access that particular resource and the system that hosts the resource (e.g., SharePoint). [[Citation: ADSecurity AD Kerberos Attacks]]

Golden Tickets can be obtained for the domain using the Key Distribution Service account KRBTGT account NTLM hash, which enables generation of TGTs for any account in Active Directory. [[Citation: Campbell 2014]]

Detection: Audit all Kerberos authentication and credential use events and review for discrepancies. Unusual remote authentication events that correlate with other suspicious activity (such as writing and executing binaries) may indicate malicious activity.

Event ID 4769 is generated on the Domain Controller when using a golden ticket after the KRBTGT password has been reset twice, as mentioned in the mitigation section. The status code 0x1F indicates the action has failed due to "Integrity check on decrypted field failed" and indicates misuse by a previously invalidated golden ticket. [[Citation: CERT-EU Golden Ticket Protection]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Authentication logs

Contributors: Ryan Becwar

### Table 602. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1097">https://attack.mitre.org/wiki/Technique/T1097</a>
<a href="http://defcon.org/images/defcon-22/dc-22-presentations/Campbell/DEFCON-22-Christopher-Campbell-The-Secret-Life-of-Krbtgt.pdf">http://defcon.org/images/defcon-22/dc-22-presentations/Campbell/DEFCON-22-Christopher-Campbell-The-Secret-Life-of-Krbtgt.pdf</a>
<a href="http://www.aorato.com/labs/pass-the-ticket/">http://www.aorato.com/labs/pass-the-ticket/</a>
<a href="https://adsecurity.org/?p=556">https://adsecurity.org/?p=556</a>
<a href="http://blog.gentilkiwi.com/secuirite/mimikatz/pass-the-ticket-kerberos">http://blog.gentilkiwi.com/secuirite/mimikatz/pass-the-ticket-kerberos</a>

# Windows Remote Management

Windows Remote Management (WinRM) is the name of both a Windows service and a protocol that allows a user to interact with a remote system (e.g., run an executable, modify the Registry, modify services).[[Citation: Microsoft WinRM]] It may be called with the `winrm` command or by any number of programs such as PowerShell. [[Citation: Jacobsen 2014]]

Detection: Monitor use of WinRM within an environment by tracking service execution. If it is not normally used or is disabled, then this may be an indicator of suspicious behavior. Monitor processes created and actions taken by the WinRM process or a WinRM invoked script to correlate it with other related events.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: File monitoring, Authentication logs, Netflow/Enclave netflow, Process monitoring, Process command-line parameters

Table 603. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1028">https://attack.mitre.org/wiki/Technique/T1028</a>
<a href="http://msdn.microsoft.com/en-us/library/aa384426">http://msdn.microsoft.com/en-us/library/aa384426</a>
<a href="http://www.slideee.com/slide/lateral-movement-with-powershell">http://www.slideee.com/slide/lateral-movement-with-powershell</a>

## Audio Capture

An adversary can leverage a computer's peripheral devices (e.g., microphones and webcams) or applications (e.g., voice and video call services) to capture audio recordings for the purpose of listening into sensitive conversations to gather information.

Malware or scripts may be used to interact with the devices through an available API provided by the operating system or an application to capture audio. Audio files may be written to disk and exfiltrated later.

Detection: Detection of this technique may be difficult due to the various APIs that may be used. Telemetry data regarding API use may not be useful depending on how a system is normally used, but may provide context to other potentially malicious activity occurring on a system.

Behavior that could indicate technique use include an unknown or unusual process accessing APIs associated with devices or software that interact with the microphone, recording devices, or recording software, and a process periodically writing files to disk that contain audio data.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10

Data Sources: API monitoring, Process monitoring, File monitoring

Table 604. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1123">https://attack.mitre.org/wiki/Technique/T1123</a>

## Custom Cryptographic Protocol

Adversaries may use a custom cryptographic protocol or algorithm to hide command and control traffic. A simple scheme, such as XOR-ing the plaintext with a fixed key, will produce a very weak ciphertext.

Custom encryption schemes may vary in sophistication. Analysis and reverse engineering of malware samples may be enough to discover the algorithm and encryption key used.

Some adversaries may also attempt to implement their own version of a well-known cryptographic algorithm instead of using a known implementation library, which may lead to unintentional errors. [[Citation: F-Secure Cosmicduke]]

Detection: If malware uses custom encryption with symmetric keys, it may be possible to obtain the algorithm and key from samples and use them to decode network traffic to detect malware communications signatures. [[Citation: Fidelis DarkComet]]

In general, analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect when communications do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Packet capture, Netflow/Enclave netflow, Process use of network, Malware reverse engineering, Process monitoring

Table 605. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1024">https://attack.mitre.org/wiki/Technique/T1024</a>
<a href="https://www.f-secure.com/documents/996508/1030745/cosmicduke%20whitepaper.pdf">https://www.f-secure.com/documents/996508/1030745/cosmicduke%20whitepaper.pdf</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>
<a href="https://www.fidelissecurity.com/sites/default/files/FTA%201018%20looking%20at%20the%20sky%20for%20a%20dark%20comet.pdf">https://www.fidelissecurity.com/sites/default/files/FTA%201018%20looking%20at%20the%20sky%20for%20a%20dark%20comet.pdf</a>

## Graphical User Interface

Cause a binary or script to execute based on interacting with the file through a graphical user interface (GUI) or in an interactive remote session such as Remote Desktop Protocol.

Detection: Detection of execution through the GUI will likely lead to significant false positives. Other factors should be considered to detect misuse of services that can lead to adversaries gaining access to systems through interactive remote sessions.

Unknown or unusual process launches outside of normal behavior on a particular system occurring through remote interactive sessions are suspicious. Collect and audit security logs that may indicate access to and use of [[Legitimate Credentials]] to access remote systems within the network.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process command-line parameters, Binary file metadata

Table 606. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1061">https://attack.mitre.org/wiki/Technique/T1061</a>

## Fallback Channels

Adversaries may use fallback or alternate communication channels if the primary channel is compromised or inaccessible in order to maintain reliable command and control and to avoid data transfer thresholds.

Detection: Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Packet capture, Netflow/Enclave netflow, Malware reverse engineering, Process use of network, Process monitoring

Table 607. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1008">https://attack.mitre.org/wiki/Technique/T1008</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>

## Exploitation of Vulnerability

Exploitation of a software vulnerability occurs when an adversary takes advantage of a



programming error in a program, service, or within the operating system software or kernel itself to execute adversary-controlled code. Exploiting software vulnerabilities may allow adversaries to run a command or binary on a remote system for lateral movement, escalate a current process to a higher privilege level, or bypass security mechanisms. Exploits may also allow an adversary access to privileged accounts and credentials. One example of this is MS14-068, which can be used to forge Kerberos tickets using domain user permissions. [[Citation: Technet MS14-068]] [[Citation: ADSecurity Detecting Forged Tickets]]

Detection: Software exploits may not always succeed or may cause the exploited process to become unstable or crash. Software and operating system crash reports may contain useful contextual information about attempted exploits that correlate with other malicious activity. Exploited processes may exhibit behavior that is unusual for the specific process, such as spawning additional processes or reading and writing to files.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: Windows Error Reporting, File monitoring, Process monitoring

Effective Permissions: User, Administrator, SYSTEM

Contributors: John Lambert, Microsoft Threat Intelligence Center

Table 608. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1068">https://attack.mitre.org/wiki/Technique/T1068</a>
<a href="https://technet.microsoft.com/en-us/library/security/ms14-068.aspx">https://technet.microsoft.com/en-us/library/security/ms14-068.aspx</a>
<a href="https://adsecurity.org/?p=1515">https://adsecurity.org/?p=1515</a>

## Hidden Users

Every user account in macOS has a userID associated with it. When creating a user, you can specify the userID for that account. There is a property value in `/Library/Preferences/com.apple.loginwindow` called `Hide500Users` that prevents users with userIDs 500 and lower from appearing at the login screen. By using the Create Account technique with a userID under 500 and enabling this property (setting it to Yes), an adversary can hide their user accounts much more easily: `sudo dscl . -create /Users/username UniqueID 401` [[Citation: Cybereason OSX Pirrit]].

Detection: This technique prevents the new user from showing up at the log in screen, but all of the other signs of a new user still exist. The user still gets a home directory and will appear in the authentication logs.

Platforms: MacOS, OS X

Data Sources: Authentication logs, File monitoring

Table 609. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1147">https://attack.mitre.org/wiki/Technique/T1147</a>
<a href="https://www2.cybereason.com/research-osx-pirrit-mac-os-x-securirty">https://www2.cybereason.com/research-osx-pirrit-mac-os-x-securirty</a>

## Binary Padding

Some security tools inspect files with static signatures to determine if they are known malicious. Adversaries may add data to files to increase the size beyond what security tools are capable of handling or to change the file hash to avoid hash-based blacklists.

Detection: Depending on the method used to pad files, a file-based signature may be capable of detecting padding using a scanning or on-access based tool.

When executed, the resulting process from padded files may also exhibit other behavior characteristics of being used to conduct an intrusion such as system and network information or [[Lateral Movement]], which could be used as event indicators that point to the source file.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Table 610. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1009">https://attack.mitre.org/wiki/Technique/T1009</a>

## Login Item

MacOS provides the option to list specific applications to run when a user logs in. These applications run under the logged in user's context, and will be started every time the user logs in. Login items installed using the Service Management Framework are not visible in the System Preferences and can only be removed by the application that created them[[Citation: Adding Login Items]]. Users have direct control over login items installed using a shared file list which are also visible in System Preferences[[Citation: Adding Login Items]]. These login items are stored in the user's `~/Library/Preferences/` directory in a plist file called `com.apple.loginitems.plist`[[Citation: Methods of Mac Malware Persistence]]. Some of these applications can open visible dialogs to the user, but they don't all have to since there is an option to 'Hide' the window. If an adversary can register their own login item or modified an existing one, then they can use it to execute their code for a persistence mechanism each time the user logs in[[Citation: Malware Persistence on OS X]][[Citation: OSX.Dok Malware]].

Detection: All the login items are viewable by going to the Apple menu → System Preferences → Users & Groups → Login items. This area should be monitored and whitelisted for known good applications. Monitor process execution resulting from login actions for unusual or unknown applications.

Platforms: MacOS, OS X

Table 611. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1162">https://attack.mitre.org/wiki/Technique/T1162</a>
<a href="https://blog.malwarebytes.com/threat-analysis/2017/04/new-osx-dok-malware-intercepts-web-traffic/">https://blog.malwarebytes.com/threat-analysis/2017/04/new-osx-dok-malware-intercepts-web-traffic/</a>
<a href="https://developer.apple.com/library/content/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/CreatingLoginItems.html">https://developer.apple.com/library/content/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/CreatingLoginItems.html</a>
<a href="https://www.rsaconference.com/writable/presentations/file%20upload/ht-r03-malware-persistence-on-os-x-yosemite%20final.pdf">https://www.rsaconference.com/writable/presentations/file%20upload/ht-r03-malware-persistence-on-os-x-yosemite%20final.pdf</a>
<a href="https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf">https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf</a>

## Redundant Access

Adversaries may use more than one remote access tool with varying command and control protocols as a hedge against detection. If one type of tool is detected and blocked or removed as a response but the organization did not gain a full understanding of the adversary's tools and access, then the adversary will be able to retain access to the network. Adversaries may also attempt to gain access to Valid Accounts to use External Remote Services such as external VPNs as a way to maintain access despite interruptions to remote access tools deployed within a target network. Web Shell is one such way to maintain access to a network through an externally accessible Web server.

Detection: Existing methods of detecting remote access tools are helpful. Backup remote access tools or other access points may not have established command and control channels open during an intrusion, so the volume of data transferred may not be as high as the primary channel unless access is lost.

Detection of tools based on beacon traffic, Valid Accounts and External Remote Services to collect account use information.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: Process monitoring, Process use of network, Packet capture, Network protocol analysis, File monitoring, Authentication logs, Binary file metadata

Table 612. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1108">https://attack.mitre.org/wiki/Technique/T1108</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf">https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf</a>

## Data Encrypted

Data is encrypted before being exfiltrated in order to hide the information that is being exfiltrated from detection or to make the exfiltration less conspicuous upon inspection by a defender. The

encryption is performed by a utility, programming library, or custom algorithm on the data itself and is considered separate from any encryption performed by the command and control or file transfer protocol. Common file archive formats that can encrypt files are RAR and zip.

Other exfiltration techniques likely apply as well to transfer the information out of the network, such as Exfiltration Over Command and Control Channel and Exfiltration Over Alternative Protocol

Detection: Encryption software and encrypted files can be detected in many ways. Common utilities that may be present on the system or brought in by an adversary may be detectable through process monitoring and monitoring for command-line arguments for known encryption utilities. This may yield a significant amount of benign events, depending on how systems in the environment are typically used. Often the encryption key is stated within command-line invocation of the software.

A process that loads the Windows DLL crypt32.dll may be used to perform encryption, decryption, or verification of file signatures.

Network traffic may also be analyzed for entropy to determine if encrypted data is being transmitted. [[Citation: Zhang 2013]] If the communications channel is unencrypted, encrypted files of known file types can be detected in transit during exfiltration with a network intrusion detection or data loss prevention system analyzing file headers. [[Citation: Wikipedia File Header Signatures]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process command-line parameters, Binary file metadata

Table 613. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1022">https://attack.mitre.org/wiki/Technique/T1022</a>
<a href="http://www.netsec.colostate.edu/zhang/DetectingEncryptedBotnetTraffic.pdf">http://www.netsec.colostate.edu/zhang/DetectingEncryptedBotnetTraffic.pdf</a> [ <a href="http://www.netsec.colostate.edu/zhang/DetectingEncryptedBotnetTraffic.pdf">http://www.netsec.colostate.edu/zhang/DetectingEncryptedBotnetTraffic.pdf</a> ]
<a href="https://en.wikipedia.org/wiki/List_of_file_signatures">https://en.wikipedia.org/wiki/List_of_file_signatures</a>

## DLL Search Order Hijacking

Windows systems use a common method to look for required DLLs to load into a program. [[Citation: Microsoft DLL Search]] Adversaries may take advantage of the Windows DLL search order and programs that ambiguously specify DLLs to gain privilege escalation and persistence.

Adversaries may perform DLL preloading, also called binary planting attacks, [[Citation: OWASP Binary Planting]] by placing a malicious DLL with the same name as an ambiguously specified DLL in a location that Windows searches before the legitimate DLL. Often this location is the current working directory of the program. Remote DLL preloading attacks occur when a program sets its current directory to a remote location such as a Web share before loading a DLL. [[Citation:

Microsoft 2269637]] Adversaries may use this behavior to cause the program to load a malicious DLL.

Adversaries may also directly modify the way a program loads DLLs by replacing an existing DLL or modifying a .manifest or .local redirection file, directory, or junction to cause the program to load a different DLL to maintain persistence or privilege escalation. [[Citation: Microsoft DLL Redirection]] [[Citation: Microsoft Manifests]] [[Citation: Mandiant Search Order]]

If a search order-vulnerable program is configured to run at a higher privilege level, then the adversary-controlled DLL that is loaded will also be executed at the higher level. In this case, the technique could be used for privilege escalation from user to administrator or SYSTEM or from administrator to SYSTEM, depending on the program.

Programs that fall victim to path hijacking may appear to behave normally because malicious DLLs may be configured to also load the legitimate DLLs they were meant to replace.

Detection: Monitor file systems for moving, renaming, replacing, or modifying DLLs. Changes in the set of DLLs that are loaded by a process (compared with past behavior) that do not correlate with known software, patches, etc., are suspicious. Monitor DLLs loaded into a process and detect DLLs that have the same file name but abnormal paths. Modifications to or creation of .manifest and .local redirection files that do not correlate with software updates are suspicious. Disallow loading of remote DLLs. [[Citation: Microsoft DLL Preloading]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: File monitoring, DLL monitoring, Process monitoring, Process command-line parameters

Effective Permissions: User, Administrator, SYSTEM

Contributors: Stefan Kanthak

Table 614. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1038">https://attack.mitre.org/wiki/Technique/T1038</a>
<a href="https://msdn.microsoft.com/en-US/library/aa375365">https://msdn.microsoft.com/en-US/library/aa375365</a>
<a href="https://www.owasp.org/index.php/Binary%20planting">https://www.owasp.org/index.php/Binary%20planting</a>
<a href="http://msdn.microsoft.com/en-US/library/ms682586">http://msdn.microsoft.com/en-US/library/ms682586</a>
<a href="http://blogs.technet.com/b/srd/archive/2010/08/23/more-information-about-dll-preloading-remote-attack-vector.aspx">http://blogs.technet.com/b/srd/archive/2010/08/23/more-information-about-dll-preloading-remote-attack-vector.aspx</a>
<a href="http://msdn.microsoft.com/en-US/library/ms682600">http://msdn.microsoft.com/en-US/library/ms682600</a>
<a href="http://blogs.technet.com/b/msrc/archive/2010/08/21/microsoft-security-advisory-2269637-released.aspx">http://blogs.technet.com/b/msrc/archive/2010/08/21/microsoft-security-advisory-2269637-released.aspx</a>
<a href="https://www.mandiant.com/blog/dll-search-order-hijacking-revisited/">https://www.mandiant.com/blog/dll-search-order-hijacking-revisited/</a>

## Data from Network Shared Drive

Sensitive data can be collected from remote systems via shared network drives (host shared directory, network file server, etc.) that are accessible from the current system prior to cmd may be used to gather information.

Detection: Monitor processes and command-line arguments for actions that could be taken to collect files from a network share. Remote access tools with built-in features may interact directly with the Windows API to gather data. Data may also be acquired through Windows system management tools such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process command-line parameters

Table 615. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1039">https://attack.mitre.org/wiki/Technique/T1039</a>

## AppInit DLLs

DLLs that are specified in the AppInit\_DLLs value in the Registry key `HKEY_LOCAL_MACHINE\Software\Microsoft\Windows NT\CurrentVersion\Windows` are loaded by user32.dll into every process that loads user32.dll. In practice this is nearly every program. This value can be abused to obtain persistence by causing a DLL to be loaded into most processes on the computer. [[Citation: AppInit Registry]]

The AppInit DLL functionality is disabled in Windows 8 and later versions when secure boot is enabled. [[Citation: AppInit Secure Boot]]

Detection: Monitor DLL loads by processes that load user32.dll and look for DLLs that are not recognized or not normally loaded into a process. Monitor the AppInit\_DLLs Registry value for modifications that do not correlate with known software, patch cycles, etc. Tools such as Sysinternals Autoruns may also be used to detect system changes that could be attempts at persistence, including listing current AppInit DLLs. [[Citation: TechNet Autoruns]]

Look for abnormal process behavior that may be due to a process loading a malicious DLL. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as making network connections for [[Command and Control]], learning details about the environment through , and conducting [[Lateral Movement]].

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Loaded DLLs, Process monitoring, Windows Registry

Table 616. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1103">https://attack.mitre.org/wiki/Technique/T1103</a>
<a href="https://support.microsoft.com/en-us/kb/197571">https://support.microsoft.com/en-us/kb/197571</a>
<a href="https://msdn.microsoft.com/en-us/library/dn280412">https://msdn.microsoft.com/en-us/library/dn280412</a>
<a href="https://technet.microsoft.com/en-us/sysinternals/bb963902">https://technet.microsoft.com/en-us/sysinternals/bb963902</a>

## Standard Non-Application Layer Protocol

Use of a standard non-application layer protocol for communication between host and C2 server or among infected hosts within a network. The list of possible protocols is extensive. [[Citation: Wikipedia OSI]] Specific examples include use of network layer protocols, such as the Internet Control Message Protocol (ICMP), and transport layer protocols, such as the User Datagram Protocol (UDP).

ICMP communication between hosts is one example. Because ICMP is part of the Internet Protocol Suite, it is required to be implemented by all IP-compatible hosts; [[Citation: Microsoft ICMP]] however, it is not as commonly monitored as other Internet Protocols such as TCP or UDP and may be used by adversaries to hide communications.

Detection: Analyze network traffic for ICMP messages or other protocols that contain abnormal data or are not normally seen within or exiting the network.

Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Table 617. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1095">https://attack.mitre.org/wiki/Technique/T1095</a>
<a href="https://support.microsoft.com/KB/170292">https://support.microsoft.com/KB/170292</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>

## Plist Modification

Property list (plist) files contain all of the information that macOS and OS X uses to configure applications and services. These files are UT-8 encoded and formatted like XML documents via a

series of keys surrounded by < >. They detail when programs should execute, file paths to the executables, program arguments, required OS permissions, and many others. plists are located in certain locations depending on their purpose such as `</code>/Library/Preferences</code> (which execute with elevated privileges) and </code>~/Library/Preferences</code> (which execute with a user's privileges). Adversaries can modify these plist files to point to their own code, can use them to execute their code in the context of another user, bypass whitelisting procedures, or even use them as a persistence mechanism[[Citation: Sofacy Komplex Trojan]].`

Detection: File system monitoring can determine if plist files are being modified. Users should not have permission to modify these in most cases. Some software tools like "Knock Knock" can detect persistence mechanisms and point to the specific files that are being referenced. This can be helpful to see what is actually being executed.

Monitor process execution for abnormal process execution resulting from modified plist files. Monitor utilities used to modify plist files or that take a plist file as an argument, which may indicate suspicious activity.

Platforms: MacOS, OS X

Data Sources: File monitoring, Process Monitoring, Process command-line parameters

Table 618. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1150">https://attack.mitre.org/wiki/Technique/T1150</a>
<a href="https://researchcenter.paloaltonetworks.com/2016/09/unit42-sofacys-komplex-os-x-trojan/">https://researchcenter.paloaltonetworks.com/2016/09/unit42-sofacys-komplex-os-x-trojan/</a>

## Netsh Helper DLL

Netsh.exe (also referred to as Netshell) is a command-line scripting utility used to interact with the network configuration of a system. It contains functionality to add helper DLLs for extending functionality of the utility. [[Citation: TechNet Netsh]] The paths to registered netsh.exe helper DLLs are entered into the Windows Registry at `</code>HKLM\SOFTWARE\Microsoft\Netsh</code>.`

Adversaries can use netsh.exe with helper DLLs to proxy execution of arbitrary code in a persistent manner when netsh.exe is executed automatically with another technique or if other persistent software is present on the system that executes netsh.exe as part of its normal functionality. Examples include some VPN software that invoke netsh.exe. [[Citation: Demaske Netsh Persistence]]

Proof of concept code exists to load Cobalt Strike's payload using netsh.exe helper DLLs. [[Citation: Github Netsh Helper CS Beacon]]

Detection: It is likely unusual for netsh.exe to have any child processes in most environments. Monitor process executions and investigate any child processes spawned by netsh.exe for malicious behavior. Monitor the `</code>HKLM\SOFTWARE\Microsoft\Netsh</code> registry key for any new or suspicious entries that do not correlate with known system files or benign software. [[Citation: Demaske Netsh Persistence]]`

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP,



Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: DLL monitoring, Windows Registry, Process monitoring

Contributors: Matthew Demaske, Adaptforward

*Table 619. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1128">https://attack.mitre.org/wiki/Technique/T1128</a>
<a href="https://technet.microsoft.com/library/bb490939.aspx">https://technet.microsoft.com/library/bb490939.aspx</a>
<a href="https://github.com/outflankbv/NetshHelperBeacon">https://github.com/outflankbv/NetshHelperBeacon</a>
<a href="https://htmlpreview.github.io/?https://github.com/MatthewDemaske/blogbackup/blob/master/netshell.html">https://htmlpreview.github.io/?https://github.com/MatthewDemaske/blogbackup/blob/master/netshell.html</a>

## Account Manipulation

Account manipulation may aid adversaries in maintaining access to credentials and certain permission levels within an environment. Manipulation could consist of modifying permissions, adding or changing permission groups, modifying account settings, or modifying how authentication is performed. In order to create or manipulate accounts, the adversary must already have sufficient permissions on systems or the domain.

Detection: Collect events that correlate with changes to account objects on systems and the domain, such as event ID 4738. [[Citation: Microsoft User Modified Event]] Monitor for modification of accounts in correlation with other suspicious activity. Changes may occur at unusual times or from unusual systems.

Use of credentials may also occur at unusual times or to unusual systems or services and may correlate with other suspicious activity.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Authentication logs, API monitoring, Windows event logs

*Table 620. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1098">https://attack.mitre.org/wiki/Technique/T1098</a>
<a href="https://docs.microsoft.com/windows/device-security/auditing/event-4738">https://docs.microsoft.com/windows/device-security/auditing/event-4738</a>

## Remote System Discovery

Adversaries will likely attempt to get a listing of other systems by IP address, hostname, or other logical identifier on a network that may be used for Net.

===Mac===

Specific to Mac, the `bonjour` protocol to discover additional Mac-based systems within the same broadcast domain. Utilities such as "ping" and others can be used to gather information about remote systems.

===Linux===

Utilities such as "ping" and others can be used to gather information about remote systems.

Detection: System and network discovery techniques normally occur throughout an operation as an adversary learns the environment. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, MacOS, OS X

Data Sources: Network protocol analysis, Process monitoring, Process use of network, Process command-line parameters

*Table 621. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1018">https://attack.mitre.org/wiki/Technique/T1018</a>

## Permission Groups Discovery

Adversaries may attempt to find local system or domain-level groups and permissions settings.

===Windows===

Examples of commands that can list groups are `net group /domain` and `net localgroup` using the Net utility.

===Mac===

On Mac, this same thing can be accomplished with the `dscacheutil -q group` for the domain, or `dscl . -list /Groups` for local groups.

===Linux===

On Linux, local groups can be enumerated with the `groups` command and domain groups via the `ldapsearch` command.

Detection: System and network discovery techniques normally occur throughout an operation as an adversary learns the environment. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: API monitoring, Process monitoring, Process command-line parameters

Table 622. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1069">https://attack.mitre.org/wiki/Technique/T1069</a>

## File Deletion

Malware, tools, or other non-native files dropped or created on a system by an adversary may leave traces behind as to what was done within a network and how. Adversaries may remove these files over the course of an intrusion to keep their footprint low or remove them at the end as part of the post-intrusion cleanup process.

There are tools available from the host operating system to perform cleanup, but adversaries may use other tools as well. Examples include native cmd functions such as DEL, secure deletion tools such as Windows Sysinternals SDelete, or other third-party file deletion tools. [[Citation: Trend Micro APT Attack Tools]]

Detection: It may be uncommon for events related to benign command-line functions such as DEL or third-party utilities or tools to be found in an environment, depending on the user base and how systems are typically used. Monitoring for command-line deletion functions to correlate with binaries or other files that an adversary may drop and remove may lead to detection of malicious activity. Another good practice is monitoring for known deletion and secure deletion tools that are not already on systems within an enterprise network that an adversary could introduce. Some monitoring tools may collect command-line arguments, but may not capture DEL commands since DEL is a native function within cmd.exe.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: File monitoring, Process command-line parameters, Binary file metadata

Contributors: Walker Johnson

Table 623. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1107">https://attack.mitre.org/wiki/Technique/T1107</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/in-depth-look-apt-attack-tools-of-the-trade/">http://blog.trendmicro.com/trendlabs-security-intelligence/in-depth-look-apt-attack-tools-of-the-trade/</a>

# Path Interception

Path interception occurs when an executable is placed in a specific path so that it is executed by an application instead of the intended target. One example of this was the use of a copy of cmd in the current working directory of a vulnerable application that loads a CMD or BAT file with the CreateProcess function. DLL Search Order Hijacking.

Detection: Monitor file creation for files named after partial directories and in locations that may be searched for common processes through the environment variable, or otherwise should not be user writable. Monitor the executing process for process executable paths that are named for partial directories. Monitor file creation for programs that are named after Windows system programs or programs commonly executed without a path (such as "findstr," "net," and "python"). If this activity occurs outside of known administration activity, upgrades, installations, or patches, then it may be suspicious.

Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as network connections made for [[Command and Control]], learning details about the environment through , and [[Lateral Movement]].

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: File monitoring, Process monitoring

Effective Permissions: User, Administrator, SYSTEM

Contributors: Stefan Kanthak

Table 624. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1034">https://attack.mitre.org/wiki/Technique/T1034</a>
<a href="https://isc.sans.edu/diary/Help+eliminate+unquoted+path+vulnerabilities/14464">https://isc.sans.edu/diary/Help+eliminate+unquoted+path+vulnerabilities/14464</a>
<a href="http://technet.microsoft.com/en-us/library/cc723564.aspx#XSLTsection127121120120">http://technet.microsoft.com/en-us/library/cc723564.aspx#XSLTsection127121120120</a>
<a href="https://blogs.technet.microsoft.com/srd/2014/04/08/ms14-019-fixing-a-binary-hijacking-via-cmd-or-bat-file/">https://blogs.technet.microsoft.com/srd/2014/04/08/ms14-019-fixing-a-binary-hijacking-via-cmd-or-bat-file/</a>
<a href="http://support.microsoft.com/KB/103000">http://support.microsoft.com/KB/103000</a>
<a 475="" 75="" 835="" 860"="" data-label="Section-Header" href="https://msdn.microsoft.com/en-us/library/fd7hx added to the compiled&lt;/a&gt;&lt;/td&gt;&lt;/tr&gt;&lt;/tbody&gt;&lt;/table&gt;&lt;/div&gt;&lt;div data-bbox="><h2>LC_LOAD_DYLIB Addition</h2></a>

Mach-O binaries have a series of headers that are used to perform certain operations when a binary is loaded. The LC\_LOAD\_DYLIB header in a Mach-O binary tells macOS and OS X which dynamic libraries (dylibs) to load during execution time. These can be added ad-hoc to the compiled

binary as long adjustments are made to the rest of the fields and dependencies[[Citation: Writing Bad Malware for OSX]]. There are tools available to perform these changes. Any changes will invalidate digital signatures on binaries because the binary is being modified. Adversaries can remediate this issue by simply removing the LC\_CODE\_SIGNATURE command from the binary so that the signature isn't checked at load time[[Citation: Malware Persistence on OS X]].

Detection: Monitor processes for those that may be used to modify binary headers. Monitor file systems for changes to application binaries and invalid checksums/signatures. Changes to binaries that do not line up with application updates or patches are also extremely suspicious.

Platforms: MacOS, OS X

Data Sources: Binary file metadata, Process Monitoring, Process command-line parameters, File monitoring

Table 625. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1161">https://attack.mitre.org/wiki/Technique/T1161</a>
<a href="https://www.blackhat.com/docs/us-15/materials/us-15-Wardle-Writing-Bad-A-Malware-For-OS-X.pdf">https://www.blackhat.com/docs/us-15/materials/us-15-Wardle-Writing-Bad-A-Malware-For-OS-X.pdf</a>
<a href="https://www.rsaconference.com/writable/presentations/file%20upload/ht-r03-malware-persistence-on-os-x-yosemite%20final.pdf">https://www.rsaconference.com/writable/presentations/file%20upload/ht-r03-malware-persistence-on-os-x-yosemite%20final.pdf</a>

## Bootkit

A bootkit is a malware variant that modifies the boot sectors of a hard drive, including the Master Boot Record (MBR) and Volume Boot Record (VBR).[[Citation: MTrends 2016]]

Adversaries may use bootkits to persist on systems at a layer below the operating system, which may make it difficult to perform full remediation unless an organization suspects one was used and can act accordingly.

===Master Boot Record=== The MBR is the section of disk that is first loaded after completing hardware initialization by the BIOS. It is the location of the boot loader. An adversary who has raw access to the boot drive may overwrite this area, diverting execution during startup from the normal boot loader to adversary code. [[Citation: Lau 2011]]

===Volume Boot Record=== The MBR passes control of the boot process to the VBR. Similar to the case of MBR, an adversary who has raw access to the boot drive may overwrite the VBR to divert execution during startup to adversary code.

Detection: Perform integrity checking on MBR and VBR. Take snapshots of MBR and VBR and compare against known good samples. Report changes to MBR and VBR as they occur for indicators of suspicious activity and further analysis.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10

Data Sources: API monitoring, MBR, VBR

Table 626. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1067">https://attack.mitre.org/wiki/Technique/T1067</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/regional/fr%20FR/offers/pdfs/ig-mtrends-2016.pdf">https://www.fireeye.com/content/dam/fireeye-www/regional/fr%20FR/offers/pdfs/ig-mtrends-2016.pdf</a>
<a href="http://www.symantec.com/connect/blogs/are-mbr-infections-back-fashion">http://www.symantec.com/connect/blogs/are-mbr-infections-back-fashion</a>

## Indicator Removal on Host

Adversaries may delete or alter generated event files on a host system, including potentially captured files such as quarantined malware. This may compromise the integrity of the security solution, causing events to go unreported, or make forensic analysis and incident response more difficult due to lack of sufficient data to determine what occurred.

Detection: File system monitoring may be used to detect improper deletion or modification of indicator files. Events not stored on the file system will require different detection mechanisms.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process command-line parameters

Table 627. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1070">https://attack.mitre.org/wiki/Technique/T1070</a>

## Re-opened Applications

Starting in Mac OS X 10.7 (Lion), users can specify certain applications to be re-opened when a user reboots their machine. While this is usually done via a Graphical User Interface (GUI) on an app-by-app basis, there are property list files (plist) that contain this information as well located at `~/Library/Preferences/com.apple.loginwindow.plist` and `~/Library/Preferences/ByHost/com.apple.loginwindow.*.plist`.

An adversary can modify one of these files directly to include a link to their malicious executable to provide a persistence mechanism each time the user reboots their machine[[Citation: Methods of Mac Malware Persistence]].

Detection: Monitoring the specific plist files associated with reopening applications can indicate when an application has registered itself to be reopened.

Platforms: MacOS, OS X

Table 628. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1164">https://attack.mitre.org/wiki/Technique/T1164</a>
<a href="https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf">https://www.virusbulletin.com/uploads/pdf/conference/vb2014/VB2014-Wardle.pdf</a>

## Exfiltration Over Other Network Medium

Exfiltration could occur over a different network medium than the command and control channel. If the command and control network is a wired Internet connection, the exfiltration may occur, for example, over a WiFi connection, modem, cellular data connection, Bluetooth, or another radio frequency (RF) channel. Adversaries could choose to do this if they have sufficient access or proximity, and the connection might not be secured or defended as well as the primary Internet-connected channel because it is not routed through the same enterprise network.

Detection: Processes utilizing the network that do not normally have network communication or have never been seen before. Processes that normally require user-driven events to access the network (for example, a mouse click or key press) but access the network without such may be malicious.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: User interface, Process monitoring

Contributors: Itzik Kotler, SafeBreach

*Table 629. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1011">https://attack.mitre.org/wiki/Technique/T1011</a>

## Data from Local System

Sensitive data can be collected from local system sources, such as the file system or databases of information residing on the system prior to Command-Line Interface, such as cmd, which has functionality to interact with the file system to gather information. Some adversaries may also use Automated Collection on the local system.

Detection: Monitor processes and command-line arguments for actions that could be taken to collect files from a system. Remote access tools with built-in features may interact directly with the Windows API to gather data. Data may also be acquired through Windows system management tools such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Process command-line parameters

Table 630. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1005">https://attack.mitre.org/wiki/Technique/T1005</a>

## Web Shell

A Web shell is a Web script that is placed on an openly accessible Web server to allow an adversary to use the Web server as a gateway into a network. A Web shell may provide a set of functions to execute or a command-line interface on the system that hosts the Web server. In addition to a server-side script, a Web shell may have a client interface program that is used to talk to the Web server (see, for example, China Chopper Web shell client). Redundant Access or as a persistence mechanism in case an adversary's primary access methods are detected and removed.

Detection: Web shells can be difficult to detect. Unlike other forms of persistent remote access, they do not initiate connections. The portion of the Web shell that is on the server may be small and innocuous looking. The PHP version of the China Chopper Web shell, for example, is the following short payload:cmd or accessing files that are not in the Web directory. File monitoring may be used to detect changes to files in the Web directory of a Web server that do not match with updates to the Web server's content and may indicate implantation of a Web shell script. Log authentication attempts to the server and any unusual traffic patterns to or from the server and internal network. [[Citation: US-CERT Alert TA15-314A Web Shells]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process monitoring, Authentication logs, Netflow/Enclave netflow, Anti-virus

Effective Permissions: User, SYSTEM

Table 631. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1100">https://attack.mitre.org/wiki/Technique/T1100</a>
<a href="https://www.fireeye.com/blog/threat-research/2013/08/breaking-down-the-china-chopper-web-shell-part-i.html">https://www.fireeye.com/blog/threat-research/2013/08/breaking-down-the-china-chopper-web-shell-part-i.html</a>
<a href="https://www.us-cert.gov/ncas/alerts/TA15-314A">https://www.us-cert.gov/ncas/alerts/TA15-314A</a>

## Service Registry Permissions Weakness

Windows stores local service configuration information in the Registry under `HKLM\SYSTEM\CurrentControlSet\Services`. The information stored under a service's Registry keys can be manipulated to modify a service's execution parameters through tools such as the service controller, sc.exe, PowerShell, or Reg. Access to Registry keys is controlled through Access Control Lists and permissions. Windows Management Instrumentation and PowerShell, so additional logging may need to be configured to gather the appropriate data.



Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Windows Registry, Services, Process command-line parameters

Effective Permissions: SYSTEM

Table 632. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1058">https://attack.mitre.org/wiki/Technique/T1058</a>
<a href="https://technet.microsoft.com/en-us/sysinternals/bb963902">https://technet.microsoft.com/en-us/sysinternals/bb963902</a>
<a href="https://msdn.microsoft.com/library/windows/desktop/ms724878.aspx">https://msdn.microsoft.com/library/windows/desktop/ms724878.aspx</a>

## Windows Admin Shares

Windows systems have hidden network shares that are accessible only to administrators and provide the ability for remote file copy and other administrative functions. Example network shares include `C$`, `ADMIN$`, and `IPC$`.

Adversaries may use this technique in conjunction with administrator-level Valid Accounts to remotely access a networked system over server message block (SMB) Scheduled Task, Service Execution, and Windows Management Instrumentation. Adversaries can also use NTLM hashes to access administrator shares on systems with Pass the Hash and certain configuration and patch levels. Net utility can be used to connect to Windows admin shares on remote systems using `net use` commands with valid credentials. Net, on the command-line interface and techniques that could be used to find remotely accessible systems.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Process use of network, Authentication logs, Process monitoring, Process command-line parameters

Table 633. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1077">https://attack.mitre.org/wiki/Technique/T1077</a>
<a href="http://support.microsoft.com/kb/314984">http://support.microsoft.com/kb/314984</a>
<a href="https://technet.microsoft.com/en-us/library/cc787851.aspx">https://technet.microsoft.com/en-us/library/cc787851.aspx</a>
<a href="https://en.wikipedia.org/wiki/Server%20Message%20Block">https://en.wikipedia.org/wiki/Server%20Message%20Block</a>
<a href="http://blogs.technet.com/b/jepayne/archive/2015/11/27/tracking-lateral-movement-part-one-special-groups-and-specific-service-accounts.aspx">http://blogs.technet.com/b/jepayne/archive/2015/11/27/tracking-lateral-movement-part-one-special-groups-and-specific-service-accounts.aspx</a>
<a href="https://technet.microsoft.com/bb490717.aspx">https://technet.microsoft.com/bb490717.aspx</a>

## Winlogon Helper DLL

Winlogon is a part of some Windows versions that performs actions at logon. In Windows systems prior to Windows Vista, a Registry key can be modified that causes Winlogon to load a DLL on startup. Adversaries may take advantage of this feature to load adversarial code at startup for persistence.

Detection: Monitor for changes to registry entries in `HKLM\Software\Microsoft\Windows NT\CurrentVersion\Winlogon\Notify` that do not correlate with known software, patch cycles, etc. Tools such as Sysinternals Autoruns may also be used to detect system changes that could be attempts at persistence, including listing current Winlogon helper values. [[Citation: TechNet Autoruns]] New DLLs written to System32 that do not correlate with known good software or patching may also be suspicious.

Look for abnormal process behavior that may be due to a process loading a malicious DLL. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as network connections made for [[Command and Control]], learning details about the environment through , and [[Lateral Movement]].

Platforms: Windows Server 2003, Windows XP, Windows Server 2003 R2

Data Sources: Windows Registry, File monitoring, Process monitoring

Table 634. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1004">https://attack.mitre.org/wiki/Technique/T1004</a>
<a href="https://technet.microsoft.com/en-us/sysinternals/bb963902">https://technet.microsoft.com/en-us/sysinternals/bb963902</a>

## Network Share Discovery

Networks often contain shared network drives and folders that enable users to access file directories on various systems across a network.

===Windows===

File sharing over a Windows network occurs over the SMB protocol. Net can be used to query a remote system for available shared drives using the `net view \\remotesystem` command. It can also be used to query shared drives on the local system using `net share`.

Adversaries may look for folders and drives shared on remote systems as a means of identifying sources of information to gather as a precursor for Windows Management Instrumentation and PowerShell.

Platforms: Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2012, Windows

Server 2008 R2, Windows Server 2012 R2, Windows Server 2003, Windows Server 2008, Windows XP, Windows Server 2003 R2, Windows Vista, MacOS, OS X

Data Sources: Process Monitoring, Process command-line parameters, Network protocol analysis, Process use of network

Table 635. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1135">https://attack.mitre.org/wiki/Technique/T1135</a>
<a href="https://en.wikipedia.org/wiki/Shared%20resource">https://en.wikipedia.org/wiki/Shared%20resource</a>
<a href="https://technet.microsoft.com/library/cc770880.aspx">https://technet.microsoft.com/library/cc770880.aspx</a>

## Remote Services

An adversary may use valid credentials to log into a service specifically designed to accept remote connections, such as telnet, SSH, and VNC. The adversary may then perform actions as the logged-on user.

Detection: Correlate use of login activity related to remote services with unusual behavior or other malicious or suspicious activity. Adversaries will likely need to learn about an environment and the relationships between systems through techniques prior to attempting [[Lateral Movement]].

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: Authentication logs

Table 636. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1021">https://attack.mitre.org/wiki/Technique/T1021</a>

## Accessibility Features

Windows contains accessibility features that may be launched with a key combination before a user has logged in (for example, when the user is on the Windows logon screen). An adversary can modify the way these programs are launched to get a command prompt or backdoor without logging in to the system.

Two common accessibility programs are `C:\Windows\System32\sethc.exe`, launched when the shift key is pressed five times and `C:\Windows\System32\utilman.exe`, launched when the Windows + U key combination is pressed. The sethc.exe program is often referred to as "sticky keys", and has been used by adversaries for unauthenticated access through a remote desktop login screen. Remote Desktop Protocol will cause the replaced file to be executed with SYSTEM privileges. [[Citation: Tilbury 2014]]

For the debugger method on Windows Vista and later as well as Windows Server 2008 and later, for

example, a Registry key may be modified that configures "cmd.exe," or another program that provides backdoor access, as a "debugger" for the accessibility program (e.g., "utilman.exe"). After the Registry is modified, pressing the appropriate key combination at the login screen while at the keyboard or when connected with RDP will cause the "debugger" program to be executed with SYSTEM privileges. [[Citation: Tilbury 2014]]

Other accessibility features exist that may also be leveraged in a similar fashion: [[Citation: DEFCON2016 Sticky Keys]]

*On-Screen Keyboard:	<code>C:\Windows\System32\osk.exe</code>	*Magnifier:
	<code>C:\Windows\System32\Magnify.exe</code>	*Narrator:
	<code>C:\Windows\System32\Narrator.exe</code>	Switcher:
	<code>C:\Windows\System32\DisplaySwitch.exe</code>	*Display Switcher:
	<code>C:\Windows\System32\AtBroker.exe</code>	*App Switcher:

Detection: Changes to accessibility utility binaries or binary paths that do not correlate with known software, patch cycles, etc., are suspicious. Command line invocation of tools capable of modifying the Registry for associated keys are also suspicious. Utility arguments and the binaries themselves should be monitored for changes. Monitor Registry keys within `HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options`.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Windows Registry, File monitoring, Process monitoring

Effective Permissions: SYSTEM

Contributors: Paul Speulstra, AECOM Global Security Operations Center

Table 637. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1015">https://attack.mitre.org/wiki/Technique/T1015</a>
<a href="http://blog.crowdstrike.com/registry-analysis-with-crowdresponse/">http://blog.crowdstrike.com/registry-analysis-with-crowdresponse/</a>
<a href="https://www.slideshare.net/DennisMaldonado5/sticky-keys-to-the-kingdom">https://www.slideshare.net/DennisMaldonado5/sticky-keys-to-the-kingdom</a>
<a href="https://www.fireeye.com/blog/threat-research/2012/08/hikit-rootkit-advanced-persistent-attack-techniques-part-1.html">https://www.fireeye.com/blog/threat-research/2012/08/hikit-rootkit-advanced-persistent-attack-techniques-part-1.html</a>

## Taint Shared Content

Content stored on network drives or in other shared locations may be tainted by adding malicious programs, scripts, or exploit code to otherwise valid files. Once a user opens the shared tainted content, the malicious portion can be executed to run the adversary's code on a remote system. Adversaries may use tainted shared content to move laterally.

Detection: Processes that write or overwrite many files to a network shared directory may be

suspicious. Monitor processes that are executed from removable media for malicious or abnormal activity such as network connections due to [[Command and Control]] and possible network techniques.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: File monitoring, Process monitoring

Table 638. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1080">https://attack.mitre.org/wiki/Technique/T1080</a>

## External Remote Services

Remote services such as VPNs, Citrix, and other access mechanisms allow users to connect to internal enterprise network resources from external locations. There are often remote service gateways that manage connections and credential authentication for these services.

Adversaries may use remote services to access and persist within a network. Valid Accounts to use the service is often a requirement, which could be obtained through credential pharming or by obtaining the credentials from users after compromising the enterprise network. Access to remote services may be used as part of Redundant Access during an operation.

Detection: Follow best practices for detecting adversary use of Valid Accounts for authenticating to remote services. Collect authentication logs and analyze for unusual access patterns, windows of activity, and access outside of normal business hours.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Authentication logs

Contributors: Daniel Oakley

Table 639. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1133">https://attack.mitre.org/wiki/Technique/T1133</a>
<a href="https://www.volexity.com/blog/2015/10/07/virtual-private-keylogging-cisco-web-vpns-leveraged-for-access-and-persistence/">https://www.volexity.com/blog/2015/10/07/virtual-private-keylogging-cisco-web-vpns-leveraged-for-access-and-persistence/</a>

## Application Deployment Software

Adversaries may deploy malicious software to systems within a network using application deployment systems employed by enterprise administrators. The permissions required for this

action vary by system configuration; local credentials may be sufficient with direct access to the deployment server, or specific domain credentials may be required. However, the system may require an administrative account to log in or to perform software deployment.

Access to a network-wide or enterprise-wide software deployment system enables an adversary to have remote code execution on all systems that are connected to such a system. The access may be used to laterally move to systems, gather information, or cause a specific effect, such as wiping the hard drives on all endpoints.

Detection: Monitor application deployments from a secondary system. Perform application deployment at regular times so that irregular deployment activity stands out. Monitor process activity that does not correlate to known good software. Monitor account login activity on the deployment system.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Process use of network, Process monitoring

*Table 640. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1017">https://attack.mitre.org/wiki/Technique/T1017</a>

## Automated Collection

Once established within a system or network, an adversary may use automated techniques for collecting internal data. Methods for performing this technique could include use of Scripting to search for and copy information fitting set criteria such as file type, location, or name at specific time intervals. This functionality could also be built into remote access tools.

This technique may incorporate use of other techniques such as File and Directory Discovery and Remote File Copy to identify and move files.

Detection: Depending on the method used, actions could include common file system commands and parameters on the command-line interface within batch files or scripts. A sequence of actions like this may be unusual, depending on the system and network environment. Automated collection may occur along with other techniques such as Data Staged. As such, file access monitoring that shows an unusual process performing sequential file opens and potentially copy actions to another location on the file system for many files at once may indicate automated collection behavior. Remote access tools with built-in features may interact directly with the Windows API to gather data. Data may also be acquired through Windows system management tools such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Data loss prevention, Process command-line parameters

Table 641. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1119">https://attack.mitre.org/wiki/Technique/T1119</a>

## Security Support Provider

Windows Security Support Provider (SSP) DLLs are loaded into the Local Security Authority (LSA) process at system start. Once loaded into the LSA, SSP DLLs have access to encrypted and plaintext passwords that are stored in Windows, such as any logged-on user's Domain password or smart card PINs. The SSP configuration is stored in two Registry keys: `HKLM\SYSTEM\CurrentControlSet\Control\Lsa\Security Packages` and `HKLM\SYSTEM\CurrentControlSet\Control\Lsa\OSConfig\Security Packages`. An adversary may modify these Registry keys to add new SSPs, which will be loaded the next time the system boots, or when the `AddSecurityPackage` Windows API function is called. [[Citation: Graeber 2014]]

Detection: Monitor the Registry for changes to the SSP Registry keys. Monitor the LSA process for DLL loads. Windows 8.1 and Windows Server 2012 R2 may generate events when unsigned SSP DLLs try to load into the LSA by setting the Registry key `HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\LSASS.exe` with `AuditLevel = 8`. [[Citation: Graeber 2014]][[Citation: Microsoft Configure LSA]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: DLL monitoring, Windows Registry, Loaded DLLs

Table 642. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1101">https://attack.mitre.org/wiki/Technique/T1101</a>
<a href="http://docplayer.net/20839173-Analysis-of-malicious-security-support-provider-dlls.html">http://docplayer.net/20839173-Analysis-of-malicious-security-support-provider-dlls.html</a>
<a href="https://technet.microsoft.com/en-us/library/dn408187.aspx">https://technet.microsoft.com/en-us/library/dn408187.aspx</a>

## HISTCONTROL

The `HISTCONTROL` environment variable keeps track of what should be saved by the `history` command and eventually into the `~/.bash_history` file when a user logs out. This setting can be configured to ignore commands that start with a space by simply setting it to `ignorespace`. `HISTCONTROL` can also be set to ignore duplicate commands by setting it to `ignoredups`. In some Linux systems, this is set by default to `ignoreboth` which covers both of the previous examples. This means that `ls` will not be saved, but `ls` would be saved by history. `HISTCONTROL` does not exist by default on macOS, but can be set by the user and will be respected. Adversaries can use this to operate without leaving traces by simply prepending a space to all of their terminal commands.

Detection: Correlating a user session with a distinct lack of new commands in their `.bash_history` can be a clue to suspicious behavior. Additionally, users checking or changing their `HISTCONTROL` environment variable is also suspicious.

Platforms: Linux, MacOS, OS X

Data Sources: Process Monitoring, Authentication logs, File monitoring, Environment variable

Table 643. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1148">https://attack.mitre.org/wiki/Technique/T1148</a>

## Rundll32

The `rundll32.exe` program can be called to execute an arbitrary binary. Adversaries may take advantage of this functionality to proxy execution of code to avoid triggering security tools that may not monitor execution of the `rundll32.exe` process because of whitelists or false positives from Windows using `rundll32.exe` for normal operations.

Detection: Use process monitoring to monitor the execution and arguments of `rundll32.exe`. Compare recent invocations of `rundll32.exe` with prior history of known good arguments and loaded DLLs to determine anomalous and potentially adversarial activity. Command arguments used with the `rundll32.exe` invocation may also be useful in determining the origin and purpose of the DLL being loaded.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: File monitoring, Process monitoring, Process command-line parameters, Binary file metadata

Table 644. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1085">https://attack.mitre.org/wiki/Technique/T1085</a>

## Network Sniffing

Network sniffing refers to using the network interface on a system to monitor or capture information sent over a wired or wireless connection.

User credentials may be sent over an insecure, unencrypted protocol that can be captured and obtained through network packet analysis. An adversary may place a network interface into promiscuous mode, using a utility to capture traffic in transit over the network or use span ports to capture a larger amount of data. In addition, Address Resolution Protocol (ARP) and Domain Name Service (DNS) poisoning can be used to capture credentials to websites, proxies, and internal systems by redirecting traffic to an adversary.



Detection: Detecting the events leading up to sniffing network traffic may be the best method of detection. From the host level, an adversary would likely need to perform a man-in-the-middle attack against other devices on a wired network in order to capture traffic that was not to or from the current compromised system. This change in the flow of information is detectable at the enclave network level. Monitor for ARP spoofing and gratuitous ARP broadcasts. Detecting compromised network devices is a bit more challenging. Auditing administrator logins, configuration changes, and device images is required to detect malicious changes.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: Network device logs, Host network interface, Netflow/Enclave netflow

Table 645. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1040">https://attack.mitre.org/wiki/Technique/T1040</a>

## Local Port Monitor

A port monitor can be set through the AddMonitor API call to set a DLL to be loaded at startup. [[Citation: AddMonitor]] This DLL can be located in `C:\Windows\System32` and will be loaded by the print spooler service, spoolsv.exe, on boot. [[Citation: Bloxham]] Alternatively, an arbitrary DLL can be loaded if permissions allow writing a fully-qualified pathname for that DLL to `HKLM\SYSTEM\CurrentControlSet\Control\Print\Monitors`. [[Citation: Bloxham]] The spoolsv.exe process also runs under SYSTEM level permissions.

Adversaries can use this technique to load malicious code at startup that will persist on system reboot and execute as SYSTEM.

Detection: \* Monitor process API calls to AddMonitor. \* Monitor DLLs that are loaded by spoolsv.exe for DLLs that are abnormal. \* New DLLs written to the System32 directory that do not correlate with known good software or patching may be suspicious. \* Monitor registry writes to `HKLM\SYSTEM\CurrentControlSet\Control\Print\Monitors`. \* Run the Autoruns utility, which checks for this Registry key as a persistence mechanism [[Citation: TechNet Autoruns]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: File monitoring, API monitoring, DLL monitoring, Windows Registry, Process monitoring

Effective Permissions: SYSTEM

Contributors: Stefan Kanthak

Table 646. Table References

## Links

<https://attack.mitre.org/wiki/Technique/T1013>

<https://technet.microsoft.com/en-us/sysinternals/bb963902>

<http://msdn.microsoft.com/en-us/library/dd183341>

<https://www.defcon.org/images/defcon-22/dc-22-presentations/Bloxham/DEFCON-22-Brady-Bloxham-Windows-API-Abuse-UPDATED.pdf>

## Source

The `source` command loads functions into the current shell or executes files in the current context. This built-in command can be run in two different ways `source /path/to/filename [arguments]` or `./path/to/filename [arguments]`. Take note of the space after the ".". Without a space, a new shell is created that runs the program instead of running the program within the current context. This is often used to make certain features or functions available to a shell or to update a specific shell's environment.

Adversaries can abuse this functionality to execute programs. The file executed with this technique does not need to be marked executable beforehand.

Detection: Monitor for command shell execution of source and subsequent processes that are started as a result of being executed by a source command. Adversaries must also drop a file to disk in order to execute it with source, and these files can also be detected by file monitoring.

Platforms: Linux, MacOS, OS X

Data Sources: Process Monitoring, File monitoring, Process command-line parameters

*Table 647. Table References*

## Links

<https://attack.mitre.org/wiki/Technique/T1153>

## Software Packing

Software packing is a method of compressing or encrypting an executable. Packing an executable changes the file signature in an attempt to avoid signature-based detection. Most decompression techniques decompress the executable code in memory.

Utilities used to perform software packing are called packers. Example packers are MPRESS and UPX. A more comprehensive list of known packers is available,[[Citation: Wikipedia Exe Compression]] but adversaries may create their own packing techniques that do not leave the same artifacts as well-known packers to evade defenses.

Detection: Use file scanning to look for known software packers or artifacts of packing techniques. Packing is not a definitive indicator of malicious activity, because legitimate software may use packing techniques to reduce binary size or to protect proprietary code.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP,

Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Binary file metadata

Table 648. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1045">https://attack.mitre.org/wiki/Technique/T1045</a>
<a href="http://en.wikipedia.org/wiki/Executable%20compression">http://en.wikipedia.org/wiki/Executable%20compression</a>

## Application Window Discovery

Adversaries may attempt to get a listing of open application windows. Window listings could convey information about how the system is used or give context to information collected by a keylogger.

In Mac, this can be done natively with a small AppleScript script.

Detection: System and network discovery techniques normally occur throughout an operation as an adversary learns the environment. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities based on the information obtained.

Monitor processes and command-line arguments for actions that could be taken to gather system and network information. Remote access tools with built-in features may interact directly with the Windows API to gather information. Information may also be acquired through Windows system management tools such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, MacOS, OS X

Data Sources: API monitoring, Process monitoring, Process command-line parameters

Table 649. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1010">https://attack.mitre.org/wiki/Technique/T1010</a>

## Hypervisor

A type-1 hypervisor is a software layer that sits between the guest operating systems and system's hardware. Rootkit functionality to hide its existence from the guest operating system. [[Citation: Myers 2007]] A malicious hypervisor of this nature could be used to persist on systems through interruption.

Detection: Type-1 hypervisors may be detected by performing timing analysis. Hypervisors emulate certain CPU instructions that would normally be executed by the hardware. If an instruction takes orders of magnitude longer to execute than normal on a system that should not contain a

hypervisor, one may be present. [[Citation: virtualization.info 2006]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: System calls

Table 650. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1062">https://attack.mitre.org/wiki/Technique/T1062</a>
<a href="https://en.wikipedia.org/wiki/Hypervisor">https://en.wikipedia.org/wiki/Hypervisor</a>
<a href="http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.90.8832&amp;rep=rep1&amp;type=pdf">http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.90.8832&amp;rep=rep1&amp;type=pdf</a>
<a href="http://en.wikipedia.org/wiki/Xen">http://en.wikipedia.org/wiki/Xen</a>
<a href="http://virtualization.info/en/news/2006/08/debunking-blue-pill-myth.html">http://virtualization.info/en/news/2006/08/debunking-blue-pill-myth.html</a>

## Credential Dumping

Credential dumping is the process of obtaining account login and password information from the operating system and software. Credentials can be used to perform Windows Credential Editor, Mimikatz, and gsecdump. These tools are in use by both professional security testers and adversaries.

Plaintext passwords can be obtained using tools such as Mimikatz to extract passwords stored by the Local Security Authority (LSA). If smart cards are used to authenticate to a domain using a personal identification number (PIN), then that PIN is also cached as a result and may be dumped. Mimikatz access the LSA Subsystem Service (LSASS) process by opening the process, locating the LSA secrets key, and decrypting the sections in memory where credential details are stored. Credential dumpers may also use methods for reflective DLL Injection to reduce potential indicators of malicious activity.

NTLM hash dumpers open the Security Accounts Manager (SAM) on the local file system (%SystemRoot%/system32/config/SAM) or create a dump of the Registry SAM key to access stored account password hashes. Some hash dumpers will open the local file system as a device and parse to the SAM table to avoid file access defenses. Others will make an in-memory copy of the SAM table before reading hashes. Detection of compromised Valid Accounts in-use by adversaries may help as well.

On Windows 8.1 and Windows Server 2012 R2, monitor Windows Logs for LSASS.exe creation to verify that LSASS started as a protected process.

Monitor processes and command-line arguments for program execution that may be indicative of credential dumping. Remote access tools may contain built-in features or incorporate existing tools like Mimikatz. PowerShell scripts also exist that contain credential dumping functionality, such as PowerSploit's Invoke-Mimikatz module, [[Citation: Powersploit]] which may require additional logging features to be configured in the operating system to collect necessary information for analysis.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: API monitoring, Process monitoring, PowerShell logs, Process command-line parameters

Table 651. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1003">https://attack.mitre.org/wiki/Technique/T1003</a>
<a href="https://github.com/gentilkiwi/mimikatz/wiki/module--sekurlsa">https://github.com/gentilkiwi/mimikatz/wiki/module--sekurlsa</a> <small>[https://github.com/gentilkiwi/mimikatz/wiki/module--sekurlsa]</small>
<a href="https://github.com/mattifestation/PowerSploit">https://github.com/mattifestation/PowerSploit</a>

## Web Service

Adversaries may use an existing, legitimate external Web service as a means for relaying commands to a compromised system.

Popular websites and social media can act as a mechanism for command and control and give a significant amount of cover due to the likelihood that hosts within a network are already communicating with them prior to a compromise. Using common services, such as those offered by Google or Twitter, makes it easier for adversaries to hide in expected noise. Web service providers commonly use SSL/TLS encryption, giving adversaries an added level of protection.

Detection: Host data that can relate unknown or suspicious process activity using a network connection is important to supplement any existing indicators of compromise based on malware command and control signatures and infrastructure or the presence of strong encryption. Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Host network interface, Netflow/Enclave netflow, Network protocol analysis, Packet capture

Table 652. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1102">https://attack.mitre.org/wiki/Technique/T1102</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>

# Query Registry

Adversaries may interact with the Windows Registry to gather information about the system, configuration, and installed software.

The Registry contains a significant amount of information about the operating system, configuration, software, and security. Reg or through running malware that may interact with the Registry through an API. Command-line invocation of utilities used to query the Registry may be detected through process and command-line monitoring. Remote access tools with built-in features may interact directly with the Windows API to gather information. Information may also be acquired through Windows system management tools such as Windows Management Instrumentation and PowerShell.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Windows Registry, Process monitoring, Process command-line parameters

*Table 653. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1012">https://attack.mitre.org/wiki/Technique/T1012</a>
<a href="https://en.wikipedia.org/wiki/Windows%20Registry">https://en.wikipedia.org/wiki/Windows%20Registry</a>

## Third-party Software

Third-party applications and software deployment systems may be in use in the network environment for administration purposes (e.g., SCCM, VNC, HBSS, Altiris, etc.). If an adversary gains access to these systems, then they may be able to execute code.

Adversaries may gain access to and use third-party application deployment systems installed within an enterprise network. Access to a network-wide or enterprise-wide software deployment system enables an adversary to have remote code execution on all systems that are connected to such a system. The access may be used to laterally move to systems, gather information, or cause a specific effect, such as wiping the hard drives on all endpoints.

The permissions required for this action vary by system configuration; local credentials may be sufficient with direct access to the deployment server, or specific domain credentials may be required. However, the system may require an administrative account to log in or to perform software deployment.

Detection: Detection methods will vary depending on the type of third-party software or system and how it is typically used.

The same investigation process can be applied here as with other potentially malicious activities where the distribution vector is initially unknown but the resulting activity follows a discernible pattern. Analyze the process execution trees, historical activities from the third-party application (such as what types of files are usually pushed), and the resulting activities or events from the

file/binary/script pushed to systems.

Often these third-party applications will have logs of their own that can be collected and correlated with other data from the environment. Audit software deployment logs and look for suspicious or unauthorized activity. A system not typically used to push software to clients that suddenly is used for such a task outside of a known admin function may be suspicious.

Perform application deployment at regular times so that irregular deployment activity stands out. Monitor process activity that does not correlate to known good software. Monitor account login activity on the deployment system.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Third-party application logs, Windows Registry, Process monitoring, Process use of network, Binary file metadata

*Table 654. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1072">https://attack.mitre.org/wiki/Technique/T1072</a>

## Remote File Copy

Files may be copied from one system to another to stage adversary tools or other files over the course of an operation. Files may be copied from an external adversary-controlled system through the FTP. Files can also be copied over on Mac and Linux with native tools like scp, rsync, and sftp.

Adversaries may also copy files laterally between internal victim systems to support Windows Admin Shares or Remote Desktop Protocol.

Detection: Monitor for file creation and files transferred within a network over SMB. Unusual processes with external network connections creating files on-system may be suspicious. Use of utilities, such as FTP, that does not normally occur may also be suspicious.

Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: File monitoring, Packet capture, Process use of network, Netflow/Enclave netflow, Network protocol analysis, Process monitoring

*Table 655. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1105">https://attack.mitre.org/wiki/Technique/T1105</a>
<a href="https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf">https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf</a>

## File System Logical Offsets

Windows allows programs to have direct access to logical volumes. Programs with direct access may read and write files directly from the drive by analyzing file system data structures. This technique bypasses Windows file access controls as well as file system monitoring tools. PowerShell, additional logging of PowerShell scripts is recommended.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: API monitoring

*Table 656. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1006">https://attack.mitre.org/wiki/Technique/T1006</a>
<a href="https://github.com/PowerShellMafia/PowerSploit/blob/master/Exfiltration/Invoke-NinjaCopy.ps1">https://github.com/PowerShellMafia/PowerSploit/blob/master/Exfiltration/Invoke-NinjaCopy.ps1</a>
<a href="http://www.codeproject.com/Articles/32169/FDump-Dumping-File-Sectors-Directly-from-Disk-usin">http://www.codeproject.com/Articles/32169/FDump-Dumping-File-Sectors-Directly-from-Disk-usin</a>

## Shared Webroot

Adversaries may add malicious content to an internally accessible website through an open network file share that contains the website's webroot or Web content directory and then browse to that content with a Web browser to cause the server to execute the malicious content. The malicious content will typically run under the context and permissions of the Web server process, often resulting in local system or administrative privileges, depending on how the Web server is configured.

This mechanism of shared access and remote execution could be used for lateral movement to the system running the Web server. For example, a Web server running PHP with an open network share could allow an adversary to upload a remote access tool and PHP script to execute the RAT on the system running the Web server when a specific page is visited.

Detection: Use file and process monitoring to detect when files are written to a Web server by a process that is not the normal Web server process or when files are written outside of normal administrative time periods. Use process monitoring to identify normal processes that run on the Web server and detect processes that are not typically executed.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10



Data Sources: File monitoring, Process monitoring

Table 657. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1051">https://attack.mitre.org/wiki/Technique/T1051</a>

## Indicator Blocking

An adversary may attempt to block indicators or events from leaving the host machine. In the case of network-based reporting of indicators, an adversary may block traffic associated with reporting to prevent central analysis. This may be accomplished by many means, such as stopping a local process or creating a host-based firewall rule to block traffic to a specific server.

Detection: Detect lack of reported activity from a host sensor. Different methods of blocking may cause different disruptions in reporting. Systems may suddenly stop reporting all data or only certain kinds of data.

Depending on the types of host information collected, an analyst may be able to detect the event that triggered a process to stop or connection to be blocked.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Sensor health and status, Process monitoring, Process command-line parameters

Table 658. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1054">https://attack.mitre.org/wiki/Technique/T1054</a>

## Input Prompt

When programs are executed that need additional privileges than are present in the current user context, it is common for the operating system to prompt the user for proper credentials to authorize the elevated privileges for the task. Adversaries can mimic this functionality to prompt users for credentials with a normal-looking prompt. This type of prompt can be accomplished with AppleScript:

```
<code>set thePassword to the text returned of (display dialog "AdobeUpdater needs permission to check for updates. Please authenticate." default answer "")</code> [[Citation: OSX Keydnep malware]]
```

Adversaries can prompt a user for a number of reasons that mimic normal usage, such as a fake installer requiring additional access or a fake malware removal suite. [[Citation: OSX Malware Exploits MacKeeper]]

Detection: This technique exploits users' tendencies to always supply credentials when prompted, which makes it very difficult to detect. Monitor process execution for unusual programs as well as

AppleScript that could be used to prompt users for credentials.

Platforms: MacOS, OS X

Data Sources: User interface, Process Monitoring

*Table 659. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1141">https://attack.mitre.org/wiki/Technique/T1141</a>
<a href="https://www.welivesecurity.com/2016/07/06/new-osxkeydnep-malware-hungry-credentials/">https://www.welivesecurity.com/2016/07/06/new-osxkeydnep-malware-hungry-credentials/</a>
<a href="https://baesystemsai.blogspot.com/2015/06/new-mac-os-malware-exploits-mackeeper.html">https://baesystemsai.blogspot.com/2015/06/new-mac-os-malware-exploits-mackeeper.html</a>

## Exfiltration Over Physical Medium

In certain circumstances, such as an air-gapped network compromise, exfiltration could occur via a physical medium or device introduced by a user. Such media could be an external hard drive, USB drive, cellular phone, MP3 player, or other removable storage and processing device. The physical medium or device could be used as the final exfiltration point or to hop between otherwise disconnected systems.

Detection: Monitor file access on removable media. Detect processes that execute when removable media are mounted.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10, MacOS, OS X

Data Sources: Data loss prevention, File monitoring

*Table 660. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1052">https://attack.mitre.org/wiki/Technique/T1052</a>

## System Time Discovery

The system time is set and stored by the Windows Time Service within a domain to maintain time synchronization between systems and services in an enterprise network. Net on Windows by performing `net time \hostname` to gather the system time on a remote system. The victim's time zone may also be inferred from the current system time or gathered by using `w32tm /tz`. Scheduled Task[[Citation: RSA EU12 They're Inside]], or to discover locality information based on time zone to assist in victim targeting.

Detection: Command-line interface monitoring may be useful to detect instances of net.exe or other command-line utilities being used to gather system time or time zone. Methods of detecting API use for gathering this information are likely less useful due to how often they may be used by legitimate software.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Process monitoring, Process command-line parameters, API monitoring

Table 661. Table References

Links
<a href="https://attack.mitre.org/wiki/Technique/T1124">https://attack.mitre.org/wiki/Technique/T1124</a>
<a href="https://technet.microsoft.com/windows-server-docs/identity/ad-ds/get-started/windows-time-service/windows-time-service-tools-and-settings">https://technet.microsoft.com/windows-server-docs/identity/ad-ds/get-started/windows-time-service/windows-time-service-tools-and-settings</a>
<a href="https://msdn.microsoft.com/ms724961.aspx">https://msdn.microsoft.com/ms724961.aspx</a>
<a href="https://www.rsaconference.com/writable/presentations/file%20upload/ht-209%20rivner%20schwartz.pdf">https://www.rsaconference.com/writable/presentations/file%20upload/ht-209%20rivner%20schwartz.pdf</a>

## Execution through Module Load

The Windows module loader can be instructed to load DLLs from arbitrary local paths and arbitrary Universal Naming Convention (UNC) network paths. This functionality resides in NTDLL.dll and is part of the Windows Native API which is called from functions like CreateProcess(), LoadLibrary(), etc. of the Win32 API. [[Citation: Wikipedia Windows Library Files]]

The module loader can load DLLs:

- \*via specification of the (fully-qualified or relative) DLL pathname in the IMPORT directory;
- \*via EXPORT forwarded to another DLL, specified with (fully-qualified or relative) pathname (but without extension);
- \*via an NTFS junction or symlink program.exe.local with the fully-qualified or relative pathname of a directory containing the DLLs specified in the IMPORT directory or forwarded EXPORTs;
- \*via `<file name="filename.extension" loadFrom="fully-qualified or relative pathname"></code>` in an embedded or external "application manifest". The file name refers to an entry in the IMPORT directory or a forwarded EXPORT.

Adversaries can use this functionality as a way to execute arbitrary code on a system.

Detection: Monitoring DLL module loads may generate a significant amount of data and may not be directly useful for defense unless collected under specific circumstances, since benign use of Windows modules load functions are common and may be difficult to distinguish from malicious behavior. Legitimate software will likely only need to load routine, bundled DLL modules or Windows system DLLs such that deviation from known module loads may be suspicious. Limiting DLL module loads to `<code>%SystemRoot%</code>` and `<code>%ProgramFiles%</code>` directories will protect against module loads from unsafe paths.

Correlation of other events with behavior surrounding module loads using API monitoring and suspicious DLLs written to disk will provide additional context to an event that may assist in

determining if it is due to malicious behavior.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10

Data Sources: Process Monitoring, API monitoring, File monitoring, DLL monitoring

Contributors: Stefan Kanthak

*Table 662. Table References*

Links
<a href="https://attack.mitre.org/wiki/Technique/T1129">https://attack.mitre.org/wiki/Technique/T1129</a>
<a href="https://en.wikipedia.org/wiki/Microsoft%20Windows%20library%20files">https://en.wikipedia.org/wiki/Microsoft%20Windows%20library%20files</a>

## Install Root Certificate

Root certificates are used in public key cryptography to identify a root certificate authority (CA). When a root certificate is installed, the system or application will trust certificates in the root's chain of trust that have been signed by the root certificate. [[Citation: Wikipedia Root Certificate]] Certificates are commonly used for establishing secure TLS/SSL communications within a web browser. When a user attempts to browse a website that presents a certificate that is not trusted an error message will be displayed to warn the user of the security risk. Depending on the security settings, the browser may not allow the user to establish a connection to the website.

Installation of a root certificate on a compromised system would give an adversary a way to degrade the security of that system. Adversaries have used this technique to avoid security warnings prompting users when compromised systems connect over HTTPS to adversary controlled web servers that spoof legitimate websites in order to collect login credentials. [[Citation: Operation Emmental]]

Atypical root certificates have also been pre-installed on systems by the manufacturer or in the software supply chain and were used in conjunction with malware/adware to provide a man-in-the-middle capability for intercepting information transmitted over secure TLS/SSL communications. [[Citation: Kaspersky Superfish]]

Detection: A system's root certificates are unlikely to change frequently. Monitor new certificates installed on a system that could be due to malicious activity. Check pre-installed certificates on new systems to ensure unnecessary or suspicious certificates are not present.

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Linux, Windows 10

Data Sources: SSL/TLS inspection, Digital Certificate Logs

Contributors: Itzik Kotler, SafeBreach

*Table 663. Table References*

## Links

<https://attack.mitre.org/wiki/Technique/T1130>

<https://en.wikipedia.org/wiki/Root%20certificate>

<http://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp-finding-holes-operation-emmental.pdf>

<https://usblog.kaspersky.com/superfish-adware-preinstalled-on-lenovo-laptops/5161/>

## Data Transfer Size Limits

An adversary may exfiltrate data in fixed size chunks instead of whole files or limit packet sizes below certain thresholds. This approach may be used to avoid triggering network data transfer threshold alerts.

Detection: Analyze network data for uncommon data flows (e.g., a client sending significantly more data than it receives from a server). If a process maintains a long connection during which it consistently sends fixed size data packets or a process opens connections and sends fixed sized data packets at regular intervals, it may be performing an aggregate data transfer. Processes utilizing the network that do not normally have network communication or have never been seen before are suspicious. Analyze packet contents to detect communications that do not follow the expected protocol behavior for the port that is being used. [[Citation: University of Birmingham C2]]

Platforms: Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows 7, Windows 8, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows 8.1, Windows 10, Linux, MacOS, OS X

Data Sources: Packet capture, Netflow/Enclave netflow, Process use of network, Process monitoring

*Table 664. Table References*

## Links

<https://attack.mitre.org/wiki/Technique/T1030>

<https://arxiv.org/ftp/arxiv/papers/1408/1408.1136.pdf>

## Course of Action

ATT&CK Mitigation.



Course of Action is a cluster galaxy available in JSON format at <https://github.com/MISP/misp-galaxy/blob/master/clusters/course> of action.json[**this location**] The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

MITRE

## Login Item Mitigation

Restrict users from being able to create their own login items. Additionally, holding the shift key during login prevents apps from opening automatically[[CiteRef::Re-Open windows on Mac]].

## Component Object Model Hijacking Mitigation

Direct mitigation of this technique may not be recommended for a particular environment since COM objects are a legitimate part of the operating system and installed software. Blocking COM object changes may have unforeseen side effects to legitimate functionality.

Instead, identify and block potentially malicious software that may execute, or be executed by, this technique using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Exfiltration Over Command and Control Channel Mitigation

Mitigations for command and control apply. Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific obfuscation technique used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool command and control signatures over time or construct protocols in such a way to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## .bash\_profile and .bashrc Mitigation

Making these files immutable and only changeable by certain administrators will limit the ability for adversaries to easily create user level persistence.

## DLL Injection Mitigation

Mitigating specific API calls will likely have unintended side effects, such as preventing legitimate software from operating properly. Efforts should be focused on preventing adversary tools from running earlier in the chain of activity and on identification of subsequent malicious behavior.

Identify or block potentially malicious software that may contain DLL injection functionality by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Bypass User Account Control Mitigation

Remove users from the local administrator group on systems. Although UAC bypass techniques

exist, it is still prudent to use the highest enforcement level for UAC when possible and mitigate bypass opportunities that exist with techniques such as [[Technique/T1038|DLL Search Order Hijacking]].

Check for common UAC bypass weaknesses on Windows systems to be aware of the risk posture and address issues where appropriate. [[CiteRef::Github UACMe]]

## Command-Line Interface Mitigation

Audit and/or block command-line interpreters by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## DLL Search Order Hijacking Mitigation

Use auditing tools capable of detecting DLL search order hijacking opportunities on systems within an enterprise and correct them. Toolkits like the PowerSploit framework contain PowerUp modules that can be used to explore systems for DLL hijacking weaknesses.

Identify and block potentially malicious software that may be executed through search order hijacking by using whitelisting [[CiteRef::Beechey 2010]] tools like AppLocker [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] that are capable of auditing and/or blocking unknown DLLs.

## Uncommonly Used Port Mitigation

Properly configure firewalls and proxies to limit outgoing traffic to only necessary ports.

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific protocol used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool C2 signatures over time or construct protocols in such a way as to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Regsvcs/Regasm Mitigation

Regsvcs and Regasm may not be necessary within a given environment. Block execution of Regsvcs.exe and Regasm.exe if they are not required for a given system or network to prevent potential misuiss by adversaries.

## Application Deployment Software Mitigation

Grant access to application deployment systems only to a limited number of authorized administrators. Ensure proper system and access isolation for critical network systems through use of firewalls, account privilege separation, group policy, and multifactor authentication. Verify that account credentials that may be used to access deployment systems are unique and not used

throughout the enterprise network. Patch deployment systems regularly to prevent potential remote access through [[Technique/T1068|Exploitation of Vulnerability]].

If the application deployment system can be configured to deploy only signed binaries, then ensure that the trusted signing certificates are not co-located with the application deployment system and are instead located on a system that cannot be accessed remotely or to which remote access is tightly controlled.

## Commonly Used Port Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific protocol used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool C2 signatures over time or construct protocols in such a way as to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Windows Management Instrumentation Mitigation

Disabling WMI or RPCS may cause system instability and should be evaluated to assess the impact to a network. By default, only administrators are allowed to connect remotely using WMI. Restrict other users who are allowed to connect, or disallow all users to connect remotely to WMI. Prevent credential overlap across systems of administrator and privileged accounts. [[CiteRef::FireEye WMI 2015]]

## Path Interception Mitigation

Eliminate path interception weaknesses in program configuration files, scripts, the PATH environment variable, services, and in shortcuts by surrounding PATH variables with quotation marks when functions allow for them [[CiteRef::Microsoft CreateProcess]]. Be aware of the search order Windows uses for executing or loading binaries and use fully qualified paths wherever appropriate [[CiteRef::MSDN DLL Security]]. Clean up old Windows Registry keys when software is uninstalled to avoid keys with no associated legitimate binaries.

Periodically search for and correct or report path interception weaknesses on systems that may have been introduced using custom or available tools that report software using insecure path configurations [[CiteRef::Kanthak Sentinel]].

Require that all executables be placed in write-protected directories. Ensure that proper permissions and directory access control are set to deny users the ability to write files to the top-level directory `C:` and system directories, such as `C:\Windows\`, to reduce places where malicious files could be placed for execution.

Identify and block potentially malicious software that may be executed through the path interception by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies, [[CiteRef::Corio 2008]] that are capable of auditing and/or blocking unknown executables.



# Graphical User Interface Mitigation

Prevent adversaries from gaining access to credentials through [\[\[Credential Access\]\]](#) that can be used to log into remote desktop sessions on systems.

Identify unnecessary system utilities, third-party tools, or potentially malicious software that may be used to log into remote interactive sessions, and audit and/or block them by using whitelisting[\[\[CiteRef::Beechey 2010\]\]](#) tools, like AppLocker[\[\[CiteRef::Windows Commands JPCERT\]\]](#)[\[\[CiteRef::NSA MS AppLocker\]\]](#) and Software Restriction Policies[\[\[CiteRef::Corio 2008\]\]](#) where appropriate.[\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

# NTFS Extended Attributes Mitigation

It may be difficult or inadvisable to block access to EA. Efforts should be focused on preventing potentially malicious software from running. Identify and block potentially malicious software that may contain functionality to hide information in EA by using whitelisting[\[\[CiteRef::Beechey 2010\]\]](#) tools like AppLocker[\[\[CiteRef::Windows Commands JPCERT\]\]](#)[\[\[CiteRef::NSA MS AppLocker\]\]](#) or Software Restriction Policies[\[\[CiteRef::Corio 2008\]\]](#) where appropriate.[\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

# Indicator Removal from Tools Mitigation

Mitigation is difficult in instances like this because the adversary may have access to the system through another channel and can learn what techniques or tools are blocked by resident defenses. Exercising best practices with configuration and security as well as ensuring that proper process is followed during investigation of potential compromise is essential to detecting a larger intrusion through discrete alerts.

Identify and block potentially malicious software that may be used by an adversary by using whitelisting[\[\[CiteRef::Beechey 2010\]\]](#) tools like AppLocker[\[\[CiteRef::Windows Commands JPCERT\]\]](#)[\[\[CiteRef::NSA MS AppLocker\]\]](#) or Software Restriction Policies[\[\[CiteRef::Corio 2008\]\]](#) where appropriate.[\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

# Clipboard Data Mitigation

Instead of blocking software based on clipboard capture behavior, identify potentially malicious software that may contain this functionality, and audit and/or block it by using whitelisting[\[\[CiteRef::Beechey 2010\]\]](#) tools, like AppLocker,[\[\[CiteRef::Windows Commands JPCERT\]\]](#)[\[\[CiteRef::NSA MS AppLocker\]\]](#) or Software Restriction Policies[\[\[CiteRef::Corio 2008\]\]](#) where appropriate.[\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

# Registry Run Keys / Start Folder Mitigation

Identify and block potentially malicious software that may be executed through run key or startup folder persistence using whitelisting[\[\[CiteRef::Beechey 2010\]\]](#) tools like AppLocker[\[\[CiteRef::Windows Commands JPCERT\]\]](#)[\[\[CiteRef::NSA MS AppLocker\]\]](#) or Software Restriction Policies[\[\[CiteRef::Corio 2008\]\]](#) where appropriate.[\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

## Multi-Stage Channels Mitigation

Command and control infrastructure used in a multi-stage channel may be blocked if known ahead of time. If unique signatures are present in the C2 traffic, they could also be used as the basis of identifying and blocking the channel. [[CiteRef::University of Birmingham C2]]

## Hidden Users Mitigation

If the computer is domain joined, then group policy can help restrict the ability to create or hide users. Similarly, preventing the modification of the `</code>/Library/Preferences/com.apple.loginwindow</code> </code> Hide500Users</code> value will force all users to be visible.`

## Data Staged Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to collect data from removable media, and audit and/or block them by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Data from Removable Media Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to collect data from removable media, and audit and/or block them by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Data from Network Shared Drive Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to collect data from a network share, and audit and/or block them by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Account Manipulation Mitigation

Use multifactor authentication. Follow guidelines to prevent or limit adversary access to [[Technique/T1078|Valid Accounts]].

Protect domain controllers by ensuring proper security configuration for critical servers. Configure access controls and firewalls to limit access to these systems. Do not allow domain administrator accounts to be used for day-to-day operations that may expose them to potential adversaries on unprivileged systems.

## AppleScript Mitigation

Require that all AppleScript be signed by a trusted developer ID before being executed - this will prevent random AppleScript code from executing.

## PowerShell Mitigation

It may be possible to remove PowerShell from systems when not needed, but a review should be performed to assess the impact to an environment, since it could be in use for many legitimate purposes and administrative functions. When PowerShell is necessary, restrict PowerShell execution policy to administrators and to only execute signed scripts. Be aware that there are methods of bypassing the PowerShell execution policy, depending on environment configuration. [\[\[CiteRef::Netspi PowerShell Execution Policy Bypass\]\]](#) Disable/restrict the WinRM Service to help prevent uses of PowerShell for remote execution.

## Input Prompt Mitigation

Users need to be trained to know which programs ask for permission and why. Follow mitigation recommendations for [\[\[Technique/T1155 | AppleScript\]\]](#).

## System Information Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information about the operating system and underlying hardware, and audit and/or block them by using whitelisting [\[\[CiteRef::Beechey 2010\]\]](#) tools, like AppLocker, [\[\[CiteRef::Windows Commands JPCERT\]\]](#) [\[\[CiteRef::NSA MS AppLocker\]\]](#) or Software Restriction Policies [\[\[CiteRef::Corio 2008\]\]](#) where appropriate. [\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

## Winlogon Helper DLL Mitigation

Upgrade the operating system to a newer version of Windows if using a version prior to Vista.

Limit the privileges of user accounts so that only authorized administrators can perform Winlogon helper changes.

Identify and block potentially malicious software that may be executed through the Winlogon helper process by using whitelisting [\[\[CiteRef::Beechey 2010\]\]](#) tools like AppLocker [\[\[CiteRef::Windows Commands JPCERT\]\]](#) [\[\[CiteRef::NSA MS AppLocker\]\]](#) that are capable of auditing and/or blocking unknown DLLs.

## Netsh Helper DLL Mitigation

Identify and block potentially malicious software that may persist in this manner by using whitelisting [\[\[CiteRef::Beechey 2010\]\]](#) tools capable of monitoring DLL loads by Windows utilities like AppLocker. [\[\[CiteRef::Windows Commands JPCERT\]\]](#) [\[\[CiteRef::NSA MS AppLocker\]\]](#)

## Network Share Connection Removal Mitigation

Follow best practices for mitigation of activity related to establishing [[Technique/T1077|Windows Admin Shares]].

Identify unnecessary system utilities or potentially malicious software that may be used to leverage network shares, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Connection Proxy Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific C2 protocol used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool C2 signatures over time or construct protocols in such a way as to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Hidden Files and Directories Mitigation

Mitigation of this technique may be difficult and unadvised due to the the legitimate use of hidden files and directories.

## Office Application Startup Mitigation

Follow Office macro security best practices suitable for your environment. Disable Office VBA macros from executing. Even setting to disable with notification could enable unsuspecting users to execute potentially malicious macros. [[CiteRef::TechNet Office Macro Security]]

For the Office Test method, create the Registry key used to execute it and set the permissions to "Read Control" to prevent easy access to the key without administrator permissions or requiring [[Privilege Escalation]]. [[CiteRef::Palo Alto Office Test Sofacy]]

Disable Office add-ins. If they are required, follow best practices for securing them by requiring them to be signed and disabling user notification for allowing add-ins. For some add-ins types (WLL, VBA) additional mitigation is likely required as disabling add-ins in the Office Trust Center does not disable WLL nor does it prevent VBA code from executing. [[CiteRef::MRWLabs Office Persistence Add-ins]]

## Bash History Mitigation

There are multiple methods of preventing a user's command history from being flushed to their .bash\_history file, including use of the following commands: `set +o history` and `set -o history` to start logging again; `unset HISTFILE` being added to a user's .bash\_rc file; and `ln -s /dev/null ~/.bash_history` to write commands to `/dev/null` instead.

## Application Window Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Private Keys Mitigation

Use strong passphrases for private keys to make cracking difficult. When possible, store keys on separate cryptographic hardware instead of on the local system. Ensure only authorized keys are allowed access to critical resources and audit access lists regularly. Ensure permissions are properly set on folders containing sensitive private keys to prevent unintended access. Use separate infrastructure for managing critical systems to prevent overlap of credentials and permissions on systems that could be used as vectors for lateral movement. Follow other best practices for mitigating access through use of [[Technique/T1078|Valid Accounts]].

## Source Mitigation

Due to potential legitimate uses of source commands, it's may be difficult to mitigate use of this technique.

## HISTCONTROL Mitigation

Prevent users from changing the `HISTCONTROL` environment variable[[CiteRef::Securing bash history]]. Also, make sure that the `HISTCONTROL` environment variable is set to “ignoredup” instead of “ignoreboth” or “ignorespace”.

## External Remote Services Mitigation

Limit access to remote services through centrally managed concentrators such as VPNs and other managed remote access systems. Deny direct remote access to internal systems through uses of network proxies, gateways, and firewalls as appropriate. Use strong two-factor or multi-factor authentication for remote service accounts to mitigate an adversary's ability to leverage stolen credentials, but be aware of [[Technique/T1111|Two-Factor Authentication Interception]] techniques for some two-factor authentication implementations.

## LC\_MAIN Hijacking Mitigation

Enforce valid digital signatures for signed code on all applications and only trust applications with signatures from trusted parties.

## Pass the Hash Mitigation

Monitor systems and domain logs for unusual credential logon activity. Prevent access to [[Technique/T1078|Valid Accounts]]. Apply patch KB2871997 to Windows 7 and higher systems to

limit the default access of accounts in the local administrator group. Limit credential overlap across systems to prevent the damage of credential compromise and reduce the adversary's ability to perform [\[\[Lateral Movement\]\]](#) between systems. Ensure that built-in and created local administrator accounts have complex, unique passwords. Do not allow a domain user to be in the local administrator group on multiple systems.

## Account Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information about system and domain accounts, and audit and/or block them by using whitelisting [\[\[CiteRef::Beechey 2010\]\]](#) tools, like AppLocker, [\[\[CiteRef::Windows Commands JPCERT\]\]](#) [\[\[CiteRef::NSA MS AppLocker\]\]](#) or Software Restriction Policies [\[\[CiteRef::Corio 2008\]\]](#) where appropriate. [\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

## Trap Mitigation

Due to potential legitimate uses of trap commands, it's may be difficult to mitigate use of this technique.

## Trusted Developer Utilities Mitigation

MSBuild.exe, dnx.exe, rcsi.exe, WinDbg.exe, and cdb.exe may not be necessary within a given environment and should be removed if not used.

Use application whitelisting configured to block execution of MSBuild.exe, dnx.exe, rcsi.exe, WinDbg.exe, and cdb.exe if they are not required for a given system or network to prevent potential misuse by adversaries. [\[\[CiteRef::Microsoft GitHub Device Guard CI Policies\]\]](#) [\[\[CiteRef::Exploit Monday Mitigate Device Guard Bypasses\]\]](#) [\[\[CiteRef::GitHub mattifestation DeviceGuardBypass\]\]](#) [\[\[CiteRef::SubTee MSBuild\]\]](#)

## Pass the Ticket Mitigation

Monitor domains for unusual credential logons. Limit credential overlap across systems to prevent the damage of credential compromise. Ensure that local administrator accounts have complex, unique passwords. Do not allow a user to be a local administrator for multiple systems. Limit domain admin account permissions to domain controllers and limited servers. Delegate other admin functions to separate accounts. [\[\[CiteRef::ADSecurity AD Kerberos Attacks\]\]](#)

For containing the impact of a previously generated golden ticket, reset the built-in KRBTGT account password twice, which will invalidate any existing golden tickets that have been created with the KRBTGT hash and other Kerberos tickets derived from it. [\[\[CiteRef::CERT-EU Golden Ticket Protection\]\]](#)

Attempt to identify and block unknown or malicious software that could be used to obtain Kerberos tickets and use them to authenticate by using whitelisting [\[\[CiteRef::Beechey 2010\]\]](#) tools, like AppLocker, [\[\[CiteRef::Windows Commands JPCERT\]\]](#) [\[\[CiteRef::NSA MS AppLocker\]\]](#) or Software Restriction Policies [\[\[CiteRef::Corio 2008\]\]](#) where appropriate. [\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

## System Owner/User Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information about system users, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Credential Dumping Mitigation

Monitor/harden access to LSASS and SAM table with tools that allow process whitelisting. Limit credential overlap across systems to prevent lateral movement opportunities using [[Technique/T1078|Valid Accounts]] if passwords and hashes are obtained. Ensure that local administrator accounts have complex, unique passwords across all systems on the network. Do not put user or admin domain accounts in the local administrator groups across systems unless they are tightly controlled, as this is often equivalent to having a local administrator account with the same password on all systems. On Windows 8.1 and Windows Server 2012 R2, enable Protected Process Light for LSA. [[CiteRef::Microsoft LSA]]

Identify and block potentially malicious software that may be used to dump credentials by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

With Windows 10, Microsoft implemented new protections called Credential Guard to protect the LSA secrets that can be used to obtain credentials through forms of credential dumping. It is not configured by default and has hardware and firmware system requirements. [[CiteRef::TechNet Credential Guard]] It also does not protect against all forms of credential dumping. [[CiteRef::GitHub SHB Credential Guard]]

## Regsvr32 Mitigation

Microsoft's Enhanced Mitigation Experience Toolkit (EMET) Attack Surface Reduction (ASR) feature can be used to block regsvr32.exe from being used to bypass whitelisting. [[CiteRef::Secure Host Baseline EMET]]

## Process Hollowing Mitigation

Mitigating specific API calls will likely have unintended side effects, such as preventing legitimate software from operating properly. Efforts should be focused on preventing adversary tools from running earlier in the chain of activity and on identifying subsequent malicious behavior.

Although process hollowing may be used to evade certain types of defenses, it is still good practice to identify potentially malicious software that may be used to perform adversarial actions, including process hollowing, and audit and/or block it by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet

## Sudo Mitigation

The sudoers file should be strictly edited such that passwords are always required and that users can't spawn risky processes as users with higher privilege. By requiring a password, even if an adversary can get terminal access, they must know the password to run anything in the sudoers file.

## Rc.common Mitigation

Limit privileges of user accounts so only authorized users can edit the rc.common file.

## Execution through API Mitigation

Mitigating specific API calls will likely have unintended side effects, such as preventing legitimate software from operating properly. Efforts should be focused on preventing adversary tools from running earlier in the chain of activity and on identifying subsequent malicious behavior. Audit and/or block potentially malicious software by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Taint Shared Content Mitigation

Protect shared folders by minimizing users who have write access. Use utilities that detect or mitigate common features used in exploitation, such as the Microsoft Enhanced Mitigation Experience Toolkit (EMET).

Identify potentially malicious software that may be used to taint content or may result from it and audit and/or block the unknown programs by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Redundant Access Mitigation

Identify and block potentially malicious software that may be used as a remote access tool, and audit and/or block it by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and will be different across various malware families and versions. Adversaries will likely change tool signatures over time or construct protocols in such a way as to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]



## Audio Capture Mitigation

Mitigating this technique specifically may be difficult as it requires fine-grained API control. Efforts should be focused on preventing unwanted or unknown code from executing on a system.

Identify and block potentially malicious software that may be used to record audio by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## New Service Mitigation

Limit privileges of user accounts and remediate [[Privilege Escalation]] vectors so only authorized administrators can create new services.

Identify and block unnecessary system utilities or potentially malicious software that may be used to create services by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Scripting Mitigation

Turn off unused features or restrict access to scripting engines such as VBScript or scriptable administration frameworks such as PowerShell.

## Rundll32 Mitigation

Microsoft's Enhanced Mitigation Experience Toolkit (EMET) Attack Surface Reduction (ASR) feature can be used to block methods of using rundll32.exe to bypass whitelisting. [[CiteRef::Secure Host Baseline EMET]]

## Fallback Channels Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific protocol used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool C2 signatures over time or construct protocols in such a way as to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Hidden Window Mitigation

Whitelist programs that are allowed to have this plist tag. All other programs should be considered suspicious.

## System Service Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information about services, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Indicator Removal on Host Mitigation

Automatically forward events to a log server or data repository to prevent conditions in which the adversary can locate and manipulate data on the local system. When possible, minimize time delay on event reporting to avoid prolonged storage on the local system. Protect generated event files that are stored locally with proper permissions and authentication. Obfuscate/encrypt event files locally and in transit to avoid giving feedback to an adversary.

## Service Registry Permissions Weakness Mitigation

Identify and block potentially malicious software that may be executed through service abuse by using whitelisting[[CiteRef::Beechey 2010]] tools like AppLocker[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] that are capable of auditing and/or blocking unknown programs.

## Timestomp Mitigation

Mitigation of timestomping specifically is likely difficult. Efforts should be focused on preventing potentially malicious software from running. Identify and block potentially malicious software that may contain functionality to perform timestomping by using whitelisting[[CiteRef::Beechey 2010]] tools like AppLocker[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## System Network Configuration Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information about a system's network configuration, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Execution through Module Load Mitigation

Directly mitigating module loads and API calls related to module loads will likely have unintended side effects, such as preventing legitimate software from operating properly. Efforts should be focused on preventing adversary tools from running earlier in the chain of activity and on identifying and correlated subsequent behavior to determine if it is the result of malicious activity.

## Shared Webroot Mitigation

Networks that allow for open development and testing of Web content and allow users to set up their own Web servers on the enterprise network may be particularly vulnerable if the systems and Web servers are not properly secured to limit privileged account use, unauthenticated network share access, and network/system isolation.

Ensure proper permissions on directories that are accessible through a Web server. Disallow remote access to the webroot or other directories used to serve Web content. Disable execution on directories within the webroot. Ensure that permissions of the Web server process are only what is required by not using built-in accounts; instead, create specific accounts to limit unnecessary access or permissions overlap across multiple systems.

## Scheduled Task Mitigation

Limit privileges of user accounts and remediate [\[\[Privilege Escalation\]\]](#) vectors so only authorized administrators can create scheduled tasks. Toolkits like the PowerSploit framework contain PowerUp modules that can be used to explore systems for permission weaknesses in scheduled tasks that could be used to escalate privileges.

Identify and block unnecessary system utilities or potentially malicious software that may be used to schedule tasks using whitelisting[\[\[CiteRef::Beechey 2010\]\]](#) tools, like AppLocker,[\[\[CiteRef::Windows Commands JPCERT\]\]](#)[\[\[CiteRef::NSA MS AppLocker\]\]](#) or Software Restriction Policies[\[\[CiteRef::Corio 2008\]\]](#) where appropriate.[\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

## Binary Padding Mitigation

Identify potentially malicious software that may be executed from a padded or otherwise obfuscated binary, and audit and/or block it by using whitelisting[\[\[CiteRef::Beechey 2010\]\]](#) tools, like AppLocker,[\[\[CiteRef::Windows Commands JPCERT\]\]](#)[\[\[CiteRef::NSA MS AppLocker\]\]](#) or Software Restriction Policies[\[\[CiteRef::Corio 2008\]\]](#) where appropriate.[\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

## Network Sniffing Mitigation

Ensure that all wireless traffic is encrypted appropriately. Use Kerberos, SSL, and multifactor authentication wherever possible. Monitor switches and network for span port usage, ARP/DNS poisoning, and router reconfiguration.

Identify and block potentially malicious software that may be used to sniff or analyze network traffic by using whitelisting[\[\[CiteRef::Beechey 2010\]\]](#) tools, like AppLocker,[\[\[CiteRef::Windows Commands JPCERT\]\]](#)[\[\[CiteRef::NSA MS AppLocker\]\]](#) or Software Restriction Policies[\[\[CiteRef::Corio 2008\]\]](#) where appropriate.[\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

## Data Encrypted Mitigation

Identify unnecessary system utilities, third-party tools, or potentially malicious software that may be used to encrypt files, and audit and/or block them by using whitelisting[\[\[CiteRef::Beechey 2010\]\]](#)

tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Standard Cryptographic Protocol Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Use of encryption protocols may make typical network-based C2 detection more difficult due to a reduced ability to signature the traffic. Prior knowledge of adversary C2 infrastructure may be useful for domain and IP address blocking, but will likely not be an effective long-term solution because adversaries can change infrastructure often. [[CiteRef::University of Birmingham C2]]

## Multilayer Encryption Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Use of encryption protocols may make typical network-based C2 detection more difficult due to a reduced ability to signature the traffic. Prior knowledge of adversary C2 infrastructure may be useful for domain and IP address blocking, but will likely not be an effective long-term solution because adversaries can change infrastructure often. [[CiteRef::University of Birmingham C2]]

## Masquerading Mitigation

When creating security rules, avoid exclusions based on file name or file path. Require signed binaries. Use file system access controls to protect folders such as C:\Windows\System32. Use tools that restrict program execution via whitelisting by attributes other than file name.

Identify potentially malicious software that may look like a legitimate program based on name and location, and audit and/or block it by using whitelisting[[CiteRef::Beechey 2010]] tools like AppLocker[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## File System Logical Offsets Mitigation

Identify potentially malicious software that may be used to access logical drives in this manner, and audit and/or block it by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Launch Agent Mitigation

Restrict user's abilities to create Launch Agents with group policy.

## Remote Services Mitigation

Limit the number of accounts that may use remote services. Use multifactor authentication where possible. Limit the permissions for accounts that are at higher risk of compromise; for example, configure SSH so users can only run specific programs. Prevent [\[\[Credential Access\]\]](#) techniques that may allow an adversary to acquire [\[\[Technique/T1078|Valid Accounts\]\]](#) that can be used by existing services.

## File Deletion Mitigation

Identify unnecessary system utilities, third-party tools, or potentially malicious software that may be used to delete files, and audit and/or block them by using whitelisting[\[\[CiteRef::Beechey 2010\]\]](#) tools like AppLocker[\[\[CiteRef::Windows Commands JPCERT\]\]](#)[\[\[CiteRef::NSA MS AppLocker\]\]](#) or Software Restriction Policies[\[\[CiteRef::Corio 2008\]\]](#) where appropriate.[\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

## Data Compressed Mitigation

Identify unnecessary system utilities, third-party tools, or potentially malicious software that may be used to compress files, and audit and/or block them by using whitelisting[\[\[CiteRef::Beechey 2010\]\]](#) tools, like AppLocker,[\[\[CiteRef::Windows Commands JPCERT\]\]](#)[\[\[CiteRef::NSA MS AppLocker\]\]](#) or Software Restriction Policies[\[\[CiteRef::Corio 2008\]\]](#) where appropriate.[\[\[CiteRef::TechNet Applocker vs SRP\]\]](#)

If network intrusion prevention or data loss prevention tools are set to block specific file types from leaving the network over unencrypted channels, then an adversary may move to an encrypted channel.

## LC\_LOAD\_DYLIB Addition Mitigation

Enforce that all binaries be signed by the correct Apple Developer IDs, and whitelist applications via known hashes. Binaries can also be baselined for what dynamic libraries they require, and if an app requires a new dynamic library that wasn't included as part of an update, it should be investigated.

## Authentication Package Mitigation

Windows 8.1, Windows Server 2012 R2, and later versions, may make LSA run as a Protected Process Light (PPL) by setting the Registry key `HKLM\SYSTEM\CurrentControlSet\Control\Lsa\RunAsPPL`, which requires all DLLs loaded by LSA to be signed by Microsoft.[\[\[CiteRef::Graeber 2014\]\]](#)[\[\[CiteRef::Microsoft Configure LSA\]\]](#)

## Startup Items Mitigation

Since StartupItems are deprecated, preventing all users from writing to the

`/Library/StartupItems` directory would prevent any startup items from getting registered. Similarly, appropriate permissions should be applied such that only specific users can edit the startup items so that they can't be leveraged for privilege escalation.

## Launch Daemon Mitigation

Limit privileges of user accounts and remediate Privilege Escalation vectors so only authorized administrators can create new Launch Daemons.

## Local Port Monitor Mitigation

Identify and block potentially malicious software that may persist in this manner by using whitelisting[[CiteRef::Beechey 2010]] tools capable of monitoring DLL loads by processes running under SYSTEM permissions.

## Accessibility Features Mitigation

To use this technique remotely, an adversary must use it in conjunction with RDP. Ensure that Network Level Authentication is enabled to force the remote desktop session to authenticate before the session is created and the login screen displayed. It is enabled by default on Windows Vista and later. [[CiteRef::TechNet RDP NLA]]

If possible, use a Remote Desktop Gateway to manage connections and security configuration of RDP within a network. [[CiteRef::TechNet RDP Gateway]]

Identify and block potentially malicious software that may be executed by an adversary with this technique by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Bootkit Mitigation

Ensure proper permissions are in place to help prevent adversary access to privileged accounts necessary to perform this action. Use Trusted Platform Module technology and a secure or trusted boot process to prevent system integrity from being compromised. [[CiteRef::TCG Trusted Platform Module]] [[CiteRef::TechNet Secure Boot Process]]

## Access Token Manipulation Mitigation

Access tokens are an integral part of the security system within Windows and cannot be turned off. However, an attacker must already have administrator level access on the local system to make full use of this technique; be sure to restrict users and accounts to the least privileges they require to do their job.

Any user can also spoof access tokens if they have legitimate credentials. Follow mitigation guidelines for preventing adversary use of [[Technique/T1078 | Valid Accounts]].

Also limit opportunities for adversaries to increase privileges by limiting [[Privilege Escalation]] opportunities.

## Valid Accounts Mitigation

Take measures to detect or prevent techniques such as [[Technique/T1003 | Credential Dumping]] or installation of keyloggers to acquire credentials through [[Technique/T1056 | Input Capture]]. Limit credential overlap across systems to prevent access if account credentials are obtained. Ensure that local administrator accounts have complex, unique passwords across all systems on the network. Do not put user or admin domain accounts in the local administrator groups across systems unless they are tightly controlled and use of accounts is segmented, as this is often equivalent to having a local administrator account with the same password on all systems. Follow best practices for design and administration of an enterprise network to limit privileged account use across administrative tiers. [[CiteRef::Microsoft Securing Privileged Access]]. Audit domain and local accounts as well as their permission levels routinely to look for situations that could allow an adversary to gain wide access by obtaining credentials of a privileged account. [[CiteRef::TechNet Credential Theft]] [[CiteRef::TechNet Least Privilege]]

## Disabling Security Tools Mitigation

Ensure proper process, registry, and file permissions are in place to prevent adversaries from disabling or interfering with security services.

## Query Registry Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information within the Registry, and audit and/or block them by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## System Firmware Mitigation

Prevent adversary access to privileged accounts or access necessary to perform this technique. Check the integrity of the existing BIOS or EFI to determine if it is vulnerable to modification. Patch the BIOS and EFI as necessary. Use Trusted Platform Module technology. [[CiteRef::TCG Trusted Platform Module]]

## Multiband Communication Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific protocol used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool C2 signatures over time or construct protocols in such a way as to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Remote System Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information on remotely available systems, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## File and Directory Discovery Mitigation

File system activity is a common part of an operating system, so it is unlikely that mitigation would be appropriate for this technique. It may still be beneficial to identify and block unnecessary system utilities or potentially malicious software by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## File System Permissions Weakness Mitigation

Use auditing tools capable of detecting file system permissions abuse opportunities on systems within an enterprise and correct them. Limit privileges of user accounts and groups so that only authorized administrators can interact with service changes and service binary target path locations. Toolkits like the PowerSploit framework contain PowerUp modules that can be used to explore systems for service file system permissions weaknesses.

Identify and block potentially malicious software that may be executed through abuse of file, directory, and service permissions by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] that are capable of auditing and/or blocking unknown programs. Deny execution from user directories such as file download directories and temp directories where able. [[CiteRef::Seclists Kanthak 7zip Installer]]

Turn off UAC's privilege elevation for standard users and installer detection for all users by modifying registry key  
<code>[HKEY\_LOCAL\_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System]</code>  
<code>to automatically deny elevation requests, add:  
<code>"ConsentPromptBehaviorUser"=dword:00000000</code>; to disable installer detection, add:  
<code>"EnableInstallerDetection"=dword:00000000</code>. [[CiteRef::Seclists Kanthak 7zip Installer]]

## Service Execution Mitigation

Ensure that permissions disallow services that run at a higher permissions level from being created or interacted with by a user with a lower permission level. Also ensure that high permission level service binaries cannot be replaced or modified by users with a lower permission level.

Identify unnecessary system utilities or potentially malicious software that may be used to interact with Windows services, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]]



tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Communication Through Removable Media Mitigation

Disable Autorun if it is unnecessary. [[CiteRef::Microsoft Disable Autorun]] Disallow or restrict removable media at an organizational policy level if they are not required for business operations. [[CiteRef::TechNet Removable Media Control]]

## Two-Factor Authentication Interception Mitigation

Remove smart cards when not in use. Protect devices and services used to transmit and receive out-of-band codes.

Identify and block potentially malicious software that may be used to intercept 2FA credentials on a system by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Plist Modification Mitigation

Prevent plist files from being modified by users by making them read-only.

## Application Shimming Mitigation

There currently aren't a lot of ways to mitigate application shimming. Disabling the Shim Engine isn't recommended because Windows depends on shimming for interoperability and software may become unstable or not work. Microsoft released an optional patch update - KB3045645 - that will remove the "auto-elevate" flag within the sdbinst.exe. This will prevent use of application shimming to bypass UAC.

Changing UAC settings to "Always Notify" will give the user more visibility when UAC elevation is requested, however, this option will not be popular among users due to the constant UAC interruptions.

## Standard Non-Application Layer Protocol Mitigation

Properly configure firewalls and proxies to limit outgoing traffic to only necessary ports and through proper network gateway systems.

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific obfuscation technique used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool C2 signatures over time or construct protocols in such a way as to avoid detection by common defensive

tools. [[CiteRef::University of Birmingham C2]]

## Data Transfer Size Limits Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary command and control infrastructure and malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific obfuscation technique used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool command and control signatures over time or construct protocols in such a way to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## AppInit DLLs Mitigation

Upgrade to Windows 8 or later and enable secure boot.

Identify and block potentially malicious software that may be executed through AppInit DLLs by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] that are capable of auditing and/or blocking unknown DLLs.

## InstallUtil Mitigation

InstallUtil may not be necessary within a given environment. Use application whitelisting configured to block execution of InstallUtil.exe if it is not required for a given system or network to prevent potential misuse by adversaries.

## Shortcut Modification Mitigation

Identify and block unknown, potentially malicious software that may be executed through shortcut modification by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Custom Command and Control Protocol Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific protocol used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool C2 signatures over time or construct protocols in such a way as to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Automated Exfiltration Mitigation

Identify unnecessary system utilities, scripts, or potentially malicious software that may be used to

transfer data outside of a network, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Change Default File Association Mitigation

Direct mitigation of this technique is not recommended since it is a legitimate function that can be performed by users for software preferences. Follow Microsoft's best practices for file associations. [[CiteRef::MSDN File Associations]]

Identify and block potentially malicious software that may be executed by this technique using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Peripheral Device Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information about peripheral devices, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Standard Application Layer Protocol Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and will be different across various malware families and versions. Adversaries will likely change tool signatures over time or construct protocols in such a way to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Cron Job Mitigation

Limit privileges of user accounts and remediate Privilege Escalation vectors so only authorized users can create scheduled tasks. Identify and block unnecessary system utilities or potentially malicious software that may be used to schedule tasks using whitelisting tools.

## Input Capture Mitigation

Identify and block potentially malicious software that may be used to acquire credentials or information from the user by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

In cases where this behavior is difficult to detect or mitigate, efforts can be made to lessen some of the impact that might result from an adversary acquiring credential information. It is also good

practice to follow mitigation recommendations for adversary use of [[Technique/T1078|Valid Accounts]].

## Launchctl Mitigation

Prevent users from installing their own launch agents or launch daemons and instead require them to be pushed out by group policy.

## Security Support Provider Mitigation

Windows 8.1, Windows Server 2012 R2, and later versions may make LSA run as a Protected Process Light (PPL) by setting the Registry key `HKLM\SYSTEM\CurrentControlSet\Control\Lsa\RunAsPPL`, which requires all SSP DLLs to be signed by Microsoft. [[CiteRef::Graeber 2014]] [[CiteRef::Microsoft Configure LSA]]

## Process Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information about processes, and audit and/or block them by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Deobfuscate/Decode Files or Information Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to deobfuscate or decode files or information, and audit and/or block them by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Replication Through Removable Media Mitigation

Disable Autorun if it is unnecessary. [[CiteRef::Microsoft Disable Autorun]] Disallow or restrict removable media at an organizational policy level if it is not required for business operations. [[CiteRef::TechNet Removable Media Control]]

Identify potentially malicious software that may be used to infect removable media or may result from tainted removable media, and audit and/or block it by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Scheduled Transfer Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic

for specific adversary command and control infrastructure and malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific obfuscation technique used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool command and control signatures over time or construct protocols in such a way to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Hypervisor Mitigation

Prevent adversary access to privileged accounts necessary to install a hypervisor.

## Automated Collection Mitigation

Encryption and off-system storage of sensitive information may be one way to mitigate collection of files, but may not stop an adversary from acquiring the information if an intrusion persists over a long period of time and the adversary is able to discover and access the data through other means. A keylogger installed on a system may be able to intercept passwords through [[Technique/T1056|Input Capture]] and be used to decrypt protected documents that an adversary may have collected. Strong passwords should be used to prevent offline cracking of encrypted documents through [[Technique/T1110|Brute Force]] techniques.

Identify unnecessary system utilities, third-party tools, or potentially malicious software that may be used to collect files and audit and/or block them by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Exfiltration Over Physical Medium Mitigation

Disable Autorun if it is unnecessary. [[CiteRef::Microsoft Disable Autorun]] Disallow or restrict removable media at an organizational policy level if they are not required for business operations. [[CiteRef::TechNet Removable Media Control]]

## Data Encoding Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific obfuscation technique used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool C2 signatures over time or construct protocols in such a way as to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## DLL Side-Loading Mitigation

Update software regularly. Install software in write-protected locations. Use the program

sxstrace.exe that is included with Windows along with manual inspection to check manifest files for side-loading vulnerabilities in software.

## Rootkit Mitigation

Identify potentially malicious software that may contain rootkit functionality, and audit and/or block it by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Network Share Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire network share information, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Modify Registry Mitigation

Identify and block unnecessary system utilities or potentially malicious software that may be used to modify the Registry by using whitelisting[[CiteRef::Beechey 2010]] tools like AppLocker[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## System Time Discovery Mitigation

Benign software uses legitimate processes to gather system time. Efforts should be focused on preventing unwanted or unknown code from executing on a system. Some common tools, such as net.exe, may be blocked by policy to prevent common ways of acquiring remote system time.

Identify unnecessary system utilities or potentially malicious software that may be used to acquire system time information, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## System Network Connections Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information about network connections, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Setuid and Setgid Mitigation

Applications with known vulnerabilities or known shell escapes should not have the setuid or setgid bits set to reduce potential damage if an application is compromised.

## Clear Command History Mitigation

**Preventing users from deleting or writing to certain files can stop adversaries from maliciously altering their `~/.bash_history` files. Additionally, making these environment variables readonly can make sure that the history is preserved** [[CiteRef Securing bash history]].

## Screen Capture Mitigation

Blocking software based on screen capture functionality may be difficult, and there may be legitimate software that performs those actions. Instead, identify potentially malicious software that may have functionality to acquire screen captures, and audit and/or block it by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Windows Admin Shares Mitigation

Do not reuse local administrator account passwords across systems. Ensure password complexity and uniqueness such that the passwords cannot be cracked or guessed. Deny remote use of local admin credentials to log into systems. Do not allow domain user accounts to be in the local Administrators group multiple systems.

Identify unnecessary system utilities or potentially malicious software that may be used to leverage SMB and the Windows admin shares, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Space after Filename Mitigation

Prevent files from having a trailing space after the extension.

## Modify Existing Service Mitigation

Use auditing tools capable of detecting privilege and service abuse opportunities on systems within an enterprise and correct them. Limit privileges of user accounts and groups so that only authorized administrators can interact with service changes and service configurations. Toolkits like the PowerSploit framework contain the PowerUp modules that can be used to explore systems for [[Privilege Escalation]] weaknesses.

Identify and block potentially malicious software that may be executed through service abuse by using whitelisting[[CiteRef::Beechey 2010]] tools like AppLocker[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] that are capable of auditing and/or blocking unknown programs.

## Third-party Software Mitigation

Evaluate the security of third-party software that could be used to deploy or execute programs. Ensure that access to management systems for deployment systems is limited, monitored, and secure. Have a strict approval policy for use of deployment systems.

Grant access to application deployment systems only to a limited number of authorized administrators. Ensure proper system and access isolation for critical network systems through use of firewalls, account privilege separation, group policy, and multifactor authentication. Verify that account credentials that may be used to access deployment systems are unique and not used throughout the enterprise network. Patch deployment systems regularly to prevent potential remote access through [[Technique/T1068|Exploitation of Vulnerability]].

If the application deployment system can be configured to deploy only signed binaries, then ensure that the trusted signing certificates are not co-located with the application deployment system and are instead located on a system that cannot be accessed remotely or to which remote access is tightly controlled.

## Video Capture Mitigation

Mitigating this technique specifically may be difficult as it requires fine-grained API control. Efforts should be focused on preventing unwanted or unknown code from executing on a system.

Identify and block potentially malicious software that may be used to capture video and images by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Install Root Certificate Mitigation

HTTP Public Key Pinning (HPKP) is one method to mitigate potential man-in-the-middle situations where an adversary uses a mis-issued or fraudulent certificate to intercept encrypted communications by enforcing use of an expected certificate. [[CiteRef::Wikipedia HPKP]]

## Brute Force Mitigation

Set account lockout policies after a certain number of failed login attempts to prevent passwords from being guessed. Use multifactor authentication. Follow best practices for mitigating access to [[Technique/T1078|Valid Accounts]]



## Email Collection Mitigation

Use of encryption provides an added layer of security to sensitive information sent over email. Encryption using public key cryptography requires the adversary to obtain the private certificate along with an encryption key to decrypt messages.

Use of two-factor authentication for public-facing webmail servers is also a recommended best practice to minimize the usefulness of user names and passwords to adversaries.

Identify unnecessary system utilities or potentially malicious software that may be used to collect email data files or access the corporate email server, and audit and/or block them by using whitelisting[[CiteRef::Beechey 2010]] tools, like AppLocker,[[CiteRef::Windows Commands JPCERT]][[CiteRef::NSA MS AppLocker]] or Software Restriction Policies[[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Exploitation of Vulnerability Mitigation

Update software regularly by employing patch management for internal enterprise endpoints and servers. Develop a robust cyber threat intelligence capability to determine what types and levels of threat may use software exploits and 0-days against a particular organization. Make it difficult for adversaries to advance their operation through exploitation of undiscovered or unpatched vulnerabilities by using sandboxing, virtualization, and exploit prevention tools such as the Microsoft Enhanced Mitigation Experience Toolkit. [[CiteRef::SRD EMET]]

## Remote File Copy Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware or unusual data transfer over known tools and protocols like FTP can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific obfuscation technique used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool C2 signatures over time or construct protocols in such a way as to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Exfiltration Over Alternative Protocol Mitigation

Follow best practices for network firewall configurations to allow only necessary ports and traffic to enter and exit the network. For example, if services like FTP are not required for sending information outside of a network, then block FTP-related ports at the network perimeter. Enforce proxies and use dedicated servers for services such as DNS and only allow those systems to communicate over respective ports/protocols, instead of all systems within a network. [[CiteRef::TechNet Firewall Design]] These actions will help reduce command and control and exfiltration path opportunities.

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary command and control infrastructure and malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may

be based on the specific obfuscation technique used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool command and control signatures over time or construct protocols in such a way to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Remote Desktop Protocol Mitigation

Disable the RDP service if it is unnecessary, remove unnecessary accounts and groups from Remote Desktop Users groups, and enable firewall rules to block RDP traffic between network security zones. Audit the Remote Desktop Users group membership regularly. Remove the local Administrators group from the list of groups allowed to log in through RDP. Limit remote user permissions if remote access is necessary. Use remote desktop gateways and multifactor authentication for remote logins. [[CiteRef::Berkley Secure]]

## Web Service Mitigation

Firewalls and Web proxies can be used to enforce external network communication policy. It may be difficult for an organization to block particular services because so many of them are commonly used during the course of business.

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific protocol or encoded commands used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool C2 signatures over time or construct protocols in such a way as to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Network Service Scanning Mitigation

Use network intrusion detection/prevention systems to detect and prevent remote service scans. Ensure that unnecessary ports and services are closed and proper network segmentation is followed to protect critical servers and devices.

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information about services running on remote systems, and audit and/or block them by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Keychain Mitigation

The password for the user's login keychain can be changed from the user's login password. This increases the complexity for an adversary because they need to know an additional password.

# Windows Management Instrumentation Event Subscription Mitigation

Disabling WMI services may cause system instability and should be evaluated to assess the impact to a network. By default, only administrators are allowed to connect remotely using WMI; restrict other users that are allowed to connect, or disallow all users from connecting remotely to WMI. Prevent credential overlap across systems of administrator and privileged accounts. [[CiteRef::FireEye WMI 2015]]

## Data from Local System Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to collect data from the local system, and audit and/or block them by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Custom Cryptographic Protocol Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Since the custom protocol used may not adhere to typical protocol standards, there may be opportunities to signature the traffic on a network level for detection. Signatures are often for unique indicators within protocols and may be based on the specific protocol used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool C2 signatures over time or construct protocols in such a way as to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Create Account Mitigation

Use and enforce multifactor authentication. Follow guidelines to prevent or limit adversary access to [[Technique/T1078|Valid Accounts]] that may be used to create privileged accounts within an environment.

Adversaries that create local accounts on systems may have limited access within a network if access levels are properly locked down. These accounts may only be needed for persistence on individual systems and their usefulness depends on the utility of the system they reside on.

Protect domain controllers by ensuring proper security configuration for critical servers. Configure access controls and firewalls to limit access to these systems. Do not allow domain administrator accounts to be used for day-to-day operations that may expose them to potential adversaries on unprivileged systems.

## Dylib Hijacking Mitigation

Prevent users from being able to write files to the search paths for applications - both in the folders

where applications are run from and the standard dylib folders. If users can't write to these directories, then they can't intercept the search path.

## Credentials in Files Mitigation

Establish an organizational policy that prohibits password storage in files. Ensure that developers and system administrators are aware of the risk associated with having plaintext passwords in software configuration files that may be left on endpoint systems or servers. Preemptively search for files containing passwords and remove when found. Restrict file shares to specific directories with access only to necessary users. Remove vulnerable Group Policy Preferences. [[CiteRef::Microsoft MS14-025]]

## Re-opened Applications Mitigation

Holding the Shift key while logging in prevents apps from opening automatically [[CiteRef::Re-Open windows on Mac]]. This feature can be disabled entirely with the following terminal command: `defaults write -g ApplePersistence -bool no`.

## Permission Groups Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information about groups and permissions, and audit and/or block them by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Logon Scripts Mitigation

Restrict write access to logon scripts to specific administrators. Prevent access to administrator accounts by mitigating [[Credential Access]] techniques and limiting account access and permissions of [[Technique/T1078 | Valid Accounts]].

Identify and block potentially malicious software that may be executed through logon script modification by using whitelisting [[CiteRef::Beechey 2010]] tools like AppLocker [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] that are capable of auditing and/or blocking unknown programs.

## Code Signing Mitigation

Process whitelisting and trusted publishers to verify authenticity of software can help prevent signed malicious or untrusted code from executing on a system. [[CiteRef::NSA MS AppLocker]] [[CiteRef::TechNet Trusted Publishers]] [[CiteRef::Securelist Digital Certificates]]

## Gatekeeper Bypass Mitigation

Other tools should be used to supplement Gatekeeper's functionality. Additionally, system settings

can prevent applications from running that haven't been downloaded through the Apple Store which can help mitigate some of these issues.

## Windows Remote Management Mitigation

Disable the WinRM service. If the service is necessary, lock down critical enclaves with separate WinRM infrastructure, accounts, and permissions. Follow WinRM best practices on configuration of authentication methods and use of host firewalls to restrict WinRM access to allow communication only to/from specific devices. [[CiteRef::NSA Spotting]]

## Web Shell Mitigation

Ensure that externally facing Web servers are patched regularly to prevent adversary access through [[Technique/T1068|Exploitation of Vulnerability]] to gain remote code access or through file inclusion weaknesses that may allow adversaries to upload files or scripts that are automatically served as Web pages.

Audit account and group permissions to ensure that accounts used to manage servers do not overlap with accounts and permissions of users in the internal network that could be acquired through [[Credential Access]] and used to log into the Web server and plant a Web shell or pivot from the Web server into the internal network. [[CiteRef::US-CERT Alert TA15-314A Web Shells]]

## Data Obfuscation Mitigation

Network intrusion detection and prevention systems that use network signatures to identify traffic for specific adversary malware can be used to mitigate activity at the network level. Signatures are often for unique indicators within protocols and may be based on the specific obfuscation technique used by a particular adversary or tool, and will likely be different across various malware families and versions. Adversaries will likely change tool C2 signatures over time or construct protocols in such a way as to avoid detection by common defensive tools. [[CiteRef::University of Birmingham C2]]

## Software Packing Mitigation

Ensure updated virus definitions. Create custom signatures for observed malware. Employ heuristic-based malware detection.

Identify and prevent execution of potentially malicious software that may have been packed by using whitelisting [[CiteRef::Beechey 2010]] tools like AppLocker [[CiteRef::Windows Commands JPCERT]] [[CiteRef::NSA MS AppLocker]] or Software Restriction Policies [[CiteRef::Corio 2008]] where appropriate. [[CiteRef::TechNet Applocker vs SRP]]

## Security Software Discovery Mitigation

Identify unnecessary system utilities or potentially malicious software that may be used to acquire information about local security software, and audit and/or block them by using whitelisting [[CiteRef::Beechey 2010]] tools, like AppLocker, [[CiteRef::Windows Commands

JPCERT]]][CiteRef::NSA MS AppLocker]] or Software Restriction Policies][CiteRef::Corio 2008]] where appropriate.][CiteRef::TechNet Applocker vs SRP]]

## intrusion Set

Name of ATT&CK Group.



intrusion Set is a cluster galaxy available in JSON format at [https://github.com/MISP/misp-galaxy/blob/master/clusters/intrusion\\_set.json](https://github.com/MISP/misp-galaxy/blob/master/clusters/intrusion_set.json)[**this location**] The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

MITRE

## Poseidon Group

Poseidon Group is a Portuguese-speaking threat group that has been active since at least 2005. The group has a history of using information exfiltrated from victims to blackmail victim companies into contracting the Poseidon Group as a security firm.][Citation: Kaspersky Poseidon Group]]

Poseidon Group is also known as:

- Poseidon Group

Table 665. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0033">https://attack.mitre.org/wiki/Group/G0033</a>
<a href="https://securelist.com/blog/research/73673/poseidon-group-a-targeted-attack-boutique-specializing-in-global-cyber-espionage/">https://securelist.com/blog/research/73673/poseidon-group-a-targeted-attack-boutique-specializing-in-global-cyber-espionage/</a>

## Group5

Group5 is a threat group with a suspected Iranian nexus, though this attribution is not definite. The group has targeted individuals connected to the Syrian opposition via spearphishing and watering holes, normally using Syrian and Iranian themes. Group5 has used two commonly available remote access tools (RATs), njRAT and NanoCore, as well as an Android RAT, DroidJack.][Citation: Citizen Lab Group5]]

Group5 is also known as:

- Group5

Table 666. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0043">https://attack.mitre.org/wiki/Group/G0043</a>
<a href="https://citizenlab.org/2016/08/group5-syria/">https://citizenlab.org/2016/08/group5-syria/</a>

# PittyTiger

PittyTiger is a threat group believed to operate out of China that uses multiple different types of malware to maintain command and control. [[Citation: Bizeul 2014]] [[Citation: Villeneuve 2014]]

PittyTiger is also known as:

- PittyTiger

Table 667. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0011">https://attack.mitre.org/wiki/Group/G0011</a>
<a href="https://www.fireeye.com/blog/threat-research/2014/07/spy-of-the-tiger.html">https://www.fireeye.com/blog/threat-research/2014/07/spy-of-the-tiger.html</a>
<a href="http://blog.cassidiancybersecurity.com/post/2014/07/The-Eye-of-the-Tiger2">http://blog.cassidiancybersecurity.com/post/2014/07/The-Eye-of-the-Tiger2</a>

# admin@338

admin@338 is a China-based cyber threat group. It has previously used newsworthy events as lures to deliver malware and has primarily targeted organizations involved in financial, economic, and trade policy, typically using publicly available RATs such as PoisonIvy, as well as some non-public backdoors. [[Citation: FireEye admin@338]]

admin@338 is also known as:

- admin@338

Table 668. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0018">https://attack.mitre.org/wiki/Group/G0018</a>
<a href="https://www.fireeye.com/blog/threat-research/2015/11/china-based-threat.html">https://www.fireeye.com/blog/threat-research/2015/11/china-based-threat.html</a>

# RTM

RTM is a cybercriminal group that has been active since at least 2015 and is primarily interested in users of remote banking systems in Russia and neighboring countries. The group uses a Trojan by the same name (RTM). [[Citation: ESET RTM Feb 2017]]

RTM is also known as:

- RTM

Table 669. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0048">https://attack.mitre.org/wiki/Group/G0048</a>
<a href="https://www.welivesecurity.com/wp-content/uploads/2017/02/Read-The-Manual.pdf">https://www.welivesecurity.com/wp-content/uploads/2017/02/Read-The-Manual.pdf</a>

# APT16

APT16 is a China-based threat group that has launched spearphishing campaigns targeting Japanese and Taiwanese organizations. [[Citation: FireEye EPS Awakens Part 2]]

APT16 is also known as:

- APT16

Table 670. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0023">https://attack.mitre.org/wiki/Group/G0023</a>
<a href="https://www.fireeye.com/blog/threat-research/2015/12/the-eps-awakens-part-two.html">https://www.fireeye.com/blog/threat-research/2015/12/the-eps-awakens-part-two.html</a>

# APT28

APT28 is a threat group that has been attributed to the Russian government. [[Citation: FireEye APT28]] [[Citation: SecureWorks TG-4127]] [[Citation: FireEye APT28 January 2017]] [[Citation: GRIZZLY STEPPE JAR]] This group reportedly compromised the Democratic National Committee in April 2016. [[Citation: CrowdStrike DNC June 2016]]

APT28 is also known as:

- APT28
- Sednit
- Sofacy
- Pawn Storm
- Fancy Bear
- STRONTIUM
- Tsar Team
- Threat Group-4127
- TG-4127

Table 671. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0007">https://attack.mitre.org/wiki/Group/G0007</a>
<a href="https://www.secureworks.com/research/threat-group-4127-targets-hillary-clinton-presidential-campaign">https://www.secureworks.com/research/threat-group-4127-targets-hillary-clinton-presidential-campaign</a>
<a href="https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf">https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-apt28.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-apt28.pdf</a>
<a href="https://www.crowdstrike.com/blog/bears-midst-intrusion-democratic-national-committee/">https://www.crowdstrike.com/blog/bears-midst-intrusion-democratic-national-committee/</a>



# Winnti Group

Winnti Group is a threat group with Chinese origins that has been active since at least 2010. The group has heavily targeted the gaming industry, but it has also expanded the scope of its targeting. Though both this group and Axiom use the malware Winnti, the two groups appear to be distinct based on differences in reporting on the groups' TTPs and targeting. [[Citation: Kaspersky Winnti April 2013]] [[Citation: Kaspersky Winnti June 2015]] [[Citation: Novetta Winnti April 2015]]

Winnti Group is also known as:

- Winnti Group
- Blackfly

Table 672. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0044">https://attack.mitre.org/wiki/Group/G0044</a>
<a href="https://kasperskycontenthub.com/wp-content/uploads/sites/43/vlpdfs/winnti-more-than-just-a-game-130410.pdf">https://kasperskycontenthub.com/wp-content/uploads/sites/43/vlpdfs/winnti-more-than-just-a-game-130410.pdf</a>
<a href="https://securelist.com/blog/incidents/70991/games-are-over/">https://securelist.com/blog/incidents/70991/games-are-over/</a>
<a href="http://www.novetta.com/wp-content/uploads/2015/04/novetta%20winntianalysis.pdf">http://www.novetta.com/wp-content/uploads/2015/04/novetta%20winntianalysis.pdf</a>

# Deep Panda

Deep Panda is a suspected Chinese threat group known to target many industries, including government, defense, financial, and telecommunications. Deep Panda also appears to be known as Black Vine based on the attribution of both group names to the Anthem intrusion. [[Citation: Symantec Black Vine]]

Deep Panda is also known as:

- Deep Panda
- Shell Crew
- WebMasters
- KungFu Kittens
- PinkPanther
- Black Vine

Table 673. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0009">https://attack.mitre.org/wiki/Group/G0009</a>
<a href="http://blog.crowdstrike.com/deep-thought-chinese-targeting-national-security-think-tanks/">http://blog.crowdstrike.com/deep-thought-chinese-targeting-national-security-think-tanks/</a>
<a href="http://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/the-black-vine-cyberespionage-group.pdf">http://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/the-black-vine-cyberespionage-group.pdf</a>

<https://www.threatconnect.com/the-anthem-hack-all-roads-lead-to-china/>

<https://www.emc.com/collateral/white-papers/h12756-wp-shell-crew.pdf>

## Molerats

Molerats is a politically-motivated threat group that has been operating since 2012. The group's victims have primarily been in the Middle East, Europe, and the United States. [[Citation: DustySky]] [[Citation: DustySky2]]

Molerats is also known as:

- Molerats
- Gaza cybergang
- Operation Molerats

Table 674. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0021">https://attack.mitre.org/wiki/Group/G0021</a>
<a href="http://www.clearskysec.com/wp-content/uploads/2016/06/Operation-DustySky2%20-6.2016%20TLP%20White.pdf">http://www.clearskysec.com/wp-content/uploads/2016/06/Operation-DustySky2%20-6.2016%20TLP%20White.pdf</a>

## Strider

Strider is a threat group that has been active since at least 2011 and has targeted victims in Russia, China, Sweden, Belgium, Iran, and Rwanda. [[Citation: Symantec Strider Blog]] [[Citation: Kaspersky ProjectSauron Blog]]

Strider is also known as:

- Strider
- ProjectSauron

Table 675. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0041">https://attack.mitre.org/wiki/Group/G0041</a>
<a href="https://securelist.com/analysis/publications/75533/faq-the-projectsauron-apt/">https://securelist.com/analysis/publications/75533/faq-the-projectsauron-apt/</a>
<a href="http://www.symantec.com/connect/blogs/strider-cyberespionage-group-turns-eye-sauron-targets">http://www.symantec.com/connect/blogs/strider-cyberespionage-group-turns-eye-sauron-targets</a>

## Sandworm Team

Sandworm Team is a cyber espionage group that has operated since approximately 2009 and has been attributed to Russia. [[Citation: iSIGHT Sandworm 2014]] This group is also known as Quedagh. [[Citation: F-Secure BlackEnergy 2014]]

Sandworm Team is also known as:

- Sandworm Team
- Quedagh

Table 676. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0034">https://attack.mitre.org/wiki/Group/G0034</a>
<a href="http://www.isightpartners.com/2014/10/cve-2014-4114/">http://www.isightpartners.com/2014/10/cve-2014-4114/</a>
<a href="https://www.f-secure.com/documents/996508/1030745/blackenergy%20whitepaper.pdf">https://www.f-secure.com/documents/996508/1030745/blackenergy%20whitepaper.pdf</a>

## FIN6

FIN6 is a cyber crime group that has stolen payment card data and sold it for profit on underground marketplaces. This group has aggressively targeted and compromised point of sale (PoS) systems in the hospitality and retail sectors. [[Citation: FireEye FIN6 April 2016]]

FIN6 is also known as:

- FIN6

Table 677. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0037">https://attack.mitre.org/wiki/Group/G0037</a>
<a href="https://www2.fireeye.com/rs/848-DID-242/images/rpt-fin6.pdf">https://www2.fireeye.com/rs/848-DID-242/images/rpt-fin6.pdf</a>

## Dust Storm

Dust Storm is a threat group that has targeted multiple industries in Japan, South Korea, the United States, Europe, and several Southeast Asian countries. [[Citation: Cylance Dust Storm]]

Dust Storm is also known as:

- Dust Storm

Table 678. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0031">https://attack.mitre.org/wiki/Group/G0031</a>
<a href="https://www.cylance.com/hubfs/2015%20cylance%20website/assets/operation-dust-storm/Op%20Dust%20Storm%20Report.pdf?t=1456259131512">https://www.cylance.com/hubfs/2015%20cylance%20website/assets/operation-dust-storm/Op%20Dust%20Storm%20Report.pdf?t=1456259131512</a>

## Cleaver

Cleaver is a threat group that has been attributed to Iranian actors and is responsible for activity tracked as Operation Cleaver. [[Citation: Cylance Cleaver]] Strong circumstantial evidence suggests

Cleaver is linked to Threat Group 2889 (TG-2889).[[Citation: Dell Threat Group 2889]]

Cleaver is also known as:

- Cleaver
- Threat Group 2889
- TG-2889

Table 679. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0003">https://attack.mitre.org/wiki/Group/G0003</a>
<a href="http://www.cylance.com/assets/Cleaver/Cylance%20Operation%20Cleaver%20Report.pdf">http://www.cylance.com/assets/Cleaver/Cylance%20Operation%20Cleaver%20Report.pdf</a>
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/suspected-iran-based-hacker-group-creates-network-of-fake-linkedin-profiles/">http://www.secureworks.com/cyber-threat-intelligence/threats/suspected-iran-based-hacker-group-creates-network-of-fake-linkedin-profiles/</a>

## APT12

APT12 is a threat group that has been attributed to China. [[Citation: Meyers Numbered Panda]] It is also known as DynCalc, IXESHE, and Numbered Panda. [[Citation: Moran 2014]] [[Citation: Meyers Numbered Panda]]

APT12 is also known as:

- APT12
- IXESHE
- DynCalc
- Numbered Panda

Table 680. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0005">https://attack.mitre.org/wiki/Group/G0005</a>
<a href="https://www.fireeye.com/blog/threat-research/2014/09/darwins-favorite-apt-group-2.html">https://www.fireeye.com/blog/threat-research/2014/09/darwins-favorite-apt-group-2.html</a>
<a href="http://www.crowdstrike.com/blog/whois-numbered-panda/">http://www.crowdstrike.com/blog/whois-numbered-panda/</a>

## Moafee

Moafee is a threat group that appears to operate from the Guandong Province of China. Due to overlapping TTPs, including similar custom tools, Moafee is thought to have a direct or indirect relationship with the threat group DragonOK. . [[Citation: Haq 2014]]

Moafee is also known as:

- Moafee

Table 681. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0002">https://attack.mitre.org/wiki/Group/G0002</a>
<a href="https://www.fireeye.com/blog/threat-research/2014/09/the-path-to-mass-producing-cyber-attacks.html">https://www.fireeye.com/blog/threat-research/2014/09/the-path-to-mass-producing-cyber-attacks.html</a>

## Threat Group-3390

is a Chinese threat group that has extensively used strategic Web compromises to target victims. [[Citation: Dell TG-3390]] The group has targeted organizations in the aerospace, government, defense, technology, energy, and manufacturing sectors. [[Citation: SecureWorks BRONZE UNION June 2017]]

Threat Group-3390 is also known as:

- Threat Group-3390
- TG-3390
- Emissary Panda
- BRONZE UNION

Table 682. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0027">https://attack.mitre.org/wiki/Group/G0027</a>
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/">http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/</a>
<a href="https://www.secureworks.com/research/bronze-union">https://www.secureworks.com/research/bronze-union</a>

## DragonOK

DragonOK is a threat group that has targeted Japanese organizations with phishing emails. Due to overlapping TTPs, including similar custom tools, DragonOK is thought to have a direct or indirect relationship with the threat group Moafee. [[Citation: Operation Quantum Entanglement]] [[Citation: Symbiotic APT Groups]] It is known to use a variety of malware, including Sysget/HelloBridge, PlugX, PoisonIvy, FormerFirstRat, NFlog, and NewCT. [[Citation: New DragonOK]]

DragonOK is also known as:

- DragonOK

Table 683. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0017">https://attack.mitre.org/wiki/Group/G0017</a>
<a href="http://researchcenter.paloaltonetworks.com/2015/04/unit-42-identifies-new-dragonok-backdoor-malware-deployed-against-japanese-targets/">http://researchcenter.paloaltonetworks.com/2015/04/unit-42-identifies-new-dragonok-backdoor-malware-deployed-against-japanese-targets/</a>

<https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/wp-operation-quantum-entanglement.pdf>

<https://dl.mandiant.com/EE/library/MIRcon2014/MIRcon%202014%20R&D%20Track%20Insight%20into%20Symbiotic%20APT.pdf>

## APT1

APT1 is a Chinese threat group that has been attributed to the 2nd Bureau of the People's Liberation Army (PLA) General Staff Department's (GSD) 3rd Department, commonly known by its Military Unit Cover Designator (MUCD) as Unit 61398. [[Citation: Mandiant APT1]]

APT1 is also known as:

- APT1
- Comment Crew
- Comment Group
- Comment Panda

Table 684. Table References

Links

<https://attack.mitre.org/wiki/Group/G0006>

<https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf>

## Taidoor

Taidoor is a threat group that has operated since at least 2009 and has primarily targeted the Taiwanese government. [[Citation: TrendMicro Taidoor]]

Taidoor is also known as:

- Taidoor

Table 685. Table References

Links

<https://attack.mitre.org/wiki/Group/G0015>

<http://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp%20the%20taidoor%20campaign.pdf>

## Night Dragon

Night Dragon is a threat group that has conducted activity originating primarily in China. [[Citation: McAfee Night Dragon]]

Night Dragon is also known as:

- Night Dragon

Table 686. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0014">https://attack.mitre.org/wiki/Group/G0014</a>
<a href="http://www.mcafee.com/us/resources/white-papers/wp-global-energy-cyberattacks-night-dragon.pdf">http://www.mcafee.com/us/resources/white-papers/wp-global-energy-cyberattacks-night-dragon.pdf</a>

## Naikon

Naikon is a threat group that has focused on targets around the South China Sea. Naikon shares some characteristics with APT30, the two groups do not appear to be exact matches. [[Citation: Baumgartner Golovkin Naikon 2015]]

Naikon is also known as:

- Naikon

Table 687. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0019">https://attack.mitre.org/wiki/Group/G0019</a>
<a href="http://cdn2.hubspot.net/hubfs/454298/Project%20CAMERASHY%20ThreatConnect%20Copyright%202015.pdf">http://cdn2.hubspot.net/hubfs/454298/Project%20CAMERASHY%20ThreatConnect%20Copyright%202015.pdf</a>
<a href="https://securelist.com/files/2015/05/TheNaikonAPT-MsnMM1.pdf">https://securelist.com/files/2015/05/TheNaikonAPT-MsnMM1.pdf</a>
<a href="https://securelist.com/analysis/publications/69953/the-naikon-apt/">https://securelist.com/analysis/publications/69953/the-naikon-apt/</a>

## Ke3chang

Ke3chang is a threat group attributed to actors operating out of China. [[Citation: Villeneuve et al 2014]]

Ke3chang is also known as:

- Ke3chang

Table 688. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0004">https://attack.mitre.org/wiki/Group/G0004</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/wp-operation-ke3chang.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/wp-operation-ke3chang.pdf</a>

## Patchwork

Patchwork is a threat group that was first observed in December 2015. While the group has not been definitively attributed, circumstantial evidence suggests the group may be a pro-Indian or

Indian entity. Much of the code used by this group was copied and pasted from online forums. [[Citation: Cymmetria Patchwork]] [[Citation: Symantec Patchwork]]

Patchwork is also known as:

- Patchwork
- Dropping Elephant
- Chinastrats

Table 689. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0040">https://attack.mitre.org/wiki/Group/G0040</a>
<a href="https://s3-us-west-2.amazonaws.com/cymmetria-blog/public/Unveiling%20Patchwork.pdf">https://s3-us-west-2.amazonaws.com/cymmetria-blog/public/Unveiling%20Patchwork.pdf</a>
<a href="http://www.symantec.com/connect/blogs/patchwork-cyberespionage-group-expands-targets-governments-wide-range-industries">http://www.symantec.com/connect/blogs/patchwork-cyberespionage-group-expands-targets-governments-wide-range-industries</a>

## APT30

APT30 is a threat group suspected to be associated with the Chinese government. Naikon shares some characteristics with APT30, the two groups do not appear to be exact matches. [[Citation: Baumgartner Golovkin Naikon 2015]]

APT30 is also known as:

- APT30

Table 690. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0013">https://attack.mitre.org/wiki/Group/G0013</a>
<a href="https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf">https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf</a>
<a href="https://securelist.com/analysis/publications/69953/the-naikon-apt/">https://securelist.com/analysis/publications/69953/the-naikon-apt/</a>

## MONSOON

MONSOON is the name of an espionage campaign that apparently started in December 2015 and was ongoing as of July 2016. It is believed that the actors behind MONSOON are the same actors behind Operation Hangover. While attribution is unclear, the campaign has targeted victims with military and political interests in the Indian Subcontinent. [[Citation: Forcepoint Monsoon]] Operation Hangover has been reported as being Indian in origin, and can be traced back to 2010. [[Citation: Operation Hangover May 2013]]

MONSOON is also known as:

- MONSOON
- Operation Hangover



Table 691. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0042">https://attack.mitre.org/wiki/Group/G0042</a>
<a href="https://www.forcepoint.com/sites/default/files/resources/files/forcepoint-security-labs-monsoon-analysis-report.pdf">https://www.forcepoint.com/sites/default/files/resources/files/forcepoint-security-labs-monsoon-analysis-report.pdf</a>
<a href="http://enterprise-manage.norman.c.bitbit.net/resources/files/Unveiling%20an%20Indian%20Cyberattack%20Infrastructure.pdf">http://enterprise-manage.norman.c.bitbit.net/resources/files/Unveiling%20an%20Indian%20Cyberattack%20Infrastructure.pdf</a>

## APT17

APT17 is a China-based threat group that has conducted network intrusions against U.S. government entities, the defense industry, law firms, information technology companies, mining companies, and non-government organizations. [[Citation: FireEye APT17]]

APT17 is also known as:

- APT17
- Deputy Dog

Table 692. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0025">https://attack.mitre.org/wiki/Group/G0025</a>
<a href="https://www2.fireeye.com/rs/fireeye/images/APT17%20Report.pdf">https://www2.fireeye.com/rs/fireeye/images/APT17%20Report.pdf</a>

## FIN7

FIN7 is a financially motivated threat group that has primarily targeted the retail and hospitality sectors, often using point-of-sale malware. It is sometimes referred to as Carbanak Group, but these appear to be two groups using the same Carbanak malware and are therefore tracked separately. [[Citation: FireEye FIN7 March 2017]] [[Citation: FireEye FIN7 April 2017]]

FIN7 is also known as:

- FIN7

Table 693. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0046">https://attack.mitre.org/wiki/Group/G0046</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/04/fin7-phishing-lnk.html">https://www.fireeye.com/blog/threat-research/2017/04/fin7-phishing-lnk.html</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/03/fin7%20spear%20phishing.html">https://www.fireeye.com/blog/threat-research/2017/03/fin7%20spear%20phishing.html</a>

# APT3

APT3 is a China-based threat group that researchers have attributed to China's Ministry of State Security. [[Citation: FireEye Clandestine Wolf]] [[Citation: Recorded Future APT3 May 2017]] This group is responsible for the campaigns known as Operation Clandestine Fox, Operation Clandestine Wolf, and Operation Double Tap. [[Citation: FireEye Clandestine Wolf]] [[Citation: FireEye Operation Double Tap]] As of June 2015, the group appears to have shifted from targeting primarily US victims to primarily political organizations in Hong Kong. [[Citation: Symantec Buckeye]]

APT3 is also known as:

- APT3
- Gothic Panda
- Pirpi
- UPS Team
- Buckeye
- Threat Group-0110
- TG-0110

Table 694. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0022">https://attack.mitre.org/wiki/Group/G0022</a>
<a href="http://www.symantec.com/connect/blogs/buckeye-cyberespionage-group-shifts-gaze-us-hong-kong">http://www.symantec.com/connect/blogs/buckeye-cyberespionage-group-shifts-gaze-us-hong-kong</a>
<a href="https://www.recordedfuture.com/chinese-mss-behind-apt3/">https://www.recordedfuture.com/chinese-mss-behind-apt3/</a>
<a href="https://www.fireeye.com/blog/threat-research/2014/11/operation%20doubletap.html">https://www.fireeye.com/blog/threat-research/2014/11/operation%20doubletap.html</a>
<a href="https://www.fireeye.com/blog/threat-research/2015/06/operation-clandestine-wolf-adobe-flash-zero-day.html">https://www.fireeye.com/blog/threat-research/2015/06/operation-clandestine-wolf-adobe-flash-zero-day.html</a>

# GCMAN

GCMAN is a threat group that focuses on targeting banks for the purpose of transferring money to e-currency services. [[Citation: Securelist GCMAN]]

GCMAN is also known as:

- GCMAN

Table 695. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0036">https://attack.mitre.org/wiki/Group/G0036</a>
<a href="https://securelist.com/blog/research/73638/apt-style-bank-robberies-increase-with-metel-gcman-and-carbanak-2-0-attacks/">https://securelist.com/blog/research/73638/apt-style-bank-robberies-increase-with-metel-gcman-and-carbanak-2-0-attacks/</a>

# Lazarus Group

Lazarus Group is a threat group that has been attributed to the North Korean government. Lazarus Group correlates to other reported campaigns, including Operation Flame, Operation 1Mission, Operation Troy, DarkSeoul, and Ten Days of Rain. [[Citation: Novetta Blockbuster]]

Lazarus Group is also known as:

- Lazarus Group
- HIDDEN COBRA
- Guardians of Peace

Table 696. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0032">https://attack.mitre.org/wiki/Group/G0032</a>
<a href="https://www.operationblockbuster.com/wp-content/uploads/2016/02/Operation-Blockbuster-Report.pdf">https://www.operationblockbuster.com/wp-content/uploads/2016/02/Operation-Blockbuster-Report.pdf</a>
<a href="https://www.us-cert.gov/ncas/alerts/TA17-164A">https://www.us-cert.gov/ncas/alerts/TA17-164A</a>

# Lotus Blossom

Lotus Blossom is threat group that has targeted government and military organizations in Southeast Asia. [[Citation: Lotus Blossom Jun 2015]] It is also known as Spring Dragon. [[Citation: Spring Dragon Jun 2015]]

Lotus Blossom is also known as:

- Lotus Blossom
- Spring Dragon

Table 697. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0030">https://attack.mitre.org/wiki/Group/G0030</a>
<a href="https://www.paloaltonetworks.com/resources/research/unit42-operation-lotus-blossom.html">https://www.paloaltonetworks.com/resources/research/unit42-operation-lotus-blossom.html</a>
<a href="https://securelist.com/blog/research/70726/the-spring-dragon-apt/">https://securelist.com/blog/research/70726/the-spring-dragon-apt/</a>

# Equation

Equation is a sophisticated threat group that employs multiple remote access tools. The group is known to use zero-day exploits and has developed the capability to overwrite the firmware of hard disk drives. [[Citation: Kaspersky Equation QA]]

Equation is also known as:

- Equation

Table 698. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0020">https://attack.mitre.org/wiki/Group/G0020</a>
<a href="https://securelist.com/files/2015/02/Equation%20group%20questions%20and%20answers.pdf">https://securelist.com/files/2015/02/Equation%20group%20questions%20and%20answers.pdf</a>

## Darkhotel

Darkhotel is a threat group that has been active since at least 2004. The group has conducted activity on hotel and business center Wi-Fi and physical connections as well as peer-to-peer and file sharing networks. The actors have also conducted spearphishing. [[Citation: Kaspersky Darkhotel]]

Darkhotel is also known as:

- Darkhotel

Table 699. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0012">https://attack.mitre.org/wiki/Group/G0012</a>
<a href="https://securelist.com/files/2014/11/darkhotel%20kl%2007.11.pdf">https://securelist.com/files/2014/11/darkhotel%20kl%2007.11.pdf</a>

## OilRig

OilRig is a threat group with suspected Iranian origins that has targeted Middle Eastern victims since at least 2015. [[Citation: Palo Alto OilRig April 2017]] [[Citation: ClearSky OilRig Jan 2017]] [[Citation: Palo Alto OilRig May 2016]] [[Citation: Palo Alto OilRig Oct 2016]]

OilRig is also known as:

- OilRig

Table 700. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0049">https://attack.mitre.org/wiki/Group/G0049</a>
<a href="http://researchcenter.paloaltonetworks.com/2016/10/unit42-oilrig-malware-campaign-updates-toolset-and-expands-targets/">http://researchcenter.paloaltonetworks.com/2016/10/unit42-oilrig-malware-campaign-updates-toolset-and-expands-targets/</a>
<a href="http://researchcenter.paloaltonetworks.com/2017/04/unit42-oilrig-actors-provide-glimpse-development-testing-efforts/">http://researchcenter.paloaltonetworks.com/2017/04/unit42-oilrig-actors-provide-glimpse-development-testing-efforts/</a>
<a href="http://www.clearskysec.com/oilrig/">http://www.clearskysec.com/oilrig/</a>
<a href="http://researchcenter.paloaltonetworks.com/2016/05/the-oilrig-campaign-attacks-on-saudi-arabian-organizations-deliver-helminth-backdoor/">http://researchcenter.paloaltonetworks.com/2016/05/the-oilrig-campaign-attacks-on-saudi-arabian-organizations-deliver-helminth-backdoor/</a>

## Dragonfly

Dragonfly is a cyber espionage group that has been active since at least 2011. They initially targeted

defense and aviation companies but shifted to focus on the energy sector in early 2013. They have also targeted companies related to industrial control systems. [[Citation: Symantec Dragonfly]]

Dragonfly is also known as:

- Dragonfly
- Energetic Bear

Table 701. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0035">https://attack.mitre.org/wiki/Group/G0035</a>
<a href="http://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/Dragonfly%20Threat%20Against%20Western%20Energy%20Suppliers.pdf">http://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/Dragonfly%20Threat%20Against%20Western%20Energy%20Suppliers.pdf</a>

## Suckfly

Suckfly is a China-based threat group that has been active since at least 2014. [[Citation: Symantec Suckfly March 2016]]

Suckfly is also known as:

- Suckfly

Table 702. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0039">https://attack.mitre.org/wiki/Group/G0039</a>
<a href="http://www.symantec.com/connect/blogs/suckfly-revealing-secret-life-your-code-signing-certificates">http://www.symantec.com/connect/blogs/suckfly-revealing-secret-life-your-code-signing-certificates</a>

## Stealth Falcon

Stealth Falcon is a threat group that has conducted targeted spyware attacks against Emirati journalists, activists, and dissidents since at least 2012. Circumstantial evidence suggests there could be a link between this group and the United Arab Emirates (UAE) government, but that has not been confirmed. [[Citation: Citizen Lab Stealth Falcon May 2016]]

Stealth Falcon is also known as:

- Stealth Falcon

Table 703. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0038">https://attack.mitre.org/wiki/Group/G0038</a>
<a href="https://citizenlab.org/2016/05/stealth-falcon/">https://citizenlab.org/2016/05/stealth-falcon/</a>

# Scarlet Mimic

Scarlet Mimic is a threat group that has targeted minority rights activists. This group has not been directly linked to a government source, but the group's motivations appear to overlap with those of the Chinese government. While there is some overlap between IP addresses used by Scarlet Mimic and Putter Panda, it has not been concluded that the groups are the same. [[Citation: Scarlet Mimic Jan 2016]]

Scarlet Mimic is also known as:

- Scarlet Mimic

Table 704. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0029">https://attack.mitre.org/wiki/Group/G0029</a>
<a href="http://researchcenter.paloaltonetworks.com/2016/01/scarlet-mimic-years-long-espionage-targets-minority-activists/">http://researchcenter.paloaltonetworks.com/2016/01/scarlet-mimic-years-long-espionage-targets-minority-activists/</a>

# Threat Group-1314

Threat Group-1314 is an unattributed threat group that has used compromised credentials to log into a victim's remote access infrastructure. [[Citation: Dell TG-1314]]

Threat Group-1314 is also known as:

- Threat Group-1314
- TG-1314

Table 705. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0028">https://attack.mitre.org/wiki/Group/G0028</a>
<a href="http://www.secureworks.com/resources/blog/living-off-the-land/">http://www.secureworks.com/resources/blog/living-off-the-land/</a>

# Turla

Turla is a threat group that has infected victims in over 45 countries, spanning a range of industries including government, embassies, military, education, research and pharmaceutical companies. [[Citation: Kaspersky Turla]]

Turla is also known as:

- Turla
- Waterbug

Table 706. Table References

Links
-------

<https://attack.mitre.org/wiki/Group/G0010>

<https://securelist.com/analysis/publications/65545/the-epic-turla-operation/>

## APT29

APT29 is threat group that has been attributed to the Russian government and has operated since at least 2008. [[Citation: F-Secure The Dukes]] [[Citation: GRIZZLY STEPPE JAR]] This group reportedly compromised the Democratic National Committee starting in the summer of 2015. [[Citation: CrowdStrike DNC June 2016]]

APT29 is also known as:

- APT29
- The Dukes
- Cozy Bear

Table 707. Table References

Links

<https://attack.mitre.org/wiki/Group/G0016>

<https://www.crowdstrike.com/blog/bears-midst-intrusion-democratic-national-committee/>

<https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf>

## FIN10

FIN10 is a financially motivated threat group that has targeted organizations in North America since at least 2013 through 2016. The group uses stolen data exfiltrated from victims to extort organizations. [[Citation: FireEye FIN10 June 2017]]

FIN10 is also known as:

- FIN10

Table 708. Table References

Links

<https://attack.mitre.org/wiki/Group/G0051>

<https://www2.fireeye.com/rs/848-DID-242/images/rpt-fin10.pdf>

## menuPass

menuPass is a threat group that appears to originate from China and has been active since approximately 2009. The group has targeted healthcare, defense, aerospace, and government sectors, and has targeted Japanese victims since at least 2014. In 2016 and 2017, the group targeted managed IT service providers, manufacturing and mining companies, and a university. [[Citation: Palo Alto menuPass Feb 2017]] [[Citation: CrowdStrike CrowdCast Oct 2013]] [[Citation: FireEye

Poison Ivy]]][Citation: PWC Cloud Hopper April 2017]]][Citation: FireEye APT10 April 2017]]

menuPass is also known as:

- menuPass
- Stone Panda
- APT10
- Red Apollo
- CVNX

Table 709. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0045">https://attack.mitre.org/wiki/Group/G0045</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/04/apt10%20menupass%20grou.html">https://www.fireeye.com/blog/threat-research/2017/04/apt10%20menupass%20grou.html</a>
<a href="https://www.pwc.co.uk/cyber-security/pdf/cloud-hopper-report-final-v4.pdf">https://www.pwc.co.uk/cyber-security/pdf/cloud-hopper-report-final-v4.pdf</a>
<a href="https://www.slideshare.net/CrowdStrike/crowd-casts-monthly-you-have-an-adversary-problem">https://www.slideshare.net/CrowdStrike/crowd-casts-monthly-you-have-an-adversary-problem</a>
<a href="http://researchcenter.paloaltonetworks.com/2017/02/unit42-menupass-returns-new-malware-new-attacks-japanese-academics-organizations/">http://researchcenter.paloaltonetworks.com/2017/02/unit42-menupass-returns-new-malware-new-attacks-japanese-academics-organizations/</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-poison-ivy.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-poison-ivy.pdf</a>

## Putter Panda

Putter Panda is a Chinese threat group that has been attributed to Unit 61486 of the 12th Bureau of the PLA's 3rd General Staff Department (GSD).[[Citation: CrowdStrike Putter Panda]]

Putter Panda is also known as:

- Putter Panda
- APT2
- MSUpdater

Table 710. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0024">https://attack.mitre.org/wiki/Group/G0024</a>
<a href="http://cdn0.vox-cdn.com/assets/4589853/crowdstrike-intelligence-report-putter-panda.original.pdf">http://cdn0.vox-cdn.com/assets/4589853/crowdstrike-intelligence-report-putter-panda.original.pdf</a>

## Axiom

Axiom is a cyber espionage group suspected to be associated with the Chinese government. Winni Group use the malware Winni, the two groups appear to be distinct based on differences in reporting on the groups' TTPs and targeting. [[Citation: Kaspersky Winni April 2013]] [[Citation: Kaspersky Winni June 2015]] [[Citation: Novetta Winni April 2015]]



Axiom is also known as:

- Axiom
- Group 72

Table 711. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0001">https://attack.mitre.org/wiki/Group/G0001</a>
<a href="https://kasperskycontenthub.com/wp-content/uploads/sites/43/vlpdfs/winnti-more-than-just-a-game-130410.pdf">https://kasperskycontenthub.com/wp-content/uploads/sites/43/vlpdfs/winnti-more-than-just-a-game-130410.pdf</a>
<a href="https://securelist.com/blog/incidents/70991/games-are-over/">https://securelist.com/blog/incidents/70991/games-are-over/</a>
<a href="http://www.novetta.com/wp-content/uploads/2014/11/Executive%20Summary-Final%201.pdf">http://www.novetta.com/wp-content/uploads/2014/11/Executive%20Summary-Final%201.pdf</a>
<a href="http://www.novetta.com/wp-content/uploads/2015/04/novetta%20winntianalysis.pdf">http://www.novetta.com/wp-content/uploads/2015/04/novetta%20winntianalysis.pdf</a>

## Carbanak

Carbanak is a threat group that mainly targets banks. It also refers to malware of the same name (Carbanak).[[Citation: Kaspersky Carbanak]]

Carbanak is also known as:

- Carbanak
- Anunak

Table 712. Table References

Links
<a href="https://attack.mitre.org/wiki/Group/G0008">https://attack.mitre.org/wiki/Group/G0008</a>
<a href="https://securelist.com/files/2015/02/Carbanak%20APT%20eng.pdf">https://securelist.com/files/2015/02/Carbanak%20APT%20eng.pdf</a>

## APT18

APT18 is a threat group that has operated since at least 2009 and has targeted a range of industries, including technology, manufacturing, human rights groups, government, and medical. [[Citation: Dell Lateral Movement]]

APT18 is also known as:

- APT18
- TG-0416
- Dynamite Panda
- Threat Group-0416

Table 713. Table References

Links
-------

<https://attack.mitre.org/wiki/Group/G0026>

<http://www.secureworks.com/resources/blog/where-you-at-indicators-of-lateral-movement-using-at-exe-on-windows-7-systems/>

## APT32

APT32 is a threat group that has been active since at least 2014. The group has targeted multiple private sector industries as well as with foreign governments, dissidents, and journalists. The group's operations are aligned with Vietnamese state interests. [[Citation: FireEye APT32 May 2017]]

APT32 is also known as:

- APT32
- OceanLotus Group

Table 714. Table References

Links

<https://attack.mitre.org/wiki/Group/G0050>

<https://www.fireeye.com/blog/threat-research/2017/05/cyber-espionage-apt32.html>

## Gamaredon Group

Gamaredon Group is a threat group that has been active since at least 2013 and has targeted individuals likely involved in the Ukrainian government. [[Citation: Palo Alto Gamaredon Feb 2017]]

Gamaredon Group is also known as:

- Gamaredon Group

Table 715. Table References

Links

<https://attack.mitre.org/wiki/Group/G0047>

<https://researchcenter.paloaltonetworks.com/2017/02/unit-42-title-gamaredon-group-toolset-evolution/>

## Malware

Name of ATT&CK software.



Malware is a cluster galaxy available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

MITRE

# OLDBAIT

OLDBAIT is a credential harvester used by APT28. [[Citation: FireEye APT28]] [[Citation: FireEye APT28 January 2017]]

Aliases: OLDBAIT, Sasfis

OLDBAIT is also known as:

- OLDBAIT
- Sasfis

Table 716. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0138">https://attack.mitre.org/wiki/Software/S0138</a>
<a href="https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf">https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-apt28.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-apt28.pdf</a>

# SOUNDBITE

SOUNDBITE is a signature backdoor used by APT32. [[Citation: FireEye APT32 May 2017]]

Table 717. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0157">https://attack.mitre.org/wiki/Software/S0157</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/05/cyber-espionage-apt32.html">https://www.fireeye.com/blog/threat-research/2017/05/cyber-espionage-apt32.html</a>

# CosmicDuke

CosmicDuke is malware that was used by APT29 from 2010 to 2015. [[Citation: F-Secure The Dukes]]

Aliases: CosmicDuke, TinyBaron, BotgenStudios, NemesisGemina

CosmicDuke is also known as:

- CosmicDuke
- TinyBaron
- BotgenStudios
- NemesisGemina

Table 718. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0050">https://attack.mitre.org/wiki/Software/S0050</a>
<a href="https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf">https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf</a>

# H1N1

H1N1 is a malware variant that has been distributed via a campaign using VBA macros to infect victims. Although it initially had only loader capabilities, it has evolved to include information-stealing functionality. [[Citation: Cisco H1N1 Part 1]]

Table 719. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0132">https://attack.mitre.org/wiki/Software/S0132</a>
<a href="http://blogs.cisco.com/security/h1n1-technical-analysis-reveals-new-capabilities">http://blogs.cisco.com/security/h1n1-technical-analysis-reveals-new-capabilities</a>

# SPACESHIP

SPACESHIP is malware developed by APT30 that allows propagation and exfiltration of data over removable devices. APT30 may use this capability to exfiltrate data across air-gaps. [[Citation: FireEye APT30]]

Table 720. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0035">https://attack.mitre.org/wiki/Software/S0035</a>
<a href="https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf">https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf</a>

# Hi-Zor

Hi-Zor is a remote access tool (RAT) that has characteristics similar to Sakula. It was used in a campaign named INOCNATION. [[Citation: Fidelis Hi-Zor]]

Table 721. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0087">https://attack.mitre.org/wiki/Software/S0087</a>
<a href="http://www.threatgeek.com/2016/01/introducing-hi-zor-rat.html">http://www.threatgeek.com/2016/01/introducing-hi-zor-rat.html</a>

# TEXTMATE

TEXTMATE is a second-stage PowerShell backdoor that is memory-resident. It was observed being used along with POWERSOURCE in February 2017. [[Citation: FireEye FIN7 March 2017]]

Aliases: TEXTMATE, DNSMessenger

TEXTMATE is also known as:

- TEXTMATE
- DNSMessenger

Table 722. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0146">https://attack.mitre.org/wiki/Software/S0146</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/03/fin7%20spear%20phishing.html">https://www.fireeye.com/blog/threat-research/2017/03/fin7%20spear%20phishing.html</a>

## Net Crawler

Net Crawler is an intranet worm capable of extracting credentials using credential dumpers and spreading to systems on a network over SMB by brute forcing accounts with recovered passwords and using PsExec to execute a copy of Net Crawler. [[Citation: Cylance Cleaver]]

Aliases: Net Crawler, NetC

Net Crawler is also known as:

- Net Crawler
- NetC

Table 723. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0056">https://attack.mitre.org/wiki/Software/S0056</a>
<a href="http://www.cylance.com/assets/Cleaver/Cylance%20Operation%20Cleaver%20Report.pdf">http://www.cylance.com/assets/Cleaver/Cylance%20Operation%20Cleaver%20Report.pdf</a>

## BlackEnergy

BlackEnergy is a malware toolkit that has been used by both criminal and APT actors. It dates back to at least 2007 and was originally designed to create botnets for use in conducting Distributed Denial of Service (DDoS) attacks, but its use has evolved to support various plug-ins. It is well known for being used during the confrontation between Georgia and Russia in 2008, as well as in targeting Ukrainian institutions. Variants include BlackEnergy 2 and BlackEnergy 3. [[Citation: F-Secure BlackEnergy 2014]]

Aliases: BlackEnergy, Black Energy

BlackEnergy is also known as:

- BlackEnergy
- Black Energy

Table 724. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0089">https://attack.mitre.org/wiki/Software/S0089</a>
<a href="https://www.f-secure.com/documents/996508/1030745/blackenergy%20whitepaper.pdf">https://www.f-secure.com/documents/996508/1030745/blackenergy%20whitepaper.pdf</a>

## Pisloader

Pisloader is a malware family that is notable due to its use of DNS as a C2 protocol as well as its use of anti-analysis tactics. It has been used by APT18 and is similar to another malware family, HTTPBrowser, that has been used by the group. [[Citation: Palo Alto DNS Requests]]

Table 725. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0124">https://attack.mitre.org/wiki/Software/S0124</a>
<a href="http://researchcenter.paloaltonetworks.com/2016/05/unit42-new-wekby-attacks-use-dns-requests-as-command-and-control-mechanism/">http://researchcenter.paloaltonetworks.com/2016/05/unit42-new-wekby-attacks-use-dns-requests-as-command-and-control-mechanism/</a>

## PHOREAL

PHOREAL is a signature backdoor used by APT32. [[Citation: FireEye APT32 May 2017]]

Table 726. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0158">https://attack.mitre.org/wiki/Software/S0158</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/05/cyber-espionage-apt32.html">https://www.fireeye.com/blog/threat-research/2017/05/cyber-espionage-apt32.html</a>

## Backdoor.Oldrea

Backdoor.Oldrea is a backdoor used by Dragonfly. It appears to be custom malware authored by the group or specifically for it. [[Citation: Symantec Dragonfly]]

Aliases: Backdoor.Oldrea, Havex

Backdoor.Oldrea is also known as:

- Backdoor.Oldrea
- Havex

Table 727. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0093">https://attack.mitre.org/wiki/Software/S0093</a>
<a href="http://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/Dragonfly%20Threat%20Against%20Western%20Energy%20Suppliers.pdf">http://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/Dragonfly%20Threat%20Against%20Western%20Energy%20Suppliers.pdf</a>

## ChChes

ChChes is a Trojan that appears to be used exclusively by menuPass. It was used to target Japanese organizations in 2016. Its lack of persistence methods suggests it may be intended as a first-stage tool. [[Citation: Palo Alto menuPass Feb 2017]] [[Citation: JPCERT ChChes Feb 2017]] [[Citation: PWC

Cloud Hopper Technical Annex April 2017]]

Aliases: ChChes, Scorpion, HAYMAKER

ChChes is also known as:

- ChChes
- Scorpion
- HAYMAKER

Table 728. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0144">https://attack.mitre.org/wiki/Software/S0144</a>
<a href="https://www.pwc.co.uk/cyber-security/pdf/cloud-hopper-annex-b-final.pdf">https://www.pwc.co.uk/cyber-security/pdf/cloud-hopper-annex-b-final.pdf</a>
<a href="http://researchcenter.paloaltonetworks.com/2017/02/unit42-menupass-returns-new-malware-new-attacks-japanese-academics-organizations/">http://researchcenter.paloaltonetworks.com/2017/02/unit42-menupass-returns-new-malware-new-attacks-japanese-academics-organizations/</a>
<a href="http://blog.jpccert.or.jp/2017/02/chches-malware—93d6.html">http://blog.jpccert.or.jp/2017/02/chches-malware—93d6.html</a>

## Hacking Team UEFI Rootkit

Hacking Team UEFI Rootkit is a rootkit developed by the company Hacking Team as a method of persistence for remote access software. [[Citation: TrendMicro Hacking Team UEFI]]

Table 729. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0047">https://attack.mitre.org/wiki/Software/S0047</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/hacking-team-uses-uefi-bios-rootkit-to-keep-rcs-9-agent-in-target-systems/">http://blog.trendmicro.com/trendlabs-security-intelligence/hacking-team-uses-uefi-bios-rootkit-to-keep-rcs-9-agent-in-target-systems/</a>

## HALFBAKED

HALFBAKED is a malware family consisting of multiple components intended to establish persistence in victim networks. [[Citation: FireEye FIN7 April 2017]]

Table 730. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0151">https://attack.mitre.org/wiki/Software/S0151</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/04/fin7-phishing-lnk.html">https://www.fireeye.com/blog/threat-research/2017/04/fin7-phishing-lnk.html</a>

## httpclient

httpclient is malware used by Putter Panda. It is a simple tool that provides a limited range of functionality, suggesting it is likely used as a second-stage or supplementary/backup tool. [[Citation: CrowdStrike Putter Panda]]

Table 731. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0068">https://attack.mitre.org/wiki/Software/S0068</a>
<a href="http://cdn0.vox-cdn.com/assets/4589853/crowdstrike-intelligence-report-putter-panda.original.pdf">http://cdn0.vox-cdn.com/assets/4589853/crowdstrike-intelligence-report-putter-panda.original.pdf</a>

## Downdelph

Downdelph is a first-stage downloader written in Delphi that has been used by APT28 in rare instances between 2013 and 2015. [[Citation: ESET Sednit Part 3]]

Aliases: Downdelph, Delphacy

Downdelph is also known as:

- Downdelph
- Delphacy

Table 732. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0134">https://attack.mitre.org/wiki/Software/S0134</a>
<a href="http://www.welivesecurity.com/wp-content/uploads/2016/10/eset-sednit-part3.pdf">http://www.welivesecurity.com/wp-content/uploads/2016/10/eset-sednit-part3.pdf</a>

## StreamEx

StreamEx is a malware family that has been used by Deep Panda since at least 2015. In 2016, it was distributed via legitimate compromised Korean websites. [[Citation: Cylance Shell Crew Feb 2017]]

Table 733. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0142">https://attack.mitre.org/wiki/Software/S0142</a>
<a href="https://www.cylance.com/shell-crew-variants-continue-to-fly-under-big-avs-radar">https://www.cylance.com/shell-crew-variants-continue-to-fly-under-big-avs-radar</a>

## Psylo

Psylo is a shellcode-based Trojan that has been used by Scarlet Mimic. It has similar characteristics as FakeM. [[Citation: Scarlet Mimic Jan 2016]]

Table 734. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0078">https://attack.mitre.org/wiki/Software/S0078</a>
<a href="http://researchcenter.paloaltonetworks.com/2016/01/scarlet-mimic-years-long-espionage-targets-minority-activists/">http://researchcenter.paloaltonetworks.com/2016/01/scarlet-mimic-years-long-espionage-targets-minority-activists/</a>



# HDoor

HDoor is malware that has been customized and used by the Naikon group. [[Citation: Baumgartner Naikon 2015]]

Aliases: HDoor, Custom HDoor

HDoor is also known as:

- HDoor
- Custom HDoor

Table 735. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0061">https://attack.mitre.org/wiki/Software/S0061</a>
<a href="https://securelist.com/files/2015/05/TheNaikonAPT-MsnMM1.pdf">https://securelist.com/files/2015/05/TheNaikonAPT-MsnMM1.pdf</a>

# Komplex

is a backdoor that has been used by APT28 on OS X and appears to be developed in a similar manner to XAgentOSX [[Citation: XAgentOSX]] [[Citation: Sofacy Komplex Trojan]].

Table 736. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0162">https://attack.mitre.org/wiki/Software/S0162</a>
<a href="https://researchcenter.paloaltonetworks.com/2017/02/unit42-xagentosx-sofacys-xagent-macos-tool/">https://researchcenter.paloaltonetworks.com/2017/02/unit42-xagentosx-sofacys-xagent-macos-tool/</a>
<a href="https://researchcenter.paloaltonetworks.com/2016/09/unit42-sofacys-komplex-os-x-trojan/">https://researchcenter.paloaltonetworks.com/2016/09/unit42-sofacys-komplex-os-x-trojan/</a>

# TinyZBot

TinyZBot is a bot written in C# that was developed by Cleaver. [[Citation: Cylance Cleaver]]

Table 737. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0004">https://attack.mitre.org/wiki/Software/S0004</a>
<a href="http://www.cylance.com/assets/Cleaver/Cylance%20Operation%20Cleaver%20Report.pdf">http://www.cylance.com/assets/Cleaver/Cylance%20Operation%20Cleaver%20Report.pdf</a>

# BACKSPACE

BACKSPACE is a backdoor used by APT30 that dates back to at least 2005. [[Citation: FireEye APT30]]

Aliases: BACKSPACE, Lecna

BACKSPACE is also known as:

- BACKSPACE
- Lecna

Table 738. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0031">https://attack.mitre.org/wiki/Software/S0031</a>
<a href="https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf">https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf</a>

## PinchDuke

PinchDuke is malware that was used by APT29 from 2008 to 2010. [[Citation: F-Secure The Dukes]]

Table 739. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0048">https://attack.mitre.org/wiki/Software/S0048</a>
<a href="https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf">https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf</a>

## CloudDuke

CloudDuke is malware that was used by APT29 in 2015. [[Citation: F-Secure The Dukes]] [[Citation: Securelist Minidionis July 2015]]

Aliases: CloudDuke, MiniDionis, CloudLook

CloudDuke is also known as:

- CloudDuke
- MiniDionis
- CloudLook

Table 740. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0054">https://attack.mitre.org/wiki/Software/S0054</a>
<a href="https://securelist.com/blog/research/71443/minidionis-one-more-apt-with-a-usage-of-cloud-drives/">https://securelist.com/blog/research/71443/minidionis-one-more-apt-with-a-usage-of-cloud-drives/</a>
<a href="https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf">https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf</a>

## WinMM

WinMM is a full-featured, simple backdoor used by Naikon. [[Citation: Baumgartner Naikon 2015]]

Table 741. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0059">https://attack.mitre.org/wiki/Software/S0059</a>

<https://securelist.com/files/2015/05/TheNaikonAPT-MsnMM1.pdf>

## MobileOrder

MobileOrder is a Trojan intended to compromise Android mobile devices. It has been used by Scarlet Mimic. [[Citation: Scarlet Mimic Jan 2016]]

Table 742. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0079">https://attack.mitre.org/wiki/Software/S0079</a>
<a href="http://researchcenter.paloaltonetworks.com/2016/01/scarlet-mimic-years-long-espionage-targets-minority-activists/">http://researchcenter.paloaltonetworks.com/2016/01/scarlet-mimic-years-long-espionage-targets-minority-activists/</a>

## Sys10

Sys10 is a backdoor that was used throughout 2013 by Naikon. [[Citation: Baumgartner Naikon 2015]]

Table 743. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0060">https://attack.mitre.org/wiki/Software/S0060</a>
<a href="https://securelist.com/files/2015/05/TheNaikonAPT-MsnMM1.pdf">https://securelist.com/files/2015/05/TheNaikonAPT-MsnMM1.pdf</a>

## Duqu

Duqu is a malware platform that uses a modular approach to extend functionality after deployment within a target network. [[Citation: Symantec W32.Duqu]]

Table 744. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0038">https://attack.mitre.org/wiki/Software/S0038</a>
<a href="https://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/w32%20duqu%20the%20precursor%20to%20the%20next%20stuxnet.pdf">https://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/w32%20duqu%20the%20precursor%20to%20the%20next%20stuxnet.pdf</a>

## FakeM

FakeM is a shellcode-based Windows backdoor that has been used by Scarlet Mimic. [[Citation: Scarlet Mimic Jan 2016]]

Table 745. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0076">https://attack.mitre.org/wiki/Software/S0076</a>

<http://researchcenter.paloaltonetworks.com/2016/01/scarlet-mimic-years-long-espionage-targets-minority-activists/>

## WINDSHIELD

WINDSHIELD is a signature backdoor used by APT32. [[Citation: FireEye APT32 May 2017]]

Table 746. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0155">https://attack.mitre.org/wiki/Software/S0155</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/05/cyber-espionage-apt32.html">https://www.fireeye.com/blog/threat-research/2017/05/cyber-espionage-apt32.html</a>

## SHIPSHAPE

SHIPSHAPE is malware developed by APT30 that allows propagation and exfiltration of data over removable devices. APT30 may use this capability to exfiltrate data across air-gaps. [[Citation: FireEye APT30]]

Table 747. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0028">https://attack.mitre.org/wiki/Software/S0028</a>
<a href="https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf">https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf</a>

## T9000

T9000 is a backdoor that is a newer variant of the T5000 malware family, also known as Plat1. Its primary function is to gather information about the victim. It has been used in multiple targeted attacks against U.S.-based organizations. [[Citation: FireEye admin@338 March 2014]] [[Citation: Palo Alto T9000 Feb 2016]]

Table 748. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0098">https://attack.mitre.org/wiki/Software/S0098</a>
<a href="http://researchcenter.paloaltonetworks.com/2016/02/t9000-advanced-modular-backdoor-uses-complex-anti-analysis-techniques/">http://researchcenter.paloaltonetworks.com/2016/02/t9000-advanced-modular-backdoor-uses-complex-anti-analysis-techniques/</a>
<a href="https://www.fireeye.com/blog/threat-research/2014/03/spear-phishing-the-news-cycle-apt-actors-leverage-interest-in-the-disappearance-of-malaysian-flight-mh-370.html">https://www.fireeye.com/blog/threat-research/2014/03/spear-phishing-the-news-cycle-apt-actors-leverage-interest-in-the-disappearance-of-malaysian-flight-mh-370.html</a>

## BS2005

BS2005 is malware that was used by Ke3chang in spearphishing campaigns since at least 2011. [[Citation: Villeneuve et al 2014]]

Table 749. Table References

## Links

<https://attack.mitre.org/wiki/Software/S0014>

<https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/wp-operation-ke3chang.pdf>

## WEBC2

WEBC2 is a backdoor used by APT1 to retrieve a Web page from a predetermined C2 server. [[Citation: Mandiant APT1 Appendix]]

Table 750. Table References

## Links

<https://attack.mitre.org/wiki/Software/S0109>

<https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report-appendix.zip>

## PlugX

PlugX is a remote access tool (RAT) that uses modular plugins. [[Citation: Lastline PlugX Analysis]] It has been used by multiple threat groups. [[Citation: FireEye Clandestine Fox Part 2]] [[Citation: New DragonOK]] [[Citation: Dell TG-3390]]

Aliases: PlugX, Sogu, Kaba

PlugX is also known as:

- PlugX
- Sogu
- Kaba

Table 751. Table References

## Links

<https://attack.mitre.org/wiki/Software/S0013>

<http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/>

<https://www.fireeye.com/blog/threat-research/2014/06/clandestine-fox-part-deux.html>

<http://labs.lastline.com/an-analysis-of-plugx>

<http://researchcenter.paloaltonetworks.com/2015/04/unit-42-identifies-new-dragonok-backdoor-malware-deployed-against-japanese-targets/>

## POSHSPY

POSHSPY is a backdoor that has been used by APT29 since at least 2015. It appears to be used as a secondary backdoor used if the actors lost access to their primary backdoors. [[Citation: FireEye

Table 752. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0150">https://attack.mitre.org/wiki/Software/S0150</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/03/dissecting%20one%20ofap.html">https://www.fireeye.com/blog/threat-research/2017/03/dissecting%20one%20ofap.html</a>

## Misdat

Misdat is a backdoor that was used by Dust Storm from 2010 to 2011. [[Citation: Cylance Dust Storm]]

Table 753. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0083">https://attack.mitre.org/wiki/Software/S0083</a>
<a href="https://www.cylance.com/hubfs/2015%20cylance%20website/assets/operation-dust-storm/Op%20Dust%20Storm%20Report.pdf?t=1456259131512">https://www.cylance.com/hubfs/2015%20cylance%20website/assets/operation-dust-storm/Op%20Dust%20Storm%20Report.pdf?t=1456259131512</a>

## Taidoor

Taidoor is malware that has been used since at least 2010, primarily to target Taiwanese government organizations. [[Citation: TrendMicro Taidoor]]

Table 754. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0011">https://attack.mitre.org/wiki/Software/S0011</a>
<a href="http://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp%20the%20taidoor%20campaign.pdf">http://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp%20the%20taidoor%20campaign.pdf</a>

## MoonWind

MoonWind is a remote access tool (RAT) that was used in 2016 to target organizations in Thailand. [[Citation: Palo Alto MoonWind March 2017]]

Table 755. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0149">https://attack.mitre.org/wiki/Software/S0149</a>
<a href="http://researchcenter.paloaltonetworks.com/2017/03/unit42-trochilus-rat-new-moonwind-rat-used-attack-thai-utility-organizations/">http://researchcenter.paloaltonetworks.com/2017/03/unit42-trochilus-rat-new-moonwind-rat-used-attack-thai-utility-organizations/</a>

## Crimson

Crimson is malware used as part of a campaign known as Operation Transparent Tribe that

targeted Indian diplomatic and military victims. [[Citation: Proofpoint Operation Transparent Tribe March 2016]]

Aliases: Crimson, MSIL/Crimson

Crimson is also known as:

- Crimson
- MSIL/Crimson

Table 756. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0115">https://attack.mitre.org/wiki/Software/S0115</a>
<a href="https://www.proofpoint.com/sites/default/files/proofpoint-operation-transparent-tribe-threat-insight-en.pdf">https://www.proofpoint.com/sites/default/files/proofpoint-operation-transparent-tribe-threat-insight-en.pdf</a>

## Rover

Rover is malware suspected of being used for espionage purposes. It was used in 2015 in a targeted email sent to an Indian Ambassador to Afghanistan. [[Citation: Palo Alto Rover]]

Table 757. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0090">https://attack.mitre.org/wiki/Software/S0090</a>
<a href="http://researchcenter.paloaltonetworks.com/2016/02/new-malware-rover-targets-indian-ambassador-to-afghanistan/">http://researchcenter.paloaltonetworks.com/2016/02/new-malware-rover-targets-indian-ambassador-to-afghanistan/</a>

## ZLib

ZLib is a full-featured backdoor that was used as a second-stage implant by Dust Storm from 2014 to 2015. It is malware and should not be confused with the compression library from which its name is derived. [[Citation: Cylance Dust Storm]]

Table 758. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0086">https://attack.mitre.org/wiki/Software/S0086</a>
<a href="https://www.cylance.com/hubfs/2015%20cylance%20website/assets/operation-dust-storm/Op%20Dust%20Storm%20Report.pdf?t=1456259131512">https://www.cylance.com/hubfs/2015%20cylance%20website/assets/operation-dust-storm/Op%20Dust%20Storm%20Report.pdf?t=1456259131512</a>

## PowerDuke

PowerDuke is a backdoor that was used by APT29 in 2016. It has primarily been delivered through Microsoft Word or Excel attachments containing malicious macros. [[Citation: Volexity PowerDuke November 2016]]

Table 759. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0139">https://attack.mitre.org/wiki/Software/S0139</a>
<a href="https://www.volexity.com/blog/2016/11/09/powerduke-post-election-spear-phishing-campaigns-targeting-think-tanks-and-ngos/">https://www.volexity.com/blog/2016/11/09/powerduke-post-election-spear-phishing-campaigns-targeting-think-tanks-and-ngos/</a>

## HTTPBrowser

HTTPBrowser is malware that has been used by several threat groups. [[Citation: ThreatStream Evasion Analysis]] [[Citation: Dell TG-3390]] It is believed to be of Chinese origin. [[Citation: ThreatConnect Anthem]]

Aliases: HTTPBrowser, Token Control, HttpDump

HTTPBrowser is also known as:

- HTTPBrowser
- Token Control
- HttpDump

Table 760. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0070">https://attack.mitre.org/wiki/Software/S0070</a>
<a href="https://www.threatstream.com/blog/evasive-maneuvers-the-wekby-group-attempts-to-evade-analysis-via-custom-rop">https://www.threatstream.com/blog/evasive-maneuvers-the-wekby-group-attempts-to-evade-analysis-via-custom-rop</a>
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/">http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/</a>
<a href="https://www.threatconnect.com/the-anthem-hack-all-roads-lead-to-china/">https://www.threatconnect.com/the-anthem-hack-all-roads-lead-to-china/</a>

## HAMMERTOSS

HAMMERTOSS is a backdoor that was used by APT29 in 2015. [[Citation: FireEye APT29]] [[Citation: F-Secure The Dukes]]

Aliases: HAMMERTOSS, HammerDuke, NetDuke

HAMMERTOSS is also known as:

- HAMMERTOSS
- HammerDuke
- NetDuke

Table 761. Table References

Links
-------



<https://attack.mitre.org/wiki/Software/S0037>

<https://www2.fireeye.com/rs/848-DID-242/images/rpt-apt29-hammertoss.pdf>

<https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf>

## PoisonIvy

PoisonIvy is a popular remote access tool (RAT) that has been used by many groups. [[Citation: FireEye Poison Ivy]]

Aliases: PoisonIvy, Poison Ivy

PoisonIvy is also known as:

- PoisonIvy
- Poison Ivy

Table 762. Table References

Links

<https://attack.mitre.org/wiki/Software/S0012>

<https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-poison-ivy.pdf>

## Carbanak

Carbanak is a remote backdoor used by a group of the same name (Carbanak). It is intended for espionage, data exfiltration, and providing remote access to infected machines. [[Citation: Kaspersky Carbanak]]

Aliases: Carbanak, Anunak

Carbanak is also known as:

- Carbanak
- Anunak

Table 763. Table References

Links

<https://attack.mitre.org/wiki/Software/S0030>

<https://securelist.com/files/2015/02/Carbanak%20APT%20eng.pdf>

## Ixeshe

Ixeshe is a malware family that has been used since 2009 to attack targets in East Asia. [[Citation: Moran 2013]]

Table 764. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0015">https://attack.mitre.org/wiki/Software/S0015</a>
<a href="https://www.fireeye.com/blog/threat-research/2013/08/survival-of-the-fittest-new-york-times-attackers-evolve-quickly.html">https://www.fireeye.com/blog/threat-research/2013/08/survival-of-the-fittest-new-york-times-attackers-evolve-quickly.html</a>

## BADNEWS

BADNEWS is malware that has been used by the actors responsible for the MONSOON campaign. Its name was given due to its use of RSS feeds, forums, and blogs for command and control. [[Citation: Forcepoint Monsoon]]

Table 765. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0128">https://attack.mitre.org/wiki/Software/S0128</a>
<a href="https://www.forcepoint.com/sites/default/files/resources/files/forcepoint-security-labs-monsoon-analysis-report.pdf">https://www.forcepoint.com/sites/default/files/resources/files/forcepoint-security-labs-monsoon-analysis-report.pdf</a>

## Flame

Flame is a sophisticated toolkit that has been used to collect information since at least 2010, largely targeting Middle East countries. [[Citation: Kaspersky Flame]]

Aliases: Flame, Flamer, sKyWIper

Flame is also known as:

- Flame
- Flamer
- sKyWIper

Table 766. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0143">https://attack.mitre.org/wiki/Software/S0143</a>
<a href="https://securelist.com/blog/incidents/34344/the-flame-questions-and-answers-51/">https://securelist.com/blog/incidents/34344/the-flame-questions-and-answers-51/</a>

## RIPTIDE

RIPTIDE is a proxy-aware backdoor used by APT12. [[Citation: Moran 2014]]

Table 767. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0003">https://attack.mitre.org/wiki/Software/S0003</a>

## CozyCar

CozyCar is malware that was used by APT29 from 2010 to 2015. It is a modular malware platform, and its backdoor component can be instructed to download and execute a variety of modules with different functionality. [[Citation: F-Secure The Dukes]]

Aliases: CozyCar, CozyDuke, CozyBear, Cozer, EuroAPT

CozyCar is also known as:

- CozyCar
- CozyDuke
- CozyBear
- Cozer
- EuroAPT

Table 768. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0046">https://attack.mitre.org/wiki/Software/S0046</a>
<a href="https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf">https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf</a>

## Mivast

Mivast is a backdoor that has been used by Deep Panda. It was reportedly used in the Anthem breach. [[Citation: Symantec Black Vine]]

Table 769. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0080">https://attack.mitre.org/wiki/Software/S0080</a>
<a href="http://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/the-black-vine-cyberespionage-group.pdf">http://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/the-black-vine-cyberespionage-group.pdf</a>

## Cherry Picker

Cherry Picker is a point of sale (PoS) memory scraper. [[Citation: Trustwave Cherry Picker]]

Table 770. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0107">https://attack.mitre.org/wiki/Software/S0107</a>
<a href="https://www.trustwave.com/Resources/SpiderLabs-Blog/Shining-the-Spotlight-on-Cherry-Picker-PoS-Malware/">https://www.trustwave.com/Resources/SpiderLabs-Blog/Shining-the-Spotlight-on-Cherry-Picker-PoS-Malware/</a>

# XTunnel

XTunnel a VPN-like network proxy tool that can relay traffic between a C2 server and a victim. It was first seen in May 2013 and reportedly used by APT28 during the compromise of the Democratic National Committee. [[Citation: CrowdStrike DNC June 2016]] [[Citation: Invincea XTunnel]] [[Citation: ESET Sednit Part 2]]

Aliases: XTunnel, X-Tunnel, XAPS

XTunnel is also known as:

- XTunnel
- X-Tunnel
- XAPS

Table 771. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0117">https://attack.mitre.org/wiki/Software/S0117</a>
<a href="http://www.welivesecurity.com/wp-content/uploads/2016/10/eset-sednit-part-2.pdf">http://www.welivesecurity.com/wp-content/uploads/2016/10/eset-sednit-part-2.pdf</a>
<a href="https://www.invincea.com/2016/07/tunnel-of-gov-dnc-hack-and-the-russian-xtunnel/">https://www.invincea.com/2016/07/tunnel-of-gov-dnc-hack-and-the-russian-xtunnel/</a>
<a href="https://www.crowdstrike.com/blog/bears-midst-intrusion-democratic-national-committee/">https://www.crowdstrike.com/blog/bears-midst-intrusion-democratic-national-committee/</a>

# GeminiDuke

GeminiDuke is malware that was used by APT29 from 2009 to 2012. [[Citation: F-Secure The Dukes]]

Table 772. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0049">https://attack.mitre.org/wiki/Software/S0049</a>
<a href="https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf">https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf</a>

# Sakula

Sakula is a remote access tool (RAT) that first surfaced in 2012 and was used in intrusions throughout 2015. [[Citation: Dell Sakula]]

Aliases: Sakula, Sakurel, VIPER

Sakula is also known as:

- Sakula
- Sakurel
- VIPER

Table 773. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0074">https://attack.mitre.org/wiki/Software/S0074</a>
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/sakula-malware-family/">http://www.secureworks.com/cyber-threat-intelligence/threats/sakula-malware-family/</a>

## Agent.btz

Agent.btz is a worm that primarily spreads itself via removable devices such as USB drives. It reportedly infected U.S. military networks in 2008. [[Citation: Securelist Agent.btz]]

*Table 774. Table References*

Links
<a href="https://attack.mitre.org/wiki/Software/S0092">https://attack.mitre.org/wiki/Software/S0092</a>
<a href="https://securelist.com/blog/virus-watch/58551/agent-btz-a-source-of-inspiration/">https://securelist.com/blog/virus-watch/58551/agent-btz-a-source-of-inspiration/</a>

## Prikormka

Prikormka is a malware family used in a campaign known as Operation Groundbait. It has predominantly been observed in Ukraine and was used as early as 2008. [[Citation: ESET Operation Groundbait]]

*Table 775. Table References*

Links
<a href="https://attack.mitre.org/wiki/Software/S0113">https://attack.mitre.org/wiki/Software/S0113</a>
<a href="http://www.welivesecurity.com/wp-content/uploads/2016/05/Operation-Groundbait.pdf">http://www.welivesecurity.com/wp-content/uploads/2016/05/Operation-Groundbait.pdf</a>

## NETEAGLE

NETEAGLE is a backdoor developed by APT30 with compile dates as early as 2008. It has two main variants known as “Scout” and “Norton.” [[Citation: FireEye APT30]]

*Table 776. Table References*

Links
<a href="https://attack.mitre.org/wiki/Software/S0034">https://attack.mitre.org/wiki/Software/S0034</a>
<a href="https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf">https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf</a>

## USBStealer

USBStealer is malware that has used by APT28 since at least 2005 to extract information from air-gapped networks. It does not have the capability to communicate over the Internet and has been used in conjunction with ADVSTORESHELL. [[Citation: ESET Sednit USBStealer 2014]] [[Citation: Kaspersky Sofacy]]

Aliases: USBStealer, USB Stealer, Win32/USBStealer

USBStealer is also known as:

- USBStealer
- USB Stealer
- Win32/USBStealer

Table 777. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0136">https://attack.mitre.org/wiki/Software/S0136</a>
<a href="http://www.welivesecurity.com/2014/11/11/sednit-espionage-group-attacking-air-gapped-networks/">http://www.welivesecurity.com/2014/11/11/sednit-espionage-group-attacking-air-gapped-networks/</a>
<a href="https://securelist.com/blog/research/72924/sofacy-apt-hits-high-profile-targets-with-updated-toolset/">https://securelist.com/blog/research/72924/sofacy-apt-hits-high-profile-targets-with-updated-toolset/</a>

## CALENDAR

CALENDAR is malware used by APT1 that mimics legitimate Gmail Calendar traffic. [[Citation: Mandiant APT1]]

Table 778. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0025">https://attack.mitre.org/wiki/Software/S0025</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf">https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf</a>

## XAgentOSX

is a trojan that has been used by APT28 on OS X and appears to be a port of their standard CHOPSTICK or XAgent trojan. [[Citation: XAgentOSX]]

Table 779. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0161">https://attack.mitre.org/wiki/Software/S0161</a>
<a href="https://researchcenter.paloaltonetworks.com/2017/02/unit42-xagentosx-sofacys-xagent-macos-tool/">https://researchcenter.paloaltonetworks.com/2017/02/unit42-xagentosx-sofacys-xagent-macos-tool/</a>

## Regin

Regin is a malware platform that has targeted victims in a range of industries, including telecom, government, and financial institutions. Some Regin timestamps date back to 2003. [[Citation: Kaspersky Regin]]

Table 780. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0019">https://attack.mitre.org/wiki/Software/S0019</a>

<https://securelist.com/files/2014/11/Kaspersky%20Lab%20whitepaper%20Regin%20platform%20eng.pdf>

## AutoIt

AutoIt is a backdoor that has been used by the actors responsible for the MONSOON campaign. The actors frequently used it in weaponized .pps files exploiting CVE-2014-6352. [[Citation: Forcepoint Monsoon]]

Table 781. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0129">https://attack.mitre.org/wiki/Software/S0129</a>
<a href="https://www.forcepoint.com/sites/default/files/resources/files/forcepoint-security-labs-monsoon-analysis-report.pdf">https://www.forcepoint.com/sites/default/files/resources/files/forcepoint-security-labs-monsoon-analysis-report.pdf</a>

## Pteranodon

Pteranodon is a custom backdoor used by Gamaredon Group. [[Citation: Palo Alto Gamaredon Feb 2017]]

Table 782. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0147">https://attack.mitre.org/wiki/Software/S0147</a>
<a href="https://researchcenter.paloaltonetworks.com/2017/02/unit-42-title-gamaredon-group-toolset-evolution/">https://researchcenter.paloaltonetworks.com/2017/02/unit-42-title-gamaredon-group-toolset-evolution/</a>

## RARSTONE

RARSTONE is malware used by the Naikon group that has some characteristics similar to PlugX. [[Citation: Aquino RARSTONE]]

Table 783. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0055">https://attack.mitre.org/wiki/Software/S0055</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/rarstone-found-in-targeted-attacks/">http://blog.trendmicro.com/trendlabs-security-intelligence/rarstone-found-in-targeted-attacks/</a>

## SHOTPUT

SHOTPUT is a custom backdoor used by APT3. [[Citation: FireEye Clandestine Wolf]]

Aliases: SHOTPUT, Backdoor.APT.CookieCutter, Pirpi

SHOTPUT is also known as:

- SHOTPUT

- Backdoor.APT.CookieCutter
- Pirpi

Table 784. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0063">https://attack.mitre.org/wiki/Software/S0063</a>
<a href="https://www.fireeye.com/blog/threat-research/2015/06/operation-clandestine-wolf-adobe-flash-zero-day.html">https://www.fireeye.com/blog/threat-research/2015/06/operation-clandestine-wolf-adobe-flash-zero-day.html</a>

## Trojan.Karagany

Trojan.Karagany is a backdoor primarily used for recon. The source code for it was leaked in 2010 and it is sold on underground forums. [[Citation: Symantec Dragonfly]]

Table 785. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0094">https://attack.mitre.org/wiki/Software/S0094</a>
<a href="http://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/Dragonfly%20Threat%20Against%20Western%20Energy%20Suppliers.pdf">http://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/Dragonfly%20Threat%20Against%20Western%20Energy%20Suppliers.pdf</a>

## Kasidet

Kasidet is a backdoor that has been dropped by using malicious VBA macros. [[Citation: Zscaler Kasidet]]

Table 786. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0088">https://attack.mitre.org/wiki/Software/S0088</a>
<a href="http://research.zscaler.com/2016/01/malicious-office-files-dropping-kasidet.html">http://research.zscaler.com/2016/01/malicious-office-files-dropping-kasidet.html</a>

## CHOPSTICK

CHOPSTICK is malware family of modular backdoors used by APT28. It has been used from at least November 2012 to August 2016 and is usually dropped on victims as second-stage malware, though it has been used as first-stage malware in several cases. [[Citation: FireEye APT28]] [[Citation: ESET Sednit Part 2]] [[Citation: FireEye APT28 January 2017]]

Aliases: CHOPSTICK, SPLM, Xagent, X-Agent, webhp

CHOPSTICK is also known as:

- CHOPSTICK
- SPLM
- Xagent



- X-Agent
- webhp

Table 787. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0023">https://attack.mitre.org/wiki/Software/S0023</a>
<a href="https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf">https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf</a>
<a href="http://www.welivesecurity.com/wp-content/uploads/2016/10/eset-sednit-part-2.pdf">http://www.welivesecurity.com/wp-content/uploads/2016/10/eset-sednit-part-2.pdf</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-apt28.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-apt28.pdf</a>

## MiniDuke

MiniDuke is malware that was used by APT29 from 2010 to 2015. The MiniDuke toolset consists of multiple downloader and backdoor components. The loader has been used with other MiniDuke components as well as in conjunction with CosmicDuke and PinchDuke. [[Citation: F-Secure The Dukes]]

Table 788. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0051">https://attack.mitre.org/wiki/Software/S0051</a>
<a href="https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf">https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf</a>

## BBSRAT

BBSRAT is malware with remote access tool functionality that has been used in targeted compromises. [[Citation: Palo Alto Networks BBSRAT]]

Table 789. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0127">https://attack.mitre.org/wiki/Software/S0127</a>
<a href="http://researchcenter.paloaltonetworks.com/2015/12/bbsrat-attacks-targeting-russian-organizations-linked-to-roaming-tiger/">http://researchcenter.paloaltonetworks.com/2015/12/bbsrat-attacks-targeting-russian-organizations-linked-to-roaming-tiger/</a>

## Elise

Elise is a custom backdoor Trojan that appears to be used exclusively by Lotus Blossom. It is part of a larger group of tools referred to as LStudio, ST Group, and APT0LSTU. [[Citation: Lotus Blossom Jun 2015]]

Aliases: Elise, BKDR\_ESILE, Page

Elise is also known as:

- Elise

- BKDR\_ESILE
- Page

Table 790. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0081">https://attack.mitre.org/wiki/Software/S0081</a>
<a href="https://www.paloaltonetworks.com/resources/research/unit42-operation-lotus-blossom.html">https://www.paloaltonetworks.com/resources/research/unit42-operation-lotus-blossom.html</a>

## BISCUIT

BISCUIT is a backdoor that has been used by APT1 since as early as 2007. [[Citation: Mandiant APT1]]

Table 791. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0017">https://attack.mitre.org/wiki/Software/S0017</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf">https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf</a>

## Uroburos

Uroburos is a rootkit used by Turla. [[Citation: Kaspersky Turla]]

Table 792. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0022">https://attack.mitre.org/wiki/Software/S0022</a>
<a href="https://securelist.com/analysis/publications/65545/the-epic-turla-operation/">https://securelist.com/analysis/publications/65545/the-epic-turla-operation/</a>

## POWERSOURCE

POWERSOURCE is a PowerShell backdoor that is a heavily obfuscated and modified version of the publicly available tool DNS\_TXT\_Pwnage. It was observed in February 2017 in spearphishing campaigns against personnel involved with United States Securities and Exchange Commission (SEC) filings at various organizations. The malware was delivered when macros were enabled by the victim and a VBS script was dropped. [[Citation: FireEye FIN7 March 2017]] [[Citation: Cisco DNSMessenger March 2017]]

Aliases: POWERSOURCE, DNSMessenger

POWERSOURCE is also known as:

- POWERSOURCE
- DNSMessenger

Table 793. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0145">https://attack.mitre.org/wiki/Software/S0145</a>
<a href="http://blog.talosintelligence.com/2017/03/dnsmessenger.html">http://blog.talosintelligence.com/2017/03/dnsmessenger.html</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/03/fin7%20spear%20phishing.html">https://www.fireeye.com/blog/threat-research/2017/03/fin7%20spear%20phishing.html</a>

## hcdLoader

hcdLoader is a remote access tool (RAT) that has been used by APT18. [[Citation: Dell Lateral Movement]]

Table 794. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0071">https://attack.mitre.org/wiki/Software/S0071</a>
<a href="http://www.secureworks.com/resources/blog/where-you-at-indicators-of-lateral-movement-using-at-exe-on-windows-7-systems/">http://www.secureworks.com/resources/blog/where-you-at-indicators-of-lateral-movement-using-at-exe-on-windows-7-systems/</a>

## Zeroaccess

Zeroaccess is a kernel-mode Rootkit that attempts to add victims to the ZeroAccess botnet, often for monetary gain. [[Citation: Sophos ZeroAccess]]

Aliases: Zeroaccess, Trojan.Zeroaccess

Zeroaccess is also known as:

- Zeroaccess
- Trojan.Zeroaccess

Table 795. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0027">https://attack.mitre.org/wiki/Software/S0027</a>
<a href="https://sophosnews.files.wordpress.com/2012/04/zeroaccess2.pdf">https://sophosnews.files.wordpress.com/2012/04/zeroaccess2.pdf</a>

## Skeleton Key

Skeleton Key is malware used to inject false credentials into domain controllers with the intent of creating a backdoor password. Skeleton Key is included as a module in Mimikatz.

Table 796. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0007">https://attack.mitre.org/wiki/Software/S0007</a>
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/skeleton-key-malware-analysis/">http://www.secureworks.com/cyber-threat-intelligence/threats/skeleton-key-malware-analysis/</a>

# Shamoon

Shamoon is malware that was first used by an Iranian group known as the "Cutting Sword of Justice" in 2012. The 2.0 version was seen in 2016 targeting Middle Eastern states. [[Citation: FireEye Shamoon Nov 2016]] [[Citation: Palo Alto Shamoon Nov 2016]]

Aliases: Shamoon, Disttrack

Shamoon is also known as:

- Shamoon
- Disttrack

Table 797. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0140">https://attack.mitre.org/wiki/Software/S0140</a>
<a href="https://www.fireeye.com/blog/threat-research/2016/11/fireeye%20respondsto.html">https://www.fireeye.com/blog/threat-research/2016/11/fireeye%20respondsto.html</a>
<a href="http://researchcenter.paloaltonetworks.com/2016/11/unit42-shamoon-2-return-disttrack-wiper/">http://researchcenter.paloaltonetworks.com/2016/11/unit42-shamoon-2-return-disttrack-wiper/</a>

# 4H RAT

4H RAT is malware that has been used by Putter Panda since at least 2007. [[Citation: CrowdStrike Putter Panda]]

Table 798. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0065">https://attack.mitre.org/wiki/Software/S0065</a>
<a href="http://cdn0.vox-cdn.com/assets/4589853/crowdstrike-intelligence-report-putter-panda.original.pdf">http://cdn0.vox-cdn.com/assets/4589853/crowdstrike-intelligence-report-putter-panda.original.pdf</a>

# BOOTRASH

BOOTRASH is a Bootkit that targets Windows operating systems. It has been used by threat actors that target the financial sector. [[Citation: MTrends 2016]]

Table 799. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0114">https://attack.mitre.org/wiki/Software/S0114</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/regional/fr%20FR/offers/pdfs/ig-mtrends-2016.pdf">https://www.fireeye.com/content/dam/fireeye-www/regional/fr%20FR/offers/pdfs/ig-mtrends-2016.pdf</a>

# China Chopper

China Chopper is a Threat Group-3390. [[Citation: Dell TG-3390]]

Table 800. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0020">https://attack.mitre.org/wiki/Software/S0020</a>
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/">http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/</a>
<a href="https://www.fireeye.com/blog/threat-research/2013/08/breaking-down-the-china-chopper-web-shell-part-i.html">https://www.fireeye.com/blog/threat-research/2013/08/breaking-down-the-china-chopper-web-shell-part-i.html</a>

## Wiper

Wiper is a family of destructive malware used in March 2013 during breaches of South Korean banks and media companies. [[Citation: Dell Wiper]]

Table 801. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0041">https://attack.mitre.org/wiki/Software/S0041</a>
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/wiper-malware-analysis-attacking-korean-financial-sector/">http://www.secureworks.com/cyber-threat-intelligence/threats/wiper-malware-analysis-attacking-korean-financial-sector/</a>

## Unknown Logger

Unknown Logger is a publicly released, free backdoor. Version 1.5 of the backdoor has been used by the actors responsible for the MONSOON campaign. [[Citation: Forcepoint Monsoon]]

Table 802. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0130">https://attack.mitre.org/wiki/Software/S0130</a>
<a href="https://www.forcepoint.com/sites/default/files/resources/files/forcepoint-security-labs-monsoon-analysis-report.pdf">https://www.forcepoint.com/sites/default/files/resources/files/forcepoint-security-labs-monsoon-analysis-report.pdf</a>

## gh0st

gh0st is a remote access tool (RAT). The source code is public and it has been used by many groups. [[Citation: FireEye Hacking Team]]

Table 803. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0032">https://attack.mitre.org/wiki/Software/S0032</a>
<a href="https://www.fireeye.com/blog/threat-research/2015/07/demonstrating%20hustle.html">https://www.fireeye.com/blog/threat-research/2015/07/demonstrating%20hustle.html</a>

## CORESHELL

CORESHELL is a downloader used by APT28. The older versions of this malware are known as

SOURFACE and newer versions as CORESHELL. It has also been referred to as Sofacy, though that term has been used widely to refer to both the group APT28 and malware families associated with the group. [[Citation: FireEye APT28]] [[Citation: FireEye APT28 January 2017]]

Aliases: CORESHELL, SOURFACE

CORESHELL is also known as:

- CORESHELL
- SOURFACE

Table 804. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0137">https://attack.mitre.org/wiki/Software/S0137</a>
<a href="https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf">https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-apt28.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-apt28.pdf</a>

## Remsec

Remsec is a modular backdoor that has been used by Strider and appears to have been designed primarily for espionage purposes. Many of its modules are written in Lua. [[Citation: Symantec Strider Blog]]

Aliases: Remsec, Backdoor.Remsec, ProjectSauron

Remsec is also known as:

- Remsec
- Backdoor.Remsec
- ProjectSauron

Table 805. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0125">https://attack.mitre.org/wiki/Software/S0125</a>
<a href="http://www.symantec.com/connect/blogs/strider-cyberespionage-group-turns-eye-sauron-targets">http://www.symantec.com/connect/blogs/strider-cyberespionage-group-turns-eye-sauron-targets</a>

## FLASHFLOOD

FLASHFLOOD is malware developed by APT30 that allows propagation and exfiltration of data over removable devices. APT30 may use this capability to exfiltrate data across air-gaps. [[Citation: FireEye APT30]]

Table 806. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0036">https://attack.mitre.org/wiki/Software/S0036</a>

<https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf>

## TINYTYPHON

TINYTYPHON is a backdoor that has been used by the actors responsible for the MONSOON campaign. The majority of its code was reportedly taken from the MyDoom worm. [[Citation: Forcepoint Monsoon]]

Table 807. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0131">https://attack.mitre.org/wiki/Software/S0131</a>
<a href="https://www.forcepoint.com/sites/default/files/resources/files/forcepoint-security-labs-monsoon-analysis-report.pdf">https://www.forcepoint.com/sites/default/files/resources/files/forcepoint-security-labs-monsoon-analysis-report.pdf</a>

## SeaDuke

SeaDuke is malware that was used by APT29 from 2014 to 2015. It was used primarily as a secondary backdoor for victims that were already compromised with CozyCar. [[Citation: F-Secure The Dukes]]

Aliases: SeaDuke, SeaDaddy, SeaDesk

SeaDuke is also known as:

- SeaDuke
- SeaDaddy
- SeaDesk

Table 808. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0053">https://attack.mitre.org/wiki/Software/S0053</a>
<a href="https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf">https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf</a>

## Janicab

is an OS X trojan that relied on a valid developer ID and oblivious users to install it. [[Citation: Janicab]]

Table 809. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0163">https://attack.mitre.org/wiki/Software/S0163</a>
<a href="http://www.thesafemac.com/new-signed-malware-called-janicab/">http://www.thesafemac.com/new-signed-malware-called-janicab/</a>

# ADVSTORESHELL

ADVSTORESHELL is a spying backdoor that has been used by APT28 from at least 2012 to 2016. It is generally used for long-term espionage and is deployed on targets deemed interesting after a reconnaissance phase. [[Citation: Kaspersky Sofacy]] [[Citation: ESET Sednit Part 2]]

Aliases: ADVSTORESHELL, NETUI, EVILTOSS, AZZY, Sedreco

ADVSTORESHELL is also known as:

- ADVSTORESHELL
- NETUI
- EVILTOSS
- AZZY
- Sedreco

Table 810. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0045">https://attack.mitre.org/wiki/Software/S0045</a>
<a href="http://www.welivesecurity.com/wp-content/uploads/2016/10/eset-sednit-part-2.pdf">http://www.welivesecurity.com/wp-content/uploads/2016/10/eset-sednit-part-2.pdf</a>
<a href="https://securelist.com/blog/research/72924/sofacy-apt-hits-high-profile-targets-with-updated-toolset/">https://securelist.com/blog/research/72924/sofacy-apt-hits-high-profile-targets-with-updated-toolset/</a>

## S-Type

S-Type is a backdoor that was used by Dust Storm from 2013 to 2014. [[Citation: Cylance Dust Storm]]

Table 811. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0085">https://attack.mitre.org/wiki/Software/S0085</a>
<a href="https://www.cylance.com/hubfs/2015%20cylance%20website/assets/operation-dust-storm/Op%20Dust%20Storm%20Report.pdf?t=1456259131512">https://www.cylance.com/hubfs/2015%20cylance%20website/assets/operation-dust-storm/Op%20Dust%20Storm%20Report.pdf?t=1456259131512</a>

## NetTraveler

NetTraveler is malware that has been used in multiple cyber espionage campaigns for basic surveillance of victims. The earliest known samples have timestamps back to 2005, and the largest number of observed samples were created between 2010 and 2013. [[Citation: Kaspersky NetTraveler]]

Table 812. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0033">https://attack.mitre.org/wiki/Software/S0033</a>



## Dyre

Dyre is a Trojan that usually targets banking information. [[Citation: Raff 2015]]

Table 813. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0024">https://attack.mitre.org/wiki/Software/S0024</a>
<a href="http://www.seculert.com/blogs/new-dyre-version-yet-another-malware-evading-sandboxes">http://www.seculert.com/blogs/new-dyre-version-yet-another-malware-evading-sandboxes</a>

## P2P ZeuS

P2P ZeuS is a closed-source fork of the leaked version of the ZeuS botnet. It presents improvements over the leaked version, including a peer-to-peer architecture. [[Citation: Dell P2P ZeuS]]

Aliases: P2P ZeuS, Peer-to-Peer ZeuS, Gameover ZeuS

P2P ZeuS is also known as:

- P2P ZeuS
- Peer-to-Peer ZeuS
- Gameover ZeuS

Table 814. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0016">https://attack.mitre.org/wiki/Software/S0016</a>
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/The%20Lifecycle%20of%20Peer%20to%20Peer%20Gameover%20ZeuS/">http://www.secureworks.com/cyber-threat-intelligence/threats/The%20Lifecycle%20of%20Peer%20to%20Peer%20Gameover%20ZeuS/</a>

## ComRAT

ComRAT is a remote access tool suspected of being a decedent of Agent.btz and used by Turla. [[Citation: Symantec Waterbug]] [[Citation: NorthSec 2015 GData Uroburos Tools]]

Table 815. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0126">https://attack.mitre.org/wiki/Software/S0126</a>
<a href="http://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/waterbug-attack-group.pdf">http://www.symantec.com/content/en/us/enterprise/media/security%20response/whitepapers/waterbug-attack-group.pdf</a>
<a href="https://www.nsec.io/wp-content/uploads/2015/05/uroburos-actors-tools-1.1.pdf">https://www.nsec.io/wp-content/uploads/2015/05/uroburos-actors-tools-1.1.pdf</a>

# Winnti

Winnti is a Trojan that has been used by multiple groups to carry out intrusions in varied regions from at least 2010 to 2016. One of the groups using this malware is referred to by the same name, Winnti Group; however, reporting indicates a second distinct group, Axiom, also uses the malware. [[Citation: Kaspersky Winnti April 2013]] [[Citation: Microsoft Winnti Jan 2017]] [[Citation: Novetta Winnti April 2015]]

Table 816. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0141">https://attack.mitre.org/wiki/Software/S0141</a>
<a href="http://www.novetta.com/wp-content/uploads/2015/04/novetta%20winntianalysis.pdf">http://www.novetta.com/wp-content/uploads/2015/04/novetta%20winntianalysis.pdf</a>
<a href="https://kasperskycontenthub.com/wp-content/uploads/sites/43/vlpdfs/winnti-more-than-just-a-game-130410.pdf">https://kasperskycontenthub.com/wp-content/uploads/sites/43/vlpdfs/winnti-more-than-just-a-game-130410.pdf</a>
<a href="https://blogs.technet.microsoft.com/mmpc/2017/01/25/detecting-threat-actors-in-recent-german-industrial-attacks-with-windows-defender-atp/">https://blogs.technet.microsoft.com/mmpc/2017/01/25/detecting-threat-actors-in-recent-german-industrial-attacks-with-windows-defender-atp/</a>

# RedLeaves

RedLeaves is a malware family used by menuPass. The code overlaps with PlugX and may be based upon the open source tool Trochilus. [[Citation: PWC Cloud Hopper Technical Annex April 2017]] [[Citation: FireEye APT10 April 2017]]

Aliases: RedLeaves, BUGJUICE

RedLeaves is also known as:

- RedLeaves
- BUGJUICE

Table 817. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0153">https://attack.mitre.org/wiki/Software/S0153</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/04/apt10%20menupass%20grou.html">https://www.fireeye.com/blog/threat-research/2017/04/apt10%20menupass%20grou.html</a>
<a href="https://www.pwc.co.uk/cyber-security/pdf/cloud-hopper-annex-b-final.pdf">https://www.pwc.co.uk/cyber-security/pdf/cloud-hopper-annex-b-final.pdf</a>

# RTM

RTM is custom malware written in Delphi. It is used by the group of the same name (RTM). [[Citation: ESET RTM Feb 2017]]

Table 818. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0148">https://attack.mitre.org/wiki/Software/S0148</a>

## CallMe

CallMe is a Trojan designed to run on Apple OSX. It is based on a publicly available tool called Tiny SHell. [[Citation: Scarlet Mimic Jan 2016]]

Table 819. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0077">https://attack.mitre.org/wiki/Software/S0077</a>
<a href="http://researchcenter.paloaltonetworks.com/2016/01/scarlet-mimic-years-long-espionage-targets-minority-activists/">http://researchcenter.paloaltonetworks.com/2016/01/scarlet-mimic-years-long-espionage-targets-minority-activists/</a>

## HIDEDRV

HIDEDRV is a rootkit used by APT28. It has been deployed along with Downdelph to execute and hide that malware. [[Citation: ESET Sednit Part 3]] [[Citation: Sekoia HideDRV Oct 2016]]

Table 820. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0135">https://attack.mitre.org/wiki/Software/S0135</a>
<a href="http://www.welivesecurity.com/wp-content/uploads/2016/10/eset-sednit-part3.pdf">http://www.welivesecurity.com/wp-content/uploads/2016/10/eset-sednit-part3.pdf</a>
<a href="http://www.sekoia.fr/blog/wp-content/uploads/2016/10/Rootkit-analysis-Use-case-on-HIDEDRV-v1.6.pdf">http://www.sekoia.fr/blog/wp-content/uploads/2016/10/Rootkit-analysis-Use-case-on-HIDEDRV-v1.6.pdf</a>

## Mis-Type

Mis-Type is a backdoor hybrid that was used by Dust Storm in 2012. [[Citation: Cylance Dust Storm]]

Table 821. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0084">https://attack.mitre.org/wiki/Software/S0084</a>
<a href="https://www.cylance.com/hubfs/2015%20cylance%20website/assets/operation-dust-storm/Op%20Dust%20Storm%20Report.pdf?t=1456259131512">https://www.cylance.com/hubfs/2015%20cylance%20website/assets/operation-dust-storm/Op%20Dust%20Storm%20Report.pdf?t=1456259131512</a>

## Hikit

Hikit is malware that has been used by Axiom for late-stage and after the initial compromise. [[Citation: Axiom]]

Table 822. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0009">https://attack.mitre.org/wiki/Software/S0009</a>

## EvilGrab

EvilGrab is a malware family with common reconnaissance capabilities. It has been deployed by menuPass via malicious Microsoft Office documents as part of spearphishing campaigns. [[Citation: PWC Cloud Hopper Technical Annex April 2017]]

Table 823. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0152">https://attack.mitre.org/wiki/Software/S0152</a>
<a href="https://www.pwc.co.uk/cyber-security/pdf/cloud-hopper-annex-b-final.pdf">https://www.pwc.co.uk/cyber-security/pdf/cloud-hopper-annex-b-final.pdf</a>

## ASPXSpy

ASPXSpy is a Web shell. It has been modified by Threat Group-3390 actors to create the ASPXTool version. [[Citation: Dell TG-3390]]

Aliases: ASPXSpy, ASPXTool

ASPXSpy is also known as:

- ASPXSpy
- ASPXTool

Table 824. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0073">https://attack.mitre.org/wiki/Software/S0073</a>
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/">http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/</a>

## Sykipot

Sykipot is malware that has been used in spearphishing campaigns since approximately 2007 against victims primarily in the US. One variant of Sykipot hijacks smart cards on victims. [[Citation: Alienvault Sykipot DOD Smart Cards]] The group using this malware has also been referred to as Sykipot. [[Citation: Blasco 2013]]

Table 825. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0018">https://attack.mitre.org/wiki/Software/S0018</a>
<a href="http://www.alienvault.com/open-threat-exchange/blog/new-sykipot-developments">http://www.alienvault.com/open-threat-exchange/blog/new-sykipot-developments</a>
<a href="https://www.alienvault.com/open-threat-exchange/blog/sykipot-variant-hijacks-dod-and-windows-smart-cards">https://www.alienvault.com/open-threat-exchange/blog/sykipot-variant-hijacks-dod-and-windows-smart-cards</a>

# GLOOXMAIL

GLOOXMAIL is malware used by APT1 that mimics legitimate Jabber/XMPP traffic. [[Citation: Mandiant APT1]]

Aliases: GLOOXMAIL, Trojan.GTALK

GLOOXMAIL is also known as:

- GLOOXMAIL
- Trojan.GTALK

Table 826. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0026">https://attack.mitre.org/wiki/Software/S0026</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf">https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf</a>

# Emissary

Emissary is a Trojan that has been used by Lotus Blossom. It shares code with Elise, with both Trojans being part of a malware group referred to as LStudio. [[Citation: Lotus Blossom Dec 2015]]

Table 827. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0082">https://attack.mitre.org/wiki/Software/S0082</a>
<a href="http://researchcenter.paloaltonetworks.com/2015/12/attack-on-french-diplomat-linked-to-operation-lotus-blossom/">http://researchcenter.paloaltonetworks.com/2015/12/attack-on-french-diplomat-linked-to-operation-lotus-blossom/</a>

# Miner-C

Miner-C is malware that mines victims for the Monero cryptocurrency. It has targeted FTP servers and Network Attached Storage (NAS) devices to spread. [[Citation: Softpedia MinerC]]

Aliases: Miner-C, Mal/Miner-C, PhotoMiner

Miner-C is also known as:

- Miner-C
- Mal/Miner-C
- PhotoMiner

Table 828. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0133">https://attack.mitre.org/wiki/Software/S0133</a>

<http://news.softpedia.com/news/cryptocurrency-mining-malware-discovered-targeting-seagate-nas-hard-drives-508119.shtml>

## KOMPROGO

KOMPROGO is a signature backdoor used by APT32 that is capable of process, file, and registry management. [[Citation: FireEye APT32 May 2017]]

Table 829. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0156">https://attack.mitre.org/wiki/Software/S0156</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/05/cyber-espionage-apt32.html">https://www.fireeye.com/blog/threat-research/2017/05/cyber-espionage-apt32.html</a>

## DustySky

DustySky is multi-stage malware written in .NET that has been used by Molerats since May 2015. [[Citation: DustySky]] [[Citation: DustySky2]]

Aliases: DustySky, NeD Worm

DustySky is also known as:

- DustySky
- NeD Worm

Table 830. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0062">https://attack.mitre.org/wiki/Software/S0062</a>
<a href="http://www.clearskysec.com/wp-content/uploads/2016/06/Operation-DustySky2%20-6.2016%20TLP%20White.pdf">http://www.clearskysec.com/wp-content/uploads/2016/06/Operation-DustySky2%20-6.2016%20TLP%20White.pdf</a>

## BUBBLEWRAP

BUBBLEWRAP is a full-featured, second-stage backdoor used by the admin@338 group. It is set to run when the system boots and includes functionality to check, upload, and register plug-ins that can further enhance its capabilities. [[Citation: FireEye admin@338]]

Aliases: BUBBLEWRAP, Backdoor.APT.FakeWinHTTPHelper

BUBBLEWRAP is also known as:

- BUBBLEWRAP
- Backdoor.APT.FakeWinHTTPHelper

Table 831. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0043">https://attack.mitre.org/wiki/Software/S0043</a>
<a href="https://www.fireeye.com/blog/threat-research/2015/11/china-based-threat.html">https://www.fireeye.com/blog/threat-research/2015/11/china-based-threat.html</a>

## pngdowner

pngdowner is malware used by Putter Panda. It is a simple tool with limited functionality and no persistence mechanism, suggesting it is used only as a simple "download-and- execute" utility. [[Citation: CrowdStrike Putter Panda]]

Table 832. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0067">https://attack.mitre.org/wiki/Software/S0067</a>
<a href="http://cdn0.vox-cdn.com/assets/4589853/crowdstrike-intelligence-report-putter-panda.original.pdf">http://cdn0.vox-cdn.com/assets/4589853/crowdstrike-intelligence-report-putter-panda.original.pdf</a>

## SslMM

SslMM is a full-featured backdoor used by Naikon that has multiple variants. [[Citation: Baumgartner Naikon 2015]]

Table 833. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0058">https://attack.mitre.org/wiki/Software/S0058</a>
<a href="https://securelist.com/files/2015/05/TheNaikonAPT-MsnMM1.pdf">https://securelist.com/files/2015/05/TheNaikonAPT-MsnMM1.pdf</a>

## Nidiran

Nidiran is a custom backdoor developed and used by Suckfly. It has been delivered via strategic web compromise. [[Citation: Symantec Suckfly March 2016]]

Aliases: Nidiran, Backdoor.Nidiran

Nidiran is also known as:

- Nidiran
- Backdoor.Nidiran

Table 834. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0118">https://attack.mitre.org/wiki/Software/S0118</a>
<a href="http://www.symantec.com/connect/blogs/suckfly-revealing-secret-life-your-code-signing-certificates">http://www.symantec.com/connect/blogs/suckfly-revealing-secret-life-your-code-signing-certificates</a>

# Trojan.Mebromi

Trojan.Mebromi is BIOS-level malware that takes control of the victim before MBR. [[Citation: Ge 2011]]

Table 835. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0001">https://attack.mitre.org/wiki/Software/S0001</a>
<a href="http://www.symantec.com/connect/blogs/bios-threat-showing-again">http://www.symantec.com/connect/blogs/bios-threat-showing-again</a>

# OwaAuth

OwaAuth is a Web shell and credential stealer deployed to Microsoft Exchange servers that appears to be exclusively used by Threat Group-3390. [[Citation: Dell TG-3390]]

Table 836. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0072">https://attack.mitre.org/wiki/Software/S0072</a>
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/">http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/</a>

# ROCKBOOT

ROCKBOOT is a Bootkit that has been used by an unidentified, suspected China-based group. [[Citation: FireEye Bootkits]]

Table 837. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0112">https://attack.mitre.org/wiki/Software/S0112</a>
<a href="https://www.fireeye.com/blog/threat-research/2015/12/fin1-targets-boot-record.html">https://www.fireeye.com/blog/threat-research/2015/12/fin1-targets-boot-record.html</a>

# SNUGRIDE

SNUGRIDE is a backdoor that has been used by menuPass as first stage malware. [[Citation: FireEye APT10 April 2017]]

Table 838. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0159">https://attack.mitre.org/wiki/Software/S0159</a>
<a href="https://www.fireeye.com/blog/threat-research/2017/04/apt10%20menupass%20grou.html">https://www.fireeye.com/blog/threat-research/2017/04/apt10%20menupass%20grou.html</a>



# OnionDuke

OnionDuke is malware that was used by APT29 from 2013 to 2015. [[Citation: F-Secure The Dukes]]

Table 839. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0052">https://attack.mitre.org/wiki/Software/S0052</a>
<a href="https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf">https://www.f-secure.com/documents/996508/1030745/dukes%20whitepaper.pdf</a>

# LOWBALL

LOWBALL is malware used by admin@338. It was used in August 2015 in email messages targeting Hong Kong-based media organizations. [[Citation: FireEye admin@338]]

Table 840. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0042">https://attack.mitre.org/wiki/Software/S0042</a>
<a href="https://www.fireeye.com/blog/threat-research/2015/11/china-based-threat.html">https://www.fireeye.com/blog/threat-research/2015/11/china-based-threat.html</a>

# BLACKCOFFEE

BLACKCOFFEE is malware that has been used by APT17 since at least 2013. [[Citation: FireEye APT17]]

Table 841. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0069">https://attack.mitre.org/wiki/Software/S0069</a>
<a href="https://www2.fireeye.com/rs/fireeye/images/APT17%20Report.pdf">https://www2.fireeye.com/rs/fireeye/images/APT17%20Report.pdf</a>

# Derusbi

Derusbi is malware used by multiple Chinese APT groups. [[Citation: Axiom]] [[Citation: ThreatConnect Anthem]] Both Windows and Linux variants have been observed. [[Citation: Fidelis Turbo]]

Table 842. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0021">https://attack.mitre.org/wiki/Software/S0021</a>
<a href="https://www.fidelissecurity.com/sites/default/files/TA%20Fidelis%20Turbo%201602%2000.pdf">https://www.fidelissecurity.com/sites/default/files/TA%20Fidelis%20Turbo%201602%2000.pdf</a>
<a href="http://www.novetta.com/wp-content/uploads/2014/11/Executive%20Summary-Final%201.pdf">http://www.novetta.com/wp-content/uploads/2014/11/Executive%20Summary-Final%201.pdf</a>
<a href="https://www.threatconnect.com/the-anthem-hack-all-roads-lead-to-china/">https://www.threatconnect.com/the-anthem-hack-all-roads-lead-to-china/</a>

# Epic

Epic is a backdoor that has been used by Turla. [[Citation: Kaspersky Turla]]

Aliases: Epic, Tavdig, Wipbot, WorldCupSec, TadjMakhal

Epic is also known as:

- Epic
- Tavdig
- Wipbot
- WorldCupSec
- TadjMakhal

Table 843. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0091">https://attack.mitre.org/wiki/Software/S0091</a>
<a href="https://securelist.com/analysis/publications/65545/the-epic-turla-operation/">https://securelist.com/analysis/publications/65545/the-epic-turla-operation/</a>

# Lurid

Lurid is a malware family that has been used by several groups, including PittyTiger, in targeted attacks as far back as 2006. [[Citation: Villeneuve 2014]] [[Citation: Villeneuve 2011]]

Aliases: Lurid, Enfal

Lurid is also known as:

- Lurid
- Enfal

Table 844. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0010">https://attack.mitre.org/wiki/Software/S0010</a>
<a href="https://www.fireeye.com/blog/threat-research/2014/07/spy-of-the-tiger.html">https://www.fireeye.com/blog/threat-research/2014/07/spy-of-the-tiger.html</a>
<a href="http://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp%20dissecting-lurid-apt.pdf">http://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp%20dissecting-lurid-apt.pdf</a>

# 3PARA RAT

3PARA RAT is a remote access tool (RAT) programmed in C++ that has been used by Putter Panda. [[Citation: CrowdStrike Putter Panda]]

Table 845. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0066">https://attack.mitre.org/wiki/Software/S0066</a>
<a href="http://cdn0.vox-cdn.com/assets/4589853/crowdstrike-intelligence-report-putter-panda.original.pdf">http://cdn0.vox-cdn.com/assets/4589853/crowdstrike-intelligence-report-putter-panda.original.pdf</a>

## JHUHUGIT

JHUHUGIT is malware used by APT28. It is based on Carberp source code and serves as reconnaissance malware. [[Citation: Kaspersky Sofacy]] [[Citation: F-Secure Sofacy 2015]] [[Citation: ESET Sednit Part 1]] [[Citation: FireEye APT28 January 2017]]

Aliases: JHUHUGIT, Seduploader, JKEYSKW, Sednit, GAMEFISH

JHUHUGIT is also known as:

- JHUHUGIT
- Seduploader
- JKEYSKW
- Sednit
- GAMEFISH

Table 846. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0044">https://attack.mitre.org/wiki/Software/S0044</a>
<a href="http://www.welivesecurity.com/wp-content/uploads/2016/10/eset-sednit-part1.pdf">http://www.welivesecurity.com/wp-content/uploads/2016/10/eset-sednit-part1.pdf</a>
<a href="https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf">https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf</a>
<a href="https://labsblog.f-secure.com/2015/09/08/sofacy-recycles-carberp-and-metasploit-code/">https://labsblog.f-secure.com/2015/09/08/sofacy-recycles-carberp-and-metasploit-code/</a>
<a href="https://securelist.com/blog/research/72924/sofacy-apt-hits-high-profile-targets-with-updated-toolset/">https://securelist.com/blog/research/72924/sofacy-apt-hits-high-profile-targets-with-updated-toolset/</a>

## ELMER

ELMER is a non-persistent, proxy-aware HTTP backdoor written in Delphi that has been used by APT16. [[Citation: FireEye EPS Awakens Part 2]]

Table 847. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0064">https://attack.mitre.org/wiki/Software/S0064</a>
<a href="https://www.fireeye.com/blog/threat-research/2015/12/the-eps-awakens-part-two.html">https://www.fireeye.com/blog/threat-research/2015/12/the-eps-awakens-part-two.html</a>

## Tool

Name of ATT&CK software.



Tool is a cluster galaxy available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

## authors

MITRE

## at

at is used to schedule tasks on a system to run at a specified date or time. [[Citation: TechNet At]]

Aliases: at, at.exe

at is also known as:

- at
- at.exe

Table 848. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0110">https://attack.mitre.org/wiki/Software/S0110</a>
<a href="https://technet.microsoft.com/en-us/library/bb490866.aspx">https://technet.microsoft.com/en-us/library/bb490866.aspx</a>

## route

route can be used to find or change information within the local system IP routing table. [[Citation: TechNet Route]]

Aliases: route, route.exe

route is also known as:

- route
- route.exe

Table 849. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0103">https://attack.mitre.org/wiki/Software/S0103</a>
<a href="https://technet.microsoft.com/en-us/library/bb490991.aspx">https://technet.microsoft.com/en-us/library/bb490991.aspx</a>

## Tasklist

The Tasklist utility displays a list of applications and services with their Process IDs (PID) for all tasks running on either a local or a remote computer. It is packaged with Windows operating systems and can be executed from the command-line interface. [[Citation: Microsoft Tasklist]]

Table 850. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0057">https://attack.mitre.org/wiki/Software/S0057</a>
<a href="https://technet.microsoft.com/en-us/library/bb491010.aspx">https://technet.microsoft.com/en-us/library/bb491010.aspx</a>

## Windows Credential Editor

Windows Credential Editor is a password dumping tool. [[Citation: Amplia WCE]]

Aliases: Windows Credential Editor, WCE

Windows Credential Editor is also known as:

- Windows Credential Editor
- WCE

*Table 851. Table References*

Links
<a href="https://attack.mitre.org/wiki/Software/S0005">https://attack.mitre.org/wiki/Software/S0005</a>
<a href="http://www.ampliasecurity.com/research/wcefaq.html">http://www.ampliasecurity.com/research/wcefaq.html</a>

## schtasks

schtasks is used to schedule execution of programs or scripts on a Windows system to run at a specific date and time. [[Citation: TechNet Schtasks]]

Aliases: schtasks, schtasks.exe

schtasks is also known as:

- schtasks
- schtasks.exe

*Table 852. Table References*

Links
<a href="https://attack.mitre.org/wiki/Software/S0111">https://attack.mitre.org/wiki/Software/S0111</a>
<a href="https://technet.microsoft.com/en-us/library/bb490996.aspx">https://technet.microsoft.com/en-us/library/bb490996.aspx</a>

## UACMe

UACMe is an open source assessment tool that contains many methods for bypassing Windows User Account Control on multiple versions of the operating system. [[Citation: Github UACMe]]

*Table 853. Table References*

Links
-------

<https://attack.mitre.org/wiki/Software/S0116>

<https://github.com/hfiref0x/UACME>

## ifconfig

ifconfig is a Unix-based utility used to gather information about and interact with the TCP/IP settings on a system. [[Citation: Wikipedia Ifconfig]]

Table 854. Table References

Links

<https://attack.mitre.org/wiki/Software/S0101>

<https://en.wikipedia.org/wiki/Ifconfig>

## Mimikatz

Mimikatz is a credential dumper capable of obtaining plaintext Windows account logins and passwords, along with many other features that make it useful for testing the security of networks. [[Citation: Deply Mimikatz]] [[Citation: Adsecurity Mimikatz Guide]]

Table 855. Table References

Links

<https://attack.mitre.org/wiki/Software/S0002>

<https://adsecurity.org/?page%20id=1821>

<https://github.com/gentilkiwi/mimikatz>

## xCmd

xCmd is an open source tool that is similar to PsExec and allows the user to execute applications on remote systems. [[Citation: xCmd]]

Table 856. Table References

Links

<https://attack.mitre.org/wiki/Software/S0123>

<https://ashwinrayaprolu.wordpress.com/2011/04/12/xcmd-an-alternative-to-psexec/>

## Systeminfo

Systeminfo is a Windows utility that can be used to gather detailed information about a computer. [[Citation: TechNet Systeminfo]]

Aliases: systeminfo.exe, Systeminfo

Systeminfo is also known as:

- systeminfo.exe
- Systeminfo

Table 857. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0096">https://attack.mitre.org/wiki/Software/S0096</a>
<a href="https://technet.microsoft.com/en-us/library/bb491007.aspx">https://technet.microsoft.com/en-us/library/bb491007.aspx</a>

## netsh

netsh is a scripting utility used to interact with networking components on local or remote systems. [[Citation: TechNet Netsh]]

Aliases: netsh, netsh.exe

netsh is also known as:

- netsh
- netsh.exe

Table 858. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0108">https://attack.mitre.org/wiki/Software/S0108</a>
<a href="https://technet.microsoft.com/library/bb490939.aspx">https://technet.microsoft.com/library/bb490939.aspx</a>

## dsquery

dsquery is a command-line utility that can be used to query Active Directory for information from a system within a domain. [[Citation: TechNet Dsquery]] It is typically installed only on Windows Server versions but can be installed on non-server variants through the Microsoft-provided Remote Server Administration Tools bundle.

Aliases: dsquery, dsquery.exe

dsquery is also known as:

- dsquery
- dsquery.exe

Table 859. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0105">https://attack.mitre.org/wiki/Software/S0105</a>
<a href="https://technet.microsoft.com/en-us/library/cc732952.aspx">https://technet.microsoft.com/en-us/library/cc732952.aspx</a>

## gsecdump

gsecdump is a publicly-available credential dumper used to obtain password hashes and LSA secrets from Windows operating systems. [[Citation: TrueSec Gsecdump]]

Table 860. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0008">https://attack.mitre.org/wiki/Software/S0008</a>
<a href="http://www.truesec.com/Tools/Tool/gsecdump%20v2.0b5">http://www.truesec.com/Tools/Tool/gsecdump%20v2.0b5</a>

## Ping

Ping is an operating system utility commonly used to troubleshoot and verify network connections. [[Citation: TechNet Ping]]

Aliases: ping.exe, Ping

Ping is also known as:

- ping.exe
- Ping

Table 861. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0097">https://attack.mitre.org/wiki/Software/S0097</a>
<a href="https://technet.microsoft.com/en-us/library/bb490968.aspx">https://technet.microsoft.com/en-us/library/bb490968.aspx</a>

## Fgdump

Fgdump is a Windows password hash dumper. [[Citation: Mandiant APT1]]

Table 862. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0120">https://attack.mitre.org/wiki/Software/S0120</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf">https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf</a>

## Lslsass

Lslsass is a publicly-available tool that can dump active logon session password hashes from the lsass process. [[Citation: Mandiant APT1]]

Table 863. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0121">https://attack.mitre.org/wiki/Software/S0121</a>



## Pass-The-Hash Toolkit

Pass-The-Hash Toolkit is a toolkit that allows an adversary to "pass" a password hash (without knowing the original password) to log in to systems. [[Citation: Mandiant APT1]]

Table 864. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0122">https://attack.mitre.org/wiki/Software/S0122</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf">https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf</a>

## FTP

FTP is a utility commonly available with operating systems to transfer information over the File Transfer Protocol (FTP). Adversaries can use it to transfer other tools onto a system or to exfiltrate data. [[Citation: Wikipedia FTP]]

Aliases: FTP, ftp.exe

FTP is also known as:

- FTP
- ftp.exe

Table 865. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0095">https://attack.mitre.org/wiki/Software/S0095</a>
<a href="https://en.wikipedia.org/wiki/File%20Transfer%20Protocol">https://en.wikipedia.org/wiki/File%20Transfer%20Protocol</a>

## ipconfig

ipconfig is a Windows utility that can be used to find information about a system's TCP/IP, DNS, DHCP, and adapter configuration. [[Citation: TechNet Ipconfig]]

Aliases: ipconfig, ipconfig.exe

ipconfig is also known as:

- ipconfig
- ipconfig.exe

Table 866. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0100">https://attack.mitre.org/wiki/Software/S0100</a>

## certutil

Certutil is a command-line utility that can be used to obtain certificate authority information and configure Certificate Services. [[Citation: TechNet Certutil]]

Aliases: certutil, certutil.exe

certutil is also known as:

- certutil
- certutil.exe

Table 867. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0160">https://attack.mitre.org/wiki/Software/S0160</a>
<a href="https://technet.microsoft.com/library/cc732443.aspx">https://technet.microsoft.com/library/cc732443.aspx</a>

## nbtstat

nbtstat is a utility used to troubleshoot NetBIOS name resolution. [[Citation: TechNet Nbtstat]]

Aliases: nbtstat, nbtstat.exe

nbtstat is also known as:

- nbtstat
- nbtstat.exe

Table 868. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0102">https://attack.mitre.org/wiki/Software/S0102</a>
<a href="https://technet.microsoft.com/en-us/library/cc940106.aspx">https://technet.microsoft.com/en-us/library/cc940106.aspx</a>

## HTRAN

HTRAN is a tool that proxies connections through intermediate hops and aids users in disguising their true geographical location. It can be used by adversaries to hide their location when interacting with the victim networks. [[Citation: Operation Quantum Entanglement]]

Aliases: HTRAN, HUC Packet Transmit Tool

HTRAN is also known as:

- HTRAN

- HUC Packet Transmit Tool

Table 869. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0040">https://attack.mitre.org/wiki/Software/S0040</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/wp-operation-quantum-entanglement.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/wp-operation-quantum-entanglement.pdf</a>

## netstat

netstat is an operating system utility that displays active TCP connections, listening ports, and network statistics. [[Citation: TechNet Netstat]]

Aliases: netstat, netstat.exe

netstat is also known as:

- netstat
- netstat.exe

Table 870. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0104">https://attack.mitre.org/wiki/Software/S0104</a>
<a href="https://technet.microsoft.com/en-us/library/bb490947.aspx">https://technet.microsoft.com/en-us/library/bb490947.aspx</a>

## pwdump

pwdump is a credential dumper. [[Citation: Wikipedia pwdump]]

Table 871. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0006">https://attack.mitre.org/wiki/Software/S0006</a>
<a href="https://en.wikipedia.org/wiki/Pwdump">https://en.wikipedia.org/wiki/Pwdump</a>

## Cachedump

Cachedump is a publicly-available tool that program extracts cached password hashes from a system's registry. [[Citation: Mandiant APT1]]

Table 872. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0119">https://attack.mitre.org/wiki/Software/S0119</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf">https://www.fireeye.com/content/dam/fireeye-www/services/pdfs/mandiant-apt1-report.pdf</a>

# Net

The Net utility is a component of the Windows operating system. It is used in command-line operations for control of users, groups, services, and network connections. Net has a great deal of functionality,[[Citation: Savill 1999]] much of which is useful for an adversary, such as gathering system and network information for , moving laterally through [[Windows admin shares]] using `net use` commands, and interacting with services.

Aliases: Net, net.exe

Net is also known as:

- Net
- net.exe

Table 873. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0039">https://attack.mitre.org/wiki/Software/S0039</a>
<a href="https://msdn.microsoft.com/en-us/library/aa939914">https://msdn.microsoft.com/en-us/library/aa939914</a>
<a href="http://windowsitpro.com/windows/netexe-reference">http://windowsitpro.com/windows/netexe-reference</a>

# PsExec

Psexec is a free Microsoft tool that can be used to execute a program on another computer. It is used by IT administrators and attackers. [[Citation: Russinovich Sysinternals]] [[Citation: SANS PsExec]]

Table 874. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0029">https://attack.mitre.org/wiki/Software/S0029</a>
<a href="https://technet.microsoft.com/en-us/sysinternals/bb897553.aspx">https://technet.microsoft.com/en-us/sysinternals/bb897553.aspx</a>
<a href="https://digital-forensics.sans.org/blog/2012/12/17/protecting-privileged-domain-accounts-psexec-deep-dive">https://digital-forensics.sans.org/blog/2012/12/17/protecting-privileged-domain-accounts-psexec-deep-dive</a>

# Arp

Arp displays information about a system's Address Resolution Protocol (ARP) cache. [[Citation: TechNet Arp]]

Aliases: Arp, arp.exe

Arp is also known as:

- Arp
- arp.exe

Table 875. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0099">https://attack.mitre.org/wiki/Software/S0099</a>
<a href="https://technet.microsoft.com/en-us/library/bb490864.aspx">https://technet.microsoft.com/en-us/library/bb490864.aspx</a>

## cmd

cmd is the Windows command-line interpreter that can be used to interact with systems and execute other processes and utilities. [[Citation: TechNet Cmd]]

Cmd.exe contains native functionality to perform many operations to interact with the system, including listing files in a directory (e.g., `dir` [[Citation: TechNet Dir]], deleting files (e.g., `del` [[Citation: TechNet Del]], and copying files (e.g., `copy` [[Citation: TechNet Copy]]).

Aliases: cmd, cmd.exe

cmd is also known as:

- cmd
- cmd.exe

Table 876. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0106">https://attack.mitre.org/wiki/Software/S0106</a>
<a href="https://technet.microsoft.com/en-us/library/cc771049.aspx">https://technet.microsoft.com/en-us/library/cc771049.aspx</a>
<a href="https://technet.microsoft.com/en-us/library/cc755121.aspx">https://technet.microsoft.com/en-us/library/cc755121.aspx</a>
<a href="https://technet.microsoft.com/en-us/library/bb490886.aspx">https://technet.microsoft.com/en-us/library/bb490886.aspx</a>
<a href="https://technet.microsoft.com/en-us/library/bb490880.aspx">https://technet.microsoft.com/en-us/library/bb490880.aspx</a>

## Cobalt Strike

Cobalt Strike is a commercial, full-featured, penetration testing tool which bills itself as “adversary simulation software designed to execute targeted attacks and emulate the post-exploitation actions of advanced threat actors”. Cobalt Strike’s interactive post-exploit capabilities cover the full range of ATT&CK tactics, all executed within a single, integrated system. Cobalt Strike leverages the capabilities of other well-known tools such as Metasploit and Mimikatz. [[Citation: cobaltstrike manual]]

The list of techniques below focuses on Cobalt Strike’s ATT&CK-relevant tactics.

Table 877. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0154">https://attack.mitre.org/wiki/Software/S0154</a>

<https://cobaltstrike.com/downloads/csmanual38.pdf>

## Reg

Reg is a Windows utility used to interact with the Windows Registry. It can be used at the command-line interface to query, add, modify, and remove information. Reg are known to be used by persistent threats. [[Citation: Windows Commands JPCERT]]

Aliases: Reg, reg.exe

Reg is also known as:

- Reg
- reg.exe

Table 878. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0075">https://attack.mitre.org/wiki/Software/S0075</a>
<a href="http://blog.jpcert.or.jp/2016/01/windows-commands-abused-by-attackers.html">http://blog.jpcert.or.jp/2016/01/windows-commands-abused-by-attackers.html</a>
<a href="https://technet.microsoft.com/en-us/library/cc732643.aspx">https://technet.microsoft.com/en-us/library/cc732643.aspx</a>

## Preventive Measure

Preventive measures based on the ransomware document overview as published in <https://docs.google.com/spreadsheets/d/1TWS238xacAto-fLKh1n5uTsdijWdCEsGIM0Y0Hvmc5g/pubhtml#> . The preventive measures are quite generic and can fit any standard Windows infrastructure and their security measures..



Preventive Measure is a cluster galaxy available in JSON format at [https://github.com/MISP/misp-galaxy/blob/master/clusters/preventive\\_measure.json](https://github.com/MISP/misp-galaxy/blob/master/clusters/preventive_measure.json) [**this location**] The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

Various

## Backup and Restore Process

Make sure to have adequate backup processes on place and frequently test a restore of these backups. (Schrödinger's backup - it is both existent and non-existent until you've tried a restore)

Table 879. Table References

Links
<a href="http://windows.microsoft.com/en-us/windows/back-up-restore-faq#1TC=windows-7">http://windows.microsoft.com/en-us/windows/back-up-restore-faq#1TC=windows-7</a> .[ <a href="http://windows.microsoft.com/en-us/windows/back-up-restore-faq#1TC=windows-7">http://windows.microsoft.com/en-us/windows/back-up-restore-faq#1TC=windows-7</a> .]

# Block Macros

Disable macros in Office files downloaded from the Internet. This can be configured to work in two different modes: A.) Open downloaded documents in 'Protected View' B.) Open downloaded documents and block all macros

Table 880. Table References

Links
<a href="https://support.office.com/en-us/article/Enable-or-disable-macros-in-Office-files-12b036fd-d140-4e74-b45e-16fed1a7e5c6?ui=en-US&amp;rs=en-US&amp;ad=US">https://support.office.com/en-us/article/Enable-or-disable-macros-in-Office-files-12b036fd-d140-4e74-b45e-16fed1a7e5c6?ui=en-US&amp;rs=en-US&amp;ad=US</a>
<a href="https://www.404techsupport.com/2016/04/office2016-macro-group-policy/?utm_source=dlvr.it&amp;utm_medium=twitter">https://www.404techsupport.com/2016/04/office2016-macro-group-policy/?utm_source=dlvr.it&amp;utm_medium=twitter</a>

# Disable WSH

Disable Windows Script Host

Table 881. Table References

Links
<a href="http://www.windowsnetworking.com/kbase/WindowsTips/WindowsXP/AdminTips/Customization/DisableWindowsScriptingHostWSH.html">http://www.windowsnetworking.com/kbase/WindowsTips/WindowsXP/AdminTips/Customization/DisableWindowsScriptingHostWSH.html</a>

# Filter Attachments Level 1

Filter the following attachments on your mail gateway: .ade, .adp, .ani, .bas, .bat, .chm, .cmd, .com, .cpl, .crt, .exe, .hlp, .ht, .hta, .inf, .ins, .isp, .jar, .job, .js, .jse, .lnk, .mda, .mdb, .mde, .mdz, .msc, .msi, .msp, .mst, .ocx, .pcd, .ps1, .reg, .scr, .sct, .shs, .svg, .url, .vb, .vbe, .vbs, .wbk, .wsc, .ws, .wsf, .wsh, .exe, .pif, .pub

# Filter Attachments Level 2

Filter the following attachments on your mail gateway: (Filter expression of Level 1 plus) .doc, .xls, .rtf, .docm, .xlsm, .pptm

# Restrict program execution

Block all program executions from the %LocalAppData% and %AppData% folder

Table 882. Table References

Links
<a href="http://www.fatdex.net/php/2014/06/01/disable-exes-from-running-inside-any-user-appdata-directory-gpo/">http://www.fatdex.net/php/2014/06/01/disable-exes-from-running-inside-any-user-appdata-directory-gpo/</a>
<a href="http://www.thirdtier.net/ransomware-prevention-kit/">http://www.thirdtier.net/ransomware-prevention-kit/</a>

## Show File Extensions

Set the registry key "HideFileExt" to 0 in order to show all file extensions, even of known file types. This helps avoiding cloaking tricks that use double extensions. (e.g. "not\_a\_virus.pdf.exe")

*Table 883. Table References*

Links
<a href="http://www.sevenforums.com/tutorials/10570-file-extensions-hide-show.htm">http://www.sevenforums.com/tutorials/10570-file-extensions-hide-show.htm</a>

## Enforce UAC Prompt

Enforce administrative users to confirm an action that requires elevated rights

*Table 884. Table References*

Links
<a href="https://technet.microsoft.com/en-us/library/dd835564(WS.10).aspx">https://technet.microsoft.com/en-us/library/dd835564(WS.10).aspx</a>

## Remove Admin Privileges

Remove and restrict administrative rights whenever possible. Malware can only modify files that users have write access to.

## Restrict Workstation Communication

Activate the Windows Firewall to restrict workstation to workstation communication

## Sandboxing Email Input

Using sandbox that opens email attachments and removes attachments based on behavior analysis

## Execution Prevention

Software that allows to control the execution of processes - sometimes integrated in Antivirus software Free: AntiHook, ProcessGuard, System Safety Monitor

## Change Default "Open With" to Notepad

Force extensions primarily used for infections to open up in Notepad rather than Windows Script Host or Internet Explorer

*Table 885. Table References*

Links
<a href="https://bluesoul.me/2016/05/12/use-gpo-to-change-the-default-behavior-of-potentially-malicious-file-extensions/">https://bluesoul.me/2016/05/12/use-gpo-to-change-the-default-behavior-of-potentially-malicious-file-extensions/</a>



# File Screening

Server-side file screening with the help of File Server Resource Manager

Table 886. Table References

Links
<a href="http://jpelectron.com/sample/Info%20and%20Documents/Stop%20crypto%20badware%20before%20it%20ruins%20your%20day/1-PreventCrypto-Readme.htm">http://jpelectron.com/sample/Info%20and%20Documents/Stop%20crypto%20badware%20before%20it%20ruins%20your%20day/1-PreventCrypto-Readme.htm</a>

## Restrict program execution #2

Block program executions (AppLocker)

Table 887. Table References

Links
<a href="https://technet.microsoft.com/en-us/library/dd759117%28v=ws.11%29.aspx">https://technet.microsoft.com/en-us/library/dd759117%28v=ws.11%29.aspx</a>
<a href="http://social.technet.microsoft.com/wiki/contents/articles/5211.how-to-configure-applocker-group-policy-to-prevent-software-from-running.aspx">http://social.technet.microsoft.com/wiki/contents/articles/5211.how-to-configure-applocker-group-policy-to-prevent-software-from-running.aspx</a>

## EMET

Detect and block exploitation techniques

Table 888. Table References

Links
<a href="http://www.microsoft.com/emet">www.microsoft.com/emet</a> [ <a href="http://www.microsoft.com/emet">www.microsoft.com/emet</a> ]
<a href="http://windowsitpro.com/security/control-emet-group-policy">http://windowsitpro.com/security/control-emet-group-policy</a>

## Sysmon

Detect Ransomware in an early stage with new Sysmon 5 File/Registry monitoring

Table 889. Table References

Links
<a href="https://twitter.com/JohnLaTwC/status/799792296883388416">https://twitter.com/JohnLaTwC/status/799792296883388416</a>

## Ransomware

Ransomware galaxy based on <https://docs.google.com/spreadsheets/d/1TWS238xacAto-fLK1n5uTsdijWdCEsGIM0Y0Hvmc5g/pubhtml> and <http://pastebin.com/raw/GHgpWjar>.



Ransomware is a cluster galaxy available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

## authors

<https://docs.google.com/spreadsheets/d/1TWS238xacAto-fLKh1n5uTsdijWdCEsGIM0Y0Hvmc5g/pubhtml> - <http://pastebin.com/raw/GHgpWjar>

## Nhtnwcuf Ransomware (Fake)

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 890. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/nhtnwcuf-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/nhtnwcuf-ransomware.html</a>

## CryptoJacky Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 891. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/cryptojacky-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/cryptojacky-ransomware.html</a>
<a href="https://twitter.com/jiriatvirlab/status/838779371750031360">https://twitter.com/jiriatvirlab/status/838779371750031360</a>

## Kaenlupuf Ransomware

About: This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 892. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/kaenlupuf-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/kaenlupuf-ransomware.html</a>

## EnjoyCrypter Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 893. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/enjey-crypter-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/enjey-crypter-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-march-10th-2017-spora-cerber-and-technical-writeups/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-march-10th-2017-spora-cerber-and-technical-writeups/</a>
<a href="https://www.bleepingcomputer.com/news/security/embittered-enjey-ransomware-developer-launches-ddos-attack-on-id-ransomware/">https://www.bleepingcomputer.com/news/security/embittered-enjey-ransomware-developer-launches-ddos-attack-on-id-ransomware/</a>

## Dangerous Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 894. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/dangerous-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/dangerous-ransomware.html</a>

## Vortex Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Vortex Ransomware is also known as:

- Fl ter r re

Table 895. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/vortex-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/vortex-ransomware.html</a>
<a href="https://twitter.com/struppigel/status/839778905091424260">https://twitter.com/struppigel/status/839778905091424260</a>

## GC47 Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 896. Table References

Links
-------

<https://id-ransomware.blogspot.co.il/2017/03/gc47-ransomware.html>

## RozaLocker Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 897. Table References*

Links

<https://id-ransomware.blogspot.co.il/2017/03/rozalocker-ransomware.html>

<https://twitter.com/jiriatvirlab/status/840863070733885440>

## CryptoMeister Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 898. Table References*

Links

<https://id-ransomware.blogspot.co.il/2017/03/cryptomeister-ransomware.html>

## GG Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Poses as Hewlett-Packard 2016

*Table 899. Table References*

Links

<https://id-ransomware.blogspot.co.il/2017/03/gg-ransomware.html>

## Project34 Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 900. Table References*

Links
-------

<a href="https://id-ransomware.blogspot.co.il/2017/03/project34-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/project34-ransomware.html</a>
---

## PetrWrap Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 901. Table References

Links
-------

<a href="https://id-ransomware.blogspot.co.il/2017/03/petrwrap-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/petrwrap-ransomware.html</a>
---

<a href="https://www.bleepingcomputer.com/news/security/petrwrap-ransomware-is-a-petya-offspring-used-in-targeted-attacks/">https://www.bleepingcomputer.com/news/security/petrwrap-ransomware-is-a-petya-offspring-used-in-targeted-attacks/</a>
---

<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-march-17th-2017-revenge-petrwrap-and-captain-kirk/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-march-17th-2017-revenge-petrwrap-and-captain-kirk/</a>
---

<a href="https://securelist.com/blog/research/77762/petrwrap-the-new-petya-based-ransomware-used-in-targeted-attacks/">https://securelist.com/blog/research/77762/petrwrap-the-new-petya-based-ransomware-used-in-targeted-attacks/</a>
---

## Karmen Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. RaaS, baed on HiddenTear

Table 902. Table References

Links
-------

<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-march-17th-2017-revenge-petrwrap-and-captain-kirk/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-march-17th-2017-revenge-petrwrap-and-captain-kirk/</a>
---

<a href="https://id-ransomware.blogspot.co.il/2017/03/karmen-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/karmen-ransomware.html</a>
---

<a href="https://twitter.com/malwrhunterteam/status/841747002438361089">https://twitter.com/malwrhunterteam/status/841747002438361089</a>
---

## Revenge Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. CryptoMix / CryptFile2 Variant

Table 903. Table References

Links
-------

<https://www.bleepingcomputer.com/news/security/revenge-ransomware-a-cryptomix-variant-being-distributed-by-rig-exploit-kit/>

<https://id-ransomware.blogspot.co.il/2017/03/revenge-ransomware.html>

## Turkish FileEncryptor Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Turkish FileEncryptor Ransomware is also known as:

- Fake CTB-Locker

*Table 904. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/turkish-fileencryptor.html">https://id-ransomware.blogspot.co.il/2017/03/turkish-fileencryptor.html</a>
<a href="https://twitter.com/JakubKroustek/status/842034887397908480">https://twitter.com/JakubKroustek/status/842034887397908480</a>

## Kirk Ransomware & Spock Decryptor

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Payments in Monero

*Table 905. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/kirkspock-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/kirkspock-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-march-17th-2017-revenge-petrwrap-and-captain-kirk/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-march-17th-2017-revenge-petrwrap-and-captain-kirk/</a>
<a href="https://www.bleepingcomputer.com/forums/t/642239/kirk-ransomware-help-support-topic-kirk-extension-ransom-notetxt/">https://www.bleepingcomputer.com/forums/t/642239/kirk-ransomware-help-support-topic-kirk-extension-ransom-notetxt/</a>
<a href="http://www.networkworld.com/article/3182415/security/star-trek-themed-kirk-ransomware-has-spock-decryptor-demands-ransom-be-paid-in-monero.html">http://www.networkworld.com/article/3182415/security/star-trek-themed-kirk-ransomware-has-spock-decryptor-demands-ransom-be-paid-in-monero.html</a>
<a href="http://www.securityweek.com/star-trek-themed-kirk-ransomware-emerges">http://www.securityweek.com/star-trek-themed-kirk-ransomware-emerges</a>
<a href="https://www.grahamcluley.com/kirk-ransomware-sports-star-trek-themed-decryptor-little-known-crypto-currency/">https://www.grahamcluley.com/kirk-ransomware-sports-star-trek-themed-decryptor-little-known-crypto-currency/</a>
<a href="https://www.virustotal.com/en/file/39a2201a88f10d81b220c973737f0becedab2e73426ab9923880fb0fb990c5cc/analysis/">https://www.virustotal.com/en/file/39a2201a88f10d81b220c973737f0becedab2e73426ab9923880fb0fb990c5cc/analysis/</a>

## ZinoCrypt Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 906. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/zinocrypt-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/zinocrypt-ransomware.html</a>
<a href="https://twitter.com/demonslay335?lang=en">https://twitter.com/demonslay335?lang=en</a>
<a href="https://twitter.com/malwrhunterteam/status/842781575410597894">https://twitter.com/malwrhunterteam/status/842781575410597894</a>

## Crptxxx Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Uses @enigma0x3's UAC bypass

Table 907. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/crptxxx-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/crptxxx-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/forums/t/609690/ultracrypter-cryptxxx-ultradecrypter-ransomware-help-topic-crypt-cryp1/page-84">https://www.bleepingcomputer.com/forums/t/609690/ultracrypter-cryptxxx-ultradecrypter-ransomware-help-topic-crypt-cryp1/page-84</a>
<a href="http://www.fixinfectedpc.com/uninstall-crptxxx-ransomware-from-pc">http://www.fixinfectedpc.com/uninstall-crptxxx-ransomware-from-pc</a>
<a href="https://twitter.com/malwrhunterteam/status/839467168760725508">https://twitter.com/malwrhunterteam/status/839467168760725508</a>

## MOTD Ransomware

About: This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 908. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/motd-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/motd-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/forums/t/642409/motd-of-ransome-hostage/">https://www.bleepingcomputer.com/forums/t/642409/motd-of-ransome-hostage/</a>
<a href="https://www.bleepingcomputer.com/forums/t/642409/motd-ransomware-help-support-topics-motdtxt-and-enc-extension/">https://www.bleepingcomputer.com/forums/t/642409/motd-ransomware-help-support-topics-motdtxt-and-enc-extension/</a>

## CryptoDevil Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 909. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/cryptodevil-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/cryptodevil-ransomware.html</a>
<a href="https://twitter.com/PolarToffee/status/843527738774507522">https://twitter.com/PolarToffee/status/843527738774507522</a>

## FabSysCrypto Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Based on HiddenTear

Table 910. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/fabsyscrypto-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/fabsyscrypto-ransomware.html</a>
<a href="https://twitter.com/struppigel/status/837565766073475072">https://twitter.com/struppigel/status/837565766073475072</a>

## Lock2017 Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 911. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/lock2017-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/lock2017-ransomware.html</a>

## RedAnts Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 912. Table References

Links
-------



<https://id-ransomware.blogspot.co.il/2017/03/redants-ransomware.html>

## ConsoleApplication1 Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 913. Table References*

Links

<https://id-ransomware.blogspot.co.il/2017/03/consoleapplication1-ransomware.html>

## KRider Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 914. Table References*

Links

<https://id-ransomware.blogspot.co.il/2017/03/krider-ransomware.html>

<https://twitter.com/malwrhunterteam/status/836995570384453632>

## CYR-Locker Ransomware (FAKE)

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. The following note is what you get if you put in the wrong key code: <https://3.bp.blogspot.com/-qsS0x-tHx00/WLM3kkKWKAI/AAAAAAAAAEDg/Zhy3eYf-ek8fY5uM0yHs7E0fEFg2AXG-gCLcB/s1600/failed-key.jpg>

*Table 915. Table References*

Links

<https://id-ransomware.blogspot.co.il/search?updated-min=2017-01-01T00:00:00-08:00&updated-max=2018-01-01T00:00:00-08:00&max-results=50>

## DotRansomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office,

Open Office, pictures, videos, shared online files etc..

Table 916. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/dotransomware.html">https://id-ransomware.blogspot.co.il/2017/02/dotransomware.html</a>

## Unlock26 Ransomware

About: This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 917. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/unlock26-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/unlock26-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/new-raas-portal-preparing-to-spread-unlock26-ransomware/">https://www.bleepingcomputer.com/news/security/new-raas-portal-preparing-to-spread-unlock26-ransomware/</a>

## PicklesRansomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Python Ransomware

Table 918. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/pickles-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/pickles-ransomware.html</a>
<a href="https://twitter.com/JakubKroustek/status/834821166116327425">https://twitter.com/JakubKroustek/status/834821166116327425</a>

## Vanguard Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. This ransomware poses at MSOffice to fool users into opening the infected file. GO Ransomware

Table 919. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/vanguard-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/vanguard-ransomware.html</a>
<a href="https://twitter.com/JAMESWT_MHT/status/834783231476166657">https://twitter.com/JAMESWT_MHT/status/834783231476166657</a>

## PyL33T Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 920. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/pyl33t-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/pyl33t-ransomware.html</a>
<a href="https://twitter.com/JanOfficial/status/834706668466405377">https://twitter.com/JanOfficial/status/834706668466405377</a>

## TrumpLocker Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. This is the old VenusLocker in disguise .To delete shadow files use the following commend: C:\Windows\system32\wbem\wmic.exe shadowcopy delete&exit [https://2.bp.blogspot.com/-8qliBHnE9yU/WK1mZn3LgwI/AAAAAAAAAD-M/ZKl7\\_Iwr1agYtlVO3HXaUrwitcowp5\\_NQCLcB/s1600/lock.jpg](https://2.bp.blogspot.com/-8qliBHnE9yU/WK1mZn3LgwI/AAAAAAAAAD-M/ZKl7_Iwr1agYtlVO3HXaUrwitcowp5_NQCLcB/s1600/lock.jpg)

Table 921. Table References

Links
<a href="https://www.bleepingcomputer.com/news/security/new-trump-locker-ransomware-is-a-fraud-just-venuslocker-in-disguise/">https://www.bleepingcomputer.com/news/security/new-trump-locker-ransomware-is-a-fraud-just-venuslocker-in-disguise/</a>
<a href="https://id-ransomware.blogspot.co.il/2017/02/trumplocker.html">https://id-ransomware.blogspot.co.il/2017/02/trumplocker.html</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-february-24th-2017-trump-locker-macos-rw-and-cryptomix/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-february-24th-2017-trump-locker-macos-rw-and-cryptomix/</a>

## Damage Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Written in Delphi

Table 922. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/damage-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/damage-ransomware.html</a>
<a href="https://decrypter.emsisoft.com/damage">https://decrypter.emsisoft.com/damage</a>
<a href="https://twitter.com/demonslay335/status/835664067843014656">https://twitter.com/demonslay335/status/835664067843014656</a>

## XYZWare Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Based on HiddenTear

Table 923. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/xyzware-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/xyzware-ransomware.html</a>
<a href="https://twitter.com/malwrhunterteam/status/833636006721122304">https://twitter.com/malwrhunterteam/status/833636006721122304</a>

## YouAreFucked Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 924. Table References

Links
<a href="https://www.enigmasoftware.com/youarefuckedransomware-removal/">https://www.enigmasoftware.com/youarefuckedransomware-removal/</a>

## CryptConsole 2.0 Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 925. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/cryptconsole-2-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/cryptconsole-2-ransomware.html</a>

## BarRax Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Based on HiddenTear

BarRax Ransomware is also known as:

- BarRaxCrypt Ransomware

Table 926. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/barraxcrypt-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/barraxcrypt-ransomware.html</a>
<a href="https://twitter.com/demonslay335/status/83566854036777792">https://twitter.com/demonslay335/status/83566854036777792</a>

## CryptoLocker by NTK Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 927. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/cryptolocker-by-ntk-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/cryptolocker-by-ntk-ransomware.html</a>

## UserFilesLocker Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

UserFilesLocker Ransomware is also known as:

- CzechoSlovak Ransomware

Table 928. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/userfileslocker-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/userfileslocker-ransomware.html</a>

## AvastVirusinfo Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. PAYING RANSOM IS USELESS, YOUR FILES WILL NOT BE FIXED. THE DAMAGE IS PERMENENT!!!!

Table 929. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017_03_01_archive.html">https://id-ransomware.blogspot.co.il/2017_03_01_archive.html</a>
<a href="https://id-ransomware.blogspot.co.il/2017/03/avastvirusinfo-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/avastvirusinfo-ransomware.html</a>

## SuchSecurity Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 930. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/03/suchsecurity-ransomware.html">https://id-ransomware.blogspot.co.il/2017/03/suchsecurity-ransomware.html</a>

## PleaseRead Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

PleaseRead Ransomware is also known as:

- VHDLocker Ransomware

Table 931. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/vhd-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/vhd-ransomware.html</a>

## Kasiski Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 932. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/kasiski-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/kasiski-ransomware.html</a>
<a href="https://twitter.com/MarceloRivero/status/832302976744173570">https://twitter.com/MarceloRivero/status/832302976744173570</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-february-17th-2017-live-hermes-reversing-and-scada-poc-ransomware/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-february-17th-2017-live-hermes-reversing-and-scada-poc-ransomware/</a>

## Fake Locky Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Fake Locky Ransomware is also known as:

- Locky Impersonator Ransomware

Table 933. Table References

Links
<a href="https://www.bleepingcomputer.com/news/security/the-locky-ransomware-encrypts-local-files-and-unmapped-network-shares/">https://www.bleepingcomputer.com/news/security/the-locky-ransomware-encrypts-local-files-and-unmapped-network-shares/</a>
<a href="https://id-ransomware.blogspot.co.il/2017/02/locky-impersonator.html">https://id-ransomware.blogspot.co.il/2017/02/locky-impersonator.html</a>
<a href="https://www.bleepingcomputer.com/news/security/locky-ransomware-switches-to-thor-extension-after-being-a-bad-malware/">https://www.bleepingcomputer.com/news/security/locky-ransomware-switches-to-thor-extension-after-being-a-bad-malware/</a>

## CryptoShield 1.0 Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. CryptoShield 1.0 is a ransomware from the CryptoMix family.

Table 934. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/cryptoshield-2-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/cryptoshield-2-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/cryptomix-variant-named-cryptoshield-1-0-ransomware-distributed-by-exploit-kits/">https://www.bleepingcomputer.com/news/security/cryptomix-variant-named-cryptoshield-1-0-ransomware-distributed-by-exploit-kits/</a>

## Hermes Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Filemarker: "HERMES"

Table 935. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/hermes-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/hermes-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-february-17th-2017-live-hermes-reversing-and-scada-poc-ransomware/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-february-17th-2017-live-hermes-reversing-and-scada-poc-ransomware/</a>
<a href="https://www.bleepingcomputer.com/forums/t/642019/hermes-ransomware-help-support-decrypt-informationhtml/">https://www.bleepingcomputer.com/forums/t/642019/hermes-ransomware-help-support-decrypt-informationhtml/</a>
<a href="https://www.bleepingcomputer.com/news/security/hermes-ransomware-decrypted-in-live-video-by-emsisofts-fabian-wosar/">https://www.bleepingcomputer.com/news/security/hermes-ransomware-decrypted-in-live-video-by-emsisofts-fabian-wosar/</a>

## LoveLock Ransomware or Love2Lock Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 936. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/lovelock-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/lovelock-ransomware.html</a>

## Wcry Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 937. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/wcry-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/wcry-ransomware.html</a>

## DUMB Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 938. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/dumb-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/dumb-ransomware.html</a>
<a href="https://twitter.com/bleepincomputer/status/816053140147597312?lang=en">https://twitter.com/bleepincomputer/status/816053140147597312?lang=en</a>

## X-Files

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 939. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017_02_01_archive.html">https://id-ransomware.blogspot.co.il/2017_02_01_archive.html</a>
<a href="https://id-ransomware.blogspot.co.il/2017/02/x-files-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/x-files-ransomware.html</a>

## Polski Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The Ransom is 249\$ and the hacker demands that the victim gets in contact through e-mail and a Polish messenger called Gadu-Gadu.

Table 940. Table References



Links
-------

<a href="https://id-ransomware.blogspot.co.il/2017/02/polski-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/polski-ransomware.html</a>
---

## YourRansom Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. This hacker demands that the victim contacts him through email and decrypts the files for FREE.(moreinfo in the link below)

*Table 941. Table References*

Links
-------

<a href="https://id-ransomware.blogspot.co.il/2017/02/yourransom-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/yourransom-ransomware.html</a>
---

<a href="https://www.bleepingcomputer.com/news/security/yourransom-is-the-latest-in-a-long-line-of-prank-and-educational-ransomware/">https://www.bleepingcomputer.com/news/security/yourransom-is-the-latest-in-a-long-line-of-prank-and-educational-ransomware/</a>
---

<a href="https://twitter.com/_ddoxer/status/827555507741274113">https://twitter.com/_ddoxer/status/827555507741274113</a>
---

## Ranion RaasRansomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Ranion Raas gives the opportunity to regular people to buy and distribute ransomware for a very cheap price. (More info in the link below). Raas service

*Table 942. Table References*

Links
-------

<a href="https://id-ransomware.blogspot.co.il/2017/02/ranion-raas.html">https://id-ransomware.blogspot.co.il/2017/02/ranion-raas.html</a>
---

<a href="https://www.bleepingcomputer.com/news/security/ranion-ransomware-as-a-service-available-on-the-dark-web-for-educational-purposes/">https://www.bleepingcomputer.com/news/security/ranion-ransomware-as-a-service-available-on-the-dark-web-for-educational-purposes/</a>
---

## Potato Ransomware

Wants a ransom to get the victim's files back . Originated in English. Spread worldwide.

*Table 943. Table References*

Links
-------

<a href="https://id-ransomware.blogspot.co.il/2017/01/polato-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/polato-ransomware.html</a>
---

## of Ransomware: OpenToYou (Formerly known as OpenToDecrypt)

This ransomware is originated in English, therefore could be used worldwide. Ransomware is

spread with the help of email spam, fake ads, fake updates, infected install files.

Table 944. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/opentodecrypt-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/opentodecrypt-ransomware.html</a>

## RansomPlus

Author of this ransomware is sergej. Ransom is 0.25 bitcoins for the return of files. Originated in English. Used worldwide. This ransomware is spread with the help of email spam, fake ads, fake updates, infected install files.

Table 945. Table References

Links
<a href="http://www.2-spyware.com/remove-ransomplus-ransomware-virus.html">http://www.2-spyware.com/remove-ransomplus-ransomware-virus.html</a>
<a href="https://id-ransomware.blogspot.co.il/2017/01/ransomplus-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/ransomplus-ransomware.html</a>
<a href="https://twitter.com/jiriavirlab/status/825411602535088129">https://twitter.com/jiriavirlab/status/825411602535088129</a>

## CryptConsole

This ransomware does not actually encrypt your file, but only changes the names of your files, just like Globe Ransomware. This ransomware is spread with the help of email spam, fake ads, fake updates, infected install files

Table 946. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/cryptconsole-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/cryptconsole-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/forums/t/638344/cryptconsole-uncrypteoutlookcom-support-topic-how-decrypt-fileshta/">https://www.bleepingcomputer.com/forums/t/638344/cryptconsole-uncrypteoutlookcom-support-topic-how-decrypt-fileshta/</a>
<a href="https://twitter.com/PolarToffee/status/824705553201057794">https://twitter.com/PolarToffee/status/824705553201057794</a>

## ZXZ Ramsomware

Originated in English, could affect users worldwide, however so far only reports from Saudi Arabia. The malware name founded by a windows server tools is called win32/wagcrypt.A

Table 947. Table References

Links
<a href="https://www.bleepingcomputer.com/forums/t/638191/zxz-ransomware-support-help-topic-zxz/?hl=%2Bzxz#entry4168310">https://www.bleepingcomputer.com/forums/t/638191/zxz-ransomware-support-help-topic-zxz/?hl=%2Bzxz#entry4168310</a>
<a href="https://id-ransomware.blogspot.co.il/2017/01/zxz-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/zxz-ransomware.html</a>

## VxLock Ransomware

Developed in Visual Studios in 2010. Original name is VxCrypt. This ransomware encrypts your files, including photos, music, MS office, Open Office, PDF... etc

*Table 948. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/vxlock-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/vxlock-ransomware.html</a>

## FunFact Ransomware

Funfact uses an open code for GNU Privacy Guard (GnuPG), then asks to email them to find out the amount of bitcoin to send (to receive a decrypt code). Written in English, can attach all over the world. The ransom is 1.22038 BTC, which is 1100USD.

*Table 949. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/funfact.html">https://id-ransomware.blogspot.co.il/2017/01/funfact.html</a>
<a href="http://www.enigmasoftware.com/funfactransomware-removal/">http://www.enigmasoftware.com/funfactransomware-removal/</a>

## ZekwaCrypt Ransomware

First spotted in May 2016, however made a big comeback in January 2017. It's directed to English speaking users, therefore is able to infect worldwide. Ransomware is spread with the help of email spam, fake ads, fake updates, infected install files.

*Table 950. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/06/zekwacrypt-ransomware.html">https://id-ransomware.blogspot.co.il/2016/06/zekwacrypt-ransomware.html</a>
<a href="http://www.2-spyware.com/remove-zekwacrypt-ransomware-virus.html">http://www.2-spyware.com/remove-zekwacrypt-ransomware-virus.html</a>

## Sage 2.0 Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. This ransomware attacks your MS Office by offering a Micro to help with your program, but instead incrypts all your files if the used id not protected. Predecessor CryLocker

*Table 951. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/sage-2-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/sage-2-ransomware.html</a>
<a href="https://isc.sans.edu/forums/diary/Sage+20+Ransomware/21959/">https://isc.sans.edu/forums/diary/Sage+20+Ransomware/21959/</a>
<a href="http://www.securityweek.com/sage-20-ransomware-demands-2000-ransom">http://www.securityweek.com/sage-20-ransomware-demands-2000-ransom</a>

<https://www.bleepingcomputer.com/news/security/sage-2-0-ransomware-gearing-up-for-possible-greater-distribution/>

<https://www.govcert.admin.ch/blog/27/sage-2.0-comes-with-ip-generation-algorithm-ipga>

## CloudSword Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. Uses the name "Window Update" to confuse its victims. Then imitates the window update process , while turning off the Window Startup Repair and changes the BootStatusPolicy using these commands:  
bcdedit.exe /set {default} recoveryenabled No  
bcdedit.exe /set {default} bootstatuspolicy ignoreallfailures

*Table 952. Table References*

Links

<https://id-ransomware.blogspot.co.il/2017/01/cloudsword.html>

<http://bestsecuritysearch.com/cloudsword-ransomware-virus-removal-steps-protection-updates/>

<https://twitter.com/BleepinComputer/status/822653335681593345>

## DN

It's directed to English speaking users, therefore is able to infect worldwide. Uses the name "Chrome Update" to confuse its victims. Then imitates the chrome update process ,while encrypting the files. DO NOT pay the ransom, since YOUR COMPUTER WILL NOT BE RESTORED FROM THIS MALWARE!!!!

DN is also known as:

- Fake

*Table 953. Table References*

Links

<https://id-ransomware.blogspot.co.il/2017/01/dn-donotopen.html>

## GarryWeber Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. Its original name is FileSpy and FileSpy Application. It is spread using email spam, fake updates, infected attachments and so on. It encryps all your files, including: music, MS Office, Open Office, pictures etc..

*Table 954. Table References*

Links

<https://id-ransomware.blogspot.co.il/2017/01/garryweber.html>

## Satan Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. Its original name is RAAS RANSOMWARE. It is spread using email spam, fake updates, infected attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures etc.. This ransomware promotes other to download viruses and spread them as ransomware to infect other users and keep 70% of the ransom. (leaving the other 30% to Satan) [https://3.bp.blogspot.com/-7fwX40eYL18/WH-tfpNjDgI/AAAAAAAAADPk/KVP\\_ji8lR0gENCMYhb324mfzIFFpiaOwACLcB/s1600/site-raas.gif](https://3.bp.blogspot.com/-7fwX40eYL18/WH-tfpNjDgI/AAAAAAAAADPk/KVP_ji8lR0gENCMYhb324mfzIFFpiaOwACLcB/s1600/site-raas.gif) RaaS

Table 955. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/satan-raas.html">https://id-ransomware.blogspot.co.il/2017/01/satan-raas.html</a>
<a href="https://www.bleepingcomputer.com/forums/t/637811/satan-ransomware-help-support-topic-stn-extension-help-decrypt-fileshtml/">https://www.bleepingcomputer.com/forums/t/637811/satan-ransomware-help-support-topic-stn-extension-help-decrypt-fileshtml/</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-january-20th-2017-satan-raas-spora-locky-and-more/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-january-20th-2017-satan-raas-spora-locky-and-more/</a>
<a href="https://www.bleepingcomputer.com/news/security/new-satan-ransomware-available-through-a-ransomware-as-a-service-/">https://www.bleepingcomputer.com/news/security/new-satan-ransomware-available-through-a-ransomware-as-a-service-/</a>
<a href="https://twitter.com/Xylit0l/status/821757718885236740">https://twitter.com/Xylit0l/status/821757718885236740</a>

## Havoc

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, infected attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures , videos, shared online files etc..

Havoc is also known as:

- HavocCrypt Ransomware

Table 956. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/havoc-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/havoc-ransomware.html</a>

## CryptoSweetTooth Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Its fake name is Bitcoin and maker's name is Santiago. Work of the encrypted requires the user to have .NET Framework 4.5.2. on his computer.

Table 957. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/cryptosweettooth.html">https://id-ransomware.blogspot.co.il/2017/01/cryptosweettooth.html</a>

## Kaandsona Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The word Kaandsona is Estonian, therefore the creator is probably from Estonia. Crashes before it encrypts

Kaandsona Ransomware is also known as:

- RansomTroll Ransomware
- Käändsõna Ransomware

*Table 958. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/kaandsona-ransomtroll.html">https://id-ransomware.blogspot.co.il/2017/01/kaandsona-ransomtroll.html</a>
<a href="https://twitter.com/BleepinComputer/status/819927858437099520">https://twitter.com/BleepinComputer/status/819927858437099520</a>

## LambdaLocker Ransomware

It's directed to English and Chinese speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Python Ransomware

*Table 959. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/lambdalocker.html">https://id-ransomware.blogspot.co.il/2017/01/lambdalocker.html</a>
<a href="http://cfoc.org/how-to-restore-files-affected-by-the-lambdalocker-ransomware/">http://cfoc.org/how-to-restore-files-affected-by-the-lambdalocker-ransomware/</a>

## NMoreia 2.0 Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

NMoreia 2.0 Ransomware is also known as:

- HakunaMatataRansomware

*Table 960. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/hakunamatata.html">https://id-ransomware.blogspot.co.il/2017/01/hakunamatata.html</a>
<a href="https://id-ransomware.blogspot.co.il/2016_03_01_archive.html">https://id-ransomware.blogspot.co.il/2016_03_01_archive.html</a>

## Marlboro Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Ransom is .2 bitcoin, however there is no point of even trying to pay, since this damage is irreversible. Once the ransom is paid the hacker does not return decrypt the files. Another name is DeMarlboro and it is written in language C++. Pretend to encrypt using RSA-2048 and AES-128 (really it's just XOR)

Table 961. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/marlboro.html">https://id-ransomware.blogspot.co.il/2017/01/marlboro.html</a>
<a href="https://decrypter.emsisoft.com/marlboro">https://decrypter.emsisoft.com/marlboro</a>
<a href="https://www.bleepingcomputer.com/news/security/marlboro-ransomware-defeated-in-one-day/">https://www.bleepingcomputer.com/news/security/marlboro-ransomware-defeated-in-one-day/</a>

## Spora Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Sample of a spam email with a viral attachment: [https://4.bp.blogspot.com/-KkJXiHG80S0/WHX4TBpkamI/AAAAAAAAADDg/F\\_bN796ndMYnzfUsgSWMXhRxFf3Ic-HtACLcB/s1600/spam-email.png](https://4.bp.blogspot.com/-KkJXiHG80S0/WHX4TBpkamI/AAAAAAAAADDg/F_bN796ndMYnzfUsgSWMXhRxFf3Ic-HtACLcB/s1600/spam-email.png)

Table 962. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/spora-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/spora-ransomware.html</a>
<a href="https://blog.gdatasoftware.com/2017/01/29442-spora-worm-and-ransomware">https://blog.gdatasoftware.com/2017/01/29442-spora-worm-and-ransomware</a>
<a href="http://blog.emsisoft.com/2017/01/10/from-darknet-with-love-meet-spora-ransomware/">http://blog.emsisoft.com/2017/01/10/from-darknet-with-love-meet-spora-ransomware/</a>

## CryptoKill Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The files get encrypted, but the decrypt key is not available. NO POINT OF PAYING THE RANSOM, THE FILES WILL NOT BE RETURNED.

Table 963. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/cryptokill-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/cryptokill-ransomware.html</a>

## All\_Your\_Documents Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office,

Open Office, pictures, videos, shared online files etc..

Table 964. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/allyourdocuments-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/allyourdocuments-ransomware.html</a>

## SerbRansom 2017 Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The ransom is 500\$ in bitcoins. The name of the hacker is R4z0rx0r Serbian Hacker.

Table 965. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/serbransom-2017.html">https://id-ransomware.blogspot.co.il/2017/02/serbransom-2017.html</a>
<a href="https://www.bleepingcomputer.com/news/security/ultranationalist-developer-behind-serbransom-ransomware/">https://www.bleepingcomputer.com/news/security/ultranationalist-developer-behind-serbransom-ransomware/</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-february-10th-2017-serpent-spora-id-ransomware/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-february-10th-2017-serpent-spora-id-ransomware/</a>
<a href="https://twitter.com/malwrhunterteam/status/830116190873849856">https://twitter.com/malwrhunterteam/status/830116190873849856</a>

## Fadesoft Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The ransom is 0.33 bitcoins.

Table 966. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/fadesoft-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/fadesoft-ransomware.html</a>
<a href="https://twitter.com/malwrhunterteam/status/829768819031805953">https://twitter.com/malwrhunterteam/status/829768819031805953</a>
<a href="https://twitter.com/malwrhunterteam/status/838700700586684416">https://twitter.com/malwrhunterteam/status/838700700586684416</a>

## HugeMe Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 967. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/hugeme-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/hugeme-ransomware.html</a>



<https://www.ozbargain.com.au/node/228888?page=3>

<https://id-ransomware.blogspot.co.il/2016/04/magic-ransomware.html>

## DynA-Crypt Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

DynA-Crypt Ransomware is also known as:

- DynA CryptoLocker Ransomware

*Table 968. Table References*

Links

<https://id-ransomware.blogspot.co.il/2017/02/dyna-crypt-ransomware.html>

<https://www.bleepingcomputer.com/news/security/dyna-crypt-not-only-encrypts-your-files-but-also-steals-your-info/>

## Serpent 2017 Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Serpent 2017 Ransomware is also known as:

- Serpent Danish Ransomware

*Table 969. Table References*

Links

<https://id-ransomware.blogspot.co.il/2017/02/serpent-danish-ransomware.html>

## Erebus 2017 Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 970. Table References*

Links

<https://id-ransomware.blogspot.co.il/2017/02/erebus-2017-ransomware.html>

<https://www.bleepingcomputer.com/news/security/erebus-ransomware-utilizes-a-uac-bypass-and-request-a-90-ransom-payment/>

## Cyber Drill Exercise

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Cyber Drill Exercise is also known as:

- Ransomuhahawhere

*Table 971. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/ransomuhahawhere.html">https://id-ransomware.blogspot.co.il/2017/02/ransomuhahawhere.html</a>

## Cancer Ransomware FAKE

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. This is a trollware that does not encrypt your files but makes your computer act crazy (like in the video in the link below). It is meant to be annoying and it is hard to erase from your PC, but possible.

*Table 972. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/cancer-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/cancer-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/watch-your-computer-go-bonkers-with-cancer-trollware/">https://www.bleepingcomputer.com/news/security/watch-your-computer-go-bonkers-with-cancer-trollware/</a>

## UpdateHost Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Poses as Microsoft Copyright 2017 and requests ransom in bitcoins.

*Table 973. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/02/updatehost-ransomware.html">https://id-ransomware.blogspot.co.il/2017/02/updatehost-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/startups/Windows_Update_Host-16362.html">https://www.bleepingcomputer.com/startups/Windows_Update_Host-16362.html</a>

## Nemesis Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Ransom is 10 bitcoins.

Table 974. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/nemesis-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/nemesis-ransomware.html</a>

## Evil Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Domain KZ is used, therefore it is assumed that the decrypter is from Kazakhstan. Coded in Javascript

Evil Ransomware is also known as:

- File0Locked KZ Ransomware

Table 975. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/evil-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/evil-ransomware.html</a>
<a href="http://www.enigmasoftware.com/evilransomware-removal/">http://www.enigmasoftware.com/evilransomware-removal/</a>
<a href="http://usproins.com/evil-ransomware-is-lurking/">http://usproins.com/evil-ransomware-is-lurking/</a>
<a href="https://twitter.com/jiriavirlab/status/818443491713884161">https://twitter.com/jiriavirlab/status/818443491713884161</a>
<a href="https://twitter.com/PolarToffee/status/826508611878793219">https://twitter.com/PolarToffee/status/826508611878793219</a>

## Ocelot Ransomware (FAKE RANSOMWARE)

It's directed to English speaking users, therefore is able to infect worldwide. This is a fake ransomware. Your files are not really encrypted, however the attacker does ask for a ransom of .03 bitcoins. It is still dangerous even though it is fake, he still go through to your computer.

Ocelot Ransomware (FAKE RANSOMWARE) is also known as:

- Ocelot Locker Ransomware

Table 976. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/ocelot-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/ocelot-ransomware.html</a>
<a href="https://twitter.com/malwrhunterteam/status/817648547231371264">https://twitter.com/malwrhunterteam/status/817648547231371264</a>

## SkyName Ransomware

It's directed to Czechoslovakianspeaking users. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Based on HiddenTear

SkyName Ransomware is also known as:

- Blablaba Ransomware

Table 977. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/skynome-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/skynome-ransomware.html</a>
<a href="https://twitter.com/malwrhunterteam/status/817079028725190656">https://twitter.com/malwrhunterteam/status/817079028725190656</a>

## MafiaWare Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Ransom is 155\$ inbitcoins. Creator of ransomware is called Mafia. Based on HiddenTear

MafiaWare Ransomware is also known as:

- Depsex Ransomware

Table 978. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/mafiaaware.html">https://id-ransomware.blogspot.co.il/2017/01/mafiaaware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-january-6th-2017-fsociety-mongodb-pseudo-darkeech-and-more/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-january-6th-2017-fsociety-mongodb-pseudo-darkeech-and-more/</a>
<a href="https://twitter.com/BleepinComputer/status/817069320937345024">https://twitter.com/BleepinComputer/status/817069320937345024</a>

## Globe3 Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Ransom is 3 bitcoins. Extension depends on the config file. It seems Globe is a ransomware kit.

Globe3 Ransomware is also known as:

- Purge Ransomware

Table 979. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/globe3-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/globe3-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/forums/t/624518/globe-ransomware-help-and-support-purge-extension-how-to-restore-fileshta/">https://www.bleepingcomputer.com/forums/t/624518/globe-ransomware-help-and-support-purge-extension-how-to-restore-fileshta/</a>
<a href="https://www.bleepingcomputer.com/news/security/the-globe-ransomware-wants-to-purge-your-files/">https://www.bleepingcomputer.com/news/security/the-globe-ransomware-wants-to-purge-your-files/</a>
<a href="https://decryptors.blogspot.co.il/2017/01/globe3-decrypter.html">https://decryptors.blogspot.co.il/2017/01/globe3-decrypter.html</a>
<a href="https://decrypter.emsisoft.com/globe3">https://decrypter.emsisoft.com/globe3</a>

# BleedGreen Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Ransom is 500\$ in bitcoins. Requires .NET Framework 4.0. Gets into your startup system and sends you notes like the one below:  
[https://4.bp.blogspot.com/-xrr6aoB\\_giw/WG1UrGpmZJI/AAAAAAAAAC-Q/KtKdQP6iLY4LHaHgudF5dKs6i1JHQOBmgCLcB/s1600/green1.jpg](https://4.bp.blogspot.com/-xrr6aoB_giw/WG1UrGpmZJI/AAAAAAAAAC-Q/KtKdQP6iLY4LHaHgudF5dKs6i1JHQOBmgCLcB/s1600/green1.jpg)

BleedGreen Ransomware is also known as:

- FireCrypt Ransomware

*Table 980. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/bleedgreen-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/bleedgreen-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/firecrypt-ransomware-comes-with-a-ddos-component/">https://www.bleepingcomputer.com/news/security/firecrypt-ransomware-comes-with-a-ddos-component/</a>

# BTCamant Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Original name is Mission 1996 or Mission: "Impossible" (1996) (like the movie)

*Table 981. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/btcamant.html">https://id-ransomware.blogspot.co.il/2017/01/btcamant.html</a>

# X3M Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. It is also possible to break in using RDP Windows with the help of Pass-the-Hash system, PuTTY, mRemoteNG, TightVNC, Chrome Remote Desktop, modified version of TeamViewer, AnyDesk, AmmyAdmin, LiteManager, Radmin and others. Ransom is 700\$ in Bitcoins.

*Table 982. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/x3m-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/x3m-ransomware.html</a>

## GOG Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 983. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/gog-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/gog-ransomware.html</a>
<a href="https://twitter.com/BleepinComputer/status/816112218815266816">https://twitter.com/BleepinComputer/status/816112218815266816</a>

## EdgeLocker

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Ransom is 0.1 Bitcoins. Original name is TrojanRansom.

Table 984. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/edgelocker-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/edgelocker-ransomware.html</a>
<a href="https://twitter.com/BleepinComputer/status/815392891338194945">https://twitter.com/BleepinComputer/status/815392891338194945</a>

## Red Alert

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Fake name: Microsoft Corporation. Based on HiddenTear

Table 985. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/red-alert-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/red-alert-ransomware.html</a>
<a href="https://twitter.com/JaromirHorejsi/status/815557601312329728">https://twitter.com/JaromirHorejsi/status/815557601312329728</a>

## First

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 986. Table References

Links
-------

<https://id-ransomware.blogspot.co.il/2017/01/first-ransomware.html>

## XCrypt Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Written on Delphi. The user requests the victim to get in touch with him through ICQ to get the ransom and return the files.

Table 987. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/xcrypt-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/xcrypt-ransomware.html</a>
<a href="https://twitter.com/JakubKroustek/status/825790584971472902">https://twitter.com/JakubKroustek/status/825790584971472902</a>

## 7Zipper Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 988. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/7zipper-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/7zipper-ransomware.html</a>
<a href="https://1.bp.blogspot.com/-ClM0LCPjQuk/WI-BgHTpdNI/AAAAAAAAADc8/JyEQ8-pcJmsXIntuP-MMdE-pohVncxTXQCLcB/s1600/7-zip-logo.png">https://1.bp.blogspot.com/-ClM0LCPjQuk/WI-BgHTpdNI/AAAAAAAAADc8/JyEQ8-pcJmsXIntuP-MMdE-pohVncxTXQCLcB/s1600/7-zip-logo.png</a>

## Zyka Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Ransom is 170\$ or EUR in Bitcoins.

Table 989. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/zyka-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/zyka-ransomware.html</a>
<a href="https://www.pcrisk.com/removal-guides/10899-zyka-ransomware">https://www.pcrisk.com/removal-guides/10899-zyka-ransomware</a>
<a href="https://download.bleepingcomputer.com/demonslay335/StupidDecrypter.zip">https://download.bleepingcomputer.com/demonslay335/StupidDecrypter.zip</a>
<a href="https://twitter.com/GrujaRS/status/826153382557712385">https://twitter.com/GrujaRS/status/826153382557712385</a>

## SureRansom Ransomware (Fake)

It's directed to English speaking users, therefore is able to strike worldwide. This ransomware does not really encrypt your files. Ransom requested is £50 using credit card.

Table 990. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/sureransom-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/sureransom-ransomware.html</a>
<a href="http://www.forbes.com/sites/leemathews/2017/01/27/fake-ransomware-is-tricking-people-into-paying/#777faed0381c">http://www.forbes.com/sites/leemathews/2017/01/27/fake-ransomware-is-tricking-people-into-paying/#777faed0381c</a>

## Netflix Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. This ransomware uses the known online library as a decoy. It poses as Netflix Code generator for Netflix login, but instead encrypts your files. The ransom is 100\$ in Bitcoins.

Table 991. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2017/01/netflix-ransomware.html">https://id-ransomware.blogspot.co.il/2017/01/netflix-ransomware.html</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/netflix-scam-delivers-ransomware/">http://blog.trendmicro.com/trendlabs-security-intelligence/netflix-scam-delivers-ransomware/</a>
<a href="https://www.bleepingcomputer.com/news/security/rogue-netflix-app-spreads-netix-ransomware-that-targets-windows-7-and-10-users/">https://www.bleepingcomputer.com/news/security/rogue-netflix-app-spreads-netix-ransomware-that-targets-windows-7-and-10-users/</a>
<a href="http://www.darkreading.com/attacks-breaches/netflix-scam-spreads-ransomware/d/d-id/1328012">http://www.darkreading.com/attacks-breaches/netflix-scam-spreads-ransomware/d/d-id/1328012</a>
<a href="https://4.bp.blogspot.com/-bQQ4DTIClvA/WJCIh6Uq2nI/AAAAAAAAADfY/hB5HcjuGgh8rRJKeLHoIRz3Ezth22-wCEw/s1600/form1.jpg">https://4.bp.blogspot.com/-bQQ4DTIClvA/WJCIh6Uq2nI/AAAAAAAAADfY/hB5HcjuGgh8rRJKeLHoIRz3Ezth22-wCEw/s1600/form1.jpg</a> <a href="https://4.bp.blogspot.com/-bQQ4DTIClvA/WJCIh6Uq2nI/AAAAAAAAADfY/hB5HcjuGgh8rRJKeLHoIRz3Ezth22-wCEw/s1600/form1.jpg">[https://4.bp.blogspot.com/-bQQ4DTIClvA/WJCIh6Uq2nI/AAAAAAAAADfY/hB5HcjuGgh8rRJKeLHoIRz3Ezth22-wCEw/s1600/form1.jpg]</a>
<a href="https://4.bp.blogspot.com/-ZnWdPDprJOG/WJCPeCtP4HI/AAAAAAAAADfw/kR0ifl1naSwTAWSuOPiw8ZCPr0tSiz1CgCLcB/s1600/netflix-akk.png">https://4.bp.blogspot.com/-ZnWdPDprJOG/WJCPeCtP4HI/AAAAAAAAADfw/kR0ifl1naSwTAWSuOPiw8ZCPr0tSiz1CgCLcB/s1600/netflix-akk.png</a>

## Merry Christmas

It's directed to English and Italian speaking users, therefore is able to infect worldwide. Most attacks are on organizations and servers. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. They pose as a Consumer complaint notification that's coming from Federal Trade Commission from USA, with an attached file called "complaint.pdf". Written in Delphi by hacker MicrRP.

Merry Christmas is also known as:

- Merry X-Mas
- MRCR

Table 992. Table References

Links
-------



<a href="https://id-ransomware.blogspot.co.il/2016/12/mrcr1-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/mrcr1-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/-merry-christmas-ransomware-now-steals-user-private-data-via-diamondfox-malware/">https://www.bleepingcomputer.com/news/security/-merry-christmas-ransomware-now-steals-user-private-data-via-diamondfox-malware/</a>
<a href="http://www.zdnet.com/article/not-such-a-merry-christmas-the-ransomware-that-also-steals-user-data/">http://www.zdnet.com/article/not-such-a-merry-christmas-the-ransomware-that-also-steals-user-data/</a>
<a href="https://www.bleepingcomputer.com/news/security/merry-christmas-ransomware-and-its-dev-comodosecurity-not-bringing-holiday-cheer/">https://www.bleepingcomputer.com/news/security/merry-christmas-ransomware-and-its-dev-comodosecurity-not-bringing-holiday-cheer/</a>
<a href="https://decrypter.emsisoft.com/mrcr">https://decrypter.emsisoft.com/mrcr</a>

## Seoirse Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Seoirse is how in Ireland people say the name George. Ransom is 0.5 Bitcoins.

*Table 993. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/seoirse-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/seoirse-ransomware.html</a>

## KillDisk Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Every file is encrypted with a personal AES-key, and then AES-key encrypts with a RSA-1028 key. Hacking by TeleBots (Sandworm). Goes under a fake name: Update center or Microsoft Update center.

*Table 994. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/killdisk-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/killdisk-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/killdisk-ransomware-now-targets-linux-prevents-boot-up-has-faulty-encryption/">https://www.bleepingcomputer.com/news/security/killdisk-ransomware-now-targets-linux-prevents-boot-up-has-faulty-encryption/</a>
<a href="https://www.bleepingcomputer.com/news/security/killdisk-disk-wiping-malware-adds-ransomware-component/">https://www.bleepingcomputer.com/news/security/killdisk-disk-wiping-malware-adds-ransomware-component/</a>
<a href="http://www.zdnet.com/article/247000-killdisk-ransomware-demands-a-fortune-forgets-to-unlock-files/">http://www.zdnet.com/article/247000-killdisk-ransomware-demands-a-fortune-forgets-to-unlock-files/</a>
<a href="http://www.securityweek.com/destructive-killdisk-malware-turns-ransomware">http://www.securityweek.com/destructive-killdisk-malware-turns-ransomware</a>
<a href="http://www.welivesecurity.com/2017/01/05/killdisk-now-targeting-linux-demands-250k-ransom-cant-decrypt/">http://www.welivesecurity.com/2017/01/05/killdisk-now-targeting-linux-demands-250k-ransom-cant-decrypt/</a>
<a href="https://cyberx-labs.com/en/blog/new-killdisk-malware-brings-ransomware-into-industrial-domain/">https://cyberx-labs.com/en/blog/new-killdisk-malware-brings-ransomware-into-industrial-domain/</a>

## DeriaLock Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Maker is arizonacode and ransom amount is 20-30\$. If the victim decides to pay the ransom, he will have to copy HWID and then speak to the hacker on Skype and forward him the payment.

*Table 995. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/derialock-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/derialock-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/new-derialock-ransomware-active-on-christmas-includes-an-unlock-all-command/">https://www.bleepingcomputer.com/news/security/new-derialock-ransomware-active-on-christmas-includes-an-unlock-all-command/</a>

## BadEncrypt Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 996. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/badencrypt-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/badencrypt-ransomware.html</a>
<a href="https://twitter.com/demonslay335/status/813064189719805952">https://twitter.com/demonslay335/status/813064189719805952</a>

## AdamLocker Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The name of the creator is puff69.

*Table 997. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/adamlocker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/adamlocker-ransomware.html</a>

## Alphabet Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. This ransomware poses as Windows 10 Critical Update Service. Offers you to update your Windows 10, but instead encrypts your files. For successful attack, the victim must have .NET Framework 4.5.2 installed on him computer.

*Table 998. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/alphabet-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/alphabet-ransomware.html</a>
<a href="https://twitter.com/PolarToffee/status/812331918633172992">https://twitter.com/PolarToffee/status/812331918633172992</a>

## KoKoKrypt Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread by its creator in forums. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files and documents and more. The ransom is 0.1 bitcoins within 72 hours. Uses Windows Update as a decoy. Creator: Talnaci Alexandru

KoKoKrypt Ransomware is also known as:

- KokoLocker Ransomware

*Table 999. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/kokokrypt-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/kokokrypt-ransomware.html</a>
<a href="http://removevirusadware.com/tips-for-removeing-kokokrypt-ransomware/">http://removevirusadware.com/tips-for-removeing-kokokrypt-ransomware/</a>

## L33TAF Locker Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Ransom is 0.5 bitcoins. The name of the creator is staffttt, he also created Fake CryptoLocker

*Table 1000. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/l33taf-locker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/l33taf-locker-ransomware.html</a>

## PClock4 Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam (for example: "you have a criminal case against you"), fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

PClock4 Ransomware is also known as:

- PClock SysGop Ransomware

*Table 1001. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/pclock4-sysgop-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/pclock4-sysgop-ransomware.html</a>

## Guster Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. This ransomware uses VBS-script to send a voice message as the first few lines of the note.

Table 1002. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/guster-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/guster-ransomware.html</a>
<a href="https://twitter.com/BleepinComputer/status/812131324979007492">https://twitter.com/BleepinComputer/status/812131324979007492</a>

## Roga

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The hacker requests the ransom in Play Store cards.

<https://3.bp.blogspot.com/-CIUef8T55f4/WGKb8U4GeaI/AAAAAAAAACzg/UFD0X2sORHYTVRNBSoqd5q7TBrOblQHmgCLcB/s1600/site.png>

Table 1003. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/roga-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/roga-ransomware.html</a>

## CryptoLocker3 Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Creator is staffttt and the ransom is 0.5 bitcoins.

CryptoLocker3 Ransomware is also known as:

- Fake CryptoLocker

Table 1004. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/cryptolocker3-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/cryptolocker3-ransomware.html</a>

## ProposalCrypt Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The ransom is 1.0 bitcoins.

Table 1005. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/proposalcrypt-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/proposalcrypt-ransomware.html</a>
<a href="http://www.archersecuritygroup.com/what-is-ransomware/">http://www.archersecuritygroup.com/what-is-ransomware/</a>
<a href="https://twitter.com/demonslay335/status/812002960083394560">https://twitter.com/demonslay335/status/812002960083394560</a>
<a href="https://twitter.com/malwrhunterteam/status/811613888705859586">https://twitter.com/malwrhunterteam/status/811613888705859586</a>

## Manifestus Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The hacker demands 0.2 bitcoins. The ransomware poses as a Window update.

Table 1006. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/manifestus-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/manifestus-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-december-23rd-2016-cryptxxx-koolova-cerber-and-more/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-december-23rd-2016-cryptxxx-koolova-cerber-and-more/</a>
<a href="https://twitter.com/struppigel/status/811587154983981056">https://twitter.com/struppigel/status/811587154983981056</a>

## EnkripsiPC Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The name of the hacker is humanpuff69 and he requests 0.5 bitcoins. The encryption password is based on the computer name

EnkripsiPC Ransomware is also known as:

- IDRANSOMv3
- Manifestus

Table 1007. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/enkripsipc-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/enkripsipc-ransomware.html</a>
<a href="https://twitter.com/demonslay335/status/811343914712100872">https://twitter.com/demonslay335/status/811343914712100872</a>
<a href="https://twitter.com/BleepinComputer/status/811264254481494016">https://twitter.com/BleepinComputer/status/811264254481494016</a>
<a href="https://twitter.com/struppigel/status/811587154983981056">https://twitter.com/struppigel/status/811587154983981056</a>

## BrainCrypt Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email

spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. So far the victims are from Belarus and Germany.

*Table 1008. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/braincrypt-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/braincrypt-ransomware.html</a>

## MSN CryptoLocker Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Ransom is 0.2 bitcoins.

*Table 1009. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/msn-cryptolocker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/msn-cryptolocker-ransomware.html</a>
<a href="https://twitter.com/struppigel/status/810766686005719040">https://twitter.com/struppigel/status/810766686005719040</a>

## CryptoBlock Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The ransom is in the amount is 0.3 bitcoins. The ransomware is disguises themselves as Adobe Systems, Incorporated. RaaS

*Table 1010. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/cryptoblock-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/cryptoblock-ransomware.html</a>
<a href="https://twitter.com/drProct0r/status/810500976415281154">https://twitter.com/drProct0r/status/810500976415281154</a>

## AES-NI Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1011. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/aes-ni-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/aes-ni-ransomware.html</a>

## Koolova Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email

spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The hacker of this ransomware tends to make lots of spelling errors in his requests. With Italian text that only targets the Test folder on the user's desktop

Table 1012. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/koolova-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/koolova-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/koolova-ransomware-decrypts-for-free-if-you-read-two-articles-about-ransomware/">https://www.bleepingcomputer.com/news/security/koolova-ransomware-decrypts-for-free-if-you-read-two-articles-about-ransomware/</a>

## Fake Globe Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc... The ransom is 1bitcoin.

Fake Globe Ransomware is also known as:

- Globe Imposter
- GlobeImposter

Table 1013. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/fake-globe-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/fake-globe-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-december-30th-2016-infected-tvs-and-open-source-ransomware-sucks/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-december-30th-2016-infected-tvs-and-open-source-ransomware-sucks/</a>
<a href="https://twitter.com/fwosar/status/812421183245287424">https://twitter.com/fwosar/status/812421183245287424</a>
<a href="https://decrypter.emsisoft.com/globeimposter">https://decrypter.emsisoft.com/globeimposter</a>
<a href="https://twitter.com/malwrhunterteam/status/809795402421641216">https://twitter.com/malwrhunterteam/status/809795402421641216</a>

## V8Locker Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc...

Table 1014. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/v8locker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/v8locker-ransomware.html</a>

## Cryptorium (Fake Ransomware)

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email

spam, fake updates, attachments and so on. It SUPPOSEDLY encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc., however your files are not really encrypted, only the names are changed.

Table 1015. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/cryptorium-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/cryptorium-ransomware.html</a>

## Antihacker2017 Ransomware

It's directed to Russian speaking users, there fore is able to infect mostly the old USSR countries. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc ... The hacker goes by the nickname Antihacker and requests the victim to send him an email for the decryption. He does not request any money only a warning about looking at porn (gay, incest and rape porn to be specific).

Table 1016. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/antihacker2017-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/antihacker2017-ransomware.html</a>

## CIA Special Agent 767 Ransomware (FAKE!!!)

It's directed to English speaking users, therefore is able to infect users all over the world. It is spread using email spam, fake updates, attachments and so on. It SUPPOSEDLY encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc... Your files are not really encrypted and nothing actually happens, however the hacker does ask the victim to pay a sum of 100\$, after 5 days the sum goes up to 250\$ and thereafter to 500\$. After the payment is received, the victim gets the following message informing him that he has been fooled and he simply needed to delete the note. <https://4.bp.blogspot.com/-T8iSbbGOz84/WFGZEbuRfCI/AAAAAAAAACm0/SO8SrwX2UIM3FPZcZl7W76oSDCsnq2vfgCPcB/s1600/code2.jpg>

Table 1017. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/cia-special-agent-767-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/cia-special-agent-767-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/virus-removal/remove-cia-special-agent-767-screen-locker">https://www.bleepingcomputer.com/virus-removal/remove-cia-special-agent-767-screen-locker</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-december-16th-2016-samas-no-more-ransom-screen-lockers-and-more/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-december-16th-2016-samas-no-more-ransom-screen-lockers-and-more/</a>
<a href="https://guides.yoosecurity.com/cia-special-agent-767-virus-locks-your-pc-screen-how-to-unlock/">https://guides.yoosecurity.com/cia-special-agent-767-virus-locks-your-pc-screen-how-to-unlock/</a>

## LoveServer Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc... This hacker request your IP address in return



for the decryption.

*Table 1018. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/loveserver-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/loveserver-ransomware.html</a>

## Kraken Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc... The hacker requests 2 bitcoins in return for the files.

*Table 1019. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/kraken-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/kraken-ransomware.html</a>

## Antix Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc... The ransom is 0.25 bitcoins and the nickname of the hacker is FRC 2016.

*Table 1020. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/antix-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/antix-ransomware.html</a>

## PayDay Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc... The ransom is R\$950 which is due in 5 days. (R\$ is a Brazilian currency) Based off of Hidden-Tear

*Table 1021. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/payday-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/payday-ransomware.html</a>
<a href="https://twitter.com/BleepinComputer/status/808316635094380544">https://twitter.com/BleepinComputer/status/808316635094380544</a>

## Slimhem Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is NOT spread using email spam, fake updates, attachments and so on. It simply places a decrypt file on your computer.

Table 1022. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/slimhem-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/slimhem-ransomware.html</a>

## M4N1F3STO Ransomware (FAKE!!!!!!)

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc... FILES DON'T REALLY GET DELETED NOR DO THEY GET ENCRYPTED!!!!!!!

Table 1023. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/m4n1f3sto-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/m4n1f3sto-ransomware.html</a>

## Dale Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc... CHIP > DALE

Dale Ransomware is also known as:

- DaleLocker Ransomware

## UltraLocker Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc... Based on the idiotic open-source ransomware called CryptoWire

Table 1024. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/ultralocker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/ultralocker-ransomware.html</a>
<a href="https://twitter.com/struppigel/status/807161652663742465">https://twitter.com/struppigel/status/807161652663742465</a>

## AES\_KEY\_GEN\_ASSIST Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc...

Table 1025. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/aeskeygenassist-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/aeskeygenassist-ransomware.html</a>
<a href="https://id-ransomware.blogspot.co.il/2016/09/dxxd-ransomware.html">https://id-ransomware.blogspot.co.il/2016/09/dxxd-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/forums/t/634258/aes-key-gen-assistprotonmailcom-help-support/">https://www.bleepingcomputer.com/forums/t/634258/aes-key-gen-assistprotonmailcom-help-support/</a>

## Code Virus Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1026. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/code-virus-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/code-virus-ransomware.html</a>

## FLKR Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1027. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/flkr-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/flkr-ransomware.html</a>

## PopCorn Time Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. These hackers claim to be students from Syria. This ransomware poses as the popular torrent movie screener called PopCorn. These criminals give you the chance to retrieve your files "for free" by spreading this virus to others. Like shown in the note below: <https://www.bleepstatic.com/images/news/ransomware/p/Popcorn-time/refer-a-friend.png>

*Table 1028. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/popcorn-time-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/popcorn-time-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/new-scheme-spread-popcorn-time-ransomware-get-chance-of-free-decryption-key/">https://www.bleepingcomputer.com/news/security/new-scheme-spread-popcorn-time-ransomware-get-chance-of-free-decryption-key/</a>

## HackedLocker Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc... NO POINT OF PAYING THE RANSOM—THE HACKER DOES NOT GIVE A DECRYPT AFTERWARDS.

Table 1029. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/hackedlocker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/hackedlocker-ransomware.html</a>

## GoldenEye Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc...

Table 1030. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/goldeneye-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/goldeneye-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/petya-ransomware-returns-with-goldeneye-version-continuing-james-bond-theme/">https://www.bleepingcomputer.com/news/security/petya-ransomware-returns-with-goldeneye-version-continuing-james-bond-theme/</a>
<a href="https://www.bleepingcomputer.com/forums/t/634778/golden-eye-virus/">https://www.bleepingcomputer.com/forums/t/634778/golden-eye-virus/</a>

## Sage Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc...

Table 1031. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/sage-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/sage-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/forums/t/634978/sage-file-sample-extension-sage/">https://www.bleepingcomputer.com/forums/t/634978/sage-file-sample-extension-sage/</a>
<a href="https://www.bleepingcomputer.com/forums/t/634747/sage-20-ransomware-sage-support-help-topic/">https://www.bleepingcomputer.com/forums/t/634747/sage-20-ransomware-sage-support-help-topic/</a>

## SQ\_ Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc... This hacker requests 4 bitcoins for ransom.

SQ\_ Ransomware is also known as:

- VO\_Ransomware

Table 1032. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/12/sq-vo-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/sq-vo-ransomware.html</a>

## Matrix

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc...

Matrix is also known as:

- Malta Ransomware

Table 1033. Table References

Links
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-december-2nd-2016-screenlockers-kangaroo-the-sfmta-and-more/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-december-2nd-2016-screenlockers-kangaroo-the-sfmta-and-more/</a>
<a href="https://id-ransomware.blogspot.co.il/2016/12/matrix-ransomware.html">https://id-ransomware.blogspot.co.il/2016/12/matrix-ransomware.html</a>
<a href="https://twitter.com/rommeljovent17/status/804251901529231360">https://twitter.com/rommeljovent17/status/804251901529231360</a>

## Satan666 Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 1034. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/satan666-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/satan666-ransomware.html</a>

## RIP (Phoenix) Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Based on HiddenTear

Table 1035. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/rip-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/rip-ransomware.html</a>
<a href="https://twitter.com/BleepinComputer/status/804810315456200704">https://twitter.com/BleepinComputer/status/804810315456200704</a>

## Locked-In Ransomware or NoValid Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Based on RemindMe

Table 1036. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/novalid-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/novalid-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/forums/t/634754/locked-in-ransomware-help-support-restore-corrupted-fileshtml/">https://www.bleepingcomputer.com/forums/t/634754/locked-in-ransomware-help-support-restore-corrupted-fileshtml/</a>
<a href="https://twitter.com/struppigel/status/807169774098796544">https://twitter.com/struppigel/status/807169774098796544</a>

## Chartwig Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 1037. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/chartwig-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/chartwig-ransomware.html</a>

## RenLocker Ransomware (FAKE)

It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The files don't actually get encrypted, their names get changed using this formula: [number][.crypter]

Table 1038. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/renlocker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/renlocker-ransomware.html</a>

## Thanksgiving Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 1039. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/thanksgiving-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/thanksgiving-ransomware.html</a>
<a href="https://id-ransomware.blogspot.co.il/2016/07/stampado-ransomware-1.html">https://id-ransomware.blogspot.co.il/2016/07/stampado-ransomware-1.html</a>

<https://twitter.com/BleepinComputer/status/801486420368093184>

## CockBlocker Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1040. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/cockblocker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/cockblocker-ransomware.html</a>
<a href="https://twitter.com/jiriatvirlab/status/801910919739674624">https://twitter.com/jiriatvirlab/status/801910919739674624</a>

## Lomix Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Based on the idiotic open-source ransomware called CryptoWire

*Table 1041. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/lomix-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/lomix-ransomware.html</a>
<a href="https://twitter.com/siri_urz/status/801815087082274816">https://twitter.com/siri_urz/status/801815087082274816</a>

## OzozaLocker Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. [https://3.bp.blogspot.com/--jubfYRaRmw/WDaOyZXkAaI/AAAAAAAAACQE/E63a4FnaOfACZ07s1xUiv\\_haxy8cp5YCACLcB/s1600/ozozalocker.png](https://3.bp.blogspot.com/--jubfYRaRmw/WDaOyZXkAaI/AAAAAAAAACQE/E63a4FnaOfACZ07s1xUiv_haxy8cp5YCACLcB/s1600/ozozalocker.png)

*Table 1042. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/ozozalocker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/ozozalocker-ransomware.html</a>
<a href="https://decrypter.emsisoft.com/ozozalocker">https://decrypter.emsisoft.com/ozozalocker</a>
<a href="https://twitter.com/malwrhunterteam/status/801503401867673603">https://twitter.com/malwrhunterteam/status/801503401867673603</a>

## Crypute Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Crypute Ransomware is also known as:

- m0on Ransomware

Table 1043. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/crypute-ransomware-m0on.html">https://id-ransomware.blogspot.co.il/2016/11/crypute-ransomware-m0on.html</a>
<a href="https://www.bleepingcomputer.com/virus-removal/threat/ransomware/">https://www.bleepingcomputer.com/virus-removal/threat/ransomware/</a>

## NMoreira Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

NMoreira Ransomware is also known as:

- Fake Maktub Ransomware

Table 1044. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/nmoreira-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/nmoreira-ransomware.html</a>
<a href="https://id-ransomware.blogspot.co.il/2016/10/airacrop-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/airacrop-ransomware.html</a>

## VindowsLocker Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. The ransom amount is 349.99\$ and the hacker seems to be from India. He disguises himself as Microsoft Support.

Table 1045. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/vindowslocker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/vindowslocker-ransomware.html</a>
<a href="https://malwarebytes.app.box.com/s/gdu18hr17mwqszej3hjlw5m3sw84k8hlph">https://malwarebytes.app.box.com/s/gdu18hr17mwqszej3hjlw5m3sw84k8hlph</a>
<a href="https://rol.im/VindowsUnlocker.zip">https://rol.im/VindowsUnlocker.zip</a>
<a href="https://twitter.com/JakubKroustek/status/800729944112427008">https://twitter.com/JakubKroustek/status/800729944112427008</a>
<a href="https://www.bleepingcomputer.com/news/security/vindowslocker-ransomware-mimics-tech-support-scam-not-the-other-way-around/">https://www.bleepingcomputer.com/news/security/vindowslocker-ransomware-mimics-tech-support-scam-not-the-other-way-around/</a>

## Donald Trump 2 Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office,



Open Office, pictures, videos, shared online files etc.. Here is the original ransomware under this name: <http://id-ransomware.blogspot.co.il/2016/09/donald-trump-ransomware.html>

Table 1046. Table References

Links
<a href="http://id-ransomware.blogspot.co.il/2016/09/donald-trump-ransomware.html">http://id-ransomware.blogspot.co.il/2016/09/donald-trump-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/the-donald-trump-ransomware-tries-to-build-walls-around-your-files/">https://www.bleepingcomputer.com/news/security/the-donald-trump-ransomware-tries-to-build-walls-around-your-files/</a>

## Nagini Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. Looks for C:\Temp\voldemort.horcrux

Nagini Ransomware is also known as:

- Voldemort Ransomware

Table 1047. Table References

Links
<a href="http://id-ransomware.blogspot.co.il/2016/09/nagini-voldemort-ransomware.html">http://id-ransomware.blogspot.co.il/2016/09/nagini-voldemort-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/the-nagini-ransomware-sics-voldemort-on-your-files/">https://www.bleepingcomputer.com/news/security/the-nagini-ransomware-sics-voldemort-on-your-files/</a>

## ShellLocker Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 1048. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/shelllocker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/shelllocker-ransomware.html</a>
<a href="https://twitter.com/JakubKroustek/status/799388289337671680">https://twitter.com/JakubKroustek/status/799388289337671680</a>

## Chip Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Chip Ransomware is also known as:

- ChipLocker Ransomware

Table 1049. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/chip-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/chip-ransomware.html</a>
<a href="http://malware-traffic-analysis.net/2016/11/17/index.html">http://malware-traffic-analysis.net/2016/11/17/index.html</a>
<a href="https://www.bleepingcomputer.com/news/security/rig-e-exploit-kit-now-distributing-new-chip-ransomware/">https://www.bleepingcomputer.com/news/security/rig-e-exploit-kit-now-distributing-new-chip-ransomware/</a>

## Dharma Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. CrySiS > Dharma Note: ATTENTION! At the moment, your system is not protected. We can fix it and restore files. To restore the system write to this address: [bitcoin143@india.com](mailto:bitcoin143@india.com). CrySiS variant

Table 1050. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/dharma-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/dharma-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/kaspersky-releases-decryptor-for-the-dharma-ransomware/">https://www.bleepingcomputer.com/news/security/kaspersky-releases-decryptor-for-the-dharma-ransomware/</a>

## Angela Merkel Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 1051. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/angela-merkel-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/angela-merkel-ransomware.html</a>
<a href="https://twitter.com/malwrhunterteam/status/798268218364358656">https://twitter.com/malwrhunterteam/status/798268218364358656</a>

## CryptoLuck Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

CryptoLuck Ransomware is also known as:

- YafunnLocker

Table 1052. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/cryptoluck-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/cryptoluck-ransomware.html</a>
<a href="http://www.bleepingcomputer.com/news/security/cryptoluck-ransomware-being-malvertised-via-rig-e-exploit-kits/">http://www.bleepingcomputer.com/news/security/cryptoluck-ransomware-being-malvertised-via-rig-e-exploit-kits/</a>
<a href="https://twitter.com/malwareforme/status/798258032115322880">https://twitter.com/malwareforme/status/798258032115322880</a>

## Crypton Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Crypton Ransomware is also known as:

- Nemesis
- X3M

*Table 1053. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/crypton-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/crypton-ransomware.html</a>
<a href="https://decrypter.emsisoft.com/crypton">https://decrypter.emsisoft.com/crypton</a>
<a href="https://www.bleepingcomputer.com/news/security/crypton-ransomware-is-here-and-its-not-so-bad/">https://www.bleepingcomputer.com/news/security/crypton-ransomware-is-here-and-its-not-so-bad-/</a>
<a href="https://twitter.com/JakubKroustek/status/829353444632825856">https://twitter.com/JakubKroustek/status/829353444632825856</a>

## Karma Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. pretends to be a Windows optimization program called Windows-TuneUp

*Table 1054. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/karma-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/karma-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/researcher-finds-the-karma-ransomware-being-distributed-via-pay-per-install-network/">https://www.bleepingcomputer.com/news/security/researcher-finds-the-karma-ransomware-being-distributed-via-pay-per-install-network/</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-november-18th-2016-crysis-cryptoluck-chip-and-more/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-november-18th-2016-crysis-cryptoluck-chip-and-more/</a>

## WickedLocker HT Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1055. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/wickedlocker-ht-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/wickedlocker-ht-ransomware.html</a>

## PClock3 Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. CryptoLocker Copycat

PClock3 Ransomware is also known as:

- PClock SuppTeam Ransomware
- WinPlock
- CryptoLocker clone

*Table 1056. Table References*

Links
<a href="https://www.bleepingcomputer.com/news/security/old-cryptolocker-copycat-named-pclock-resurfaces-with-new-attacks/">https://www.bleepingcomputer.com/news/security/old-cryptolocker-copycat-named-pclock-resurfaces-with-new-attacks/</a>
<a href="https://id-ransomware.blogspot.co.il/2016/11/suppteam-ransomware-sysras.html">https://id-ransomware.blogspot.co.il/2016/11/suppteam-ransomware-sysras.html</a>
<a href="http://researchcenter.paloaltonetworks.com/2015/09/updated-pclock-ransomware-still-comes-up-short/">http://researchcenter.paloaltonetworks.com/2015/09/updated-pclock-ransomware-still-comes-up-short/</a>
<a href="https://decrypter.emsisoft.com/">https://decrypter.emsisoft.com/</a>

## Kolobo Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Kolobo Ransomware is also known as:

- Kolobocheq Ransomware

*Table 1057. Table References*

Links
<a href="https://www.ransomware.wiki/tag/kolobo/">https://www.ransomware.wiki/tag/kolobo/</a>
<a href="https://id-ransomware.blogspot.co.il/2016/11/kolobo-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/kolobo-ransomware.html</a>
<a href="https://forum.drweb.com/index.php?showtopic=315142">https://forum.drweb.com/index.php?showtopic=315142</a>

## PaySafeGen (German) Ransomware

This is most likely to affect German speaking users, since the note is written in German. Mostly affects users in German speaking countries. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

PaySafeGen (German) Ransomware is also known as:

- Paysafecard Generator 2016

*Table 1058. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/paysafegen-german-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/paysafegen-german-ransomware.html</a>
<a href="https://twitter.com/JakubKroustek/status/796083768155078656">https://twitter.com/JakubKroustek/status/796083768155078656</a>

## Telecrypt Ransomware

This is most likely to affect Russian speaking users, since the note is written in Russian. Therefore, residents of Russian speaking country are affected. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. The ransomware's authors would request around \$75 from their victims to provide them with a decryptor (payments are accepted via Russian payment services Qiwi or Yandex.Money ). Right from the start, however, researchers suggested that TeleCrypt was written by cybercriminals without advanced skills. Telecrypt will generate a random string to encrypt with that is between 10-20 length and only contain the letters vo,pr,bm,xu,zt,dq.

*Table 1059. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/telecrypt-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/telecrypt-ransomware.html</a>
<a href="http://www.securityweek.com/telecrypt-ransoms-encryption-cracked">http://www.securityweek.com/telecrypt-ransoms-encryption-cracked</a>
<a href="https://malwarebytes.app.box.com/s/kkxwzgbpwe7oh59xqfwcz97uk0q05kp3">https://malwarebytes.app.box.com/s/kkxwzgbpwe7oh59xqfwcz97uk0q05kp3</a>
<a href="https://blog.malwarebytes.com/threat-analysis/2016/11/telecrypt-the-ransomware-abusing-telegram-api-defeated/">https://blog.malwarebytes.com/threat-analysis/2016/11/telecrypt-the-ransomware-abusing-telegram-api-defeated/</a>
<a href="https://securelist.com/blog/research/76558/the-first-cryptor-to-exploit-telegram/">https://securelist.com/blog/research/76558/the-first-cryptor-to-exploit-telegram/</a>

## CerberTear Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 1060. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/cerbertear-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/cerbertear-ransomware.html</a>
<a href="https://www.tripwire.com/state-of-security/security-data-protection/cyber-security/november-2016-month-ransomware/">https://www.tripwire.com/state-of-security/security-data-protection/cyber-security/november-2016-month-ransomware/</a>
<a href="https://twitter.com/struppigel/status/795630452128227333">https://twitter.com/struppigel/status/795630452128227333</a>

## FuckSociety Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Hidden Tear >> APT Ransomware + HYPERLINK "https://id-ransomware.blogspot.ru/2016/05/remindme-ransomware-2.html" "\_blank" RemindMe > FuckSociety

Table 1061. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/fucksociety-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/fucksociety-ransomware.html</a>

## PayDOS Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Batch file; Passcode: AES1014DW256 or RSA1014DJW2048

PayDOS Ransomware is also known as:

- Serpent Ransomware

Table 1062. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/paydos-ransomware-serpent.html">https://id-ransomware.blogspot.co.il/2016/11/paydos-ransomware-serpent.html</a>
<a href="https://www.bleepingcomputer.com/news/security/ransomware-goes-retro-with-paydos-and-serpent-written-as-batch-files/">https://www.bleepingcomputer.com/news/security/ransomware-goes-retro-with-paydos-and-serpent-written-as-batch-files/</a>

<https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-november-4th-2016-cerber-paydos-alcatraz-locker-and-more/>

<https://www.proofpoint.com/us/threat-insight/post/new-serpent-ransomware-targets-danish-speakers>

## zScreenLocker Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1063. Table References*

Links

<https://id-ransomware.blogspot.co.il/2016/11/zscreenlocker-ransomware.html>

<https://www.tripwire.com/state-of-security/security-data-protection/cyber-security/november-2016-month-ransomware/>

<https://twitter.com/struppigel/status/794077145349967872>

## Gremit Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1064. Table References*

Links

<https://id-ransomware.blogspot.co.il/2016/11/gremit-ransomware.html>

<https://twitter.com/struppigel/status/794444032286060544>

<https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-november-4th-2016-cerber-paydos-alcatraz-locker-and-more/>

## Hollycrypt Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1065. Table References*

Links

<https://id-ransomware.blogspot.co.il/2016/11/hollycrypt-ransomware.html>

## BTCLocker Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

BTCLocker Ransomware is also known as:

- BTC Ransomware

*Table 1066. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/btclocker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/btclocker-ransomware.html</a>

## Kangaroo Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. From the developer behind the Apocalypse Ransomware, Fabiansomware, and Esmeralda

*Table 1067. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/kangaroo-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/kangaroo-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/the-kangaroo-ransomware-not-only-encrypts-your-data-but-tries-to-lock-you-out-of-windows/">https://www.bleepingcomputer.com/news/security/the-kangaroo-ransomware-not-only-encrypts-your-data-but-tries-to-lock-you-out-of-windows/</a>

## DummyEncrypter Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1068. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/dummyencrypter-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/dummyencrypter-ransomware.html</a>

## Encryptss77 Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office,



Open Office, pictures, videos, shared online files etc..

Encryptss77 Ransomware is also known as:

- SFX Monster Ransomware

*Table 1069. Table References*

Links
<a href="http://virusinfo.info/showthread.php?t=201710">http://virusinfo.info/showthread.php?t=201710</a>
<a href="https://id-ransomware.blogspot.co.il/2016/11/encryptss77-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/encryptss77-ransomware.html</a>

## WinRarer Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1070. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/winrarer-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/winrarer-ransomware.html</a>

## Russian Globe Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1071. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/russian-globe-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/russian-globe-ransomware.html</a>

## ZeroCrypt Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1072. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/11/zerocrypt-ransomware.html">https://id-ransomware.blogspot.co.il/2016/11/zerocrypt-ransomware.html</a>

## RotorCrypt(RotoCrypt, Tar) Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1073. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/rotorcrypt-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/rotorcrypt-ransomware.html</a>

## Ishtar Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.

*Table 1074. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/ishtar-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/ishtar-ransomware.html</a>

## MasterBuster Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1075. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/masterbuster-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/masterbuster-ransomware.html</a>
<a href="https://twitter.com/struppigel/status/791943837874651136">https://twitter.com/struppigel/status/791943837874651136</a>

## JackPot Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

JackPot Ransomware is also known as:

- Jack.Pot Ransomware

Table 1076. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/jackpot-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/jackpot-ransomware.html</a>
<a href="https://twitter.com/struppigel/status/791639214152617985">https://twitter.com/struppigel/status/791639214152617985</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-october-28-2016-locky-angry-duck-and-more/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-october-28-2016-locky-angry-duck-and-more/</a>

## ONYX Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Georgian ransomware

Table 1077. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/onyx-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/onyx-ransomware.html</a>
<a href="https://twitter.com/struppigel/status/791557636164558848">https://twitter.com/struppigel/status/791557636164558848</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-october-28-2016-locky-angry-duck-and-more/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-october-28-2016-locky-angry-duck-and-more/</a>

## IFN643 Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 1078. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/ifn643-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/ifn643-ransomware.html</a>
<a href="https://twitter.com/struppigel/status/791576159960072192">https://twitter.com/struppigel/status/791576159960072192</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-october-28-2016-locky-angry-duck-and-more/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-october-28-2016-locky-angry-duck-and-more/</a>

## Alcatraz Locker Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Table 1079. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/alcatraz-locker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/alcatraz-locker-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-november-4th-2016-cerber-paydos-alcatraz-locker-and-more/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-november-4th-2016-cerber-paydos-alcatraz-locker-and-more/</a>
<a href="https://twitter.com/PolarToffee/status/792796055020642304">https://twitter.com/PolarToffee/status/792796055020642304</a>

## Esmeralda Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1080. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/esmeralda-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/esmeralda-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/forums/t/630835/esmeralda-ransomware/">https://www.bleepingcomputer.com/forums/t/630835/esmeralda-ransomware/</a>

## Encryptile Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1081. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/encryptile-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/encryptile-ransomware.html</a>

## Fileice Ransomware Survey Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Sample of how the hacker tricks the user using the survey method. [https://1.bp.blogspot.com/-72ECd1vsUdE/WBMSzPQEgzI/AAAAAAAAABzA/i8V-Kg8Gstcn\\_7-YZK\\_PDC2VgafWcfDgCLcB/s1600/survey-screen.png](https://1.bp.blogspot.com/-72ECd1vsUdE/WBMSzPQEgzI/AAAAAAAAABzA/i8V-Kg8Gstcn_7-YZK_PDC2VgafWcfDgCLcB/s1600/survey-screen.png) The hacker definatly has a sense of humor: [https://1.bp.blogspot.com/-2AlvtcvdyUY/WBMVptG\\_V5I/AAAAAAAAABzc/1KvAMeDmY2w9BN9vkkqZO8LWkBu7T9mvDAcLcB/s1600/ThxForYurTyme.JPG](https://1.bp.blogspot.com/-2AlvtcvdyUY/WBMVptG_V5I/AAAAAAAAABzc/1KvAMeDmY2w9BN9vkkqZO8LWkBu7T9mvDAcLcB/s1600/ThxForYurTyme.JPG)

*Table 1082. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/fileice-ransomware-survey.html">https://id-ransomware.blogspot.co.il/2016/10/fileice-ransomware-survey.html</a>

<https://www.bleepingcomputer.com/news/security/in-dev-ransomware-forces-you-do-to-survey-before-unlocking-computer/>

## CryptoWire Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1083. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/cryptowire-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/cryptowire-ransomware.html</a>
<a href="https://twitter.com/struppigel/status/791554654664552448">https://twitter.com/struppigel/status/791554654664552448</a>
<a href="https://www.bleepingcomputer.com/news/security/-proof-of-concept-cryptowire-ransomware-spawns-lomix-and-ultralocker-families/">https://www.bleepingcomputer.com/news/security/-proof-of-concept-cryptowire-ransomware-spawns-lomix-and-ultralocker-families/</a>

## Hucky Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Based on Locky

Hucky Ransomware is also known as:

- Hungarian Locky Ransomware

*Table 1084. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/hucky-ransomware-hungarian-locky.html">https://id-ransomware.blogspot.co.il/2016/10/hucky-ransomware-hungarian-locky.html</a>
<a href="https://blog.avast.com/hucky-ransomware-a-hungarian-locky-wannabe">https://blog.avast.com/hucky-ransomware-a-hungarian-locky-wannabe</a>
<a href="https://twitter.com/struppigel/status/846241982347427840">https://twitter.com/struppigel/status/846241982347427840</a>

## Winnix Cryptor Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1085. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/winnix-cryptor-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/winnix-cryptor-ransomware.html</a>

<https://twitter.com/PolarToffee/status/811940037638111232>

## AngryDuck Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Demands 10 BTC

*Table 1086. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/angryduck-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/angryduck-ransomware.html</a>
<a href="https://twitter.com/demonslay335/status/790334746488365057">https://twitter.com/demonslay335/status/790334746488365057</a>

## Lock93 Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1087. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/lock93-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/lock93-ransomware.html</a>
<a href="https://twitter.com/malwrhunterteam/status/789882488365678592">https://twitter.com/malwrhunterteam/status/789882488365678592</a>

## ASN1 Encoder Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1088. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/asn1-encoder-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/asn1-encoder-ransomware.html</a>
<a href="https://malwarebreakdown.com/2017/03/02/rig-ek-at-92-53-105-43-drops-asn1-ransomware/">https://malwarebreakdown.com/2017/03/02/rig-ek-at-92-53-105-43-drops-asn1-ransomware/</a>

## Click Me Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. The hacker tries to get the user to play a game

and when the user clicks the button, there is no game, just 20 pictures in a .gif below:  
<https://3.bp.blogspot.com/-1zgO3-bBazs/WAkPYqXuayI/AAAAAAAAABxI/DO3vycRW-TozneSfRTdeKyXGNETjSMehgCLcB/s1600/all-images.gif>

*Table 1089. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/click-me-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/click-me-ransomware.html</a>
<a href="https://www.youtube.com/watch?v=Xe30kV4ip8w">https://www.youtube.com/watch?v=Xe30kV4ip8w</a>

## AiraCrop Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1090. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/airacrop-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/airacrop-ransomware.html</a>

## JapanLocker Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Base64 encoding, ROT13, and top-bottom swapping

JapanLocker Ransomware is also known as:

- SHC Ransomware
- SHCLocker
- SyNcryption

*Table 1091. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/japanlocker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/japanlocker-ransomware.html</a>
<a href="https://www.cyber.nj.gov/threat-profiles/ransomware-variants/japanlocker">https://www.cyber.nj.gov/threat-profiles/ransomware-variants/japanlocker</a>
<a href="https://github.com/fortiguard-lion/schRansomwareDecryptor/blob/master/schRansomwarev1_decryptor.php">https://github.com/fortiguard-lion/schRansomwareDecryptor/blob/master/schRansomwarev1_decryptor.php</a>
<a href="https://blog.fortinet.com/2016/10/19/japanlocker-an-excavation-to-its-indonesian-roots">https://blog.fortinet.com/2016/10/19/japanlocker-an-excavation-to-its-indonesian-roots</a>

## Anubis Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. EDA2

*Table 1092. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/anubis-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/anubis-ransomware.html</a>
<a href="http://nyxbone.com/malware/Anubis.html">http://nyxbone.com/malware/Anubis.html</a>

## XTPLocker 5.0 Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1093. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/xtplocker-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/xtplocker-ransomware.html</a>

## Exotic Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. Also encrypts executables

*Table 1094. Table References*

Links
<a href="https://www.bleepingcomputer.com/news/security/eviltwins-exotic-ransomware-targets-executable-files/">https://www.bleepingcomputer.com/news/security/eviltwins-exotic-ransomware-targets-executable-files/</a>
<a href="https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-october-14-2016-exotic-lockydump-comrade-and-more/">https://www.bleepingcomputer.com/news/security/the-week-in-ransomware-october-14-2016-exotic-lockydump-comrade-and-more/</a>
<a href="https://www.cyber.nj.gov/threat-profiles/ransomware-variants/exotic-ransomware">https://www.cyber.nj.gov/threat-profiles/ransomware-variants/exotic-ransomware</a>
<a href="https://id-ransomware.blogspot.co.il/2016/10/exotic-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/exotic-ransomware.html</a>

## APT Ransomware v.2

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office,



Open Office, pictures, videos, shared online files etc.. NO POINT TO PAY THE RANSOM, THE FILES ARE COMPLETELY DESTROYED

*Table 1095. Table References*

Links

<https://id-ransomware.blogspot.co.il/2016/10/apt-ransomware-2.html>

## Windows\_Security Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Windows\_Security Ransomware is also known as:

- WS Go Ransomware
- Trojan.Encoder.6491

*Table 1096. Table References*

Links

<https://id-ransomware.blogspot.co.il/2016/10/ws-go-ransomware.html>

<https://www.cyber.nj.gov/threat-profiles/ransomware-variants/apt-ransomware-v2>

## NCrypt Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1097. Table References*

Links

<https://id-ransomware.blogspot.co.il/2016/10/ncrypt-ransomware.html>

## Venis Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. In [devVenisRansom@protonmail.com](mailto:devVenisRansom@protonmail.com)

*Table 1098. Table References*

Links

<https://id-ransomware.blogspot.co.il/2016/10/venis-ransomware.html>

<https://twitter.com/Antelox/status/785849412635521024>

<http://pastebin.com/HuK99Xmj>

## Enigma 2 Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1099. Table References*

Links

<https://id-ransomware.blogspot.co.il/2016/10/enigma-2-ransomware.html>

## Deadly Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc.. sample is set to encrypt only in 2017...

Deadly Ransomware is also known as:

- Deadly for a Good Purpose Ransomware

*Table 1100. Table References*

Links

<https://id-ransomware.blogspot.co.il/2016/10/deadly-ransomware.html>

<https://twitter.com/malwrhunterteam/status/785533373007728640>

## Comrade Circle Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1101. Table References*

Links

<https://id-ransomware.blogspot.co.il/2016/10/comrade-circle-ransomware.html>

## Globe2 Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

Globe2 Ransomware is also known as:

- Purge Ransomware

*Table 1102. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/globe2-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/globe2-ransomware.html</a>
<a href="https://success.trendmicro.com/portal_kb_articledetail?solutionid=1114221">https://success.trendmicro.com/portal_kb_articledetail?solutionid=1114221</a>

## Kostya Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1103. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/kostya-ransomware.html">https://id-ransomware.blogspot.co.il/2016/10/kostya-ransomware.html</a>
<a href="http://www.bleepingcomputer.com/news/security/the-week-in-ransomware-october-14-2016-exotic-lockydump-comrade-and-more/">http://www.bleepingcomputer.com/news/security/the-week-in-ransomware-october-14-2016-exotic-lockydump-comrade-and-more/</a>

## Fs0ciety Locker Ransomware

This is most likely to affect English speaking users, since the note is written in English. English is understood worldwide, thus anyone can be harmed. The hacker spread the virus using email spam, fake updates, and harmful attachments. All your files are compromised including music, MS Office, Open Office, pictures, videos, shared online files etc..

*Table 1104. Table References*

Links
<a href="https://id-ransomware.blogspot.co.il/2016/10/fs0ciety-locker-ransomware.htm">https://id-ransomware.blogspot.co.il/2016/10/fs0ciety-locker-ransomware.htm</a>

## Erebus Ransomware

It's directed to English speaking users, therefore is able to infect worldwide. It is spread using email spam, fake updates, attachments and so on. It encrypts all your files, including: music, MS Office, Open Office, pictures, videos, shared online files etc.. After the files are decrypted, the shadow files

are deleted using the following command: vssadmin.exe Delete Shadows /All /Quiet

Table 1105. Table References

Links
<a href="https://id-ransomware.blogspot.co.il/2016/09/erebus-ransomware.html">https://id-ransomware.blogspot.co.il/2016/09/erebus-ransomware.html</a>

## WannaCry

According to numerous open-source reports, a widespread ransomware campaign is affecting various organizations with reports of tens of thousands of infections in as many as 74 countries, including the United States, United Kingdom, Spain, Russia, Taiwan, France, and Japan. The software can run in as many as 27 different languages. The latest version of this ransomware variant, known as WannaCry, WCry, or Wanna Decryptor, was discovered the morning of May 12, 2017, by an independent security researcher and has spread rapidly over several hours, with initial reports beginning around 4:00 AM EDT, May 12, 2017. Open-source reporting indicates a requested ransom of .1781 bitcoins, roughly \$300 U.S.

WannaCry is also known as:

- WannaCrypt
- WannaCry
- WanaCrypt0r
- WCrypt
- WCRY

Table 1106. Table References

Links
<a href="https://gist.github.com/rain-1/989428fa5504f378b993ee6efbc0b168">https://gist.github.com/rain-1/989428fa5504f378b993ee6efbc0b168</a>

## .CryptoHasYou.

Ransomware

Table 1107. Table References

Links
<a href="http://www.nyxbone.com/malware/CryptoHasYou.html">http://www.nyxbone.com/malware/CryptoHasYou.html</a>

## 777

Ransomware

777 is also known as:

- Sevleg

Table 1108. Table References

Links
<a href="https://decrypter.emsisoft.com/777">https://decrypter.emsisoft.com/777</a>

## 7ev3n

Ransomware

7ev3n is also known as:

- 7ev3n-HONE\$T

Table 1109. Table References

Links
<a href="https://github.com/hasherezade/malware_analysis/tree/master/7ev3n">https://github.com/hasherezade/malware_analysis/tree/master/7ev3n</a>
<a href="https://www.youtube.com/watch?v=RDNbH5HDO1E&amp;feature=youtu.be">https://www.youtube.com/watch?v=RDNbH5HDO1E&amp;feature=youtu.be</a>
<a href="http://www.nyxbone.com/malware/7ev3n-HONE\$T.html">http://www.nyxbone.com/malware/7ev3n-HONE\$T.html</a>

## 8lock8

Ransomware Based on HiddenTear

Table 1110. Table References

Links
<a href="http://www.bleepingcomputer.com/forums/t/614025/8lock8-help-support-topic-8lock8-read-ittxt/">http://www.bleepingcomputer.com/forums/t/614025/8lock8-help-support-topic-8lock8-read-ittxt/</a>

## AiraCrop

Ransomware related to TeamXRat

Table 1111. Table References

Links
<a href="https://twitter.com/PolarToffee/status/796079699478900736">https://twitter.com/PolarToffee/status/796079699478900736</a>

## Al-Namrood

Ransomware

Table 1112. Table References

Links
<a href="https://decrypter.emsisoft.com/al-namrood">https://decrypter.emsisoft.com/al-namrood</a>

# ALFA Ransomware

Ransomware Made by creators of Cerber

*Table 1113. Table References*

Links
-------

<a href="http://www.bleepingcomputer.com/news/security/new-alfa-or-alpha-ransomware-from-the-same-devs-as-cerber/">http://www.bleepingcomputer.com/news/security/new-alfa-or-alpha-ransomware-from-the-same-devs-as-cerber/</a>
---

# Alma Ransomware

Ransomware

*Table 1114. Table References*

Links
-------

<a href="https://cta-service-cms2.hubspot.com/ctas/v2/public/cs/c/?cta\_guid=d4173312-989b-4721-ad00-8308fff353b3&placement\_guid=22f2fe97-c748-4d6a-9e1e-ba3fb1060abe&portal\_id=326665&redirect\_url=APefjpGnqFjmP\_xzeUZ1Y55ovglY1y1ch7CgMDLit5GTHcW9N0ztpnIE-ZReqqv8MDj687\_4Joou7Cd2rSx8-De8uhFQAD\_Len9QpT7Xvu8neW5drkdtTPV7hAaou0osAi2O61dizFXibewmpO60UUCd5OazCGz1V6yT\_3UFMgL0x9S1VeOvoL\_uacuER8g2H3f1EfbtYBw5QFWeUmrjk-9dGzOGspyn303k9XagBtF3SSX4YWSyuEs03Vq7Fxb04KkyKc4GJx-igK98Qta8iMafUam8ikg8XKPkob0FK6Pe-wRZ0QVWIIkM&hsutk=34612af1cd87864cf7162095872571d1&utm\_referrer=https%3A%2F%2Finfo.phishlabs.com%2Fblog%2Falma-ransomware-analysis-of-a-new-ransomware-threat-and-a-decrypter&canon=https%3A%2F%2Finfo.phishlabs.com%2Fblog%2Falma-ransomware-analysis-of-a-new-ransomware-threat-and-a-decrypter&class="bare">https://cta-service-cms2.hubspot.com/ctas/v2/public/cs/c/?cta\_guid=d4173312-989b-4721-ad00-8308fff353b3&placement\_guid=22f2fe97-c748-4d6a-9e1e-ba3fb1060abe&portal\_id=326665&redirect\_url=APefjpGnqFjmP\_xzeUZ1Y55ovglY1y1ch7CgMDLit5GTHcW9N0ztpnIE-ZReqqv8MDj687\_4Joou7Cd2rSx8-De8uhFQAD\_Len9QpT7Xvu8neW5drkdtTPV7hAaou0osAi2O61dizFXibewmpO60UUCd5OazCGz1V6yT\_3UFMgL0x9S1VeOvoL\_uacuER8g2H3f1EfbtYBw5QFWeUmrjk-9dGzOGspyn303k9XagBtF3SSX4YWSyuEs03Vq7Fxb04KkyKc4GJx-igK98Qta8iMafUam8ikg8XKPkob0FK6Pe-wRZ0QVWIIkM&hsutk=34612af1cd87864cf7162095872571d1&utm\_referrer=https%3A%2F%2Finfo.phishlabs.com%2Fblog%2Falma-ransomware-analysis-of-a-new-ransomware-threat-and-a-decrypter&canon=https%3A%2F%2Finfo.phishlabs.com%2Fblog%2Falma-ransomware-analysis-of-a-new-ransomware-threat-and-a-decrypter&em>hstc=61627571.34612af1cd87864cf7162095872571d1.1472135921345.1472140656779.1472593507113.3&hssc=61627571.1.1472593507113&hsfp=1114323283[<a href="https://cta-service-cms2.hubspot.com/ctas/v2/public/cs/c/?cta\_guid=d4173312-989b-4721-ad00-8308fff353b3&placement\_guid=22f2fe97-c748-4d6a-9e1e-ba3fb1060abe&portal\_id=326665&redirect\_url=APefjpGnqFjmP\_xzeUZ1Y55ovglY1y1ch7CgMDLit5GTHcW9N0ztpnIE-ZReqqv8MDj687\_4Joou7Cd2rSx8-De8uhFQAD\_Len9QpT7Xvu8neW5drkdtTPV7hAaou0osAi2O61dizFXibewmpO60UUCd5OazCGz1V6yT\_3UFMgL0x9S1VeOvoL\_uacuER8g2H3f1EfbtYBw5QFWeUmrjk-9dGzOGspyn303k9XagBtF3SSX4YWSyuEs03Vq7Fxb04KkyKc4GJx-igK98Qta8iMafUam8ikg8XKPkob0FK6Pe-wRZ0QVWIIkM&hsutk=34612af1cd87864cf7162095872571d1&utm\_referrer=https%3A%2F%2Finfo.phishlabs.com%2Fblog%2Falma-ransomware-analysis-of-a-new-ransomware-threat-and-a-decrypter&canon=https%3A%2F%2Finfo.phishlabs.com%2Fblog%2Falma-ransomware-analysis-of-a-new-ransomware-threat-and-a-decrypter&class="bare">https://cta-service-cms2.hubspot.com/ctas/v2/public/cs/c/?cta\_guid=d4173312-989b-4721-ad00-8308fff353b3&placement\_guid=22f2fe97-c748-4d6a-9e1e-ba3fb1060abe&portal\_id=326665&redirect\_url=APefjpGnqFjmP\_xzeUZ1Y55ovglY1y1ch7CgMDLit5GTHcW9N0ztpnIE-ZReqqv8MDj687\_4Joou7Cd2rSx8-De8uhFQAD\_Len9QpT7Xvu8neW5drkdtTPV7hAaou0osAi2O61dizFXibewmpO60UUCd5OazCGz1V6yT\_3UFMgL0x9S1VeOvoL\_uacuER8g2H3f1EfbtYBw5QFWeUmrjk-9dGzOGspyn303k9XagBtF3SSX4YWSyuEs03Vq7Fxb04KkyKc4GJx-igK98Qta8iMafUam8ikg8XKPkob0FK6Pe-wRZ0QVWIIkM&hsutk=34612af1cd87864cf7162095872571d1&utm\_referrer=https%3A%2F%2Finfo.phishlabs.com%2Fblog%2Falma-ransomware-analysis-of-a-new-ransomware-threat-and-a-decrypter&canon=https%3A%2F%2Finfo.phishlabs.com%2Fblog%2Falma-ransomware-analysis-of-a-new-ransomware-threat-and-a-decrypter&

<https://info.phishlabs.com/blog/alma-ransomware-analysis-of-a-new-ransomware-threat-and-a-decrypter>

<http://www.bleepingcomputer.com/news/security/new-alma-locker-ransomware-being-distributed-via-the-rig-exploit-kit/>

## Alpha Ransomware

Ransomware

Alpha Ransomware is also known as:

- AlphaLocker

*Table 1115. Table References*

Links

<http://download.bleepingcomputer.com/demonslay335/AlphaDecrypter.zip>

<http://www.bleepingcomputer.com/news/security/decrypted-alpha-ransomware-continues-the-trend-of-accepting-amazon-cards/>

<https://twitter.com/malwarebread/status/804714048499621888>

## AMBA

Ransomware Websites only [amba@riseup.net](mailto:amba@riseup.net)

*Table 1116. Table References*

Links

[https://twitter.com/benkow\\_/status/747813034006020096](https://twitter.com/benkow_/status/747813034006020096)

## AngleWare

Ransomware

*Table 1117. Table References*

Links

<https://twitter.com/BleepinComputer/status/844531418474708993>

## Anony

Ransomware Based on HiddenTear

Anony is also known as:

- ngocanh

*Table 1118. Table References*



Links
<a href="https://twitter.com/struppigel/status/842047409446387714">https://twitter.com/struppigel/status/842047409446387714</a>

## Apocalypse

Ransomware [decryption@mail.ru](mailto:decryption@mail.ru) [recoveryhelp@bk.ru](mailto:recoveryhelp@bk.ru) [ransomware.attack@list.ru](mailto:ransomware.attack@list.ru)  
[esmeraldaencryption@mail.ru](mailto:esmeraldaencryption@mail.ru) [dr.compress@bk.ru](mailto:dr.compress@bk.ru)

Apocalypse is also known as:

- Fabiansomeware

*Table 1119. Table References*

Links
<a href="https://decrypter.emsisoft.com/apocalypse">https://decrypter.emsisoft.com/apocalypse</a>
<a href="http://blog.emsisoft.com/2016/06/29/apocalypse-ransomware-which-targets-companies-through-insecure-rdp/">http://blog.emsisoft.com/2016/06/29/apocalypse-ransomware-which-targets-companies-through-insecure-rdp/</a>

## ApocalypseVM

Ransomware Apocalypse ransomware version which uses VMprotect

*Table 1120. Table References*

Links
<a href="http://decrypter.emsisoft.com/download/apocalypsevm">http://decrypter.emsisoft.com/download/apocalypsevm</a>

## AutoLocky

Ransomware

*Table 1121. Table References*

Links
<a href="https://decrypter.emsisoft.com/autolocky">https://decrypter.emsisoft.com/autolocky</a>

## Aw3s0m3Sc0t7

Ransomware

*Table 1122. Table References*

Links
<a href="https://twitter.com/struppigel/status/828902907668000770">https://twitter.com/struppigel/status/828902907668000770</a>

# BadBlock

Ransomware

Table 1123. Table References

Links
<a href="https://decrypter.emsisoft.com/badblock">https://decrypter.emsisoft.com/badblock</a>
<a href="http://www.nyxbone.com/malware/BadBlock.html">http://www.nyxbone.com/malware/BadBlock.html</a>
<a href="http://www.nyxbone.com/images/articulos/malware/badblock/5.png">http://www.nyxbone.com/images/articulos/malware/badblock/5.png</a>

# BaksoCrypt

Ransomware Based on my-Little-Ransomware

Table 1124. Table References

Links
<a href="https://twitter.com/JakubKroustek/status/760482299007922176">https://twitter.com/JakubKroustek/status/760482299007922176</a>
<a href="https://0xc1r3ng.wordpress.com/2016/06/24/bakso-crypt-simple-ransomware/">https://0xc1r3ng.wordpress.com/2016/06/24/bakso-crypt-simple-ransomware/</a>

# Bandarchor

Ransomware Files might be partially encrypted

Bandarchor is also known as:

- Rakhni

Table 1125. Table References

Links
<a href="https://reaqta.com/2016/03/bandarchor-ransomware-still-active/">https://reaqta.com/2016/03/bandarchor-ransomware-still-active/</a>
<a href="https://www.bleepingcomputer.com/news/security/new-bandarchor-ransomware-variant-spreads-via-malvertising-on-adult-sites/">https://www.bleepingcomputer.com/news/security/new-bandarchor-ransomware-variant-spreads-via-malvertising-on-adult-sites/</a>

# Bart

Ransomware Possible affiliations with RockLoader, Locky and Dridex

Bart is also known as:

- BaCrypt

Table 1126. Table References

Links
<a href="http://now.avg.com/barts-shenanigans-are-no-match-for-avg/">http://now.avg.com/barts-shenanigans-are-no-match-for-avg/</a>

<http://phishme.com/rockloader-downloading-new-ransomware-bart/>

<https://www.proofpoint.com/us/threat-insight/post/New-Bart-Ransomware-from-Threat-Actors-Spreading-Dridex-and-Locky>

## BitCryptor

Ransomware Has a GUI. CryptoGraphic Locker family. Newer CoinVault variant.

*Table 1127. Table References*

Links

<https://noransom.kaspersky.com/>

## BitStak

Ransomware

*Table 1128. Table References*

Links

<https://download.bleepingcomputer.com/demonslay335/BitStakDecrypter.zip>

## BlackShades Crypter

Ransomware

BlackShades Crypter is also known as:

- SilentShade

*Table 1129. Table References*

Links

<http://nyxbone.com/malware/BlackShades.html>

## Blocatto

Ransomware Based on HiddenTear

*Table 1130. Table References*

Links

<http://www.bleepingcomputer.com/forums/t/614456/blocatto-ransomware-blocatto-help-support-leggi-questo-filetxt/>

## Booyah

Ransomware EXE was replaced to neutralize threat

Booyah is also known as:

- Salami

## Brazilian

Ransomware Based on EDA2

*Table 1131. Table References*

Links
<a href="http://www.nyxbone.com/malware/brazilianRansom.html">http://www.nyxbone.com/malware/brazilianRansom.html</a>
<a href="http://www.nyxbone.com/images/articulos/malware/brazilianRansom/0.png">http://www.nyxbone.com/images/articulos/malware/brazilianRansom/0.png</a>

## Brazilian Globe

Ransomware

*Table 1132. Table References*

Links
<a href="https://twitter.com/JakubKroustek/status/821831437884211201">https://twitter.com/JakubKroustek/status/821831437884211201</a>

## BrLock

Ransomware

*Table 1133. Table References*

Links
<a href="https://www.proofpoint.com/us/threat-insight/post/ransomware-explosion-continues-cryptfle2-brlock-mm-locker-discovered">https://www.proofpoint.com/us/threat-insight/post/ransomware-explosion-continues-cryptfle2-brlock-mm-locker-discovered</a>

## Browlock

Ransomware no local encryption, browser only

## BTCWare Related to / new version of CryptXXX

Ransomware

*Table 1134. Table References*

Links
<a href="https://twitter.com/malwrhunterteam/status/845199679340011520">https://twitter.com/malwrhunterteam/status/845199679340011520</a>

# Bucbi

Ransomware no file name change, no extension

*Table 1135. Table References*

Links
<a href="http://researchcenter.paloaltonetworks.com/2016/05/unit42-bucbi-ransomware-is-back-with-a-ukrainian-makeover/">http://researchcenter.paloaltonetworks.com/2016/05/unit42-bucbi-ransomware-is-back-with-a-ukrainian-makeover/</a>

# BuyUnlockCode

Ransomware Does not delete Shadow Copies

# Central Security Treatment Organization

Ransomware

*Table 1136. Table References*

Links
<a href="http://www.bleepingcomputer.com/forums/t/625820/central-security-treatment-organization-ransomware-help-topic-cry-extension/">http://www.bleepingcomputer.com/forums/t/625820/central-security-treatment-organization-ransomware-help-topic-cry-extension/</a>

# Cerber

Ransomware

Cerber is also known as:

- CRBR ENCRYPTOR

*Table 1137. Table References*

Links
<a href="https://blog.malwarebytes.org/threat-analysis/2016/03/cerber-ransomware-new-but-mature/">https://blog.malwarebytes.org/threat-analysis/2016/03/cerber-ransomware-new-but-mature/</a>
<a href="https://community.rsa.com/community/products/netwitness/blog/2016/11/04/the-evolution-of-cerber-v410">https://community.rsa.com/community/products/netwitness/blog/2016/11/04/the-evolution-of-cerber-v410</a>
<a href="https://www.bleepingcomputer.com/news/security/cerber-renames-itself-as-crbr-encryptor-to-be-a-pita/">https://www.bleepingcomputer.com/news/security/cerber-renames-itself-as-crbr-encryptor-to-be-a-pita/</a>

# Chimera

Ransomware

*Table 1138. Table References*

Links
-------

<http://www.bleepingcomputer.com/news/security/chimera-ransomware-decryption-keys-released-by-petya-devs/>

<https://blog.malwarebytes.org/threat-analysis/2015/12/inside-chimera-ransomware-the-first-doxingware-in-wild/>

## Clock

Ransomware Does not encrypt anything

*Table 1139. Table References*

Links

<https://twitter.com/JakubKroustek/status/794956809866018816>

## CoinVault

Ransomware CryptoGraphic Locker family. Has a GUI. Do not confuse with CrypVault!

*Table 1140. Table References*

Links

<https://noransom.kaspersky.com/>

## Coverton

Ransomware

*Table 1141. Table References*

Links

<http://www.bleepingcomputer.com/news/security/paying-the-coverton-ransomware-may-not-get-your-data-back/>

## Cryaki

Ransomware

*Table 1142. Table References*

Links

<https://support.kaspersky.com/viruses/disinfection/8547>

## Crybola

Ransomware

*Table 1143. Table References*

Links
<a href="https://support.kaspersky.com/viruses/disinfection/8547">https://support.kaspersky.com/viruses/disinfection/8547</a>

## CryFile

Ransomware

*Table 1144. Table References*

Links
SHTODELATVAM.txt[SHTODELATVAM.txt]
Instructionaga.txt[Instructionaga.txt]

## CryLocker

Ransomware Identifies victim locations w/Google Maps API

CryLocker is also known as:

- Cry
- CSTO
- Central Security Treatment Organization

*Table 1145. Table References*

Links
<a href="http://www.bleepingcomputer.com/news/security/the-crylocker-ransomware-communicates-using-udp-and-stores-data-on-imgur-com/">http://www.bleepingcomputer.com/news/security/the-crylocker-ransomware-communicates-using-udp-and-stores-data-on-imgur-com/</a>

## CrypMIC

Ransomware CryptXXX clone/spinoff

*Table 1146. Table References*

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/crypmic-ransomware-wants-to-follow-cryptxxx/">http://blog.trendmicro.com/trendlabs-security-intelligence/crypmic-ransomware-wants-to-follow-cryptxxx/</a>

## Crypren

Ransomware

*Table 1147. Table References*

Links
<a href="https://github.com/pekeinfo/DecryptCrypren">https://github.com/pekeinfo/DecryptCrypren</a>

<http://www.nyxbone.com/malware/Crypren.html>

<http://www.nyxbone.com/images/articulos/malware/crypren/0.png>

## Crypt38

Ransomware

*Table 1148. Table References*

Links

<https://download.bleepingcomputer.com/demonslay335/Crypt38Keygen.zip>

<https://blog.fortinet.com/2016/06/17/buggy-russian-ransomware-inadvertently-allows-free-decryption>

## Crypter

Ransomware Does not actually encrypt the files, but simply renames them

*Table 1149. Table References*

Links

<https://twitter.com/jiriavirlab/status/802554159564062722>

## CryptFile2

Ransomware

*Table 1150. Table References*

Links

<https://www.proofpoint.com/us/threat-insight/post/ransomware-explosion-continues-cryptfile2-brlock-mm-locker-discovered>

## CryptInfinite

Ransomware

*Table 1151. Table References*

Links

<https://decrypter.emsisoft.com/>

## CryptoBit

Ransomware sekretzbel0ngt0us.KEY - do not confuse with CryptorBit.

*Table 1152. Table References*



Links
<a href="http://www.pandasecurity.com/mediacenter/panda-security/cryptobit/">http://www.pandasecurity.com/mediacenter/panda-security/cryptobit/</a>
<a href="http://news.softpedia.com/news/new-cryptobit-ransomware-could-be-decryptable-503239.shtml">http://news.softpedia.com/news/new-cryptobit-ransomware-could-be-decryptable-503239.shtml</a>

## CryptoDefense

Ransomware no extension change

*Table 1153. Table References*

Links
<a href="https://decrypter.emsisoft.com/">https://decrypter.emsisoft.com/</a>

## CryptoFinancial

Ransomware

CryptoFinancial is also known as:

- Ranscam

*Table 1154. Table References*

Links
<a href="http://blog.talosintel.com/2016/07/ranscam.html">http://blog.talosintel.com/2016/07/ranscam.html</a>
<a href="https://nakedsecurity.sophos.com/2016/07/13/ransomware-that-demands-money-and-gives-you-back-nothing/">https://nakedsecurity.sophos.com/2016/07/13/ransomware-that-demands-money-and-gives-you-back-nothing/</a>

## CryptoFortress

Ransomware Mimics Torrentlocker. Encrypts only 50% of each file up to 5 MB

## CryptoGraphic Locker

Ransomware Has a GUI. Subvariants: CoinVault BitCryptor

## CryptoHost

Ransomware RAR's victim's files has a GUI

CryptoHost is also known as:

- Manamecrypt
- Telograph
- ROI Locker

Table 1155. Table References

Links
<a href="http://www.bleepingcomputer.com/news/security/cryptohost-decrypted-locks-files-in-a-password-protected-rar-file/">http://www.bleepingcomputer.com/news/security/cryptohost-decrypted-locks-files-in-a-password-protected-rar-file/</a>

## CryptoJoker

Ransomware

## CryptoLocker

Ransomware no longer relevant

Table 1156. Table References

Links
<a href="https://www.fireeye.com/blog/executive-perspective/2014/08/your-locker-of-information-for-cryptolocker-decryption.html">https://www.fireeye.com/blog/executive-perspective/2014/08/your-locker-of-information-for-cryptolocker-decryption.html</a>
<a href="https://reaqta.com/2016/04/uncovering-ransomware-distribution-operation-part-2/">https://reaqta.com/2016/04/uncovering-ransomware-distribution-operation-part-2/</a>

## CryptoLocker 1.0.0

Ransomware

Table 1157. Table References

Links
<a href="https://twitter.com/malwrhunterteam/status/839747940122001408">https://twitter.com/malwrhunterteam/status/839747940122001408</a>

## CryptoLocker 5.1

Ransomware

Table 1158. Table References

Links
<a href="https://twitter.com/malwrhunterteam/status/782890104947867649">https://twitter.com/malwrhunterteam/status/782890104947867649</a>

## CryptoMix

Ransomware

CryptoMix is also known as:

- Zeta

Table 1159. Table References

Links
-------

<a href="http://www.nyxbone.com/malware/CryptoMix.html">http://www.nyxbone.com/malware/CryptoMix.html</a>
---

<a href="https://www.cert.pl/en/news/single/technical-analysis-of-cryptomixcryptfile2-ransomware/">https://www.cert.pl/en/news/single/technical-analysis-of-cryptomixcryptfile2-ransomware/</a>
---

## CryptoRansomware

Ransomware

*Table 1160. Table References*

Links
-------

<a href="https://twitter.com/malwrhunterteam/status/817672617658347521">https://twitter.com/malwrhunterteam/status/817672617658347521</a>
---

## CryptoRoger

Ransomware

*Table 1161. Table References*

Links
-------

<a href="http://www.bleepingcomputer.com/news/security/new-ransomware-called-cryptoroger-that-appends-crptrgr-to-encrypted-files/">http://www.bleepingcomputer.com/news/security/new-ransomware-called-cryptoroger-that-appends-crptrgr-to-encrypted-files/</a>
---

## CryptoShadow

Ransomware

*Table 1162. Table References*

Links
-------

<a href="https://twitter.com/struppigel/status/821992610164277248">https://twitter.com/struppigel/status/821992610164277248</a>
---

## CryptoShocker

Ransomware

*Table 1163. Table References*

Links
-------

<a href="http://www.bleepingcomputer.com/forums/t/617601/cryptoshocker-ransomware-help-and-support-topic-locked-attentionurl/">http://www.bleepingcomputer.com/forums/t/617601/cryptoshocker-ransomware-help-and-support-topic-locked-attentionurl/</a>
---

## CryptoTorLocker2015

Ransomware

*Table 1164. Table References*

Links

<http://www.bleepingcomputer.com/forums/t/565020/new-cryptorlocker2015-ransomware-discovered-and-easily-decrypted/>

## CryptoTrooper

Ransomware

*Table 1165. Table References*

Links

<http://news.softpedia.com/news/new-open-source-linux-ransomware-shows-infosec-community-divide-508669.shtml>

## CryptoWall 1

Ransomware

## CryptoWall 2

Ransomware

## CryptoWall 3

Ransomware

*Table 1166. Table References*

Links

<https://blogs.technet.microsoft.com/mmpc/2015/01/13/crowti-update-cryptowall-3-0/>

<https://www.virustotal.com/en/file/45317968759d3e37282ceb75149f627d648534c5b4685f6da3966d8f6fca662d/analysis/>

## CryptoWall 4

Ransomware

## CryptXXX

Ransomware Comes with Bedep

CryptXXX is also known as:

- CryptProjectXXX

*Table 1167. Table References*

Links
<a href="https://support.kaspersky.com/viruses/disinfection/8547">https://support.kaspersky.com/viruses/disinfection/8547</a>
<a href="http://www.bleepingcomputer.com/virus-removal/cryptxxx-ransomware-help-information">http://www.bleepingcomputer.com/virus-removal/cryptxxx-ransomware-help-information</a>

## CryptXXX 2.0

Ransomware Locks screen. Ransom note names are an ID. Comes with Bedep.

CryptXXX 2.0 is also known as:

- CryptProjectXXX

*Table 1168. Table References*

Links
<a href="https://support.kaspersky.com/viruses/disinfection/8547">https://support.kaspersky.com/viruses/disinfection/8547</a>
<a href="https://www.proofpoint.com/us/threat-insight/post/cryptxxx2-ransomware-authors-strike-back-against-free-decryption-tool">https://www.proofpoint.com/us/threat-insight/post/cryptxxx2-ransomware-authors-strike-back-against-free-decryption-tool</a>
<a href="http://blogs.cisco.com/security/cryptxxx-technical-deep-dive">http://blogs.cisco.com/security/cryptxxx-technical-deep-dive</a>

## CryptXXX 3.0

Ransomware Comes with Bedep

CryptXXX 3.0 is also known as:

- UltraDeCrypter
- UltraCrypter

*Table 1169. Table References*

Links
<a href="https://support.kaspersky.com/viruses/disinfection/8547">https://support.kaspersky.com/viruses/disinfection/8547</a>
<a href="http://www.bleepingcomputer.com/news/security/cryptxxx-updated-to-version-3-0-decryptors-no-longer-work/">http://www.bleepingcomputer.com/news/security/cryptxxx-updated-to-version-3-0-decryptors-no-longer-work/</a>
<a href="http://blogs.cisco.com/security/cryptxxx-technical-deep-dive">http://blogs.cisco.com/security/cryptxxx-technical-deep-dive</a>

## CryptXXX 3.1

Ransomware StilerX credential stealing

*Table 1170. Table References*

Links
<a href="https://support.kaspersky.com/viruses/disinfection/8547">https://support.kaspersky.com/viruses/disinfection/8547</a>
<a href="https://www.proofpoint.com/us/threat-insight/post/cryptxxx-ransomware-learns-samba-other-new-tricks-with-version3100">https://www.proofpoint.com/us/threat-insight/post/cryptxxx-ransomware-learns-samba-other-new-tricks-with-version3100</a>

# CryPy

Ransomware

Table 1171. Table References

Links
<a href="http://www.bleepingcomputer.com/news/security/ctb-faker-ransomware-does-a-poor-job-imitating-ctb-locker/">http://www.bleepingcomputer.com/news/security/ctb-faker-ransomware-does-a-poor-job-imitating-ctb-locker/</a>

## CTB-Faker

Ransomware

CTB-Faker is also known as:

- Citroni

## CTB-Locker WEB

Ransomware websites only

Table 1172. Table References

Links
<a href="https://thisissecurity.net/2016/02/26/a-lockpicking-exercise/">https://thisissecurity.net/2016/02/26/a-lockpicking-exercise/</a>
<a href="https://github.com/eyecatchup/Citroni-php">https://github.com/eyecatchup/Citroni-php</a>

## CuteRansomware

Ransomware Based on my-Little-Ransomware

CuteRansomware is also known as:

- my-Little-Ransomware

Table 1173. Table References

Links
<a href="https://github.com/aaaddress1/my-Little-Ransomware/tree/master/decryptoTool">https://github.com/aaaddress1/my-Little-Ransomware/tree/master/decryptoTool</a>
<a href="https://github.com/aaaddress1/my-Little-Ransomware">https://github.com/aaaddress1/my-Little-Ransomware</a>

## Cyber SpLiTTER Vbs

Ransomware Based on HiddenTear

Cyber SpLiTTER Vbs is also known as:

- CyberSplitter

Table 1174. Table References

Links
<a href="https://twitter.com/struppigel/status/778871886616862720">https://twitter.com/struppigel/status/778871886616862720</a>
<a href="https://twitter.com/struppigel/status/806758133720698881">https://twitter.com/struppigel/status/806758133720698881</a>

## Death Bitches

Ransomware

Table 1175. Table References

Links
<a href="https://twitter.com/JaromirHorejsi/status/815555258478981121">https://twitter.com/JaromirHorejsi/status/815555258478981121</a>

## DeCrypt Protect

Ransomware

Table 1176. Table References

Links
<a href="http://www.malwareremovalguides.info/decrypt-files-with-decrypt_mblblock-exe-decrypt-protect/">http://www.malwareremovalguides.info/decrypt-files-with-decrypt_mblblock-exe-decrypt-protect/</a>

## DEDCryptor

Ransomware Based on EDA2

Table 1177. Table References

Links
<a href="http://www.bleepingcomputer.com/forums/t/617395/dedcryptor-ded-help-support-topic/">http://www.bleepingcomputer.com/forums/t/617395/dedcryptor-ded-help-support-topic/</a>
<a href="http://www.nyxbone.com/malware/DEDCryptor.html">http://www.nyxbone.com/malware/DEDCryptor.html</a>

## Demo

Ransomware only encrypts .jpg files

Table 1178. Table References

Links
<a href="https://twitter.com/struppigel/status/798573300779745281">https://twitter.com/struppigel/status/798573300779745281</a>

## DetoxCrypto

Ransomware - Based on Detox: Calipso, We are all Pokemons, Nullbyte

Table 1179. Table References

Links
<a href="http://www.bleepingcomputer.com/news/security/new-detoxcrypto-ransomware-pretends-to-be-pokemongo-or-uploads-a-picture-of-your-screen/">http://www.bleepingcomputer.com/news/security/new-detoxcrypto-ransomware-pretends-to-be-pokemongo-or-uploads-a-picture-of-your-screen/</a>

## Digisom

Ransomware

Table 1180. Table References

Links
<a href="https://twitter.com/PolarToffee/status/829727052316160000">https://twitter.com/PolarToffee/status/829727052316160000</a>

## DirtyDecrypt

Ransomware

Table 1181. Table References

Links
<a href="https://twitter.com/demonslay335/status/752586334527709184">https://twitter.com/demonslay335/status/752586334527709184</a>

## DMALocker

Ransomware no extension change Encrypted files have prefix: Version 1: ABCXYZ11 - Version 2: !DMALOCK - Version 3: !DMALOCK3.0 - Version 4: !DMALOCK4.0

Table 1182. Table References

Links
<a href="https://decrypter.emsisoft.com/">https://decrypter.emsisoft.com/</a>
<a href="https://github.com/hasherezade/dma_unlocker">https://github.com/hasherezade/dma_unlocker</a>
<a href="https://drive.google.com/drive/folders/0Bzb5kQFOXkiSMm94QzdyM3hCdDg">https://drive.google.com/drive/folders/0Bzb5kQFOXkiSMm94QzdyM3hCdDg</a>
<a href="https://blog.malwarebytes.org/threat-analysis/2016/02/dma-locker-a-new-ransomware-but-no-reason-to-panic/">https://blog.malwarebytes.org/threat-analysis/2016/02/dma-locker-a-new-ransomware-but-no-reason-to-panic/</a>

## DMALocker 3.0

Ransomware

Table 1183. Table References

Links
<a href="https://drive.google.com/drive/folders/0Bzb5kQFOXkiSMm94QzdyM3hCdDg">https://drive.google.com/drive/folders/0Bzb5kQFOXkiSMm94QzdyM3hCdDg</a>
<a href="https://blog.malwarebytes.org/threat-analysis/2016/02/dma-locker-strikes-back/">https://blog.malwarebytes.org/threat-analysis/2016/02/dma-locker-strikes-back/</a>



# DN Ransomware

Ransomware Code to decrypt: 83KYG9NW-3K39V-2T3HJ-93F3Q-GT

Table 1184. Table References

Links
<a href="https://twitter.com/BleepinComputer/status/822500056511213568">https://twitter.com/BleepinComputer/status/822500056511213568</a>

# Domino

Ransomware Based on Hidden Tear

Table 1185. Table References

Links
<a href="http://www.nyxbone.com/malware/Domino.html">http://www.nyxbone.com/malware/Domino.html</a>
<a href="http://www.bleepingcomputer.com/news/security/the-curious-case-of-the-domino-ransomware-a-windows-crack-and-a-cow/">http://www.bleepingcomputer.com/news/security/the-curious-case-of-the-domino-ransomware-a-windows-crack-and-a-cow/</a>

# DoNotChange

Ransomware

Table 1186. Table References

Links
<a href="https://www.bleepingcomputer.com/forums/t/643330/donotchange-ransomware-id-7es642406cry-do-not-change-the-file-namecryp/">https://www.bleepingcomputer.com/forums/t/643330/donotchange-ransomware-id-7es642406cry-do-not-change-the-file-namecryp/</a>

# DummyLocker

Ransomware

Table 1187. Table References

Links
<a href="https://twitter.com/struppigel/status/794108322932785158">https://twitter.com/struppigel/status/794108322932785158</a>

# DXXD

Ransomware

Table 1188. Table References

Links
<a href="https://www.bleepingcomputer.com/forums/t/627831/dxxd-ransomware-dxxd-help-support-readmetxt/">https://www.bleepingcomputer.com/forums/t/627831/dxxd-ransomware-dxxd-help-support-readmetxt/</a>

<https://www.bleepingcomputer.com/news/security/the-dxxd-ransomware-displays-legal-notice-before-users-login/>

## HiddenTear

Ransomware Open sourced C#

HiddenTear is also known as:

- Cryptear
- EDA2

*Table 1189. Table References*

Links

<http://www.utkusen.com/blog/dealing-with-script-kiddies-cryptear-b-incident.html>

## EduCrypt

Ransomware Based on Hidden Tear

EduCrypt is also known as:

- EduCrypter

*Table 1190. Table References*

Links

[http://www.filedropper.com/decrypter\\_1](http://www.filedropper.com/decrypter_1)

<https://twitter.com/JakubKroustek/status/747031171347910656>

## EiTest

Ransomware

*Table 1191. Table References*

Links

<https://twitter.com/BroadAnalysis/status/845688819533930497>

<https://twitter.com/malwrhunterteam/status/845652520202616832>

## El-Polocker

Ransomware Has a GUI

El-Polocker is also known as:

- Los Pollos Hermanos

# Encoder.xxxx

Ransomware Coded in GO

Encoder.xxxx is also known as:

- Trojan.Encoder.6491

*Table 1192. Table References*

Links
<a href="http://www.bleepingcomputer.com/news/security/the-week-in-ransomware-october-14-2016-exotic-lockydump-comrade-and-more/">http://www.bleepingcomputer.com/news/security/the-week-in-ransomware-october-14-2016-exotic-lockydump-comrade-and-more/</a>
<a href="http://vms.drweb.ru/virus/?_is=1&amp;i=8747343">http://vms.drweb.ru/virus/?_is=1&amp;i=8747343</a>

# encryptoJJS

Ransomware

# Enigma

Ransomware

*Table 1193. Table References*

Links
<a href="http://www.bleepingcomputer.com/news/security/the-enigma-ransomware-targets-russian-speaking-users/">http://www.bleepingcomputer.com/news/security/the-enigma-ransomware-targets-russian-speaking-users/</a>

# Enjey

Ransomware Based on RemindMe

*Table 1194. Table References*

Links
<a href="https://twitter.com/malwrhunterteam/status/839022018230112256">https://twitter.com/malwrhunterteam/status/839022018230112256</a>

# Fairware

Ransomware Target Linux O.S.

*Table 1195. Table References*

Links
<a href="http://www.bleepingcomputer.com/news/security/new-fairware-ransomware-targeting-linux-computers/">http://www.bleepingcomputer.com/news/security/new-fairware-ransomware-targeting-linux-computers/</a>

# Fakben

Ransomware Based on Hidden Tear

*Table 1196. Table References*

Links

<https://blog.fortinet.com/post/fakben-team-ransomware-uses-open-source-hidden-tear-code>

# FakeCryptoLocker

Ransomware

*Table 1197. Table References*

Links

<https://twitter.com/PolarToffee/status/812312402779836416>

# Fantom

Ransomware Based on EDA2

Fantom is also known as:

- Comrad Circle

*Table 1198. Table References*

Links

<http://www.bleepingcomputer.com/news/security/fantom-ransomware-encrypts-your-files-while-pretending-to-be-windows-update/>

# FenixLocker

Ransomware

*Table 1199. Table References*

Links

<https://decrypter.emsisoft.com/fenixlocker>

<https://twitter.com/fwosar/status/777197255057084416>

# FILE FROZR

Ransomware RaaS

*Table 1200. Table References*

Links

<https://twitter.com/rommeljovent17/status/846973265650335744>

## FileLocker

Ransomware

*Table 1201. Table References*

Links

<https://twitter.com/jiriavirlab/status/836616468775251968>

## FireCrypt

Ransomware

*Table 1202. Table References*

Links

<https://www.bleepingcomputer.com/news/security/firecrypt-ransomware-comes-with-a-ddos-component/>

## Flyper

Ransomware Based on EDA2 / HiddenTear

*Table 1203. Table References*

Links

<https://twitter.com/malwrhunterteam/status/773771485643149312>

## Fonco

Ransomware contact email [safefiles32@mail.ru](mailto:safefiles32@mail.ru) also as prefix in encrypted file contents

## FortuneCookie

Ransomware

*Table 1204. Table References*

Links

<https://twitter.com/struppigel/status/842302481774321664>

## Free-Freedom

Ransomware Unlock code is: adam or adamdude9

Free-Freedom is also known as:

- Roga

Table 1205. Table References

Links
<a href="https://twitter.com/BleepinComputer/status/812135608374226944">https://twitter.com/BleepinComputer/status/812135608374226944</a>

## FSociety

Ransomware Based on EDA2 and RemindMe

Table 1206. Table References

Links
<a href="https://www.bleepingcomputer.com/forums/t/628199/fsociety-locker-ransomware-help-support-fsocietyhtml/">https://www.bleepingcomputer.com/forums/t/628199/fsociety-locker-ransomware-help-support-fsocietyhtml/</a>
<a href="http://www.bleepingcomputer.com/news/security/new-fsociety-ransomware-pays-homage-to-mr-robot/">http://www.bleepingcomputer.com/news/security/new-fsociety-ransomware-pays-homage-to-mr-robot/</a>
<a href="https://twitter.com/siri_urz/status/795969998707720193">https://twitter.com/siri_urz/status/795969998707720193</a>

## Fury

Ransomware

Table 1207. Table References

Links
<a href="https://support.kaspersky.com/viruses/disinfection/8547">https://support.kaspersky.com/viruses/disinfection/8547</a>

## GhostCrypt

Ransomware Based on Hidden Tear

Table 1208. Table References

Links
<a href="https://download.bleepingcomputer.com/demonslay335/GhostCryptDecrypter.zip">https://download.bleepingcomputer.com/demonslay335/GhostCryptDecrypter.zip</a>
<a href="http://www.bleepingcomputer.com/forums/t/614197/ghostcrypt-z81928819-help-support-topic-read-this-filetxt/">http://www.bleepingcomputer.com/forums/t/614197/ghostcrypt-z81928819-help-support-topic-read-this-filetxt/</a>

## Gingerbread

Ransomware

Table 1209. Table References

Links
<a href="https://twitter.com/ni_fi_70/status/796353782699425792">https://twitter.com/ni_fi_70/status/796353782699425792</a>

# Globe v1

Ransomware

Globe v1 is also known as:

- Purge

*Table 1210. Table References*

Links
<a href="https://success.trendmicro.com/portal_kb_articledetail?solutionid=1114221">https://success.trendmicro.com/portal_kb_articledetail?solutionid=1114221</a>
<a href="http://www.bleepingcomputer.com/news/security/the-globe-ransomware-wants-to-purge-your-files/">http://www.bleepingcomputer.com/news/security/the-globe-ransomware-wants-to-purge-your-files/</a>

# GNL Locker

Ransomware Only encrypts DE or NL country. Variants, from old to latest: Zyklon Locker, WildFire locker, Hades Locker

*Table 1211. Table References*

Links
<a href="http://www.bleepingcomputer.com/forums/t/611342/gnl-locker-support-and-help-topic-locked-and-unlock-files-instructionshtml/">http://www.bleepingcomputer.com/forums/t/611342/gnl-locker-support-and-help-topic-locked-and-unlock-files-instructionshtml/</a>

# Gomasom

Ransomware

*Table 1212. Table References*

Links
<a href="https://decrypter.emsisoft.com/">https://decrypter.emsisoft.com/</a>

# Goopic

Ransomware

*Table 1213. Table References*

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/angler-shift-ek-landscape-new-crypto-ransomware-activity/">http://blog.trendmicro.com/trendlabs-security-intelligence/angler-shift-ek-landscape-new-crypto-ransomware-activity/</a>

# Gopher

Ransomware OS X ransomware (PoC)

# Hacked

Ransomware Jigsaw Ransomware variant

Table 1214. Table References

Links
<a href="https://twitter.com/demonslay335/status/806878803507101696">https://twitter.com/demonslay335/status/806878803507101696</a>

# HappyDayzz

Ransomware

Table 1215. Table References

Links
<a href="https://twitter.com/malwrhunterteam/status/847114064224497666">https://twitter.com/malwrhunterteam/status/847114064224497666</a>

# Harasom

Ransomware

Table 1216. Table References

Links
<a href="https://decrypter.emsisoft.com/">https://decrypter.emsisoft.com/</a>

# HDDCryptor

Ransomware Uses <https://diskcryptor.net> for full disk encryption

HDDCryptor is also known as:

- Mamba

Table 1217. Table References

Links
<a href="https://www.linkedin.com/pulse/mamba-new-full-disk-encryption-ransomware-family-member-marinho">https://www.linkedin.com/pulse/mamba-new-full-disk-encryption-ransomware-family-member-marinho</a>
<a href="https://blog.trendmicro.com/trendlabs-security-intelligence/bksod-by-ransomware-hddcryptor-uses-commercial-tools-to-encrypt-network-shares-and-lock-hdds/">blog.trendmicro.com/trendlabs-security-intelligence/bksod-by-ransomware-hddcryptor-uses-commercial-tools-to-encrypt-network-shares-and-lock-hdds/</a>

# Heimdall

Ransomware File marker: "Heimdall---"



Table 1218. Table References

Links

<https://www.bleepingcomputer.com/news/security/heimdall-open-source-php-ransomware-targets-web-servers/>

## Help\_dcfile

Ransomware

## Herbst

Ransomware

Table 1219. Table References

Links

<https://blog.fortinet.com/2016/06/03/cooking-up-autumn-herbst-ransomware>

## Hi Buddy!

Ransomware Based on HiddenTear

Table 1220. Table References

Links

<http://www.nyxbone.com/malware/hibuddy.html>

## Hitler

Ransomware Deletes files

Table 1221. Table References

Links

<http://www.bleepingcomputer.com/news/security/development-version-of-the-hitler-ransomware-discovered/>

<https://twitter.com/jiriatvirlab/status/825310545800740864>

## HolyCrypt

Ransomware

Table 1222. Table References

Links

<http://www.bleepingcomputer.com/news/security/new-python-ransomware-called-holycrypt-discovered/>

# HTCryptor

Ransomware Includes a feature to disable the victim's windows firewall Modified in-dev  
HiddenTear

*Table 1223. Table References*

Links
<a href="https://twitter.com/BleepinComputer/status/803288396814839808">https://twitter.com/BleepinComputer/status/803288396814839808</a>

# HydraCrypt

Ransomware CrypBoss Family

*Table 1224. Table References*

Links
<a href="https://decrypter.emsisoft.com/">https://decrypter.emsisoft.com/</a>
<a href="http://www.malware-traffic-analysis.net/2016/02/03/index2.html">http://www.malware-traffic-analysis.net/2016/02/03/index2.html</a>

# iLock

Ransomware

*Table 1225. Table References*

Links
<a href="https://twitter.com/BleepinComputer/status/817085367144873985">https://twitter.com/BleepinComputer/status/817085367144873985</a>

# iLockLight

Ransomware

# International Police Association

Ransomware CryptoTorLocker2015 variant

*Table 1226. Table References*

Links
<a href="http://download.bleepingcomputer.com/Nathan/StopPirates_Decrypter.exe">http://download.bleepingcomputer.com/Nathan/StopPirates_Decrypter.exe</a>

# iRansom

Ransomware

*Table 1227. Table References*

Links

<https://twitter.com/demonslay335/status/796134264744083460>

## JagerDecryptor

Ransomware Prepends filenames

*Table 1228. Table References*

Links

<https://twitter.com/JakubKroustek/status/757873976047697920>

## Jeiphoos

Ransomware Windows, Linux. Campaign stopped. Actor claimed he deleted the master key.

Jeiphoos is also known as:

- Encryptor RaaS
- Sarento

*Table 1229. Table References*

Links

<http://www.nyxbone.com/malware/RaaS.html>

<http://blog.trendmicro.com/trendlabs-security-intelligence/the-rise-and-fall-of-encryptor-raas/>

## Jhon Woddy

Ransomware Same codebase as DNRansomware Lock screen password is M3VZ>5BwGGVH

*Table 1230. Table References*

Links

<https://download.bleepingcomputer.com/demonslay335/DoNotOpenDecrypter.zip>

<https://twitter.com/BleepinComputer/status/822509105487245317>

## Jigsaw

Ransomware Has a GUI

Jigsaw is also known as:

- CryptoHitMan

*Table 1231. Table References*

Links

<http://www.bleepingcomputer.com/news/security/jigsaw-ransomware-decrypt-ed-will-delete-your-files-until-you-pay-the-ransom/>

<https://www.helpnetsecurity.com/2016/04/20/jigsaw-crypto-ransomware/>

<https://twitter.com/demonslay335/status/795819556166139905>

## Job Crypter

Ransomware Based on HiddenTear, but uses TripleDES, decrypter is PoC

*Table 1232. Table References*

Links

<http://www.nyxbone.com/malware/jobcrypter.html>

<http://forum.malekal.com/jobcrypter-geniesanstravaille-extension-locked-crypto-ransomware-t54381.html>

<https://twitter.com/malwrhunterteam/status/828914052973858816>

## JohnnyCryptor

Ransomware

## KawaiiLocker

Ransomware

*Table 1233. Table References*

Links

<https://safezone.cc/resources/kawaii-decryptor.195/>

## KeRanger

Ransomware OS X Ransomware

*Table 1234. Table References*

Links

<http://news.drweb.com/show/?i=9877&lng=en&c=5>

<http://www.welivesecurity.com/2016/03/07/new-mac-ransomware-appears-keranger-spread-via-transmission-app/>

## KeyBTC

Ransomware

*Table 1235. Table References*

Links
<a href="https://decrypter.emsisoft.com/">https://decrypter.emsisoft.com/</a>

## KEYHolder

Ransomware via remote attacker. [tuyuljahat@hotmail.com](mailto:tuyuljahat@hotmail.com) contact address

*Table 1236. Table References*

Links
<a href="http://www.bleepingcomputer.com/forums/t/559463/keyholder-ransomware-support-and-help-topic-how-decryptgifhow-decrypthtml">http://www.bleepingcomputer.com/forums/t/559463/keyholder-ransomware-support-and-help-topic-how-decryptgifhow-decrypthtml</a>

## KillerLocker

Ransomware Possibly Portuguese dev

*Table 1237. Table References*

Links
<a href="https://twitter.com/malwrhunterteam/status/782232299840634881">https://twitter.com/malwrhunterteam/status/782232299840634881</a>

## KimcilWare

Ransomware websites only

*Table 1238. Table References*

Links
<a href="https://blog.fortinet.com/post/kimcilware-ransomware-how-to-decrypt-encrypted-files-and-who-is-behind-it">https://blog.fortinet.com/post/kimcilware-ransomware-how-to-decrypt-encrypted-files-and-who-is-behind-it</a>
<a href="http://www.bleepingcomputer.com/news/security/the-kimcilware-ransomware-targets-web-sites-running-the-magento-platform/">http://www.bleepingcomputer.com/news/security/the-kimcilware-ransomware-targets-web-sites-running-the-magento-platform/</a>

## Korean

Ransomware Based on HiddenTear

*Table 1239. Table References*

Links
<a href="http://www.nyxbone.com/malware/koreanRansom.html">http://www.nyxbone.com/malware/koreanRansom.html</a>

## Kozy.Jozy

Ransomware      Potential      Kit      [selectedkozy.jozy@yahoo.com](mailto:selectedkozy.jozy@yahoo.com)      [kozy.jozy@yahoo.com](mailto:kozy.jozy@yahoo.com)  
[unlock92@india.com](mailto:unlock92@india.com)

Kozy.Jozy is also known as:

- QC

Table 1240. Table References

Links
<a href="http://www.nyxbone.com/malware/KozyJozy.html">http://www.nyxbone.com/malware/KozyJozy.html</a>
<a href="http://www.bleepingcomputer.com/forums/t/617802/kozyjozy-ransomware-help-support-wjpg-31392e30362e32303136-num-lsbj1/">http://www.bleepingcomputer.com/forums/t/617802/kozyjozy-ransomware-help-support-wjpg-31392e30362e32303136-num-lsbj1/</a>

## KratosCrypt

Ransomware [kratosdimetrici@gmail.com](mailto:kratosdimetrici@gmail.com)

Table 1241. Table References

Links
<a href="https://twitter.com/demonslay335/status/746090483722686465">https://twitter.com/demonslay335/status/746090483722686465</a>

## KryptoLocker

Ransomware Based on HiddenTear

## LanRan

Ransomware Variant of open-source MyLittleRansomware

Table 1242. Table References

Links
<a href="https://twitter.com/struppigel/status/847689644854595584">https://twitter.com/struppigel/status/847689644854595584</a>

## LeChiffre

Ransomware Encrypts first 0x2000 and last 0x2000 bytes. Via remote attacker

Table 1243. Table References

Links
<a href="https://decrypter.emsisoft.com/lechiffre">https://decrypter.emsisoft.com/lechiffre</a>
<a href="https://blog.malwarebytes.org/threat-analysis/2016/01/lechiffre-a-manually-run-ransomware/">https://blog.malwarebytes.org/threat-analysis/2016/01/lechiffre-a-manually-run-ransomware/</a>

## Lick

Ransomware Variant of Kirk

Table 1244. Table References

Links

<https://twitter.com/JakubKroustek/status/842404866614038529>

## Linux.Encoder

Ransomware Linux Ransomware

Linux.Encoder is also known as:

- Linux.Encoder.{0,3}

*Table 1245. Table References*

Links

<https://labs.bitdefender.com/2015/11/linux-ransomware-debut-fails-on-predictable-encryption-key/>

## LK Encryption

Ransomware Based on HiddenTear

*Table 1246. Table References*

Links

<https://twitter.com/malwrhunterteam/status/845183290873044994>

## LLTP Locker

Ransomware Targeting Spanish speaking victims

*Table 1247. Table References*

Links

<https://www.bleepingcomputer.com/news/security/new-lltp-ransomware-appears-to-be-a-rewritten-venus-locker/>

## Locker

Ransomware has GUI

*Table 1248. Table References*

Links

<http://www.bleepingcomputer.com/forums/t/577246/locker-ransomware-support-and-help-topic/page-32#entry3721545>

## LockLock

Ransomware

Table 1249. Table References

Links
<a href="https://www.bleepingcomputer.com/forums/t/626750/locklock-ransomware-locklock-help-support/">https://www.bleepingcomputer.com/forums/t/626750/locklock-ransomware-locklock-help-support/</a>

## Locky

Ransomware Affiliations with Dridex and Necurs botnets

Table 1250. Table References

Links
<a href="http://www.bleepingcomputer.com/news/security/new-locky-version-adds-the-zepto-extension-to-encrypted-files/">http://www.bleepingcomputer.com/news/security/new-locky-version-adds-the-zepto-extension-to-encrypted-files/</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/new-locky-ransomware-spotted-in-the-brazilian-underground-market-uses-windows-script-files/">http://blog.trendmicro.com/trendlabs-security-intelligence/new-locky-ransomware-spotted-in-the-brazilian-underground-market-uses-windows-script-files/</a>
<a href="https://nakedsecurity.sophos.com/2016/10/06/odin-ransomware-takes-over-from-zepto-and-locky/">https://nakedsecurity.sophos.com/2016/10/06/odin-ransomware-takes-over-from-zepto-and-locky/</a>
<a href="https://www.bleepingcomputer.com/news/security/locky-ransomware-switches-to-egyptian-mythology-with-the-osiris-extension/">https://www.bleepingcomputer.com/news/security/locky-ransomware-switches-to-egyptian-mythology-with-the-osiris-extension/</a>

## Lortok

Ransomware

## LowLevel04

Ransomware Prepends filenames

## M4N1F3STO

Ransomware Does not encrypt Unlock code=suckmydicknigga

Table 1251. Table References

Links
<a href="https://twitter.com/jiriatvirlab/status/808015275367002113">https://twitter.com/jiriatvirlab/status/808015275367002113</a>

## Mabouia

Ransomware OS X ransomware (PoC)

## MacAndChess

Ransomware Based on HiddenTear



# Magic

Ransomware Based on EDA2

# MaktubLocker

Ransomware

*Table 1252. Table References*

Links
<a href="https://blog.malwarebytes.org/threat-analysis/2016/03/maktub-locker-beautiful-and-dangerous/">https://blog.malwarebytes.org/threat-analysis/2016/03/maktub-locker-beautiful-and-dangerous/</a>

# MarsJoke

Ransomware

*Table 1253. Table References*

Links
<a href="https://securelist.ru/blog/issledovaniya/29376/polyglot-the-fake-ctb-locker/">https://securelist.ru/blog/issledovaniya/29376/polyglot-the-fake-ctb-locker/</a>
<a href="https://www.proofpoint.com/us/threat-insight/post/MarsJoke-Ransomware-Mimics-CTB-Locker">https://www.proofpoint.com/us/threat-insight/post/MarsJoke-Ransomware-Mimics-CTB-Locker</a>

# Meister

Ransomware Targeting French victims

*Table 1254. Table References*

Links
<a href="https://twitter.com/siri_urz/status/840913419024945152">https://twitter.com/siri_urz/status/840913419024945152</a>

# Meteoritan

Ransomware

*Table 1255. Table References*

Links
<a href="https://twitter.com/malwrhunterteam/status/844614889620561924">https://twitter.com/malwrhunterteam/status/844614889620561924</a>

# MIRCOP

Ransomware Prepends files Demands 48.48 BTC

MIRCOP is also known as:

- Crypt888

Table 1256. Table References

Links
<a href="http://www.bleepingcomputer.com/forums/t/618457/mircop-ransomware-help-support-lock-mircop/">http://www.bleepingcomputer.com/forums/t/618457/mircop-ransomware-help-support-lock-mircop/</a>
<a href="https://www.avast.com/ransomware-decryption-tools#!">https://www.avast.com/ransomware-decryption-tools#!</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/instruction-less-ransomware-mircop-channels-guy-fawkes/">http://blog.trendmicro.com/trendlabs-security-intelligence/instruction-less-ransomware-mircop-channels-guy-fawkes/</a>
<a href="http://www.nyxbone.com/malware/Mircop.html">http://www.nyxbone.com/malware/Mircop.html</a>

## MireWare

Ransomware Based on HiddenTear

## Mischa

Ransomware Packaged with Petya PDFBewerbungsmappe.exe

Mischa is also known as:

- "Petya's little brother"

Table 1257. Table References

Links
<a href="http://www.bleepingcomputer.com/news/security/petya-is-back-and-with-a-friend-named-mischa-ransomware/">http://www.bleepingcomputer.com/news/security/petya-is-back-and-with-a-friend-named-mischa-ransomware/</a>

## MM Locker

Ransomware Based on EDA2

MM Locker is also known as:

- Booyah

Table 1258. Table References

Links
<a href="https://www.proofpoint.com/us/threat-insight/post/ransomware-explosion-continues-cryptfile2-brlock-mm-locker-discovered">https://www.proofpoint.com/us/threat-insight/post/ransomware-explosion-continues-cryptfile2-brlock-mm-locker-discovered</a>

## Mobef

Ransomware

Mobef is also known as:

- Yakes
- CryptoBit

Table 1259. Table References

Links
<a href="http://nyxbone.com/malware/Mobef.html">http://nyxbone.com/malware/Mobef.html</a>
<a href="http://researchcenter.paloaltonetworks.com/2016/07/unit42-cryptobit-another-ransomware-family-gets-an-update/">http://researchcenter.paloaltonetworks.com/2016/07/unit42-cryptobit-another-ransomware-family-gets-an-update/</a>
<a href="http://nyxbone.com/images/articulos/malware/mobef/0.png">http://nyxbone.com/images/articulos/malware/mobef/0.png</a>

## Monument

Ransomware Use the DarkLocker 5 porn screenlocker - Jigsaw variant

Table 1260. Table References

Links
<a href="https://twitter.com/malwrhunterteam/status/844826339186135040">https://twitter.com/malwrhunterteam/status/844826339186135040</a>

## N-Splitter

Ransomware Russian Koolova Variant

Table 1261. Table References

Links
<a href="https://twitter.com/JakubKroustek/status/815961663644008448">https://twitter.com/JakubKroustek/status/815961663644008448</a>
<a href="https://www.youtube.com/watch?v=dAVMgX8Zti4&amp;feature=youtu.be&amp;list=UU_TMZYaLIgjsdJMwurHAi4Q">https://www.youtube.com/watch?v=dAVMgX8Zti4&amp;feature=youtu.be&amp;list=UU_TMZYaLIgjsdJMwurHAi4Q</a>

## n1n1n1

Ransomware Filemaker: "333333333333"

Table 1262. Table References

Links
<a href="https://twitter.com/demonslay335/status/790608484303712256">https://twitter.com/demonslay335/status/790608484303712256</a>
<a href="https://twitter.com/demonslay335/status/831891344897482754">https://twitter.com/demonslay335/status/831891344897482754</a>

## NanoLocker

Ransomware no extension change, has a GUI

Table 1263. Table References

Links
-------

<http://github.com/Cyberclues/nanolocker-decryptor>

## Nemucod

Ransomware 7zip (a0.exe) variant cannot be decrypted Encrypts the first 2048 Bytes

*Table 1264. Table References*

Links
<a href="https://decrypter.emsisoft.com/nemucod">https://decrypter.emsisoft.com/nemucod</a>
<a href="https://github.com/Antelox/NemucodFR">https://github.com/Antelox/NemucodFR</a>
<a href="http://www.bleepingcomputer.com/news/security/decryptor-released-for-the-nemucod-trojans-encrypted-ransomware/">http://www.bleepingcomputer.com/news/security/decryptor-released-for-the-nemucod-trojans-encrypted-ransomware/</a>
<a href="https://blog.cisecurity.org/malware-analysis-report-nemucod-ransomware/">https://blog.cisecurity.org/malware-analysis-report-nemucod-ransomware/</a>

## Netix

Ransomware

Netix is also known as:

- RANSOM\_NETIX.A

*Table 1265. Table References*

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/netflix-scam-delivers-ransomware/">http://blog.trendmicro.com/trendlabs-security-intelligence/netflix-scam-delivers-ransomware/</a>

## Nhtnwcuf

Ransomware Does not encrypt the files / Files are destroyed

*Table 1266. Table References*

Links
<a href="https://twitter.com/demonslay335/status/839221457360195589">https://twitter.com/demonslay335/status/839221457360195589</a>

## NMoreira

Ransomware

NMoreira is also known as:

- XRatTeam
- XPan

*Table 1267. Table References*

Links
<a href="https://decrypter.emsisoft.com/nmoreira">https://decrypter.emsisoft.com/nmoreira</a>
<a href="https://twitter.com/fwosar/status/803682662481174528">https://twitter.com/fwosar/status/803682662481174528</a>

## NoobCrypt

Ransomware

*Table 1268. Table References*

Links
<a href="https://twitter.com/JakubKroustek/status/757267550346641408">https://twitter.com/JakubKroustek/status/757267550346641408</a>
<a href="https://www.bleepingcomputer.com/news/security/noobcrypt-ransomware-dev-shows-noobness-by-using-same-password-for-everyone/">https://www.bleepingcomputer.com/news/security/noobcrypt-ransomware-dev-shows-noobness-by-using-same-password-for-everyone/</a>

## Nuke

Ransomware

## Nullbyte

Ransomware

*Table 1269. Table References*

Links
<a href="https://download.bleepingcomputer.com/demonslay335/NullByteDecrypter.zip">https://download.bleepingcomputer.com/demonslay335/NullByteDecrypter.zip</a>
<a href="https://www.bleepingcomputer.com/news/security/the-nullbyte-ransomware-pretends-to-be-the-necrobot-pokemon-go-application/">https://www.bleepingcomputer.com/news/security/the-nullbyte-ransomware-pretends-to-be-the-necrobot-pokemon-go-application/</a>

## ODCODC

Ransomware

*Table 1270. Table References*

Links
<a href="http://download.bleepingcomputer.com/BloodDolly/ODCODCDecoder.zip">http://download.bleepingcomputer.com/BloodDolly/ODCODCDecoder.zip</a>
<a href="http://www.nyxbone.com/malware/odcodc.html">http://www.nyxbone.com/malware/odcodc.html</a>
<a href="https://twitter.com/PolarToffee/status/813762510302183424">https://twitter.com/PolarToffee/status/813762510302183424</a>
<a href="http://www.nyxbone.com/images/articulos/malware/odcodc/1c.png">http://www.nyxbone.com/images/articulos/malware/odcodc/1c.png</a>

## Offline ransomware

Ransomware email addresses overlap with .777 addresses

Offline ransomware is also known as:

- Vipasana
- Cryakl

*Table 1271. Table References*

Links
<a href="https://support.kaspersky.com/viruses/disinfection/8547">https://support.kaspersky.com/viruses/disinfection/8547</a>
<a href="http://bartblaze.blogspot.com.co/2016/02/vipasana-ransomware-new-ransom-on-block.html">http://bartblaze.blogspot.com.co/2016/02/vipasana-ransomware-new-ransom-on-block.html</a>

## OMG! Ransomware

Ransomware

OMG! Ransomware is also known as:

- GPCode

## Operation Global III

Ransomware Is a file infector (virus)

*Table 1272. Table References*

Links
<a href="http://news.thewindowsclub.com/operation-global-iii-ransomware-decryption-tool-released-70341/">http://news.thewindowsclub.com/operation-global-iii-ransomware-decryption-tool-released-70341/</a>

## Owl

Ransomware

Owl is also known as:

- CryptoWire

*Table 1273. Table References*

Links
<a href="https://twitter.com/JakubKroustek/status/842342996775448576">https://twitter.com/JakubKroustek/status/842342996775448576</a>

## PadCrypt

Ransomware has a live support chat

*Table 1274. Table References*

Links
-------

<http://www.bleepingcomputer.com/news/security/padcrypt-the-first-ransomware-with-live-support-chat-and-an-uninstaller/>

<https://twitter.com/malwrhunterteam/status/798141978810732544>

## Padlock Screenlocker

Ransomware Unlock code is: ajVr/G\ RJz0R

*Table 1275. Table References*

Links

<https://twitter.com/BleepinComputer/status/811635075158839296>

## Patcher

Ransomware Targeting macOS users

*Table 1276. Table References*

Links

<https://blog.malwarebytes.com/cybercrime/2017/02/decrypting-after-a-findzip-ransomware-infection/>

<https://www.bleepingcomputer.com/news/security/new-macos-patcher-ransomware-locks-data-for-good-no-way-to-recover-your-files/>

## Petya

Ransomware encrypts disk partitions PDFBewerbungsmappe.exe

Petya is also known as:

- Goldeneye

*Table 1277. Table References*

Links

<http://www.thewindowsclub.com/petya-ransomware-decrypt-tool-password-generator>

[https://www.youtube.com/watch?v=mSqxFjZq\\_z4](https://www.youtube.com/watch?v=mSqxFjZq_z4)

<https://blog.malwarebytes.org/threat-analysis/2016/04/petya-ransomware/>

<https://www.bleepingcomputer.com/news/security/petya-ransomware-returns-with-goldeneye-version-continuing-james-bond-theme/>

## Philadelphia

Ransomware Coded by "The\_Rainmaker"

*Table 1278. Table References*

Links

<https://decrypter.emsisoft.com/philadelphia>

[www.bleepingcomputer.com/news/security/the-philadelphia-ransomware-offers-a-mercy-button-for-compassionate-criminals/](http://www.bleepingcomputer.com/news/security/the-philadelphia-ransomware-offers-a-mercy-button-for-compassionate-criminals/)

## PizzaCrypts

Ransomware

*Table 1279. Table References*

Links

<http://download.bleepingcomputer.com/BloodDolly/JuicyLemonDecoder.zip>

## PokemonGO

Ransomware Based on Hidden Tear

*Table 1280. Table References*

Links

<http://www.nyxbone.com/malware/pokemonGO.html>

<http://www.bleepingcomputer.com/news/security/pokemongo-ransomware-installs-backdoor-accounts-and-spreads-to-other-drives/>

## Polyglot

Ransomware Immitates CTB-Locker

*Table 1281. Table References*

Links

<https://support.kaspersky.com/8547>

<https://securelist.com/blog/research/76182/polyglot-the-fake-ctb-locker/>

## PowerWare

Ransomware Open-sourced PowerShell

PowerWare is also known as:

- PoshCoder

*Table 1282. Table References*

Links

[https://github.com/pan-unit42/public\\_tools/blob/master/powerware/powerware\\_decrypt.py](https://github.com/pan-unit42/public_tools/blob/master/powerware/powerware_decrypt.py)



<https://download.bleepingcomputer.com/demonslay335/PowerLockyDecrypter.zip>

<https://www.carbonblack.com/2016/03/25/threat-alert-powerware-new-ransomware-written-in-powershell-targets-organizations-via-microsoft-word/>

<http://researchcenter.paloaltonetworks.com/2016/07/unit42-powerware-ransomware-spoofing-locky-malware-family/>

## PowerWorm

Ransomware no decryption possible, throws key away, destroys the files

## Princess Locker

Ransomware

*Table 1283. Table References*

Links

<https://hshrzd.wordpress.com/2016/11/17/princess-locker-decryptor/>

<https://www.bleepingcomputer.com/news/security/introducing-her-royal-highness-the-princess-locker-ransomware/>

<https://blog.malwarebytes.com/threat-analysis/2016/11/princess-ransomware/>

## PRISM

Ransomware

*Table 1284. Table References*

Links

<http://www.enigmasoftware.com/prismyourcomputerhasbeenlockedransomware-removal/>

## Ps2exe

Ransomware

*Table 1285. Table References*

Links

<https://twitter.com/jiriatvirlab/status/803297700175286273>

## R

Ransomware

*Table 1286. Table References*

Links

<https://twitter.com/malwrhunterteam/status/846705481741733892>

## R980

Ransomware

*Table 1287. Table References*

Links

<https://otx.alienvault.com/pulse/57976b52b900fe01376feb01/>

## RAA encryptor

Ransomware Possible affiliation with Pony

RAA encryptor is also known as:

- RAA

*Table 1288. Table References*

Links

<https://reakta.com/2016/06/raa-ransomware-delivering-pony/>

<http://www.bleepingcomputer.com/news/security/the-new-raa-ransomware-is-created-entirely-using-javascript/>

## Rabion

Ransomware RaaS Copy of Ranion RaaS

*Table 1289. Table References*

Links

<https://twitter.com/CryptoInsane/status/846181140025282561>

## Radamant

Ransomware

*Table 1290. Table References*

Links

<https://decrypter.emsisoft.com/radamant>

<http://www.bleepingcomputer.com/news/security/new-radamant-ransomware-kit-adds-rdm-extension-to-encrypted-files/>

<http://www.nyxbone.com/malware/radamant.html>

# Rakhni

Ransomware Files might be partially encrypted

Rakhni is also known as:

- Agent.iih
- Aura
- Autoit
- Pletor
- Rotor
- Lamer
- Isda
- Cryptokluchen
- Bandarchor

*Table 1291. Table References*

Links
-------

<a href="https://support.kaspersky.com/us/viruses/disinfection/10556">https://support.kaspersky.com/us/viruses/disinfection/10556</a>
---

# Ramsomeer

Ransomware Based on the DUMB ransomware

# Rannoh

Ransomware

*Table 1292. Table References*

Links
-------

<a href="https://support.kaspersky.com/viruses/disinfection/8547">https://support.kaspersky.com/viruses/disinfection/8547</a>
---

# RanRan

Ransomware

*Table 1293. Table References*

Links
-------

<a href="https://github.com/pan-unit42/public_tools/tree/master/ranran_decryption">https://github.com/pan-unit42/public_tools/tree/master/ranran_decryption</a>
---

<a href="http://researchcenter.paloaltonetworks.com/2017/03/unit42-targeted-ransomware-attacks-middle-eastern-government-organizations-political-purposes/">http://researchcenter.paloaltonetworks.com/2017/03/unit42-targeted-ransomware-attacks-middle-eastern-government-organizations-political-purposes/</a>
---

<https://www.bleepingcomputer.com/news/security/new-ranran-ransomware-uses-encryption-tiers-political-messages/>

## Ransoc

Ransomware Doesn't encrypt user files

*Table 1294. Table References*

Links

<https://www.proofpoint.com/us/threat-insight/post/ransoc-desktop-locking-ransomware-ransacks-local-files-social-media-profiles>

<https://www.bleepingcomputer.com/news/security/ransoc-ransomware-extorts-users-who-accessed-questionable-content/>

## Ransom32

Ransomware no extension change, Javascript Ransomware

## RansomLock

Ransomware Locks the desktop

*Table 1295. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2009-041513-1400-99&tabid=2](https://www.symantec.com/security_response/writeup.jsp?docid=2009-041513-1400-99&tabid=2)

## RarVault

Ransomware

## Razy

Ransomware

*Table 1296. Table References*

Links

[http://www.nyxbone.com/malware/Razy\(German\).html](http://www.nyxbone.com/malware/Razy(German).html)

<http://nyxbone.com/malware/Razy.html>

## Rector

Ransomware

*Table 1297. Table References*

Links
-------

<a href="https://support.kaspersky.com/viruses/disinfection/4264">https://support.kaspersky.com/viruses/disinfection/4264</a>
---

## RektLocker

Ransomware

*Table 1298. Table References*

Links
-------

<a href="https://support.kaspersky.com/viruses/disinfection/4264">https://support.kaspersky.com/viruses/disinfection/4264</a>
---

## RemindMe

Ransomware

*Table 1299. Table References*

Links
-------

<a href="http://www.nyxbone.com/malware/RemindMe.html">http://www.nyxbone.com/malware/RemindMe.html</a>
---

<a href="http://i.imgur.com/gV6i5SN.jpg">http://i.imgur.com/gV6i5SN.jpg</a>
---

## Rokku

Ransomware possibly related with Chimera

*Table 1300. Table References*

Links
-------

<a href="https://blog.malwarebytes.org/threat-analysis/2016/04/rokku-ransomware/">https://blog.malwarebytes.org/threat-analysis/2016/04/rokku-ransomware/</a>
---

## RoshaLock

Ransomware Stores your files in a password protected RAR file

*Table 1301. Table References*

Links
-------

<a href="https://twitter.com/siri_urz/status/842452104279134209">https://twitter.com/siri_urz/status/842452104279134209</a>
---

## Ransomewere

Ransomware Based on HT/EDA2 Utilizes the Jigsaw Ransomware background

*Table 1302. Table References*

Links
-------

<https://twitter.com/struppigel/status/801812325657440256>

## RussianRoulette

Ransomware Variant of the Philadelphia ransomware

*Table 1303. Table References*

Links

<https://twitter.com/struppigel/status/823925410392080385>

## SADStory

Ransomware Variant of CryPy

*Table 1304. Table References*

Links

<https://twitter.com/malwrhunterteam/status/845356853039190016>

## Sage 2.2

Ransomware Sage 2.2 deletes volume snapshots through vssadmin.exe, disables startup repair, uses process wscript.exe to execute a VBScript, and coordinates the execution of scheduled tasks via schtasks.exe.

*Table 1305. Table References*

Links

<https://malwarebreakdown.com/2017/03/16/sage-2-2-ransomware-from-good-man-gate>

<https://malwarebreakdown.com/2017/03/10/finding-a-good-man/>

## Samas-Samsam

Ransomware Targeted attacks -Jexboss -PSExec -Hyena

Samas-Samsam is also known as:

- samsam.exe
- MIKOPONI.exe
- RikiRafael.exe
- showmehowto.exe

*Table 1306. Table References*

Links

<https://download.bleepingcomputer.com/demonslay335/SamSamStringDecrypter.zip>

<http://blog.talosintel.com/2016/03/samsam-ransomware.html>

[http://www.intelsecurity.com/advanced-threat-research/content/Analysis\\_SamSa\\_Ransomware.pdf](http://www.intelsecurity.com/advanced-threat-research/content/Analysis_SamSa_Ransomware.pdf)

## Sanction

Ransomware Based on HiddenTear, but heavily modified keygen

## Sanctions

Ransomware

*Table 1307. Table References*

Links

<https://www.bleepingcomputer.com/news/security/sanctions-ransomware-makes-fun-of-usa-sanctions-against-russia/>

## Sardoninir

Ransomware

*Table 1308. Table References*

Links

<https://twitter.com/BleepinComputer/status/835955409953357825>

## Satana

Ransomware

*Table 1309. Table References*

Links

<https://blog.malwarebytes.com/threat-analysis/2016/06/satana-ransomware/>

<https://blog.kaspersky.com/satana-ransomware/12558/>

## Scraper

Ransomware

*Table 1310. Table References*

Links

<http://securelist.com/blog/research/69481/a-flawed-ransomware-encryptor/>

# Serpico

Ransomware DetoxCrypto Variant

Table 1311. Table References

Links
<a href="http://www.nyxbone.com/malware/Serpico.html">http://www.nyxbone.com/malware/Serpico.html</a>

# Shark

Ransomware

Shark is also known as:

- Atom

Table 1312. Table References

Links
<a href="http://www.bleepingcomputer.com/news/security/the-shark-ransomware-project-allows-to-create-your-own-customized-ransomware/">http://www.bleepingcomputer.com/news/security/the-shark-ransomware-project-allows-to-create-your-own-customized-ransomware/</a>
<a href="http://www.bleepingcomputer.com/news/security/shark-ransomware-rebrands-as-atom-for-a-fresh-start/">http://www.bleepingcomputer.com/news/security/shark-ransomware-rebrands-as-atom-for-a-fresh-start/</a>

# ShinoLocker

Ransomware

Table 1313. Table References

Links
<a href="https://twitter.com/JakubKroustek/status/760560147131408384">https://twitter.com/JakubKroustek/status/760560147131408384</a>
<a href="http://www.bleepingcomputer.com/news/security/new-educational-shinolocker-ransomware-project-released/">http://www.bleepingcomputer.com/news/security/new-educational-shinolocker-ransomware-project-released/</a>

# Shujin

Ransomware

Shujin is also known as:

- KinCrypt

Table 1314. Table References

Links
<a href="http://www.nyxbone.com/malware/chineseRansom.html">http://www.nyxbone.com/malware/chineseRansom.html</a>



<http://blog.trendmicro.com/trendlabs-security-intelligence/chinese-language-ransomware-makes-appearance/>

## Simple\_Encoder

Ransomware

*Table 1315. Table References*

Links

<http://www.bleepingcomputer.com/news/security/the-shark-ransomware-project-allows-to-create-your-own-customized-ransomware/>

## SkidLocker

Ransomware Based on EDA2

SkidLocker is also known as:

- Pompous

*Table 1316. Table References*

Links

<http://www.bleepingcomputer.com/news/security/pompous-ransomware-dev-gets-defeated-by-backdoor/>

<http://www.nyxbone.com/malware/SkidLocker.html>

## Smash!

Ransomware

*Table 1317. Table References*

Links

<https://www.bleepingcomputer.com/news/security/smash-ransomware-is-cute-rather-than-dangerous/>

## Smr32

Ransomware

## SNSLocker

Ransomware Based on EDA2

*Table 1318. Table References*

Links
<a href="http://nyxbone.com/malware/SNSLocker.html">http://nyxbone.com/malware/SNSLocker.html</a>
<a href="http://nyxbone.com/images/articulos/malware/snslocker/16.png">http://nyxbone.com/images/articulos/malware/snslocker/16.png</a>

## Sport

Ransomware

## Stampado

Ransomware Coded by "The\_Rainmaker" Randomly deletes a file every 6hrs up to 96hrs then deletes decryption key

*Table 1319. Table References*

Links
<a href="https://success.trendmicro.com/portal_kb_articledetail?solutionid=1114221">https://success.trendmicro.com/portal_kb_articledetail?solutionid=1114221</a>
<a href="http://www.bleepingcomputer.com/news/security/stampado-ransomware-campaign-decrypted-before-it-started/">http://www.bleepingcomputer.com/news/security/stampado-ransomware-campaign-decrypted-before-it-started/</a>
<a href="https://decrypter.emsisoft.com/stampado">https://decrypter.emsisoft.com/stampado</a>
<a href="https://cdn.streamable.com/video/mp4/kfh3.mp4">https://cdn.streamable.com/video/mp4/kfh3.mp4</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/the-economics-behind-ransomware-prices/">http://blog.trendmicro.com/trendlabs-security-intelligence/the-economics-behind-ransomware-prices/</a>

## Strictor

Ransomware Based on EDA2, shows Guy Fawkes mask

*Table 1320. Table References*

Links
<a href="http://www.nyxbone.com/malware/Strictor.html">http://www.nyxbone.com/malware/Strictor.html</a>

## Surprise

Ransomware Based on EDA2

## Survey

Ransomware Still in development, shows FileIce survey

*Table 1321. Table References*

Links
<a href="http://www.bleepingcomputer.com/news/security/in-dev-ransomware-forces-you-do-to-survey-before-unlocking-computer/">http://www.bleepingcomputer.com/news/security/in-dev-ransomware-forces-you-do-to-survey-before-unlocking-computer/</a>

# SynoLocker

Ransomware Exploited Synology NAS firmware directly over WAN

# SZFLocker

Ransomware

Table 1322. Table References

Links
<a href="http://now.avg.com/dont-pay-the-ransom-avg-releases-six-free-decryption-tools-to-retrieve-your-files/">http://now.avg.com/dont-pay-the-ransom-avg-releases-six-free-decryption-tools-to-retrieve-your-files/</a>

# TeamXrat

Ransomware

Table 1323. Table References

Links
<a href="https://securelist.com/blog/research/76153/teamxrat-brazilian-cybercrime-meets-ransomware/">https://securelist.com/blog/research/76153/teamxrat-brazilian-cybercrime-meets-ransomware/</a>

# TeslaCrypt 0.x - 2.2.0

Ransomware Factorization

TeslaCrypt 0.x - 2.2.0 is also known as:

- AlphaCrypt

Table 1324. Table References

Links
<a href="http://www.bleepingcomputer.com/forums/t/576600/tesldecoder-released-to-decrypt-exx-ezz-ecc-files-encrypted-by-teslacrypt/">http://www.bleepingcomputer.com/forums/t/576600/tesldecoder-released-to-decrypt-exx-ezz-ecc-files-encrypted-by-teslacrypt/</a>
<a href="http://www.talosintel.com/teslacrypt_tool/">http://www.talosintel.com/teslacrypt_tool/</a>

# TeslaCrypt 3.0+

Ransomware 4.0+ has no extension

Table 1325. Table References

Links
<a href="http://www.bleepingcomputer.com/forums/t/576600/tesldecoder-released-to-decrypt-exx-ezz-ecc-files-encrypted-by-teslacrypt/">http://www.bleepingcomputer.com/forums/t/576600/tesldecoder-released-to-decrypt-exx-ezz-ecc-files-encrypted-by-teslacrypt/</a>

<http://www.welivesecurity.com/2016/05/18/eset-releases-decryptor-recent-variants-teslacrypt-ransomware/>

<https://blog.kaspersky.com/raknidecryptor-vs-teslacrypt/12169/>

## TeslaCrypt 4.1A

Ransomware

Table 1326. Table References

Links

<http://www.bleepingcomputer.com/forums/t/576600/tesldecoder-released-to-decrypt-exx-ezz-ecc-files-encrypted-by-teslacrypt/>

<http://www.welivesecurity.com/2016/05/18/eset-releases-decryptor-recent-variants-teslacrypt-ransomware/>

<https://blog.kaspersky.com/raknidecryptor-vs-teslacrypt/12169/>

<https://www.endgame.com/blog/your-package-has-been-successfully-encrypted-teslacrypt-41a-and-malware-attack-chain>

## TeslaCrypt 4.2

Ransomware

Table 1327. Table References

Links

<http://www.bleepingcomputer.com/forums/t/576600/tesldecoder-released-to-decrypt-exx-ezz-ecc-files-encrypted-by-teslacrypt/>

<http://www.welivesecurity.com/2016/05/18/eset-releases-decryptor-recent-variants-teslacrypt-ransomware/>

<https://blog.kaspersky.com/raknidecryptor-vs-teslacrypt/12169/>

<http://www.bleepingcomputer.com/news/security/teslacrypt-4-2-released-with-quite-a-few-modifications/>

## Threat Finder

Ransomware Files cannot be decrypted Has a GUI

## TorrentLocker

Ransomware Newer variants not decryptable. Only first 2 MB are encrypted

TorrentLocker is also known as:

- Crypt0L0cker
- CryptoFortress

- Teerac

Table 1328. Table References

Links
<a href="http://www.bleepingcomputer.com/forums/t/547708/torrentlocker-ransomware-cracked-and-decrypter-has-been-made/">http://www.bleepingcomputer.com/forums/t/547708/torrentlocker-ransomware-cracked-and-decrypter-has-been-made/</a>
<a href="https://twitter.com/PolarToffee/status/804008236600934403">https://twitter.com/PolarToffee/status/804008236600934403</a>
<a href="http://blog.talosintelligence.com/2017/03/crypt0l0cker-torrentlocker-old-dog-new.html">http://blog.talosintelligence.com/2017/03/crypt0l0cker-torrentlocker-old-dog-new.html</a>

## TowerWeb

Ransomware

Table 1329. Table References

Links
<a href="http://www.bleepingcomputer.com/forums/t/618055/towerweb-ransomware-help-support-topic-payment-instructionsjpg/">http://www.bleepingcomputer.com/forums/t/618055/towerweb-ransomware-help-support-topic-payment-instructionsjpg/</a>

## Toxcrypt

Ransomware

## Trojan

Ransomware

Trojan is also known as:

- BrainCrypt

Table 1330. Table References

Links
<a href="https://download.bleepingcomputer.com/demonslay335/BrainCryptDecrypter.zip">https://download.bleepingcomputer.com/demonslay335/BrainCryptDecrypter.zip</a>
<a href="https://twitter.com/PolarToffee/status/811249250285842432">https://twitter.com/PolarToffee/status/811249250285842432</a>

## Troldesh orShade, XTBL

Ransomware May download additional malware after encryption

Table 1331. Table References

Links
<a href="https://www.nomoreransom.org/uploads/ShadeDecryptor_how-to_guide.pdf">https://www.nomoreransom.org/uploads/ShadeDecryptor_how-to_guide.pdf</a>
<a href="http://www.nyxbone.com/malware/Troldesh.html">http://www.nyxbone.com/malware/Troldesh.html</a>

<https://www.bleepingcomputer.com/news/security/kelihos-botnet-delivering-shade-troldesh-ransomware-with-no-more-ransom-extension/>

## TrueCrypter

Ransomware

*Table 1332. Table References*

Links

<http://www.bleepingcomputer.com/news/security/truecrypter-ransomware-accepts-payment-in-bitcoins-or-amazon-gift-card/>

## Turkish

Ransomware

*Table 1333. Table References*

Links

<https://twitter.com/struppigel/status/821991600637313024>

## Turkish Ransom

Ransomware

*Table 1334. Table References*

Links

<http://www.nyxbone.com/malware/turkishRansom.html>

## UmbreCrypt

Ransomware CrypBoss Family

*Table 1335. Table References*

Links

<http://www.thewindowsclub.com/emsisoft-decrypter-hydracrypt-umbrecrypt-ransomware>

## UnblockUPC

Ransomware

*Table 1336. Table References*

Links

<https://www.bleepingcomputer.com/forums/t/627582/unblockupc-ransomware-help-support-topic-files-encryptedtxt/>

## Ungluk

Ransomware Ransom note instructs to use Bitmessage to get in contact with attacker - Secretishere.key - SECRETISHIDINGHEREINSIDE.KEY - secret.key

## Unlock92

Ransomware

*Table 1337. Table References*

Links

<https://twitter.com/malwrhunterteam/status/839038399944224768>

## VapeLauncher

Ransomware CryptoWire variant

*Table 1338. Table References*

Links

<https://twitter.com/struppigel/status/839771195830648833>

## VaultCrypt

Ransomware

VaultCrypt is also known as:

- CrypVault
- Zlader

*Table 1339. Table References*

Links

<http://www.nyxbone.com/malware/russianRansom.html>

## VBRANSOM 7

Ransomware

*Table 1340. Table References*

Links

<https://twitter.com/BleepinComputer/status/817851339078336513>

# VenusLocker

Ransomware Based on EDA2

Table 1341. Table References

Links
<a href="https://blog.malwarebytes.com/threat-analysis/2016/08/venus-locker-another-net-ransomware/?utm_source=twitter&amp;utm_medium=social">https://blog.malwarebytes.com/threat-analysis/2016/08/venus-locker-another-net-ransomware/?utm_source=twitter&amp;utm_medium=social</a>
<a href="http://www.nyxbone.com/malware/venusLocker.html">http://www.nyxbone.com/malware/venusLocker.html</a>

# Virlock

Ransomware Polymorphism / Self-replication

Table 1342. Table References

Links
<a href="http://www.nyxbone.com/malware/Virlock.html">http://www.nyxbone.com/malware/Virlock.html</a>
<a href="http://www.welivesecurity.com/2014/12/22/win32virlock-first-self-reproducing-ransomware-also-shape-shifter/">http://www.welivesecurity.com/2014/12/22/win32virlock-first-self-reproducing-ransomware-also-shape-shifter/</a>

# Virus-Encoder

Ransomware

Virus-Encoder is also known as:

- CrySiS

Table 1343. Table References

Links
<a href="http://www.welivesecurity.com/2016/11/24/new-decryption-tool-crysis-ransomware/">http://www.welivesecurity.com/2016/11/24/new-decryption-tool-crysis-ransomware/</a>
<a href="http://media.kaspersky.com/utilities/VirusUtilities/EN/rakhnidecryptor.zip">http://media.kaspersky.com/utilities/VirusUtilities/EN/rakhnidecryptor.zip</a>
<a href="http://www.nyxbone.com/malware/virus-encoder.html">http://www.nyxbone.com/malware/virus-encoder.html</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/crysis-targeting-businesses-in-australia-new-zealand-via-brute-forced-rdps/">http://blog.trendmicro.com/trendlabs-security-intelligence/crysis-targeting-businesses-in-australia-new-zealand-via-brute-forced-rdps/</a>

# WildFire Locker

Ransomware Zyklon variant

WildFire Locker is also known as:

- Hades Locker

Table 1344. Table References



Links
-------

<a href="https://labs.opendns.com/2016/07/13/wildfire-ransomware-gaining-momentum/">https://labs.opendns.com/2016/07/13/wildfire-ransomware-gaining-momentum/</a>
---

## Xorist

Ransomware encrypted files will still have the original non-encrypted header of 0x33 bytes length

*Table 1345. Table References*

Links
-------

<a href="https://support.kaspersky.com/viruses/disinfection/2911">https://support.kaspersky.com/viruses/disinfection/2911</a>
---

<a href="https://decrypter.emsisoft.com/xorist">https://decrypter.emsisoft.com/xorist</a>
---

## XRTN

Ransomware VaultCrypt family

## You Have Been Hacked!!!

Ransomware Attempt to steal passwords

*Table 1346. Table References*

Links
-------

<a href="https://twitter.com/malwrhunterteam/status/808280549802418181">https://twitter.com/malwrhunterteam/status/808280549802418181</a>
---

## Zcrypt

Ransomware

Zcrypt is also known as:

- Zcryptor

*Table 1347. Table References*

Links
-------

<a href="https://blogs.technet.microsoft.com/mmpc/2016/05/26/link-lnk-to-ransom/">https://blogs.technet.microsoft.com/mmpc/2016/05/26/link-lnk-to-ransom/</a>
---

## Zeta

Ransomware

Zeta is also known as:

- CryptoMix

*Table 1348. Table References*

Links

<https://twitter.com/JakubKroustek/status/804009831518572544>

## Zimbra

Ransomware [mpriksen@priest.com](mailto:mpriksen@priest.com)

*Table 1349. Table References*

Links

<http://www.bleepingcomputer.com/forums/t/617874/zimbra-ransomware-written-in-python-help-and-support-topic-crypto-howtotxt/>

## Zlader

Ransomware VaultCrypt family

Zlader is also known as:

- Russian
- VaultCrypt
- CrypVault

*Table 1350. Table References*

Links

<http://www.nyxbone.com/malware/russianRansom.html>

## Zorro

Ransomware

*Table 1351. Table References*

Links

<https://twitter.com/BleepinComputer/status/844538370323812353>

## Zyklon

Ransomware Hidden Tear family, GNL Locker variant

Zyklon is also known as:

- GNL Locker

# vxLock

Ransomware

## Jaff

We recently observed several large scale email campaigns that were attempting to distribute a new variant of ransomware that has been dubbed "Jaff". Interestingly we identified several characteristics that we have previously observed being used during Dridex and Locky campaigns. In a short period of time, we observed multiple campaigns featuring high volumes of malicious spam emails being distributed, each using a PDF attachment with an embedded Microsoft Word document functioning as the initial downloader for the Jaff ransomware.

Table 1352. Table References

Links
<a href="http://blog.talosintelligence.com/2017/05/jaff-ransomware.html">http://blog.talosintelligence.com/2017/05/jaff-ransomware.html</a>
<a href="https://www.bleepingcomputer.com/news/security/jaff-ransomware-distributed-via-necurs-malspam-and-asking-for-a-3-700-ransom/">https://www.bleepingcomputer.com/news/security/jaff-ransomware-distributed-via-necurs-malspam-and-asking-for-a-3-700-ransom/</a>

## Uiwix Ransomware

Using EternalBlue SMB Exploit To Infect Victims

Table 1353. Table References

Links
<a href="https://www.bleepingcomputer.com/news/security/uiwix-ransomware-using-eternalblue-smb-exploit-to-infect-victims/">https://www.bleepingcomputer.com/news/security/uiwix-ransomware-using-eternalblue-smb-exploit-to-infect-victims/</a>

## SOREBRECT

Fileless, Code-injecting Ransomware

Table 1354. Table References

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/analyzing-fileless-code-injecting-sorebrect-ransomware/">http://blog.trendmicro.com/trendlabs-security-intelligence/analyzing-fileless-code-injecting-sorebrect-ransomware/</a>

## Cyron

claims it detected "Children Pornsites" in your browser history

Table 1355. Table References

Links
<a href="https://twitter.com/struppigel/status/899524853426008064">https://twitter.com/struppigel/status/899524853426008064</a>

## Kappa

Made with OXAR builder; decryptable

*Table 1356. Table References*

Links
<a href="https://twitter.com/struppigel/status/899528477824700416">https://twitter.com/struppigel/status/899528477824700416</a>

## Trojan Dz

CyberSplitter variant

*Table 1357. Table References*

Links
<a href="https://twitter.com/struppigel/status/899537940539478016">https://twitter.com/struppigel/status/899537940539478016</a>

## Xolzsec

ransomware written by self proclaimed script kiddies that should really be considered trollware

*Table 1358. Table References*

Links
<a href="https://twitter.com/struppigel/status/899916577252028416">https://twitter.com/struppigel/status/899916577252028416</a>

## FlatChestWare

HiddenTear variant; decryptable

*Table 1359. Table References*

Links
<a href="https://twitter.com/struppigel/status/900238572409823232">https://twitter.com/struppigel/status/900238572409823232</a>

## SynAck

The ransomware does not use a customized desktop wallpaper to signal its presence, and the only way to discover that SynAck has infected your PC is by the ransom notes dropped on the user's desktop, named in the format: RESTORE\_INFO-[id].txt. For example: RESTORE\_INFO-4ABFA0EF.txt. In addition, SynAck also appends its own extension at the end of all files it encrypted. This file extensions format is ten random alpha characters for each file. For example: test.jpg.XbMiJQiuoh. Experts believe the group behind SynAck uses RDP brute-force attacks to access remote computers and manually download and install the ransomware.

SynAck is also known as:

- Syn Ack

Table 1360. Table References

Links
<a href="https://www.bleepingcomputer.com/news/security/synack-ransomware-sees-huge-spike-in-activity/">https://www.bleepingcomputer.com/news/security/synack-ransomware-sees-huge-spike-in-activity/</a>

## SyncCrypt

A new ransomware called SyncCrypt was discovered by Emsisoft security researcher xXToffeeXx that is being distributed by spam attachments containing WSF files. When installed these attachments will encrypt a computer and append the .kk extension to encrypted files.

Table 1361. Table References

Links
<a href="https://www.bleepingcomputer.com/news/security/synccrypt-ransomware-hides-inside-jpg-files-appends-kk-extension/">https://www.bleepingcomputer.com/news/security/synccrypt-ransomware-hides-inside-jpg-files-appends-kk-extension/</a>

## Bad Rabbit

On October 24, 2017, Cisco Talos was alerted to a widescale ransomware campaign affecting organizations across eastern Europe and Russia. As was the case in previous situations, we quickly mobilized to assess the situation and ensure that customers remain protected from this and other threats as they emerge across the threat landscape. There have been several large scale ransomware campaigns over the last several months. This appears to have some similarities to Nyetya in that it is also based on Petya ransomware. Major portions of the code appear to have been rewritten. The distribution does not appear to have the sophistication of the supply chain attacks we have seen recently.

Bad Rabbit is also known as:

- BadRabbit
- Bad-Rabbit

Table 1362. Table References

Links
<a href="http://blog.talosintelligence.com/2017/10/bad-rabbit.html">http://blog.talosintelligence.com/2017/10/bad-rabbit.html</a>

## RAT

remote administration tool or remote access tool (RAT), also called sometimes remote access trojan, is a piece of software or programming that allows a remote "operator" to control a system as if they have physical access to that system..



RAT is a cluster galaxy available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

## authors

Various

# TeamViewer

TeamViewer is a proprietary computer software package for remote control, desktop sharing, online meetings, web conferencing and file transfer between computers.

*Table 1363. Table References*

Links
<a href="https://www.teamviewer.com">https://www.teamviewer.com</a>

# JadeRAT

JadeRAT is just one example of numerous mobile surveillanceware families we've seen in recent months, indicating that actors are continuing to incorporate mobile tools in their attack chains.

*Table 1364. Table References*

Links
<a href="https://blog.lookout.com/mobile-threat-jaderat">https://blog.lookout.com/mobile-threat-jaderat</a>

# Back Orifice

Back Orifice (often shortened to BO) is a computer program designed for remote system administration. It enables a user to control a computer running the Microsoft Windows operating system from a remote location.

Back Orifice is also known as:

- BO

*Table 1365. Table References*

Links
<a href="http://www.cultdeadcow.com/tools/bo.html">http://www.cultdeadcow.com/tools/bo.html</a>
<a href="http://www.symantec.com/avcenter/warn/backorifice.html">http://www.symantec.com/avcenter/warn/backorifice.html</a>

# Netbus

NetBus or Netbus is a software program for remotely controlling a Microsoft Windows computer system over a network. It was created in 1998 and has been very controversial for its potential of being used as a backdoor.

Netbus is also known as:

- NetBus

Table 1366. Table References

Links
<a href="http://www.symantec.com/avcenter/warn/backorifice.html">http://www.symantec.com/avcenter/warn/backorifice.html</a>
<a href="https://www.f-secure.com/v-descs/netbus.shtml">https://www.f-secure.com/v-descs/netbus.shtml</a>

## PoisonIvy

Poison Ivy is a RAT which was freely available and first released in 2005.

PoisonIvy is also known as:

- Poison Ivy
- Backdoor.Win32.PoisonIvy
- Gen:Trojan.Heur.PT

Table 1367. Table References

Links
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-poison-ivy.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-poison-ivy.pdf</a>
<a href="https://www.f-secure.com/v-descs/backdoor_w32_poisonivy.shtml">https://www.f-secure.com/v-descs/backdoor_w32_poisonivy.shtml</a>

## Sub7

Sub7, or SubSeven or Sub7Server, is a Trojan horse program.[1] Its name was derived by spelling NetBus backwards ("suBteN") and swapping "ten" with "seven". Sub7 was created by Mobman. Mobman has not maintained or updated the software since 2004, however an author known as Read101 has carried on the Sub7 legacy.

Sub7 is also known as:

- SubSeven
- Sub7Server

Table 1368. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2001-020114-5445-99">https://www.symantec.com/security_response/writeup.jsp?docid=2001-020114-5445-99</a>

## Beast Trojan

Beast is a Windows-based backdoor trojan horse, more commonly known in the hacking community as a Remote Administration Tool or a "RAT". It is capable of infecting versions of Windows from 95 to 10.

Table 1369. Table References

Links
<a href="https://en.wikipedia.org/wiki/Beast_(Trojan_horse)">https://en.wikipedia.org/wiki/Beast_(Trojan_horse)</a>

## Bifrost

Bifrost is a discontinued backdoor trojan horse family of more than 10 variants which can infect Windows 95 through Windows 10 (although on modern Windows systems, after Windows XP, its functionality is limited). Bifrost uses the typical server, server builder, and client backdoor program configuration to allow a remote attacker, who uses the client, to execute arbitrary code on the compromised machine (which runs the server whose behavior can be controlled by the server editor).

*Table 1370. Table References*

Links
<a href="https://www.revolvvy.com/main/index.php?s=Bifrost%20(trojan%20horse)&amp;item_type=topic">https://www.revolvvy.com/main/index.php?s=Bifrost%20(trojan%20horse)&amp;item_type=topic</a>
<a href="http://malware-info.blogspot.lu/2008/10/bifrost-trojan.html">http://malware-info.blogspot.lu/2008/10/bifrost-trojan.html</a>

## Blackshades

Blackshades is the name of a malicious trojan horse used by hackers to control computers remotely. The malware targets computers using Microsoft Windows -based operating systems.[2] According to US officials, over 500,000 computer systems have been infected worldwide with the software.

*Table 1371. Table References*

Links
<a href="https://krebsonsecurity.com/2014/05/blackshades-trojan-users-had-it-coming/">https://krebsonsecurity.com/2014/05/blackshades-trojan-users-had-it-coming/</a>

## DarkComet

DarkComet is a Remote Administration Tool (RAT) which was developed by Jean-Pierre Lesueur (known as DarkCoderSc), an independent programmer and computer security coder from the United Kingdom. Although the RAT was developed back in 2008, it began to proliferate at the start of 2012.

DarkComet is also known as:

- Dark Comet

*Table 1372. Table References*

Links
<a href="https://blog.malwarebytes.com/threat-analysis/2012/06/you-dirty-rat-part-1-darkcomet/">https://blog.malwarebytes.com/threat-analysis/2012/06/you-dirty-rat-part-1-darkcomet/</a>
<a href="https://blogs.cisco.com/security/talos/darkkomet-rat-spam">https://blogs.cisco.com/security/talos/darkkomet-rat-spam</a>



## Lanfiltrator

Backdoor.Lanfiltrator is a backdoor Trojan that gives an attacker unauthorized access to a compromised computer. The detection is used for a family of Trojans that are produced by the Backdoor.Lanfiltrator generator.

Table 1373. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2002-121116-0350-99">https://www.symantec.com/security_response/writeup.jsp?docid=2002-121116-0350-99</a>

## Win32.HsIdir

Win32.HsIdir is an advanced remote administrator tool systems was done by the original author HS32-Idir, it is the development of the release made since 2006 Copyright © 2006-2010 HS32-Idir.

Table 1374. Table References

Links
<a href="http://lexmarket.su/thread-27692.html">http://lexmarket.su/thread-27692.html</a>
<a href="https://www.nulled.to/topic/129749-win32hsidir-rat/">https://www.nulled.to/topic/129749-win32hsidir-rat/</a>

## Optix Pro

Optix Pro is a configurable remote access tool or Trojan, similar to SubSeven or BO2K

Table 1375. Table References

Links
<a href="https://en.wikipedia.org/wiki/Optix_Pro">https://en.wikipedia.org/wiki/Optix_Pro</a>
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2002-090416-0521-99">https://www.symantec.com/security_response/writeup.jsp?docid=2002-090416-0521-99</a>
<a href="https://www.symantec.com/security_response/attacksignatures/detail.jsp?asid=20208">https://www.symantec.com/security_response/attacksignatures/detail.jsp?asid=20208</a>

## Back Orifice 2000

Back Orifice 2000 (often shortened to BO2k) is a computer program designed for remote system administration. It enables a user to control a computer running the Microsoft Windows operating system from a remote location. The name is a pun on Microsoft BackOffice Server software. Back Orifice 2000 is a new version of the famous Back Orifice backdoor trojan (hacker's remote access tool). It was created by the Cult of Dead Cow hackers group in July 1999. Originally the BO2K was released as a source code and utilities package on a CD-ROM. There are reports that some files on that CD-ROM were infected with CIH virus, so the people who got that CD might get infected and spread not only the compiled backdoor, but also the CIH virus.

Back Orifice 2000 is also known as:

- BO2k

Table 1376. Table References

Links
<a href="https://en.wikipedia.org/wiki/Back_Orifice_2000">https://en.wikipedia.org/wiki/Back_Orifice_2000</a>
<a href="https://home.mcafee.com/VirusInfo/VirusProfile.aspx?key=10229">https://home.mcafee.com/VirusInfo/VirusProfile.aspx?key=10229</a>
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2000-121814-5417-99">https://www.symantec.com/security_response/writeup.jsp?docid=2000-121814-5417-99</a>
<a href="https://www.f-secure.com/v-descs/bo2k.shtml">https://www.f-secure.com/v-descs/bo2k.shtml</a>

## RealVNC

The software consists of a server and client application for the Virtual Network Computing (VNC) protocol to control another

RealVNC is also known as:

- VNC Connect
- VNC Viewer

Table 1377. Table References

Links
<a href="https://www.realvnc.com/">https://www.realvnc.com/</a>

## Adwind RAT

Backdoor:Java/Adwind is a Java archive (.JAR) file that drops a malicious component onto the machines and runs as a backdoor. When active, it is capable of stealing user information and may also be used to distribute other malware.

Adwind RAT is also known as:

- UNRECOM
- UNiversal REmote COntrol Multi-Platform
- Frutas
- AlienSpy
- Unrecom
- Jsocket
- JBifrost

Table 1378. Table References

Links
<a href="https://securelist.com/securelist/files/2016/02/KL_AdwindPublicReport_2016.pdf">https://securelist.com/securelist/files/2016/02/KL_AdwindPublicReport_2016.pdf</a>
<a href="https://www.f-secure.com/v-descs/backdoor_java_adwind.shtml">https://www.f-secure.com/v-descs/backdoor_java_adwind.shtml</a>
<a href="https://blog.fortinet.com/2016/08/16/jbifrost-yet-another-incarnation-of-the-adwind-rat">https://blog.fortinet.com/2016/08/16/jbifrost-yet-another-incarnation-of-the-adwind-rat</a>

# Albertino Advanced RAT

Table 1379. Table References

Links
<a href="https://www.virustotal.com/en/file/b31812e5b4c63c5b52c9b23e76a5ea9439465ab366a9291c6074bfae5c328e73/analysis/1359376345/">https://www.virustotal.com/en/file/b31812e5b4c63c5b52c9b23e76a5ea9439465ab366a9291c6074bfae5c328e73/analysis/1359376345/</a>

## Arcom

The malware is a Remote Access Trojan (RAT), known as Arcom RAT, and it is sold on underground forums for \$2000.00.

Table 1380. Table References

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2012-112912-5237-99">https://www.symantec.com/security_response/writeup.jsp?docid=2012-112912-5237-99</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/tsunami-warning-leads-to-arcom-rat/">http://blog.trendmicro.com/trendlabs-security-intelligence/tsunami-warning-leads-to-arcom-rat/</a>

## BlackNix

BlackNix rat is a rat coded in delphi.

Table 1381. Table References

Links
<a href="https://leakforums.net/thread-18123?tid=18123&amp;&amp;pg=1">https://leakforums.net/thread-18123?tid=18123&amp;&amp;pg=1</a>

## Blue Banana

Blue Banana is a RAT (Remote Administration Tool) created purely in Java

Table 1382. Table References

Links
<a href="https://leakforums.net/thread-123872">https://leakforums.net/thread-123872</a>
<a href="https://techanarchy.net/2014/02/blue-banana-rat-config/">https://techanarchy.net/2014/02/blue-banana-rat-config/</a>

## Bozok

Bozok, like many other popular RATs, is freely available. The author of the Bozok RAT goes by the moniker “Slayer616” and has created another RAT known as Schwarze Sonne, or “SS-RAT” for short. Both of these RATs are free and easy to find — various APT actors have used both in previous targeted attacks.

Table 1383. Table References

Links
-------

<https://www.fireeye.com/blog/threat-research/2013/10/know-your-enemy-tracking-a-rapidly-evolving-apt-actor.html>

## ClientMesh

ClientMesh is a Remote Administration Application which allows a user to control a number of client PCs from around the world.

*Table 1384. Table References*

Links
<a href="https://sinister.ly/Thread-ClientMesh-RAT-In-Built-FUD-Crypter-Stable-DDoSer-No-PortForwarding-40-Lifetime">https://sinister.ly/Thread-ClientMesh-RAT-In-Built-FUD-Crypter-Stable-DDoSer-No-PortForwarding-40-Lifetime</a>
<a href="https://blog.yakuza112.org/2012/clientmesh-rat-v5-cracked-clean/">https://blog.yakuza112.org/2012/clientmesh-rat-v5-cracked-clean/</a>

## CyberGate

CyberGate is a powerful, fully configurable and stable Remote Administration Tool coded in Delphi that is continuously getting developed. Using cybergate you can log the victim's passwords and can also get the screen shots of his computer's screen.

*Table 1385. Table References*

Links
<a href="http://www.hackersthirst.com/2011/03/cybergate-rat-hacking-facebook-twitter.html">http://www.hackersthirst.com/2011/03/cybergate-rat-hacking-facebook-twitter.html</a>
<a href="http://www.nbcnews.com/id/41584097/ns/technology_and_science-security/t/cybergate-leaked-emails-hint-corporate-hacking-conspiracy/">http://www.nbcnews.com/id/41584097/ns/technology_and_science-security/t/cybergate-leaked-emails-hint-corporate-hacking-conspiracy/</a>

## Dark DDoSeR

*Table 1386. Table References*

Links
<a href="http://meinblogzumtesten.blogspot.lu/2013/05/dark-ddoser-v56c-cracked.html">http://meinblogzumtesten.blogspot.lu/2013/05/dark-ddoser-v56c-cracked.html</a>

## DarkRat

In March 2017, Fujitsu Cyber Threat Intelligence uncovered a newly developed remote access tool referred to by its developer as 'Dark RAT' – a tool used to steal sensitive information from victims. Offered as a Fully Undetectable build (FUD) the RAT has a tiered price model including 24/7 support and an Android version. Android malware has seen a significant rise in interest and in 2015 this resulted in the arrests of a number of suspects involved in the infamous DroidJack malware.

DarkRat is also known as:

- DarkRAT

*Table 1387. Table References*

Links
<a href="https://www.infosecurity-magazine.com/blogs/the-dark-rat/">https://www.infosecurity-magazine.com/blogs/the-dark-rat/</a>
<a href="http://darkratphp.blogspot.lu/">http://darkratphp.blogspot.lu/</a>

## Greame

*Table 1388. Table References*

Links
<a href="https://sites.google.com/site/greymecompany/greame-rat-project">https://sites.google.com/site/greymecompany/greame-rat-project</a>

## HawkEye

HawkEye is a popular RAT that can be used as a keylogger, it is also able to identify login events and record the destination, username, and password.

*Table 1389. Table References*

Links
<a href="http://securityaffairs.co/wordpress/54837/hacking/one-stop-shop-hacking.html">http://securityaffairs.co/wordpress/54837/hacking/one-stop-shop-hacking.html</a>

## jRAT

jRAT is the cross-platform remote administrator tool that is coded in Java, Because its coded in Java it gives jRAT possibilities to run on all operation systems, Which includes Windows, Mac OSX and Linux distributions.

jRAT is also known as:

- JacksBot

*Table 1390. Table References*

Links
<a href="https://www.rekings.com/shop/jrat/">https://www.rekings.com/shop/jrat/</a>

## jSpy

jSpy is a Java RAT.

*Table 1391. Table References*

Links
<a href="https://leakforums.net/thread-479505">https://leakforums.net/thread-479505</a>

## LuxNET

Just saying that this is a very badly coded RAT by the biggest skid in this world, that is XilluX. The connection is very unstable, the GUI is always flickering because of the bad Multi-Threading and many more bugs.

*Table 1392. Table References*

Links
<a href="https://leakforums.net/thread-284656">https://leakforums.net/thread-284656</a>

## NJRat

NJRat is a remote access trojan (RAT), first spotted in June 2013 with samples dating back to November 2012. It was developed and is supported by Arabic speakers and mainly used by cybercrime groups against targets in the Middle East. In addition to targeting some governments in the region, the trojan is used to control botnets and conduct other typical cybercrime activity. It infects victims via phishing attacks and drive-by downloads and propagates through infected USB keys or networked drives. It can download and execute additional malware, execute shell commands, read and write registry keys, capture screenshots, log keystrokes, and spy on webcams.

NJRat is also known as:

- Njw0rm

*Table 1393. Table References*

Links
<a href="https://www.cyber.nj.gov/threat-profiles/trojan-variants/njrat">https://www.cyber.nj.gov/threat-profiles/trojan-variants/njrat</a>

## Pandora

Remote administrator tool that has been developed for Windows operation system. With advanced features and stable structure, Pandora's structure is based on advanced client / server architecture. was configured using modern technology.

*Table 1394. Table References*

Links
<a href="https://www.rekings.com/pandora-rat-2-2/">https://www.rekings.com/pandora-rat-2-2/</a>

## Predator Pain

Unlike Zeus, Predator Pain and Limitless are relatively simple keyloggers. They indiscriminately steal web credentials and mail client credentials, as well as capturing keystrokes and screen captures. The output is human readable, which is good if you are managing a few infected machines only, but the design doesn't scale well when there are a lot of infected machines and logs involved.

Predator Pain is also known as:

- PredatorPain

*Table 1395. Table References*

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/predator-pain-and-limitless-behind-the-fraud/">http://blog.trendmicro.com/trendlabs-security-intelligence/predator-pain-and-limitless-behind-the-fraud/</a>
<a href="https://www.trendmicro.de/cloud-content/us/pdfs/security-intelligence/white-papers/wp-predator-pain-and-limitless.pdf">https://www.trendmicro.de/cloud-content/us/pdfs/security-intelligence/white-papers/wp-predator-pain-and-limitless.pdf</a>

## Punisher RAT

Remote administration tool

*Table 1396. Table References*

Links
<a href="http://punisher-rat.blogspot.lu/">http://punisher-rat.blogspot.lu/</a>

## SpyGate

This is tool that allow you to control your computer form anywhere in world with full support to unicode language.

*Table 1397. Table References*

Links
<a href="https://www.rekings.com/spygate-rat-3-2/">https://www.rekings.com/spygate-rat-3-2/</a>
<a href="https://www.symantec.com/security_response/attacksignatures/detail.jsp%3Fasid%3D27950">https://www.symantec.com/security_response/attacksignatures/detail.jsp%3Fasid%3D27950</a>
<a href="http://spygate-rat.blogspot.lu/">http://spygate-rat.blogspot.lu/</a>

## Small-Net

RAT

Small-Net is also known as:

- SmallNet

*Table 1398. Table References*

Links
<a href="http://small-net-rat.blogspot.lu/">http://small-net-rat.blogspot.lu/</a>

## Vantom

Vantom is a free RAT with good option and very stable.

Table 1399. Table References

Links
<a href="https://www.rekings.com/vantom-rat/">https://www.rekings.com/vantom-rat/</a>

## Xena

Xena RAT is a fully-functional, stable, state-of-the-art RAT, coded in a native language called Delphi, it has almost no dependencies.

Table 1400. Table References

Links
<a href="https://leakforums.net/thread-497480">https://leakforums.net/thread-497480</a>

## XtremeRAT

This malware has been used in targeted attacks as well as traditional cybercrime. During our investigation we found that the majority of XtremeRAT activity is associated with spam campaigns that typically distribute Zeus variants and other banking-focused malware.

Table 1401. Table References

Links
<a href="https://www.fireeye.com/blog/threat-research/2014/02/xtremerat-nuisance-or-threat.html">https://www.fireeye.com/blog/threat-research/2014/02/xtremerat-nuisance-or-threat.html</a>

## Netwire

NetWire has a built-in keylogger that can capture inputs from peripheral devices such as USB card readers.

Table 1402. Table References

Links
<a href="https://www.secureworks.com/blog/netwire-rat-steals-payment-card-data">https://www.secureworks.com/blog/netwire-rat-steals-payment-card-data</a>

## Gh0st RAT

Gh0st RAT is a Trojan horse for the Windows platform that the operators of GhostNet used to hack into some of the most sensitive computer networks on Earth. It is a cyber spying computer program. .

Table 1403. Table References

Links
-------



## Plasma RAT

Plasma RAT's stub is fairly advanced, having many robust features. Some of the features include botkilling, Cryptocurrencies Mining (CPU and GPU), persistence, anti-analysis, torrent seeding, AV killer, 7 DDoS methods and a keylogger. The RAT is coded in VB.Net. There is also a Botnet version of it (Plasma HTTP), which is pretty similar to the RAT version.

*Table 1404. Table References*

Links

<http://www.zunzutech.com/blog/security/analysis-of-plasma-rats-source-code/>

## Babylon

Babylon is a highly advanced remote administration tool with no dependencies. The server is developed in C++ which is an ideal language for high performance and the client is developed in C#(.Net Framework 4.5)

*Table 1405. Table References*

Links

<https://www.rekings.com/babylon-rat/>

## Imminent Monitor

RAT

*Table 1406. Table References*

Links

<http://www.imminentmethods.info/>

## DroidJack

DroidJack is a RAT (Remote Access Trojan/Remote Administration Tool) nature of remote accessing, monitoring and managing tool (Java based) for Android mobile OS. You can use it to perform a complete remote control to any Android devices infected with DroidJack through your PC. It comes with powerful function and user-friendly operation – even allows attackers to fully take over the mobile phone and steal, record the victim's private data wilfully.

*Table 1407. Table References*

Links

<http://droidjack.net/>

# Quasar RAT

Quasar is a fast and light-weight remote administration tool coded in C#. Providing high stability and an easy-to-use user interface

Table 1408. Table References

Links
<a href="https://github.com/quasar/QuasarRAT">https://github.com/quasar/QuasarRAT</a>

# Dendroid

Dendroid is malware that affects Android OS and targets the mobile platform. It was first discovered in early of 2014 by Symantec and appeared in the underground for sale for \$300. Some things were noted in Dendroid, such as being able to hide from emulators at the time. When first discovered in 2014 it was one of the most sophisticated Android remote administration tools known at that time. It was one of the first Trojan applications to get past Google's Bouncer and caused researchers to warn about it being easier to create Android malware due to it. It also seems to have follow in the footsteps of Zeus and SpyEye by having simple-to-use command and control panels. The code appeared to be leaked somewhere around 2014. It was noted that an apk binder was included in the leak, which provided a simple way to bind Dendroid to legitimate applications.

Table 1409. Table References

Links
<a href="https://github.com/qqshow/dendroid">https://github.com/qqshow/dendroid</a>
<a href="https://github.com/nyx0/Dendroid">https://github.com/nyx0/Dendroid</a>

# Ratty

A Java R.A.T. program

Table 1410. Table References

Links
<a href="https://github.com/shotskeber/Ratty">https://github.com/shotskeber/Ratty</a>

# RaTRon

Java RAT

Table 1411. Table References

Links
<a href="http://level23hacktools.com/forum/showthread.php?t=27971">http://level23hacktools.com/forum/showthread.php?t=27971</a>
<a href="https://leakforums.net/thread-405562?tid=405562&amp;&amp;pq=1">https://leakforums.net/thread-405562?tid=405562&amp;&amp;pq=1</a>

# Arabian-Attacker RAT

Table 1412. Table References

Links
<a href="http://arabian-attacker.software.informer.com/">http://arabian-attacker.software.informer.com/</a>

# Androrat

Androrat is a client/server application developed in Java Android for the client side and in Java/Swing for the Server.

Table 1413. Table References

Links
<a href="https://latesthackingnews.com/2015/05/31/how-to-hack-android-phones-with-androrat/">https://latesthackingnews.com/2015/05/31/how-to-hack-android-phones-with-androrat/</a>
<a href="https://github.com/wszf/androrat">https://github.com/wszf/androrat</a>

# Adzok

Remote Administrator

Table 1414. Table References

Links
<a href="http://adzok.com/">http://adzok.com/</a>

# Schwarze-Sonne-RAT

Schwarze-Sonne-RAT is also known as:

- SS-RAT
- Schwarze Sonne

Table 1415. Table References

Links
<a href="https://github.com/mwsrc/Schwarze-Sonne-RAT">https://github.com/mwsrc/Schwarze-Sonne-RAT</a>

# Cyber Eye RAT

Table 1416. Table References

Links
<a href="https://www.indetectables.net/viewtopic.php?t=24245">https://www.indetectables.net/viewtopic.php?t=24245</a>

## Batch NET

## RWX RAT

Table 1417. Table References

Links
<a href="https://leakforums.net/thread-530663">https://leakforums.net/thread-530663</a>

## Spynet

Spy-Net is a software that allow you to control any computer in world using Windows Operating System.He is back using new functions and good options to give you full control of your remote computer.Stable and fast, this software offer to you a good interface, creating a easy way to use all his functions

Table 1418. Table References

Links
<a href="http://spynet-rat-officiel.blogspot.lu/">http://spynet-rat-officiel.blogspot.lu/</a>

## CTOS

Table 1419. Table References

Links
<a href="https://leakforums.net/thread-559871">https://leakforums.net/thread-559871</a>

## Virus RAT

Table 1420. Table References

Links
<a href="https://github.com/mwsrc/Virus-RAT-v8.0-Beta">https://github.com/mwsrc/Virus-RAT-v8.0-Beta</a>

## Atelier Web Remote Commander

Table 1421. Table References

Links
<a href="http://www.atelierweb.com/products/">http://www.atelierweb.com/products/</a>

## drat

A distributed, parallelized (Map Reduce) wrapper around Apache™ RAT to allow it to complete on large code repositories of multiple file types where Apache™ RAT hangs forev

Table 1422. Table References

Links
<a href="https://github.com/chrismattmann/drat">https://github.com/chrismattmann/drat</a>

## MoSucker

MoSucker is a powerful backdoor - hacker's remote access tool.

Table 1423. Table References

Links
<a href="https://www.f-secure.com/v-descs/mosuck.shtml">https://www.f-secure.com/v-descs/mosuck.shtml</a>

## Theef

Table 1424. Table References

Links
<a href="http://www.grayhatforum.org/thread-4373-post-5213.html#pid5213">http://www.grayhatforum.org/thread-4373-post-5213.html#pid5213</a>
<a href="http://www.spy-emergency.com/research/T/Theef_Download_Creator.html">http://www.spy-emergency.com/research/T/Theef_Download_Creator.html</a>
<a href="http://www.spy-emergency.com/research/T/Theef.html">http://www.spy-emergency.com/research/T/Theef.html</a>

## ProRat

ProRat is a Microsoft Windows based backdoor trojan, more commonly known as a Remote Administration Tool. As with other trojan horses it uses a client and server. ProRat opens a port on the computer which allows the client to perform numerous operations on the server (the machine being controlled).

Table 1425. Table References

Links
<a href="http://prorat.software.informer.com/">http://prorat.software.informer.com/</a>
<a href="http://malware.wikia.com/wiki/ProRat">http://malware.wikia.com/wiki/ProRat</a>

## Setro

Table 1426. Table References

Links
<a href="https://sites.google.com/site/greymecompany/setro-rat-project">https://sites.google.com/site/greymecompany/setro-rat-project</a>

## Indetectables RAT

Table 1427. Table References

Links
-------

<a href="http://www.connect-trojan.net/2015/03/indetectables-rat-v.0.5-beta.html">http://www.connect-trojan.net/2015/03/indetectables-rat-v.0.5-beta.html</a>
---

## Luminosity Link

*Table 1428. Table References*

Links
-------

<a href="https://luminosity.link/">https://luminosity.link/</a>
---

## Orcus

*Table 1429. Table References*

Links
-------

<a href="https://orcustechnologies.com/">https://orcustechnologies.com/</a>
---

## Blizzard

*Table 1430. Table References*

Links
-------

<a href="http://www.connect-trojan.net/2014/10/blizzard-rat-lite-v1.3.1.html">http://www.connect-trojan.net/2014/10/blizzard-rat-lite-v1.3.1.html</a>
---

## Kazybot

*Table 1431. Table References*

Links
-------

<a href="https://www.rekings.com/kazybot-lite-php-rat/">https://www.rekings.com/kazybot-lite-php-rat/</a>
---

<a href="http://telussecuritylabs.com/threats/show/TSL20150122-06">http://telussecuritylabs.com/threats/show/TSL20150122-06</a>
---

## BX

*Table 1432. Table References*

Links
-------

<a href="http://www.connect-trojan.net/2015/01/bx-rat-v1.0.html">http://www.connect-trojan.net/2015/01/bx-rat-v1.0.html</a>
---

## death

## Sky Wyder

*Table 1433. Table References*

Links
-------

<https://rubear.me/threads/sky-wyder-2016-cracked.127/>

## DarkTrack

*Table 1434. Table References*

Links

<https://www.rekings.com/darktrack-4-alien/>

<http://news.softpedia.com/news/free-darktrack-rat-has-the-potential-of-being-the-best-rat-on-the-market-508179.shtml>

## xRAT

Free, Open-Source Remote Administration Tool. xRAT 2.0 is a fast and light-weight Remote Administration Tool coded in C# (using .NET Framework 2.0).

*Table 1435. Table References*

Links

<https://github.com/c4bbage/xRAT>

## Biodox

*Table 1436. Table References*

Links

<http://sakhackingarticles.blogspot.lu/2014/08/biodox-rat.html>

## Offence

Offense RAT is a free remote administration tool made in Delphi 9.

*Table 1437. Table References*

Links

<https://leakforums.net/thread-31386?tid=31386&&pq=1>

## Apocalypse

*Table 1438. Table References*

Links

<https://leakforums.net/thread-36962>

## JCage

*Table 1439. Table References*

Links
-------

<a href="https://leakforums.net/thread-363920">https://leakforums.net/thread-363920</a>
---

## Nuclear RAT

Nuclear RAT (short for Nuclear Remote Administration Tool) is a backdoor trojan horse that infects Windows NT family systems (Windows 2000, XP, 2003).

*Table 1440. Table References*

Links
-------

<a href="http://malware.wikia.com/wiki/Nuclear_RAT">http://malware.wikia.com/wiki/Nuclear_RAT</a>
---

<a href="http://www.nuclearwintercrew.com/Products-View/21/Nuclear_RAT_2.1.0/">http://www.nuclearwintercrew.com/Products-View/21/Nuclear_RAT_2.1.0/</a>
---

## Ozone

C++ REMOTE CONTROL PROGRAM

*Table 1441. Table References*

Links
-------

<a href="http://ozonercp.com/">http://ozonercp.com/</a>
---

## Xanity

*Table 1442. Table References*

Links
-------

<a href="https://github.com/alienwithin/xanity-php-rat">https://github.com/alienwithin/xanity-php-rat</a>
---

## DarkMoon

DarkMoon is also known as:

- Dark Moon

## Xpert

*Table 1443. Table References*

Links
-------

<a href="http://broad-product.biz/forum/r-a-t-(remote-administration-tools)/xpert-rat-3-0-10-by-abronsius(vb6)">http://broad-product.biz/forum/r-a-t-(remote-administration-tools)/xpert-rat-3-0-10-by-abronsius(vb6)/</a>
--

<a href="https://www.nulled.to/topic/18355-xpert-rat-309/">https://www.nulled.to/topic/18355-xpert-rat-309/</a>
---

<a href="https://trickytamilan.blogspot.lu/2016/03/xpert-rat.html">https://trickytamilan.blogspot.lu/2016/03/xpert-rat.html</a>
---



# Kiler RAT

This remote access trojan (RAT) has capabilities ranging from manipulating the registry to opening a reverse shell. From stealing credentials stored in browsers to accessing the victims webcam. Through the Command & Control (CnC) server software, the attacker has capabilities to create and configure the malware to spread utilizing physic devices, such as USB drives, but also to use the victim as a pivot point to gain more access laterally throughout the network. This remote access trojan could be classified as a variant of the well known njrat, as they share many similar features such as their display style, several abilities and a general template for communication methods . However, where njrat left off KilerRat has taken over. KilerRat is a very feature rich RAT with an active development force that is rapidly gaining in popularity amongst the middle eastern community and the world.

Kiler RAT is also known as:

- Njw0rm

*Table 1444. Table References*

Links
<a href="https://www.alienvault.com/blogs/labs-research/kilerrat-taking-over-where-njrat-remote-access-trojan-left-off">https://www.alienvault.com/blogs/labs-research/kilerrat-taking-over-where-njrat-remote-access-trojan-left-off</a>

# Brat

# MINI-MO

# Lost Door

Unlike most attack tools that one can only find in cybercriminal underground markets, Lost Door is very easy to obtain. It's promoted on social media sites like YouTube and Facebook. Its maker, "OussamiO," even has his own Facebook page where details on his creation can be found. He also has a dedicated blog ([http://lost-door\[.\]blogspot\[.\]com/](http://lost-door[.]blogspot[.]com/)) where tutorial videos and instructions on using the RAT is found. Any cybercriminal or threat actor can purchase and use the RAT to launch attacks.

Lost Door is also known as:

- LostDoor

*Table 1445. Table References*

Links
<a href="http://lost-door.blogspot.lu/">http://lost-door.blogspot.lu/</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/lost-door-rat-accessible-customizable-attack-tool/">http://blog.trendmicro.com/trendlabs-security-intelligence/lost-door-rat-accessible-customizable-attack-tool/</a>
<a href="https://www.cyber.nj.gov/threat-profiles/trojan-variants/lost-door-rat">https://www.cyber.nj.gov/threat-profiles/trojan-variants/lost-door-rat</a>

## Loki RAT

Loki RAT is a php RAT that means no port forwarding is needed for this RAT, If you dont know how to setup this RAT click on tutorial.

Table 1446. Table References

Links
<a href="https://www.rekings.com/loki-rat-php-rat/">https://www.rekings.com/loki-rat-php-rat/</a>

## MLRat

Table 1447. Table References

Links
<a href="https://github.com/BahNahNah/MLRat">https://github.com/BahNahNah/MLRat</a>

## SpyCronic

Table 1448. Table References

Links
<a href="http://perfect-conexao.blogspot.lu/2014/09/spycronic-1021.html">http://perfect-conexao.blogspot.lu/2014/09/spycronic-1021.html</a>
<a href="http://www.connect-trojan.net/2013/09/spycronic-v1.02.1.html">http://www.connect-trojan.net/2013/09/spycronic-v1.02.1.html</a>
<a href="https://ranger-exploit.com/spycronic-v1-02-1/">https://ranger-exploit.com/spycronic-v1-02-1/</a>

## Pupy

Pupy is an opensource, cross-platform (Windows, Linux, OSX, Android) remote administration and post-exploitation tool mainly written in python

Table 1449. Table References

Links
<a href="https://github.com/n1nj4sec/pupy">https://github.com/n1nj4sec/pupy</a>

## Nova

Nova is a proof of concept demonstrating screen sharing over UDP hole punching.

Table 1450. Table References

Links
<a href="http://novarat.sourceforge.net/">http://novarat.sourceforge.net/</a>

# BD Y3K RAT

BD Y3K RAT is also known as:

- Back Door Y3K RAT
- Y3k

*Table 1451. Table References*

Links
<a href="https://tools.cisco.com/security/center/viewIpsSignature.x?signatureId=9401&amp;signatureSubId=2">https://tools.cisco.com/security/center/viewIpsSignature.x?signatureId=9401&amp;signatureSubId=2</a>
<a href="https://tools.cisco.com/security/center/viewIpsSignature.x?signatureId=9401&amp;signatureSubId=0&amp;softwareVersion=6.0&amp;releaseVersion=S177">https://tools.cisco.com/security/center/viewIpsSignature.x?signatureId=9401&amp;signatureSubId=0&amp;softwareVersion=6.0&amp;releaseVersion=S177</a>
<a href="https://www.symantec.com/security_response/attacksignatures/detail.jsp?asid=20292">https://www.symantec.com/security_response/attacksignatures/detail.jsp?asid=20292</a>
<a href="https://www.symantec.com/security_response/attacksignatures/detail.jsp?asid=20264">https://www.symantec.com/security_response/attacksignatures/detail.jsp?asid=20264</a>

# Turkojan

Turkojan is a remote administration and spying tool for Microsoft Windows operating systems.

*Table 1452. Table References*

Links
<a href="http://turkojan.blogspot.lu/">http://turkojan.blogspot.lu/</a>

# TINY

TINY is a set of programs that lets you control a DOS computer from any Java-capable machine over a TCP/IP connection. It is comparable to programs like VNC, CarbonCopy, and GotoMyPC except that the host machine is a DOS computer rather than a Windows one.

*Table 1453. Table References*

Links
<a href="http://josh.com/tiny/">http://josh.com/tiny/</a>

# SharK

sharK is an advanced reverse connecting, firewall bypassing remote administration tool written in VB6. With sharK you will be able to administrate every PC (using Windows OS) remotely.

SharK is also known as:

- SHARK
- Shark

*Table 1454. Table References*

Links
<a href="https://www.security-database.com/toolswatch/SharK-3-Remote-Administration-Tool.html">https://www.security-database.com/toolswatch/SharK-3-Remote-Administration-Tool.html</a>
<a href="http://lpc1.clpccd.cc.ca.us/lpc/mdaoud/CNT7501/NETLABS/Ethical_Hacking_Lab_05.pdf">http://lpc1.clpccd.cc.ca.us/lpc/mdaoud/CNT7501/NETLABS/Ethical_Hacking_Lab_05.pdf</a>

## Snowdoor

Backdoor.Snowdoor is a Backdoor Trojan Horse that allows unauthorized access to an infected computer. It creates an open C drive share with its default settings. By default, the Trojan listens on port 5,328.

Snowdoor is also known as:

- Backdoor.Blizzard
- Backdoor.Fxdor
- Backdoor.Snowdoor
- Backdoor:Win32/Snowdoor

*Table 1455. Table References*

Links
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2003-022018-5040-99">https://www.symantec.com/security_response/writeup.jsp?docid=2003-022018-5040-99</a>

## Paradox

*Table 1456. Table References*

Links
<a href="https://www.nulled.to/topic/155464-paradox-rat/">https://www.nulled.to/topic/155464-paradox-rat/</a>

## SpyNote

Android RAT

*Table 1457. Table References*

Links
<a href="https://www.rekings.com/spynote-v4-android-rat/">https://www.rekings.com/spynote-v4-android-rat/</a>

## ZOMBIE SLAYER

## HTTP WEB BACKDOOR

## NET-MONITOR PRO

Net Monitor for Employees lets you see what everyone's doing - without leaving your desk. Monitor

the activity of all employees. Plus you can share your screen with your employees PCs, making demos and presentations much easier.

*Table 1458. Table References*

Links
<a href="https://networklookout.com/help/">https://networklookout.com/help/</a>

## DameWare Mini Remote Control

Affordable remote control software for all your customer support and help desk needs.

DameWare Mini Remote Control is also known as:

- dameware

*Table 1459. Table References*

Links
<a href="http://www.dameware.com/dameware-mini-remote-control">http://www.dameware.com/dameware-mini-remote-control</a>

## Remote Utilities

Remote Utilities is a free remote access program with some really great features. It works by pairing two remote computers together with what they call an "Internet ID." You can control a total of 10 PCs with Remote Utilities.

*Table 1460. Table References*

Links
<a href="https://www.remoteutilities.com/">https://www.remoteutilities.com/</a>

## Ammyy Admin

Ammyy Admin is a completely portable remote access program that's extremely simple to setup. It works by connecting one computer to another via an ID supplied by the program.

Ammyy Admin is also known as:

- Ammyy

*Table 1461. Table References*

Links
<a href="http://ammyy-admin.soft32.com/">http://ammyy-admin.soft32.com/</a>

## Ultra VNC

UltraVNC works a bit like Remote Utilities, where a server and viewer is installed on two PCs, and

the viewer is used to control the server.

*Table 1462. Table References*

Links
<a href="http://www.uvnc.com/">http://www.uvnc.com/</a>

## AeroAdmin

AeroAdmin is probably the easiest program to use for free remote access. There are hardly any settings, and everything is quick and to the point, which is perfect for spontaneous support.

*Table 1463. Table References*

Links
<a href="http://www.aeroadmin.com/en/">http://www.aeroadmin.com/en/</a>

## Windows Remote Desktop

Windows Remote Desktop is the remote access software built into the Windows operating system. No additional download is necessary to use the program.

## RemotePC

RemotePC, for good or bad, is a more simple free remote desktop program. You're only allowed one connection (unless you upgrade) but for many of you, that'll be just fine.

*Table 1464. Table References*

Links
<a href="https://www.remotepc.com/">https://www.remotepc.com/</a>

## Seecreen

Seecreen (previously called Firnass) is an extremely tiny (500 KB), yet powerful free remote access program that's absolutely perfect for on-demand, instant support.

Seecreen is also known as:

- Firnass

*Table 1465. Table References*

Links
<a href="http://seecreen.com/">http://seecreen.com/</a>

# Chrome Remote Desktop

Chrome Remote Desktop is an extension for the Google Chrome web browser that lets you setup a computer for remote access from any other Chrome browser.

*Table 1466. Table References*

Links
<a href="https://chrome.google.com/webstore/detail/chrome-remote-desktop/gbchcmhahfdphkhkmpfmihenigmpp?hl=en">https://chrome.google.com/webstore/detail/chrome-remote-desktop/gbchcmhahfdphkhkmpfmihenigmpp?hl=en</a>

# AnyDesk

AnyDesk is a remote desktop program that you can run portably or install like a regular program.

*Table 1467. Table References*

Links
<a href="https://anydesk.com/remote-desktop">https://anydesk.com/remote-desktop</a>

# LiteManager

LiteManager is another remote access program, and it's strikingly similar to Remote Utilities, which I explain on the first page of this list. However, unlike Remote Utilities, which can control a total of only 10 PCs, LiteManager supports up to 30 slots for storing and connecting to remote computers, and also has lots of useful features.

*Table 1468. Table References*

Links
<a href="http://www.litemanager.com/">http://www.litemanager.com/</a>

# Comodo Unite

Comodo Unite is another free remote access program that creates a secure VPN between multiple computers. Once a VPN is established, you can remotely have access to applications and files through the client software.

*Table 1469. Table References*

Links
<a href="https://www.comodo.com/home/download/download.php?prod=comodounite">https://www.comodo.com/home/download/download.php?prod=comodounite</a>

# ShowMyPC

ShowMyPC is a portable and free remote access program that's nearly identical to UltraVNC but uses a password to make a connection instead of an IP address.

Table 1470. Table References

Links
<a href="https://showmypc.com/">https://showmypc.com/</a>

## join.me

join.me is a remote access program from the producers of LogMeIn that provides quick access to another computer over an internet browser.

Table 1471. Table References

Links
<a href="https://www.join.me/">https://www.join.me/</a>

## DesktopNow

DesktopNow is a free remote access program from NCH Software. After optionally forwarding the proper port number in your router, and signing up for a free account, you can access your PC from anywhere through a web browser.

Table 1472. Table References

Links
<a href="http://www.nchsoftware.com/remotedesktop/index.html">http://www.nchsoftware.com/remotedesktop/index.html</a>

## BeamYourScreen

Another free and portable remote access program is BeamYourScreen. This program works like some of the others in this list, where the presenter is given an ID number they must share with another user so they can connect to the presenter's screen.

Table 1473. Table References

Links
<a href="http://www.beamyourscreen.com/">http://www.beamyourscreen.com/</a>

## Casa RAT

## Bandook RAT

Bandook is a FWB#++ reverse connection rat (Remote Administration Tool), with a small size server when packed 30 KB, and a long list of amazing features

Table 1474. Table References

Links
-------



[http://www.nuclearwintercrew.com/Products-View/57/Bandook\\_RAT\\_v1.35](http://www.nuclearwintercrew.com/Products-View/57/Bandook_RAT_v1.35)  
NEW\_/[[http://www.nuclearwintercrew.com/Products-View/57/Bandook\\_RAT\\_v1.35](http://www.nuclearwintercrew.com/Products-View/57/Bandook_RAT_v1.35)NEW\_] ]

## Cerberus RAT

Table 1475. Table References

Links

<http://www.hacktohell.org/2011/05/setting-up-cerberus-ratremote.html>

## Syndrome RAT

### Snoopy

Snoopy is a Remote Administration Tool. Software for controlling user computer remotely from other computer on local network or Internet.

Table 1476. Table References

Links

<http://www.spy-emergency.com/research/S/Snoopy.html>

## 5p00f3r.N\$ RAT

### P. Storrie RAT

A. Storrie RAT is also known as:

- P.Storrie RAT

## xHacker Pro RAT

### NetDevil

Backdoor.NetDevil allows a hacker to remotely control an infected computer.

Table 1477. Table References

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2002-021310-3452-99](https://www.symantec.com/security_response/writeup.jsp?docid=2002-021310-3452-99)

## NanoCore

In September of 2015, a DigiTrust client visited a web link that was providing an Adobe Flash Player update. The client, an international retail organization, attempted to download and run what appeared to be a regular update. The computer trying to download this update was a back office

system that processed end of day credit card transactions. This system also had the capability of connecting to the corporate network which contained company sales reports. DigiTrust experts were alerted to something malicious and blocked the download. The investigation found that what appeared to be an Adobe Flash Player update, was a Remote Access Trojan called NanoCore. If installation had been successful, customer credit card data, personal information, and internal sales information could have been captured and monetized. During the analysis of NanoCore, our experts found that there was much more to this RAT than simply being another Remote Access Trojan.

*Table 1478. Table References*

Links
<a href="https://www.digitrustgroup.com/nanocore-not-your-average-rat/">https://www.digitrustgroup.com/nanocore-not-your-average-rat/</a>

## Cobian RAT

The Zscaler ThreatLabZ research team has been monitoring a new remote access Trojan (RAT) family called Cobian RAT since February 2017. The RAT builder for this family was first advertised on multiple underground forums where cybercriminals often buy and sell exploit and malware kits. This RAT builder caught our attention as it was being offered for free and had lot of similarities to the njRAT/H-Worm family

*Table 1479. Table References*

Links
<a href="https://www.zscaler.com/blogs/research/cobian-rat-backdoored-rat">https://www.zscaler.com/blogs/research/cobian-rat-backdoored-rat</a>

## Netsupport Manager

NetSupport Manager continues to deliver the very latest in remote access, PC support and desktop management capabilities. From a desktop, laptop, tablet or smartphone, monitor multiple systems in a single action, deliver hands-on remote support, collaborate and even record or play back sessions. When needed, gather real-time hardware and software inventory, monitor services and even view system config remotely to help resolve issues quickly.

*Table 1480. Table References*

Links
<a href="http://www.netsupportmanager.com/index.asp">http://www.netsupportmanager.com/index.asp</a>

## Vortex

## Assassin

## Net Devil

Net Devil is also known as:

- NetDevil

Table 1481. Table References

Links
<a href="https://www.symantec.com/security_response/attacksignatures/detail.jsp?asid=20702">https://www.symantec.com/security_response/attacksignatures/detail.jsp?asid=20702</a>

## A4Zeta

Table 1482. Table References

Links
<a href="http://www.megasecurity.org/trojans/a/a4zeta/A4zeta_b2.html">http://www.megasecurity.org/trojans/a/a4zeta/A4zeta_b2.html</a>

## Greek Hackers RAT

Table 1483. Table References

Links
<a href="http://www.connect-trojan.net/2013/04/greek-hackers-rat-1.0.html?m=0">http://www.connect-trojan.net/2013/04/greek-hackers-rat-1.0.html?m=0</a>

## MRA RAT

Table 1484. Table References

Links
<a href="http://www.connect-trojan.net/2013/04/greek-hackers-rat-1.0.html?m=0">http://www.connect-trojan.net/2013/04/greek-hackers-rat-1.0.html?m=0</a>

## Sparta RAT

Table 1485. Table References

Links
<a href="http://www.connect-trojan.net/2015/09/sparta-rat-1.2-by-azooz-ejram.html">http://www.connect-trojan.net/2015/09/sparta-rat-1.2-by-azooz-ejram.html</a>

## LokiTech

## MadRAT

## Tequila Bandita

Table 1486. Table References

Links
<a href="http://www.connect-trojan.net/2013/07/tequila-bandita-1.3b2.html">http://www.connect-trojan.net/2013/07/tequila-bandita-1.3b2.html</a>

# Toquito Bandito

*Table 1487. Table References*

Links
<a href="http://www.megasecurity.org/trojans/t/toquitobandito/Toquitobandito_all.html">http://www.megasecurity.org/trojans/t/toquitobandito/Toquitobandito_all.html</a>

# Mofotro

Mofotro is a new rat coded by Cool\_mofu\_2.

*Table 1488. Table References*

Links
<a href="http://www.megasecurity.org/trojans/m/mofotro/Mofotro_beta.html">http://www.megasecurity.org/trojans/m/mofotro/Mofotro_beta.html</a>
<a href="http://www.megasecurity.org/trojans/m/mofotro/Mofotroresurrection.html">http://www.megasecurity.org/trojans/m/mofotro/Mofotroresurrection.html</a>
<a href="http://www.megasecurity.org/trojans/m/mofotro/Mofotro_beta1.5.html">http://www.megasecurity.org/trojans/m/mofotro/Mofotro_beta1.5.html</a>

# Hav-RAT

Written in Delphi

*Table 1489. Table References*

Links
<a href="http://www.megasecurity.org/trojans/h/hav/Havrat1.2.html">http://www.megasecurity.org/trojans/h/hav/Havrat1.2.html</a>

# ComRAT

ComRAT is a remote access tool suspected of being a decedent of Agent.btz and used by Turla.

*Table 1490. Table References*

Links
<a href="https://attack.mitre.org/wiki/Software/S0126">https://attack.mitre.org/wiki/Software/S0126</a>

# 4H RAT

4H RAT is malware that has been used by Putter Panda since at least 2007.

*Table 1491. Table References*

Links
<a href="https://attack.mitre.org/wiki/Software/S0065">https://attack.mitre.org/wiki/Software/S0065</a>

# Darknet RAT

Darknet RAT is also known as:

- Dark NET RAT

*Table 1492. Table References*

Links
<a href="http://www.connect-trojan.net/2015/06/dark-net-rat-v.0.3.9.0.html">http://www.connect-trojan.net/2015/06/dark-net-rat-v.0.3.9.0.html</a>

# CIA RAT

# Minimo

# miniRAT

# Pain RAT

# PlugX

PLUGX is a remote access tool (RAT) used in targeted attacks aimed toward government-related institutions and key industries. It was utilized the same way as Poison Ivy, a RAT involved in a campaign dating back to 2008.

PlugX is also known as:

- Korplug

*Table 1493. Table References*

Links
<a href="https://www.lastline.com/labsblog/an-analysis-of-plugx-malware/">https://www.lastline.com/labsblog/an-analysis-of-plugx-malware/</a>
<a href="https://www.trendmicro.com/vinfo/us/threat-encyclopedia/malware/PLUGX">https://www.trendmicro.com/vinfo/us/threat-encyclopedia/malware/PLUGX</a>

# UNITEDRAKE

The existence of the UNITEDRAKE RAT first came to light in 2014 as part of a series of classified documents leaked by former NSA contractor Edward Snowden.

*Table 1494. Table References*

Links
<a href="http://thehackernews.com/2017/09/shadowbrokers-unitedrake-hacking.html">http://thehackernews.com/2017/09/shadowbrokers-unitedrake-hacking.html</a>
<a href="https://www.itnews.com.au/news/shadowbrokers-release-unitedrake-nsa-malware-472771">https://www.itnews.com.au/news/shadowbrokers-release-unitedrake-nsa-malware-472771</a>

# MegaTrojan

Written in Visual Basic

*Table 1495. Table References*

Links
<a href="http://www.megasecurity.org/trojans/m/mega/Megatrojan1.0.html">http://www.megasecurity.org/trojans/m/mega/Megatrojan1.0.html</a>

# Venomous Ivy

## Xploit

## Arctic R.A.T.

Arctic R.A.T. is also known as:

- Artic

*Table 1496. Table References*

Links
<a href="http://anti-virus-soft.com/threats/artic">http://anti-virus-soft.com/threats/artic</a>

# Golden Phoenix

*Table 1497. Table References*

Links
<a href="http://www.connect-trojan.net/2014/02/golden-phoenix-rat-0.2.html">http://www.connect-trojan.net/2014/02/golden-phoenix-rat-0.2.html</a>

# GraphicBooting

*Table 1498. Table References*

Links
<a href="http://www.connect-trojan.net/2014/10/graphicbooting-rat-v0.1-beta.html?m=0">http://www.connect-trojan.net/2014/10/graphicbooting-rat-v0.1-beta.html?m=0</a>

# Pocket RAT

## Erebus

## SharpEye

*Table 1499. Table References*

Links
-------

<a href="http://www.connect-trojan.net/2014/10/sharpeye-rat-1.0-beta-1.html">http://www.connect-trojan.net/2014/10/sharpeye-rat-1.0-beta-1.html</a>
---

<a href="http://www.connect-trojan.net/2014/02/sharpeye-rat-1.0-beta-2.html">http://www.connect-trojan.net/2014/02/sharpeye-rat-1.0-beta-2.html</a>
---

## Vortex

## Archelaus Beta

*Table 1500. Table References*

Links
-------

<a href="http://www.connect-trojan.net/2014/02/archelaus-rat-beta.html">http://www.connect-trojan.net/2014/02/archelaus-rat-beta.html</a>
---

## BlackHole

C# RAT (Remote Administration Tool) - Educational purposes only

*Table 1501. Table References*

Links
-------

<a href="https://github.com/hussein-aitlahcen/BlackHole">https://github.com/hussein-aitlahcen/BlackHole</a>
---

## Vanguard

*Table 1502. Table References*

Links
-------

<a href="http://ktwox7.blogspot.lu/2010/12/vanguard-remote-administration.html">http://ktwox7.blogspot.lu/2010/12/vanguard-remote-administration.html</a>
---

## Ahtapod

*Table 1503. Table References*

Links
-------

<a href="http://www.ibtimes.co.uk/turkish-journalist-baris-pehlivan-jailed-terrorism-was-framed-by-hackers-says-report-1577481">http://www.ibtimes.co.uk/turkish-journalist-baris-pehlivan-jailed-terrorism-was-framed-by-hackers-says-report-1577481</a>
---

## FINSPY

Though we have not identified the targets, FINSPY is sold by Gamma Group to multiple nation-state clients, and we assess with moderate confidence that it was being used along with the zero-day to carry out cyber espionage.

*Table 1504. Table References*

Links
-------

## Seed RAT

Seed is a firewall bypass plus trojan, injects into default browser and has a simple purpose: to be compact (4kb server size) and useful while uploading bigger and full trojans, or even making Seed download them somewhere. Has computer info, process manager, file manager, with download, create folder, delete, execute and upload. And a remote download function. Everything with a easy to use interface, reminds an instant messenger.

*Table 1505. Table References*

Links

[http://www.nuclearwintercrew.com/Products-View/25/Seed\\_1.1/](http://www.nuclearwintercrew.com/Products-View/25/Seed_1.1/)

## SharpBot

## TorCT PHP RAT

*Table 1506. Table References*

Links

<https://github.com/alienwithin/torCT-PHP-RAT>

## A32s RAT

## Char0n

## Nytro

## Syla

*Table 1507. Table References*

Links

<http://www.connect-trojan.net/2013/07/syla-rat-0.3.html>

## Cobalt Strike

Cobalt Strike is software for Adversary Simulations and Red Team Operations.

*Table 1508. Table References*

Links

<https://www.cobaltstrike.com/>



# Sakula

The RAT, which according to compile timestamps first surfaced in November 2012, has been used in targeted intrusions through 2015. Sakula enables an adversary to run interactive commands as well as to download and execute additional components.

Sakula is also known as:

- Sakurel
- VIPER

*Table 1509. Table References*

Links
<a href="https://www.secureworks.com/research/sakula-malware-family">https://www.secureworks.com/research/sakula-malware-family</a>

# hcdLoader

hcdLoader is a remote access tool (RAT) that has been used by APT18.

*Table 1510. Table References*

Links
<a href="https://attack.mitre.org/wiki/Software/S0071">https://attack.mitre.org/wiki/Software/S0071</a>

# Crimson

*Table 1511. Table References*

Links
<a href="http://www.connect-trojan.net/2015/01/crimson-rat-3.0.0.html">http://www.connect-trojan.net/2015/01/crimson-rat-3.0.0.html</a>

# KjW0rm

*Table 1512. Table References*

Links
<a href="http://hack-defender.blogspot.fr/2015/12/kjw0rm-v05x.html">http://hack-defender.blogspot.fr/2015/12/kjw0rm-v05x.html</a>

# Ghost

Ghost is also known as:

- Ucul

*Table 1513. Table References*

Links
-------

<https://www.youtube.com/watch?v=xXZW4ajVYkI>

## 9002

## Sandro RAT

## Mega

## WiRAT

## 3PARA RAT

*Table 1514. Table References*

Links

<https://books.google.fr/books?isbn=2212290136>

## BBS RAT

## Konni

KONNI is a remote access Trojan (RAT) that was first reported in May of 2017, but is believed to have been in use for over 3 years. As Part of our daily threat monitoring, FortiGuard Labs came across a new variant of the KONNI RAT and decided to take a deeper look.

Konni is also known as:

- KONNI

*Table 1515. Table References*

Links

<https://blog.fortinet.com/2017/08/15/a-quick-look-at-a-new-konni-rat-variant>

[https://www.cylance.com/en\\_us/blog/threat-spotlight-konni-stealthy-remote-access-trojan.html](https://www.cylance.com/en_us/blog/threat-spotlight-konni-stealthy-remote-access-trojan.html)

<https://vallejo.cc/2017/07/08/analysis-of-new-variant-of-konni-rat/>

<http://blog.talosintelligence.com/2017/07/konni-references-north-korean-missile-capabilities.html>

## Felismus RAT

## Xsser

Xsser mRAT is a piece of malware that targets iOS devices that have software limitations removed. The app is installed via a rogue repository on Cydia, the most popular third-party application store

for jailbroken iPhones. Once the malicious bundle has been installed and executed, it gains persistence - preventing the user from deleting it. The mRAT then makes server-side checks and proceeds to steal data from the user's device and executes remote commands as directed by its command-and-control (C2) server.

Xsser is also known as:

- mRAT

*Table 1516. Table References*

Links
<a href="https://blogs.akamai.com/2014/12/ios-and-android-os-targeted-by-man-in-the-middle-attacks.html">https://blogs.akamai.com/2014/12/ios-and-android-os-targeted-by-man-in-the-middle-attacks.html</a>
<a href="http://malware.wikia.com/wiki/Xsser_mRAT">http://malware.wikia.com/wiki/Xsser_mRAT</a>

## GovRAT

GovRAT is an old cyberespionage tool, it has been in the wild since 2014 and it was used by various threat actors across the years.

*Table 1517. Table References*

Links
<a href="http://securityaffairs.co/wordpress/41714/cyber-crime/govrat-platform.html">http://securityaffairs.co/wordpress/41714/cyber-crime/govrat-platform.html</a>
<a href="http://securityaffairs.co/wordpress/51202/cyber-crime/govrat-2-0-attacks.html">http://securityaffairs.co/wordpress/51202/cyber-crime/govrat-2-0-attacks.html</a>

## Rottie3

*Table 1518. Table References*

Links
<a href="https://www.youtube.com/watch?v=jUg5—68Iqs">https://www.youtube.com/watch?v=jUg5—68Iqs</a>

## Killer RAT

## Hi-Zor

*Table 1519. Table References*

Links
<a href="https://www.fidelissecurity.com/threatgeek/2016/01/introducing-hi-zor-rat">https://www.fidelissecurity.com/threatgeek/2016/01/introducing-hi-zor-rat</a>

## Quaverse

Quaverse RAT or QRAT is a fairly new Remote Access Tool (RAT) introduced in May 2015. This RAT is marketed as an undetectable Java RAT. As you might expect from a RAT, the tool is capable of grabbing passwords, key logging and browsing files on the victim's computer. On a regular basis for

the past several months, we have observed the inclusion of QRAT in a number of spam campaigns.

Quaverse is also known as:

- QRAT

*Table 1520. Table References*

Links
<a href="https://www.trustwave.com/Resources/SpiderLabs-Blog/Quaverse-RAT—Remote-Access-as-a-Service/">https://www.trustwave.com/Resources/SpiderLabs-Blog/Quaverse-RAT—Remote-Access-as-a-Service/</a>

## Heseber

## Cardinal

Cardinal is a remote access trojan (RAT) discovered by Palo Alto Networks in 2017 and has been active for over two years. It is delivered via a downloader, known as Carp, and uses malicious macros in Microsoft Excel documents to compile embedded C# programming language source code into an executable that runs and deploys the Cardinal RAT. The malicious Excel files use different tactics to get the victims to execute it.

*Table 1521. Table References*

Links
<a href="https://researchcenter.paloaltonetworks.com/2017/04/unit42-cardinal-rat-active-two-years/">https://researchcenter.paloaltonetworks.com/2017/04/unit42-cardinal-rat-active-two-years/</a>
<a href="https://www.scmagazine.com/cardinal-rats-unique-downloader-allowed-it-to-avoid-detection-for-years/article/651927/">https://www.scmagazine.com/cardinal-rats-unique-downloader-allowed-it-to-avoid-detection-for-years/article/651927/</a>
<a href="https://www.cyber.nj.gov/threat-profiles/trojan-variants/cardinal">https://www.cyber.nj.gov/threat-profiles/trojan-variants/cardinal</a>

## OmniRAT

Works on all Android, Windows, Linux and Mac devices!

*Table 1522. Table References*

Links
<a href="https://omnirat.eu/en/">https://omnirat.eu/en/</a>

## Jfect

*Table 1523. Table References*

Links
<a href="https://www.youtube.com/watch?v=qKdoExQFb68">https://www.youtube.com/watch?v=qKdoExQFb68</a>

## Trochilus

Trochilus is a remote access trojan (RAT) first identified in October 2015 when attackers used it to infect visitors of a Myanmar website. It was then used in a 2016 cyber-espionage campaign, dubbed "the Seven Pointed Dagger," managed by another group, "Group 27," who also uses the PlugX trojan. Trochilus is primarily spread via emails with a malicious .RAR attachment containing the malware. The trojan's functionality includes a shellcode extension, remote uninstall, a file manager, and the ability to download and execute, upload and execute, and access the system information. Once present on a system, Trochilus can move laterally in the network for better access. This trojan operates in memory only and does not write to the disk, helping it evade detection.

Table 1524. Table References

Links
<a href="https://researchcenter.paloaltonetworks.com/2017/03/unit42-trochilus-rat-new-moonwind-rat-used-attack-thai-utility-organizations/">https://researchcenter.paloaltonetworks.com/2017/03/unit42-trochilus-rat-new-moonwind-rat-used-attack-thai-utility-organizations/</a>
<a href="http://securityaffairs.co/wordpress/43889/cyber-crime/new-rat-trochilus.html">http://securityaffairs.co/wordpress/43889/cyber-crime/new-rat-trochilus.html</a>

## Matryoshka

Their most commonly used initial attack vector is a simple, yet alarmingly effective, spearphishing attack, infecting unsuspecting victims via a malicious email attachment (usually an executable that has been disguised as something else). From there, Matryoshka runs second stage malware via a dropper and covertly installs a Remote Access Toolkit (RAT). This is done using a reflective loader technique that allows the malware to run in process memory, rather than being written to disk. This not only hides the install of the RAT but also ensures that the RAT will be 'reinstalled' after system restart.

Table 1525. Table References

Links
<a href="https://www.alienvault.com/blogs/security-essentials/matryoshka-malware-from-copykittens-group">https://www.alienvault.com/blogs/security-essentials/matryoshka-malware-from-copykittens-group</a>

## Mangit

First discovered by Trend Micro in June, Mangit is a new malware family being marketed on both the Dark web and open internet. Users have the option to rent the trojan's infrastructure for about \$600 per 10-day period or buy the source code for about \$8,800. Mangit was allegedly developed by "Ric", a Brazilian hacker, who makes himself available via Skype to discuss rental agreements. Once the malware is rented or purchased, the user controls a portion of the Mangit botnet, the trojan, the dropper, an auto-update system, and the server infrastructure to run their attacks. Mangit contains support for nine Brazillian banks including Citibank, HSBC, and Santander. The malware can also be used to steal user PayPal credentials. Mangit has the capability to collect banking credentials, receive SMS texts when a victim is accessing their bank account, and take over victim's browsers. To circumvent two-factor authentication, attackers can use Mangit to lock victim's browsers and push pop-ups to the victim asking for the verification code they just received.

Table 1526. Table References

Links
<a href="http://virusguides.com/newly-discovered-mangit-malware-offers-banking-trojan-service/">http://virusguides.com/newly-discovered-mangit-malware-offers-banking-trojan-service/</a>
<a href="https://www.cyber.nj.gov/threat-profiles/trojan-variants/mangit">https://www.cyber.nj.gov/threat-profiles/trojan-variants/mangit</a>
<a href="http://news.softpedia.com/news/new-malware-mangit-surfaces-as-banking-trojan-as-a-service-505458.shtml">http://news.softpedia.com/news/new-malware-mangit-surfaces-as-banking-trojan-as-a-service-505458.shtml</a>

## LeGeNd

Table 1527. Table References

Links
<a href="http://www.connect-trojan.net/2016/08/legend-rat-v1.3-by-ahmed-ibrahim.html">http://www.connect-trojan.net/2016/08/legend-rat-v1.3-by-ahmed-ibrahim.html</a>
<a href="http://www.connect-trojan.net/2016/11/legend-rat-v1.9-by-ahmed-ibrahim.html">http://www.connect-trojan.net/2016/11/legend-rat-v1.9-by-ahmed-ibrahim.html</a>

## Revenge-RAT

Revenge v0.1 was a simple tool, according to a researcher known as Rui, who says the malware's author didn't bother obfuscating the RAT's source code. This raised a question mark with the researchers, who couldn't explain why VirusTotal scanners couldn't pick it up as a threat right away. Revenge, which was written in Visual Basic, also didn't feature too many working features, compared to similar RATs. Even Napoleon admitted that his tool was still in the early development stages, a reason why he provided the RAT for free.

Table 1528. Table References

Links
<a href="http://www.securitynewspaper.com/2016/08/31/unsophisticated-revenge-rat-released-online-free-exclusive/">http://www.securitynewspaper.com/2016/08/31/unsophisticated-revenge-rat-released-online-free-exclusive/</a>

## vjw0rm 0.1

Table 1529. Table References

Links
<a href="https://twitter.com/malwrhunterteam/status/816993165119016960?lang=en">https://twitter.com/malwrhunterteam/status/816993165119016960?lang=en</a>

## rokrat

ROKRAT is a remote access trojan (RAT) that leverages a malicious Hangual Word Processor (HWP) document sent in spearphishing emails to infect hosts. The HWP document contains an embedded Encapsulated PostScript (EPS) object. The object exploits an EPS buffer overflow vulnerability and downloads a binary disguised as a .JPG file. The file is then decoded and the ROKRAT executable is initiated. The trojan uses legitimate Twitter, Yandex, and Mediafire websites for its command and control communications and exfiltration platforms, making them difficult to block globally. Additionally, the platforms use HTTPS connections, making it more difficult to gather additional

data on its activities. Cisco's Talos Group identified two email campaigns. In one, attackers send potential victims emails from an email server of a private university in Seoul, South Korea with a sender email address of "kgf2016@yonsei.ac.kr," the contact email for the Korea Global Forum, adding a sense of legitimacy to the email. It is likely that the email address was compromised and used by the attackers in this campaign. The second is less sophisticated and sends emails claiming to be from a free Korean mail service with a the subject line, "Request Help" and attached malicious HWP filename, "I'm a munchon person in Gangwon-do, North Korea." The ROKRAT developer uses several techniques to hinder analysis, including identifying tools usually used by malware analysts or within sandbox environments. Once it has infected a device, this trojan can execute commands, move a file, remove a file, kill a process, download and execute a file, upload documents, capture screenshots, and log keystrokes. Researchers believe the developer is a native Korean speaker and the campaign is currently targeting Korean-speakers.

Table 1530. Table References

Links
<a href="http://blog.talosintelligence.com/2017/04/introducing-rokrat.html">http://blog.talosintelligence.com/2017/04/introducing-rokrat.html</a>

## Qarallax

Travelers applying for a US Visa in Switzerland were recently targeted by cyber-criminals linked to a malware called QRAT. Twitter user @hkashfi posted a Tweet saying that one of his friends received a file (US Travel Docs Information.jar) from someone posing as USTRAVELDOCS.COM support personnel using the Skype account ustravelidocs-switzerland (notice the "i" between "travel" and "docs").

Qarallax is also known as:

- qrat

Table 1531. Table References

Links
<a href="https://labsblog.f-secure.com/2016/06/07/qarallax-rat-spying-on-us-visa-applicants/">https://labsblog.f-secure.com/2016/06/07/qarallax-rat-spying-on-us-visa-applicants/</a>

## MoonWind

MoonWind is a remote access tool (RAT) that was used in 2016 to target organizations in Thailand.

Table 1532. Table References

Links
<a href="https://researchcenter.paloaltonetworks.com/2017/03/unit42-trochilus-rat-new-moonwind-rat-used-attack-thai-utility-organizations/">https://researchcenter.paloaltonetworks.com/2017/03/unit42-trochilus-rat-new-moonwind-rat-used-attack-thai-utility-organizations/</a>
<a href="https://attack.mitre.org/wiki/Software/S0149">https://attack.mitre.org/wiki/Software/S0149</a>

## Remcos

Remcos is another RAT (Remote Administration Tool) that was first discovered being sold in hacking forums in the second half of 2016. Since then, it has been updated with more features, and just recently, we've seen its payload being distributed in the wild for the first time.

*Table 1533. Table References*

Links
<a href="https://blog.fortinet.com/2017/02/14/remcos-a-new-rat-in-the-wild-2">https://blog.fortinet.com/2017/02/14/remcos-a-new-rat-in-the-wild-2</a>

## Client Maximus

The purpose of the Client Maximus malware is financial fraud. As such, its code aspires to create the capabilities that most banking Trojans have, which allow attackers to monitor victims' web navigation and interrupt online banking session at will. After taking over a victim's banking session, an attacker operating this malware can initiate a fraudulent transaction from the account and use social engineering screens to manipulate the unwitting victim into authorizing it.

*Table 1534. Table References*

Links
<a href="https://securityintelligence.com/client-maximus-new-remote-overlay-malware-highlights-rising-malcode-sophistication-in-brazil/">https://securityintelligence.com/client-maximus-new-remote-overlay-malware-highlights-rising-malcode-sophistication-in-brazil/</a>

## TheFat RAT

Thefatrat a massive exploiting tool revealed >> An easy tool to generate backdoor and easy tool to post exploitation attack like browser attack,dll . This tool compiles a malware with popular payload and then the compiled malware can be execute on windows, android, mac . The malware that created with this tool also have an ability to bypass most...

*Table 1535. Table References*

Links
<a href="https://github.com/Screetsec/TheFatRat">https://github.com/Screetsec/TheFatRat</a>

## RedLeaves

Since around October 2016, JPCERT/CC has been confirming information leakage and other damages caused by malware 'RedLeaves'. It is a new type of malware which has been observed since 2016 in attachments to targeted emails.

*Table 1536. Table References*

Links
<a href="http://blog.jpccert.or.jp/2017/04/redleaves---malware-based-on-open-source-rat.html">http://blog.jpccert.or.jp/2017/04/redleaves---malware-based-on-open-source-rat.html</a>



## Rurktar

Dubbed Rurktar, the tool hasn't had all of its functionality implemented yet, but G DATA says "it is relatively safe to say [it] is intended for use in targeted spying operations." The malicious program could be used for reconnaissance operations, as well as to spy on infected computers users, and steal or upload files.

Table 1537. Table References

Links
<a href="http://www.securityweek.com/rurktar-malware-espionage-tool-development">http://www.securityweek.com/rurktar-malware-espionage-tool-development</a>

## RATAttack

RATAttack is a remote access trojan (RAT) that uses the Telegram protocol to support encrypted communication between the victim's machine and the attacker. The Telegram protocol also provides a simple method to communicate to the target, negating the need for port forwarding. Before using RATAttack, the attacker must create a Telegram bot and embed the bot's Telegram token into the trojan's configuration file. When a system is infected with RATAttack, it connects to the bot's Telegram channel. The attacker can then connect to the same channel and manage the RATAttack clients on the infected host machines. The trojan's code was available on GitHub then was taken down by the author on April 19, 2017.

Table 1538. Table References

Links
<a href="https://www.cyber.nj.gov/threat-profiles/trojan-variants/ratattack">https://www.cyber.nj.gov/threat-profiles/trojan-variants/ratattack</a>

## KhRAT

So called because the Command and Control (C2) infrastructure from previous variants of the malware was located in Cambodia, as discussed by Roland Dela Paz at Forecpoint here, KHRAT is a Trojan that registers victims using their infected machine's username, system language and local IP address. KHRAT provides the threat actors typical RAT features and access to the victim system, including keylogging, screenshot capabilities, remote shell access and so on.

Table 1539. Table References

Links
<a href="https://researchcenter.paloaltonetworks.com/2017/08/unit42-updated-khrat-malware-used-in-cambodia-attacks/">https://researchcenter.paloaltonetworks.com/2017/08/unit42-updated-khrat-malware-used-in-cambodia-attacks/</a>

## RevCode

Table 1540. Table References

Links
<a href="https://revcode.eu/">https://revcode.eu/</a>

# AhNyth Android

Android Remote Administration Tool

Table 1541. Table References

Links
<a href="https://github.com/AhMyth/AhMyth-Android-RAT">https://github.com/AhMyth/AhMyth-Android-RAT</a>

## Socket23

SOCKET23 was launched from his web site and immediately infected major French corporations between August and October 1998. The virus (distributing the Trojan) was known as W32/HLLP.DeTroie.A (alias W32/Cheval.TCV). Never had a virus so disrupted French industry. The author quickly offered his own remover and made his apologies on his web site (now suppressed). Jean-Christophe X (18) was arrested on Tuesday 15 June 1999 in the Paris area and placed under judicial investigation for 'fraudulent intrusion of data in a data processing system, suppression and fraudulent modification of data'

Table 1542. Table References

Links
<a href="https://www.virusbulletin.com/uploads/pdf/magazine/1999/199908.pdf">https://www.virusbulletin.com/uploads/pdf/magazine/1999/199908.pdf</a>

## PowerRAT

## MacSpy

MacSpy is advertised as the "most sophisticated Mac spyware ever", with the low starting price of free. While the idea of malware-as-a-service (MaaS) isn't a new one with players such as Tox and Shark the game, it can be said that MacSpy is one of the first seen for the OS X platform.

Table 1543. Table References

Links
<a href="https://www.alienvault.com/blogs/labs-research/macspy-os-x-rat-as-a-service">https://www.alienvault.com/blogs/labs-research/macspy-os-x-rat-as-a-service</a>

## DNSMessenger

Talos recently analyzed an interesting malware sample that made use of DNS TXT record queries and responses to create a bidirectional Command and Control (C2) channel. This allows the attacker to use DNS communications to submit new commands to be run on infected machines and return the results of the command execution to the attacker. This is an extremely uncommon and evasive way of administering a RAT. The use of multiple stages of Powershell with various stages being completely fileless indicates an attacker who has taken significant measures to avoid detection.

Table 1544. Table References

Links
-------

<a href="http://blog.talosintelligence.com/2017/03/dnsmessenger.html">http://blog.talosintelligence.com/2017/03/dnsmessenger.html</a>
---

## PentagonRAT

*Table 1545. Table References*

Links
-------

<a href="http://pentagon-rat.blogspot.fr/">http://pentagon-rat.blogspot.fr/</a>
---

## NewCore

NewCore is a remote access trojan first discovered by Fortinet researchers while conducting analysis on a China-linked APT campaign targeting Vietnamese organizations. The trojan is a DLL file, executed after a trojan downloader is installed on the targeted machine. Based on strings in the code, the trojan may be compiled from the publicly-available source code of the PcClient and PcCortr backdoor trojans.

*Table 1546. Table References*

Links
-------

<a href="https://www.cyber.nj.gov/threat-profiles/trojan-variants/newcore">https://www.cyber.nj.gov/threat-profiles/trojan-variants/newcore</a>
---

## Deeper RAT

## Xyligan

## H-w0rm

## htpRAT

On November 8, 2016 a non-disclosed entity in Laos was spear-phished by a group closely related to known Chinese adversaries and most likely affiliated with the Chinese government. The attackers utilized a new kind of Remote Access Trojan (RAT) that has not been previously observed or reported. The new RAT extends the capabilities of traditional RATs by providing complete remote execution of custom commands and programming. htpRAT, uncovered by RiskIQ cyber investigators, is the newest weapon in the Chinese adversary's arsenal in a campaign against Association of Southeast Asian Nations (ASEAN). Most RATs can log keystrokes, take screenshots, record audio and video from a webcam or microphone, install and uninstall programs and manage files. They support a fixed set of commands operators can execute using different command IDs —'file download' or 'file upload,' for example—and must be completely rebuilt to have different functionality. htpRAT, on the other hand, serves as a conduit for operators to do their job with greater precision and effect. On the Command and Control (C2) server side, threat actors can build new functionality in commands, which can be sent to the malware to execute. This capability makes htpRAT a small, agile, and incredibly dynamic piece of malware. Operators can change

functionality, such as searching for a different file on the victim's network, simply by wrapping commands.

Table 1547. Table References

Links
<a href="https://cdn.riskiq.com/wp-content/uploads/2017/10/RiskIQ-htpRAT-Malware-Attacks.pdf?_ga=2.159415805.1155855406.1509033001-1017609577.1507615928">https://cdn.riskiq.com/wp-content/uploads/2017/10/RiskIQ-htpRAT-Malware-Attacks.pdf?_ga=2.159415805.1155855406.1509033001-1017609577.1507615928</a>

## Sector

Activity sectors.



Sector is a cluster galaxy available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

**authors**

Various

**Unknown**

**Other**

**Academia - University**

**Activists**

**Aerospace**

**Agriculture**

**Arts**

**Bank**

**Chemical**

**Citizens**

**Civil Aviation**

**Country**

**Culture**

**Data Broker**

**Defense**

**Development**

**Diplomacy**

**Education**

**Electric**

**Electronic**

**Employment**

**Energy**

**Entertainment**

**Environment**

**Finance**

**Food**

**Game**

**Gas**

**Government, Administration**

**Health**

**Higher education**

**Hotels**

**Infrastructure**

**Intelligence**

**IT**

**IT - Hacker**

**IT - ISP**

**IT - Security**

**Justice**

**Manufacturing**

**Maritime**

**Military**

**Multi-sector**

**News - Media**

**NGO**

**Oil**

**Payment**

**Pharmacy**

**Police - Law enforcement**

**Research - Innovation**

**Satellite navigation**

**Security systems**

**Social networks**

**Space**

**Steel**

**Telecoms**

**Think Tanks**

**Trade**

**Transport**

**Travel**

**Turbine**

**Tourism**

**Life science**

**Biomedical**

**High tech**

**Opposition**

**Political party**

**Hospitality**

**Automotive**

**Metal**

**Railway**

**Water**

**Smart meter**

**Retail**

**Retail**

**Technology**

**engineering**

**Mining**

**Sport**

**Restaurant**

**Semi-conductors**

**Insurance**



**Legal**

**Shipping**

**Logistic**

**Construction**

**Industrial**

**Communication equipment**

**Security Service**

**Tax firm**

**Television broadcast**

**Separatists**

**Dissidents**

**Digital services**

**Digital infrastructure**

**Security actors**

**eCommerce**

**Islamic forums**

**Journalist**

**Streaming service**

**Puplishing industry**

**Publishing industry**

**Islamic organisation**

**Casino**

**Consulting**

**Online marketplace**

**DNS service provider**

**Veterinary**

**Marketing**

**Video Sharing**

**Advertising**

**Investment**

**Accounting**

**Programming**

**Managed Services Provider**

**Lawyers**

**Civil society**

**Petrochemical**

# Immigration

## TDS

TDS is a list of Traffic Direction System used by adversaries.



TDS is a cluster galaxy available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

Kafeine

## Keitaro

Keitaro TDS is among the mostly used TDS in drive by infection chains

*Table 1548. Table References*

Links
<a href="https://keitarotds.com/">https://keitarotds.com/</a>

## ShadowTDS

ShadowTDS is advertised underground since 2016-02. It's in fact more like a Social Engineering kit focused on Android and embedding a TDS

## Sutra

Sutra TDS was dominant from 2012 till 2015

*Table 1549. Table References*

Links
<a href="http://kytoon.com/sutra-tds.html">http://kytoon.com/sutra-tds.html</a>

## SimpleTDS

SimpleTDS is a basic open source TDS

SimpleTDS is also known as:

- Stds

*Table 1550. Table References*

Links
<a href="https://sourceforge.net/projects/simpletds/">https://sourceforge.net/projects/simpletds/</a>

## BossTDS

BossTDS

Table 1551. Table References

Links
<a href="http://bosstds.com/">http://bosstds.com/</a>

## BlackHat TDS

BlackHat TDS is sold underground.

Table 1552. Table References

Links
<a href="http://malware.dontneedcoffee.com/2014/04/meet-blackhat-tds.html">http://malware.dontneedcoffee.com/2014/04/meet-blackhat-tds.html</a>

## Futuristic TDS

Futuristic TDS is the TDS component of BlackOS/CookieBomb/NorthTale Iframer

## Orchid TDS

Orchid TDS was sold underground. Rare usage

## Threat actor

Known or estimated adversary groups targeting organizations and employees. Adversary groups are regularly confused with their initial operation or campaign..



Threat actor is a cluster galaxy available in JSON format at [https://github.com/MISP/misp-galaxy/blob/master/clusters/threat\\_actor.json](https://github.com/MISP/misp-galaxy/blob/master/clusters/threat_actor.json)[**this location**] The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

Alexandre Dulaunoy - Florian Roth - Thomas Schreck - Timo Steffens - Various

## Comment Crew

PLA Unit 61398 (Chinese: 61398部, Pinyin: 61398 bùduì) is the Military Unit Cover Designator (MUCD)[1] of a People's Liberation Army advanced persistent threat unit that has been alleged to be a source of Chinese computer hacking attacks

Comment Crew is also known as:

- Comment Panda

- PLA Unit 61398
- APT 1
- APT1
- Advanced Persistent Threat 1
- Byzantine Candor
- Group 3
- TG-8223
- Comment Group

*Table 1553. Table References*

Links
<a href="https://en.wikipedia.org/wiki/PLA_Unit_61398">https://en.wikipedia.org/wiki/PLA_Unit_61398</a>
<a href="http://intelreport.mandiant.com/Mandiant_APT1_Report.pdf">http://intelreport.mandiant.com/Mandiant_APT1_Report.pdf</a>

## Stalker Panda

### Nitro

These attackers were the subject of an extensive report by Symantec in 2011, which termed the attackers Nitro and stated: 'The goal of the attackers appears to be to collect intellectual property such as design documents, formulas, and manufacturing processes. In addition, the same attackers appear to have a lengthy operation history including attacks on other industries and organizations. Attacks on the chemical industry are merely their latest attack wave. As part of our investigations, we were also able to identify and contact one of the attackers to try and gain insights into the motivations behind these attacks.' Palo Alto Networks reported on continued activity by the attackers in 2014.

Nitro is also known as:

- Covert Grove

*Table 1554. Table References*

Links
<a href="http://www.symantec.com/content/en/us/enterprise/media/security_response/whitepapers/the_nitro_attacks.pdf">http://www.symantec.com/content/en/us/enterprise/media/security_response/whitepapers/the_nitro_attacks.pdf</a>

### Codoso

The New York Times described Codoso as: 'A collection of hackers for hire that the security industry has been tracking for years. Over the years, the group has breached banks, law firms and tech companies, and once hijacked the Forbes website to try to infect visitors' computers with malware.'

Codoso is also known as:

- C0d0so
- Sunshop Group

Table 1555. Table References

Links
<a href="https://www.proofpoint.com/us/exploring-bergard-old-malware-new-tricks">https://www.proofpoint.com/us/exploring-bergard-old-malware-new-tricks</a>
<a href="https://www.nytimes.com/2016/06/12/technology/the-chinese-hackers-in-the-back-office.html">https://www.nytimes.com/2016/06/12/technology/the-chinese-hackers-in-the-back-office.html</a>

## Dust Storm

Table 1556. Table References

Links
<a href="https://www.cylance.com/hubfs/2015_cylance_website/assets/operation-dust-storm/Op_Dust_Storm_Report.pdf">https://www.cylance.com/hubfs/2015_cylance_website/assets/operation-dust-storm/Op_Dust_Storm_Report.pdf</a>

## Karma Panda

Adversary targeting dissident groups in China and its surroundings.

Table 1557. Table References

Links
<a href="http://www.rsaconference.com/writable/presentations/file_upload/anf-t07b-the-art-of-attribution-identifying-and-pursuing-your-cyber-adversaries_final.pdf">http://www.rsaconference.com/writable/presentations/file_upload/anf-t07b-the-art-of-attribution-identifying-and-pursuing-your-cyber-adversaries_final.pdf</a>

## Keyhole Panda

## Wet Panda

## Foxy Panda

Adversary group targeting telecommunication and technology organizations.

## Predator Panda

## Union Panda

## Spicy Panda

## Eloquent Panda

# Dizzy Panda

Dizzy Panda is also known as:

- LadyBoyle

# Putter Panda

Putter Panda were the subject of an extensive report by CrowdStrike, which stated: 'The CrowdStrike Intelligence team has been tracking this particular unit since 2012, under the codename PUTTER PANDA, and has documented activity dating back to 2007. The report identifies Chen Ping, aka cpyy, and the primary location of Unit 61486.'

Putter Panda is also known as:

- PLA Unit 61486
- APT 2
- Group 36
- APT-2
- MSUpdater
- 4HCrew
- SULPHUR
- TG-6952

*Table 1558. Table References*

Links
<a href="http://cdn0.vox-cdn.com/assets/4589853/crowdstrike-intelligence-report-putter-panda.original.pdf">http://cdn0.vox-cdn.com/assets/4589853/crowdstrike-intelligence-report-putter-panda.original.pdf</a>

# UPS

Symantec described UPS in 2016 report as: 'Buckeye (also known as APT3, Gothic Panda, UPS Team, and TG-0110) is a cyberespionage group that is believed to have been operating for well over half a decade. Traditionally, the group attacked organizations in the US as well as other targets. However, Buckeyes focus appears to have changed as of June 2015, when the group began compromising political entities in Hong Kong.'

UPS is also known as:

- Gothic Panda
- TG-0110
- APT 3
- Group 6
- UPS Team

- APT3
- Buckeye

Table 1559. Table References

Links
<a href="https://www.fireeye.com/blog/threat-research/2015/06/operation-clandestine-wolf-adobe-flash-zero-day.html">https://www.fireeye.com/blog/threat-research/2015/06/operation-clandestine-wolf-adobe-flash-zero-day.html</a>
<a href="http://www.symantec.com/connect/blogs/buckeye-cyberespionage-group-shifts-gaze-us-hong-kong">http://www.symantec.com/connect/blogs/buckeye-cyberespionage-group-shifts-gaze-us-hong-kong</a>

## DarkHotel

Kaspersky described DarkHotel in a 2014 report as: '... DarkHotel drives its campaigns by spear-phishing targets with highly advanced Flash zero-day exploits that effectively evade the latest Windows and Adobe defenses, and yet they also imprecisely spread among large numbers of vague targets with peer-to-peer spreading tactics. Moreover, this crews most unusual characteristic is that for several years the Darkhotel APT has maintained a capability to use hotel networks to follow and hit selected targets as they travel around the world.'

DarkHotel is also known as:

- DUBNIUM
- Fallout Team

Table 1560. Table References

Links
<a href="https://securelist.com/blog/research/71713/darkhotels-attacks-in-2015/">https://securelist.com/blog/research/71713/darkhotels-attacks-in-2015/</a>
<a href="https://blogs.technet.microsoft.com/mmpc/2016/06/09/reverse-engineering-dubnium-2">https://blogs.technet.microsoft.com/mmpc/2016/06/09/reverse-engineering-dubnium-2</a>

## IXESHE

A group of China-based attackers, who conducted a number of spear phishing attacks in 2013.

IXESHE is also known as:

- Numbered Panda
- TG-2754
- BeeBus
- Group 22
- DynCalc
- Crimson Iron
- APT12
- APT 12



Table 1561. Table References

Links
<a href="http://www.crowdstrike.com/blog/whois-numbered-panda/">http://www.crowdstrike.com/blog/whois-numbered-panda/</a>

## APT 16

Table 1562. Table References

Links
<a href="https://www.fireeye.com/blog/threat-research/2015/12/the_eps_awakens.html">https://www.fireeye.com/blog/threat-research/2015/12/the_eps_awakens.html</a>

## Aurora Panda

FireEye described APT17 in a 2015 report as: 'APT17, also known as DeputyDog, is a China based threat group that FireEye Intelligence has observed conducting network intrusions against U.S. government entities, the defense industry, law firms, information technology companies, mining companies, and non-government organizations.'

Aurora Panda is also known as:

- APT 17
- Deputy Dog
- Group 8
- APT17
- Hidden Lynx
- Tailgater Team

Table 1563. Table References

Links
<a href="http://www.fireeye.com/blog/technical/cyber-exploits/2013/09/operation-deputydog-zero-day-cve-2013-3893-attack-against-japanese-targets.html">http://www.fireeye.com/blog/technical/cyber-exploits/2013/09/operation-deputydog-zero-day-cve-2013-3893-attack-against-japanese-targets.html</a>
<a href="http://www.symantec.com/content/en/us/enterprise/media/security_response/whitepapers/hidden_lynx.pdf">http://www.symantec.com/content/en/us/enterprise/media/security_response/whitepapers/hidden_lynx.pdf</a>

## Wekby

Wekby was described by Palo Alto Networks in a 2015 report as: 'Wekby is a group that has been active for a number of years, targeting various industries such as healthcare, telecommunications, aerospace, defense, and high tech. The group is known to leverage recently released exploits very shortly after those exploits are available, such as in the case of HackingTeams Flash zero - day exploit.'

Wekby is also known as:

- Dynamite Panda

- TG-0416
- APT 18
- SCANDIUM
- APT18

Table 1564. Table References

Links
<a href="https://threatpost.com/apt-gang-branches-out-to-medical-espionage-in-community-health-breach/107828">https://threatpost.com/apt-gang-branches-out-to-medical-espionage-in-community-health-breach/107828</a>

## Tropic Trooper

TrendMicro described Tropic Trooper in a 2015 report as: 'Taiwan and the Philippines have become the targets of an ongoing campaign called Operation TropicTrooper. Active since 2012, the attackers behind the campaign have set their sights on the Taiwanese government as well as a number of companies in the heavy industry. The same campaign has also targeted key Philippine military agencies.'

Tropic Trooper is also known as:

- Operation Tropic Trooper

Table 1565. Table References

Links
<a href="http://researchcenter.paloaltonetworks.com/2016/11/unit42-tropic-trooper-targets-taiwanese-government-and-fossil-fuel-provider-with-poison-ivy/">http://researchcenter.paloaltonetworks.com/2016/11/unit42-tropic-trooper-targets-taiwanese-government-and-fossil-fuel-provider-with-poison-ivy/</a>
<a href="http://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp-operation-tropic-trooper.pdf">http://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp-operation-tropic-trooper.pdf</a>

## Axiom

The Winnti grouping of activity is large and may actually be a number of linked groups rather than a single discrete entity. Kaspersky describe Winnti as: 'The Winnti group has been attacking companies in the online video game industry since 2009 and is currently still active. The groups objectives are stealing digital certificates signed by legitimate software vendors in addition to intellectual property theft, including the source code of online game projects. The majority of the victims are from South East Asia.'

Axiom is also known as:

- Winnti Group
- Tailgater Team
- Group 72
- Group72

- Tailgater
- Ragebeast
- Blackfly
- Lead
- Wicked Spider
- Barium

Table 1566. Table References

Links
<a href="http://securelist.com/blog/research/57585/winnti-faq-more-than-just-a-game/">http://securelist.com/blog/research/57585/winnti-faq-more-than-just-a-game/</a>
<a href="http://williamshowalter.com/a-universal-windows-bootkit/">http://williamshowalter.com/a-universal-windows-bootkit/</a>
<a href="https://blogs.technet.microsoft.com/mmpc/2017/01/25/detecting-threat-actors-in-recent-german-industrial-attacks-with-windows-defender-atp">https://blogs.technet.microsoft.com/mmpc/2017/01/25/detecting-threat-actors-in-recent-german-industrial-attacks-with-windows-defender-atp</a>

## Shell Crew

Adversary group targeting financial, technology, non-profit organisations.

Shell Crew is also known as:

- Deep Panda
- WebMasters
- APT 19
- KungFu Kittens
- Black Vine
- Group 13
- PinkPanther
- Sh3llCr3w

Table 1567. Table References

Links
<a href="http://cybercampaigns.net/wp-content/uploads/2013/06/Deep-Panda.pdf">http://cybercampaigns.net/wp-content/uploads/2013/06/Deep-Panda.pdf</a>
<a href="http://www.rsaconference.com/writable/presentations/file_upload/anf-t07b-the-art-of-attribution-identifying-and-pursuing-your-cyber-adversaries_final.pdf">http://www.rsaconference.com/writable/presentations/file_upload/anf-t07b-the-art-of-attribution-identifying-and-pursuing-your-cyber-adversaries_final.pdf</a>

## Naikon

Kaspersky described Naikon in a 2015 report as: 'The Naikon group is mostly active in countries such as the Philippines, Malaysia, Cambodia, Indonesia, Vietnam, Myanmar, Singapore, and Nepal, hitting a variety of targets in a very opportunistic way.'

Naikon is also known as:

- PLA Unit 78020
- Override Panda
- Camerashy
- APT.Naikon

*Table 1568. Table References*

Links
<a href="https://securelist.com/analysis/publications/69953/the-naikon-apt/">https://securelist.com/analysis/publications/69953/the-naikon-apt/</a>
<a href="http://www.fireeye.com/blog/technical/malware-research/2014/03/spear-phishing-the-news-cycle-apt-actors-leverage-interest-in-the-disappearance-of-malaysian-flight-mh-370.html">http://www.fireeye.com/blog/technical/malware-research/2014/03/spear-phishing-the-news-cycle-apt-actors-leverage-interest-in-the-disappearance-of-malaysian-flight-mh-370.html</a>

## Lotus Blossom

Lotus Blossom is also known as:

- Spring Dragon
- ST Group

*Table 1569. Table References*

Links
<a href="https://securelist.com/blog/research/70726/the-spring-dragon-apt/">https://securelist.com/blog/research/70726/the-spring-dragon-apt/</a>
<a href="https://securelist.com/spring-dragon-updated-activity/79067/">https://securelist.com/spring-dragon-updated-activity/79067/</a>

## Lotus Panda

Lotus Panda is also known as:

- Elise

## Hurricane Panda

*Table 1570. Table References*

Links
<a href="http://www.crowdstrike.com/blog/cyber-deterrence-in-action-a-story-of-one-long-hurricane-panda-campaign/">http://www.crowdstrike.com/blog/cyber-deterrence-in-action-a-story-of-one-long-hurricane-panda-campaign/</a>

## Emissary Panda

A China-based actor that targets foreign embassies to collect data on government, defence, and technology sectors.

Emissary Panda is also known as:

- TG-3390
- APT 27
- TEMP.Hippo
- Group 35
- HIPPOTeam
- APT27
- Operation Iron Tiger

Table 1571. Table References

Links
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/">http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/</a>
<a href="http://www.scmagazineuk.com/iran-and-russia-blamed-for-state-sponsored-espionage/article/330401/">http://www.scmagazineuk.com/iran-and-russia-blamed-for-state-sponsored-espionage/article/330401/</a>

## Stone Panda

Stone Panda is also known as:

- APT10
- APT 10
- menuPass
- happyyongzi
- POTASSIUM
- DustStorm
- Red Apollo
- CVNX

Table 1572. Table References

Links
<a href="http://researchcenter.paloaltonetworks.com/2017/02/unit42-menupass-returns-new-malware-new-attacks-japanese-academics-organizations/">http://researchcenter.paloaltonetworks.com/2017/02/unit42-menupass-returns-new-malware-new-attacks-japanese-academics-organizations/</a>

## Nightshade Panda

Nightshade Panda is also known as:

- APT 9
- Flowerlady/Flowershow
- Flowerlady

- Flowershow

Table 1573. Table References

Links
<a href="https://otx.alienvault.com/pulse/55bbc68e67db8c2d547ae393/">https://otx.alienvault.com/pulse/55bbc68e67db8c2d547ae393/</a>

## Hellsing

Hellsing is also known as:

- Goblin Panda
- Cycldek

Table 1574. Table References

Links
<a href="https://securelist.com/analysis/publications/69567/the-chronicles-of-the-hellsing-apt-the-empire-strikes-back/">https://securelist.com/analysis/publications/69567/the-chronicles-of-the-hellsing-apt-the-empire-strikes-back/</a>

## Night Dragon

Table 1575. Table References

Links
<a href="https://kc.mcafee.com/corporate/index?page=content&amp;id=KB71150">https://kc.mcafee.com/corporate/index?page=content&amp;id=KB71150</a>

## Mirage

Mirage is also known as:

- Vixen Panda
- Ke3Chang
- GREF
- Playful Dragon
- APT 15
- Metushy
- Social Network Team

Table 1576. Table References

Links
<a href="https://www.fireeye.com/blog/threat-research/2014/09/forced-to-adapt-xslcmd-backdoor-now-on-os-x.html">https://www.fireeye.com/blog/threat-research/2014/09/forced-to-adapt-xslcmd-backdoor-now-on-os-x.html</a>

# Anchor Panda

PLA Navy

Anchor Panda is also known as:

- APT14
- APT 14
- QAZTeam
- ALUMINUM

*Table 1577. Table References*

Links
<a href="http://www.crowdstrike.com/blog/whois-anchor-panda/">http://www.crowdstrike.com/blog/whois-anchor-panda/</a>

# NetTraveler

NetTraveler is also known as:

- APT 21

*Table 1578. Table References*

Links
<a href="https://securelist.com/blog/research/35936/nettraveler-is-running-red-star-apt-attacks-compromise-high-profile-victims/">https://securelist.com/blog/research/35936/nettraveler-is-running-red-star-apt-attacks-compromise-high-profile-victims/</a>

# Ice Fog

Operate since at least 2011, from several locations in China, with members in Korea and Japan as well.

Ice Fog is also known as:

- IceFog
- Dagger Panda

*Table 1579. Table References*

Links
<a href="https://securelist.com/blog/research/57331/the-icefog-apt-a-tale-of-cloak-and-three-daggers/">https://securelist.com/blog/research/57331/the-icefog-apt-a-tale-of-cloak-and-three-daggers/</a>

# Pitty Panda

The Pitty Tiger group has been active since at least 2011. They have been seen using HeartBleed vulnerability in order to directly get valid credentials

Pitty Panda is also known as:

- PittyTiger
- MANGANESE

*Table 1580. Table References*

Links
<a href="http://blog.airbuscybersecurity.com/post/2014/07/The-Eye-of-the-Tiger2">http://blog.airbuscybersecurity.com/post/2014/07/The-Eye-of-the-Tiger2</a>

## Roaming Tiger

*Table 1581. Table References*

Links
<a href="http://researchcenter.paloaltonetworks.com/2015/12/bbsrat-attacks-targeting-russian-organizations-linked-to-roaming-tiger/">http://researchcenter.paloaltonetworks.com/2015/12/bbsrat-attacks-targeting-russian-organizations-linked-to-roaming-tiger/</a>

## Beijing Group

Beijing Group is also known as:

- Sneaky Panda

## Radio Panda

Radio Panda is also known as:

- Shrouded Crossbow

## APT.3102

*Table 1582. Table References*

Links
<a href="http://researchcenter.paloaltonetworks.com/2015/09/chinese-actors-use-3102-malware-in-attacks-on-us-government-and-eu-media/">http://researchcenter.paloaltonetworks.com/2015/09/chinese-actors-use-3102-malware-in-attacks-on-us-government-and-eu-media/</a>

## Samurai Panda

Samurai Panda is also known as:

- PLA Navy
- APT4
- APT 4
- Getkys



- SykipotGroup
- Wkysol

Table 1583. Table References

Links
<a href="http://www.crowdstrike.com/blog/whois-samurai-panda/">http://www.crowdstrike.com/blog/whois-samurai-panda/</a>

## Impersonating Panda

### Violin Panda

Violin Panda is also known as:

- APT20
- APT 20
- TH3Bug

Table 1584. Table References

Links
<a href="http://researchcenter.paloaltonetworks.com/2014/09/recent-watering-hole-attacks-attributed-apt-group-th3bug-using-poison-ivy/">http://researchcenter.paloaltonetworks.com/2014/09/recent-watering-hole-attacks-attributed-apt-group-th3bug-using-poison-ivy/</a>

### Toxic Panda

A group targeting dissident groups in China and at the boundaries.

Table 1585. Table References

Links
<a href="http://www.rsaconference.com/writable/presentations/file_upload/anf-t07b-the-art-of-attribution-identifying-and-pursuing-your-cyber-adversaries_final.pdf">http://www.rsaconference.com/writable/presentations/file_upload/anf-t07b-the-art-of-attribution-identifying-and-pursuing-your-cyber-adversaries_final.pdf</a>

### Temper Panda

China-based cyber threat group. It has previously used newsworthy events as lures to deliver malware and has primarily targeted organizations involved in financial, economic, and trade policy, typically using publicly available RATs such as PoisonIvy, as well as some non-public backdoors.

Temper Panda is also known as:

- Admin338
- Team338
- MAGNESIUM

- admin@338

Table 1586. Table References

Links
<a href="https://www.fireeye.com/blog/threat-research/2013/10/know-your-enemy-tracking-a-rapidly-evolving-apt-actor.html">https://www.fireeye.com/blog/threat-research/2013/10/know-your-enemy-tracking-a-rapidly-evolving-apt-actor.html</a>
<a href="https://www.fireeye.com/blog/threat-research/2015/11/china-based-threat.html">https://www.fireeye.com/blog/threat-research/2015/11/china-based-threat.html</a>

## Pirate Panda

Pirate Panda is also known as:

- APT23
- KeyBoy

Table 1587. Table References

Links
<a href="https://community.rapid7.com/community/infosec/blog/2013/06/07/keyboy-targeted-attacks-against-vietnam-and-india">https://community.rapid7.com/community/infosec/blog/2013/06/07/keyboy-targeted-attacks-against-vietnam-and-india</a>

## Flying Kitten

Activity: defense and aerospace sectors, also interested in targeting entities in the oil/gas industry.

Flying Kitten is also known as:

- SaffronRose
- Saffron Rose
- AjaxSecurityTeam
- Ajax Security Team
- Group 26

Table 1588. Table References

Links
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-operation-saffron-rose.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-operation-saffron-rose.pdf</a>

## Cutting Kitten

While tracking a suspected Iran-based threat group known as Threat Group-2889[1] (TG-2889), Dell SecureWorks Counter Threat Unit™ (CTU) researchers uncovered a network of fake LinkedIn profiles. These convincing profiles form a self-referenced network of seemingly established LinkedIn users. CTU researchers assess with high confidence the purpose of this network is to target potential victims through social engineering. Most of the legitimate LinkedIn accounts

associated with the fake accounts belong to individuals in the Middle East, and CTU researchers assess with medium confidence that these individuals are likely targets of TG-2889.

Cutting Kitten is also known as:

- ITSecTeam
- Threat Group 2889
- TG-2889
- Ghambar

*Table 1589. Table References*

Links
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/suspected-iran-based-hacker-group-creates-network-of-fake-linkedin-profiles/">http://www.secureworks.com/cyber-threat-intelligence/threats/suspected-iran-based-hacker-group-creates-network-of-fake-linkedin-profiles/</a>

## Charming Kitten

Charming Kitten (aka Parastoo, aka Newscaster) is an group with a suspected nexus to Iran that targets organizations involved in government, defense technology, military, and diplomacy sectors.

Charming Kitten is also known as:

- Newscaster
- Parastoo
- Group 83
- Newsbeef

*Table 1590. Table References*

Links
<a href="https://en.wikipedia.org/wiki/Operation_Newscaster">https://en.wikipedia.org/wiki/Operation_Newscaster</a>

## APT33

Our analysis reveals that APT33 is a capable group that has carried out cyber espionage operations since at least 2013. We assess APT33 works at the behest of the Iranian government.

APT33 is also known as:

*Table 1591. Table References*

Links
<a href="https://www.fireeye.com/blog/threat-research/2017/09/apt33-insights-into-iranian-cyber-espionage.html">https://www.fireeye.com/blog/threat-research/2017/09/apt33-insights-into-iranian-cyber-espionage.html</a>

## Magic Kitten

Earliest activity back to November 2008. An established group of cyber attackers based in Iran, who carried on several campaigns in 2013, including a series of attacks targeting political dissidents and those supporting Iranian political opposition.

Magic Kitten is also known as:

- Group 42

Table 1592. Table References

Links
<a href="http://www.scmagazineuk.com/iran-and-russia-blamed-for-state-sponsored-espionage/article/330401/">http://www.scmagazineuk.com/iran-and-russia-blamed-for-state-sponsored-espionage/article/330401/</a>

## Rocket Kitten

Targets Saudi Arabia, Israel, US, Iran, high ranking defense officials, embassies of various target countries, notable Iran researchers, human rights activists, media and journalists, academic institutions and various scholars, including scientists in the fields of physics and nuclear sciences.

Rocket Kitten is also known as:

- TEMP.Beanie
- Operation Woolen Goldfish
- Thamar Reservoir

Table 1593. Table References

Links
<a href="https://www.trendmicro.com/vinfo/us/security/news/cyber-attacks/operation-woolen-goldfish-when-kittens-go-phishing">https://www.trendmicro.com/vinfo/us/security/news/cyber-attacks/operation-woolen-goldfish-when-kittens-go-phishing</a>
<a href="https://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp-the-spy-kittens-are-back.pdf">https://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp-the-spy-kittens-are-back.pdf</a>
<a href="http://www.clearskysec.com/thamar-reservoir/">http://www.clearskysec.com/thamar-reservoir/</a>
<a href="https://citizenlab.org/2015/08/iran_two_factor_phishing/">https://citizenlab.org/2015/08/iran_two_factor_phishing/</a>
<a href="https://blog.checkpoint.com/wp-content/uploads/2015/11/rocket-kitten-report.pdf">https://blog.checkpoint.com/wp-content/uploads/2015/11/rocket-kitten-report.pdf</a>

## Cleaver

A group of cyber actors utilizing infrastructure located in Iran have been conducting computer network exploitation activity against public and private U.S. organizations, including Cleared Defense Contractors (CDCs), academic institutions, and energy sector companies.

Cleaver is also known as:

- Operation Cleaver
- Tarh Andishan
- Alibaba
- 2889
- TG-2889

Table 1594. Table References

Links
<a href="http://cdn2.hubspot.net/hubfs/270968/assets/Cleaver/Cylance_Operation_Cleaver_Report.pdf">http://cdn2.hubspot.net/hubfs/270968/assets/Cleaver/Cylance_Operation_Cleaver_Report.pdf</a>

## Sands Casino

## Rebel Jackal

This is a pro-Islamist organization that generally conducts attacks motivated by real world events in which its members believe that members of the Muslim faith were wronged. Its attacks generally involve website defacements; however, the group did develop a RAT that it refers to as Fallaga RAT, but which appears to simply be a fork of the njRAT malware popular amongst hackers in the Middle East/North Africa region.

Rebel Jackal is also known as:

- FallagaTeam

## Viking Jackal

Viking Jackal is also known as:

- Vikingdom

## Sofacy

The Sofacy Group (also known as APT28, Pawn Storm, Fancy Bear and Sednit) is a cyber espionage group believed to have ties to the Russian government. Likely operating since 2007, the group is known to target government, military, and security organizations. It has been characterized as an advanced persistent threat.

Sofacy is also known as:

- APT 28
- APT28
- Pawn Storm
- Fancy Bear
- Sednit

- TsarTeam
- TG-4127
- Group-4127
- STRONTIUM
- TAG\_0700
- Swallowtail
- IRON TWILIGHT

Table 1595. Table References

Links
<a href="https://en.wikipedia.org/wiki/Sofacy_Group">https://en.wikipedia.org/wiki/Sofacy_Group</a>

## APT 29

A 2015 report by F-Secure describe APT29 as: 'The Dukes are a well-resourced, highly dedicated and organized cyberespionage group that we believe has been working for the Russian Federation since at least 2008 to collect intelligence in support of foreign and security policy decision-making. The Dukes show unusual confidence in their ability to continue successfully compromising their targets, as well as in their ability to operate with impunity. The Dukes primarily target Western governments and related organizations, such as government ministries and agencies, political think tanks, and governmental subcontractors. Their targets have also included the governments of members of the Commonwealth of Independent States;Asian, African, and Middle Eastern governments;organizations associated with Chechen extremism;and Russian speakers engaged in the illicit trade of controlled substances and drugs. The Dukes are known to employ a vast arsenal of malware toolsets, which we identify as MiniDuke, CosmicDuke, OnionDuke, CozyDuke, CloudDuke, SeaDuke, HammerDuke, PinchDuke, and GeminiDuke. In recent years, the Dukes have engaged in apparently biannual large - scale spear - phishing campaigns against hundreds or even thousands of recipients associated with governmental institutions and affiliated organizations. These campaigns utilize a smash - and - grab approach involving a fast but noisy breakin followed by the rapid collection and exfiltration of as much data as possible.If the compromised target is discovered to be of value, the Dukes will quickly switch the toolset used and move to using stealthier tactics focused on persistent compromise and long - term intelligence gathering '

APT 29 is also known as:

- Dukes
- Group 100
- Cozy Duke
- CozyDuke
- EuroAPT
- CozyBear
- CozyCar

- Cozer
- Office Monkeys
- OfficeMonkeys
- APT29
- Cozy Bear
- The Dukes
- Minidionis
- SeaDuke

Table 1596. Table References

Links
<a href="https://labsblog.f-secure.com/2015/09/17/the-dukes-7-years-of-russian-cyber-espionage/">https://labsblog.f-secure.com/2015/09/17/the-dukes-7-years-of-russian-cyber-espionage/</a>

## Turla Group

A 2014 Guardian article described Turla as: 'Dubbed the Turla hackers, initial intelligence had indicated western powers were key targets, but it was later determined embassies for Eastern Bloc nations were of more interest. Embassies in Belgium, Ukraine, China, Jordan, Greece, Kazakhstan, Armenia, Poland, and Germany were all attacked, though researchers from Kaspersky Lab and Symantec could not confirm which countries were the true targets. In one case from May 2012, the office of the prime minister of a former Soviet Union member country was infected, leading to 60 further computers being affected, Symantec researchers said. There were some other victims, including the ministry for health of a Western European country, the ministry for education of a Central American country, a state electricity provider in the Middle East and a medical organisation in the US, according to Symantec. It is believed the group was also responsible for a much - documented 2008 attack on the US Central Command. The attackers - who continue to operate - have ostensibly sought to carry out surveillance on targets and pilfer data, though their use of encryption across their networks has made it difficult to ascertain exactly what the hackers took. Kaspersky Lab, however, picked up a number of the attackers searches through their victims emails, which included terms such as Nato and EU energy dialogue. Though attribution is difficult to substantiate, Russia has previously been suspected of carrying out the attacks and Symantec's Gavin O' Gorman told the Guardian a number of the hackers appeared to be using Russian names and language in their notes for their malicious code. Cyrillic was also seen in use.'

Turla Group is also known as:

- Turla
- Snake
- Venomous Bear
- Group 88
- Waterbug
- WRAITH

- Turla Team
- Uroburos
- Pfinet
- TAG\_0530
- KRYPTON
- Hippo Team

Table 1597. Table References

Links
<a href="https://www.first.org/resources/papers/tbilisi2014/turla-operations_and_development.pdf">https://www.first.org/resources/papers/tbilisi2014/turla-operations_and_development.pdf</a>
<a href="https://www.circl.lu/pub/tr-25/">https://www.circl.lu/pub/tr-25/</a>
<a href="https://www.theguardian.com/technology/2014/aug/07/turla-hackers-spying-governments-researcher-kaspersky-symantec">https://www.theguardian.com/technology/2014/aug/07/turla-hackers-spying-governments-researcher-kaspersky-symantec</a>

## Energetic Bear

A Russian group that collects intelligence on the energy industry.

Energetic Bear is also known as:

- Dragonfly
- Crouching Yeti
- Group 24
- Havex
- CrouchingYeti
- Koala Team

Table 1598. Table References

Links
<a href="http://www.scmagazineuk.com/iran-and-russia-blamed-for-state-sponsored-espionage/article/330401/">http://www.scmagazineuk.com/iran-and-russia-blamed-for-state-sponsored-espionage/article/330401/</a>

## Sandworm

Sandworm is also known as:

- Sandworm Team
- Black Energy
- BlackEnergy
- Quedagh
- Voodoo Bear



Table 1599. Table References

Links
<a href="http://www.isightpartners.com/2014/10/cve-2014-4114/">http://www.isightpartners.com/2014/10/cve-2014-4114/</a>

## TeleBots

We will refer to the gang behind the malware as TeleBots. However it's important to say that these attackers, and the toolset used, share a number of similarities with the BlackEnergy group, which conducted attacks against the energy industry in Ukraine in December 2015 and January 2016. In fact, we think that the BlackEnergy group has evolved into the TeleBots group.

Table 1600. Table References

Links
<a href="http://www.welivesecurity.com/2016/12/13/rise-telebots-analyzing-disruptive-killdisk-attacks/">http://www.welivesecurity.com/2016/12/13/rise-telebots-analyzing-disruptive-killdisk-attacks/</a>

## Anunak

Groups targeting financial organizations or people with significant financial assets.

Anunak is also known as:

- Carbanak
- Carbon Spider
- FIN7

Table 1601. Table References

Links
<a href="https://en.wikipedia.org/wiki/Carbanak">https://en.wikipedia.org/wiki/Carbanak</a>
<a href="https://www.proofpoint.com/us/threat-insight/post/fin7carbanak-threat-actor-unleashes-bateleur-jscript-backdoor">https://www.proofpoint.com/us/threat-insight/post/fin7carbanak-threat-actor-unleashes-bateleur-jscript-backdoor</a>

## TeamSpy Crew

TeamSpy Crew is also known as:

- TeamSpy
- Team Bear
- Berserk Bear

Table 1602. Table References

Links
<a href="https://securelist.com/blog/incidents/35520/the-teamspy-crew-attacks-abusing-teamviewer-for-cyberespionage-8/">https://securelist.com/blog/incidents/35520/the-teamspy-crew-attacks-abusing-teamviewer-for-cyberespionage-8/</a>

# BuhTrap

*Table 1603. Table References*

Links

<http://www.welivesecurity.com/2015/11/11/operathion-buhtrap-malware-distributed-via-ammyy-com/>

## Berserk Bear

## Wolf Spider

Wolf Spider is also known as:

- FIN4

## Boulder Bear

First observed activity in December 2013.

## Shark Spider

This group's activity was first observed in November 2013. It leverages a banking Trojan more commonly known as Shylock which aims to compromise online banking credentials and credentials related to Bitcoin wallets.

## Union Spider

Adversary targeting manufacturing and industrial organizations.

*Table 1604. Table References*

Links

[http://www.rsaconference.com/writable/presentations/file\\_upload/anf-t07b-the-art-of-attribution-identifying-and-pursuing-your-cyber-adversaries\\_final.pdf](http://www.rsaconference.com/writable/presentations/file_upload/anf-t07b-the-art-of-attribution-identifying-and-pursuing-your-cyber-adversaries_final.pdf)

## Silent Chollima

Silent Chollima is also known as:

- OperationTroy
- Guardian of Peace
- GOP
- WHOis Team

*Table 1605. Table References*

Links
<a href="http://www.rsaconference.com/writable/presentations/file_upload/anf-t07b-the-art-of-attribution-identifying-and-pursuing-your-cyber-adversaries_final.pdf">http://www.rsaconference.com/writable/presentations/file_upload/anf-t07b-the-art-of-attribution-identifying-and-pursuing-your-cyber-adversaries_final.pdf</a>

## Lazarus Group

Since 2009, HIDDEN COBRA actors have leveraged their capabilities to target and compromise a range of victims; some intrusions have resulted in the exfiltration of data while others have been disruptive in nature. Commercial reporting has referred to this activity as Lazarus Group and Guardians of Peace. Tools and capabilities used by HIDDEN COBRA actors include DDoS botnets, keyloggers, remote access tools (RATs), and wiper malware. Variants of malware and tools used by HIDDEN COBRA actors include Destover, Duuzer, and Hangman.

Lazarus Group is also known as:

- Operation DarkSeoul
- Hidden Cobra

*Table 1606. Table References*

Links
<a href="https://threatpost.com/operation-blockbuster-coalition-ties-destructive-attacks-to-lazarus-group/116422/">https://threatpost.com/operation-blockbuster-coalition-ties-destructive-attacks-to-lazarus-group/116422/</a>
<a href="https://www.us-cert.gov/ncas/alerts/TA17-164A">https://www.us-cert.gov/ncas/alerts/TA17-164A</a>

## Viceroy Tiger

Viceroy Tiger is also known as:

- Appin
- OperationHangover

*Table 1607. Table References*

Links
<a href="http://enterprise-manage.norman.c.bitbit.net/resources/files/Unveiling_an_Indian_Cyberattack_Infrastructure.pdf">http://enterprise-manage.norman.c.bitbit.net/resources/files/Unveiling_an_Indian_Cyberattack_Infrastructure.pdf</a>

## Pizzo Spider

Pizzo Spider is also known as:

- DD4BC
- Ambiorx

# Corsair Jackal

Corsair Jackal is also known as:

- TunisianCyberArmy

# SNOWGLOBE

In 2014, researchers at Kaspersky Lab discovered and reported on three zero-days that were being used in cyberattacks in the wild. Two of these zero-day vulnerabilities are associated with an advanced threat actor we call Animal Farm. Over the past few years, Animal Farm has targeted a wide range of global organizations. The group has been active since at least 2009 and there are signs that earlier malware versions were developed as far back as 2007.

SNOWGLOBE is also known as:

- Animal Farm

Table 1608. Table References

Links
<a href="https://securelist.com/blog/research/69114/animals-in-the-apt-farm/">https://securelist.com/blog/research/69114/animals-in-the-apt-farm/</a>

# Deadeye Jackal

The Syrian Electronic Army (SEA) is a group of computer hackers which first surfaced online in 2011 to support the government of Syrian President Bashar al-Assad. Using spamming, website defacement, malware, phishing, and denial of service attacks, it has targeted political opposition groups, western news organizations, human rights groups and websites that are seemingly neutral to the Syrian conflict. It has also hacked government websites in the Middle East and Europe, as well as US defense contractors. As of 2011 the SEA has been **the first Arab country to have a public Internet Army hosted on its national networks to openly launch cyber attacks on its enemies**. The precise nature of SEA's relationship with the Syrian government has changed over time and is unclear

Deadeye Jackal is also known as:

- SyrianElectronicArmy
- SEA

Table 1609. Table References

Links
<a href="https://en.wikipedia.org/wiki/Syrian_Electronic_Army">https://en.wikipedia.org/wiki/Syrian_Electronic_Army</a>

# Operation C-Major

Group targeting Indian Army or related assets in India. Attribution to a Pakistani connection has

been made by TrendMicro.

Operation C-Major is also known as:

- C-Major

*Table 1610. Table References*

Links
<a href="http://documents.trendmicro.com/assets/pdf/Indian-military-personnel-targeted-by-information-theft-campaign-cmajor.pdf">http://documents.trendmicro.com/assets/pdf/Indian-military-personnel-targeted-by-information-theft-campaign-cmajor.pdf</a>

## Stealth Falcon

Group targeting Emirati journalists, activists, and dissidents.

Stealth Falcon is also known as:

- FruityArmor

*Table 1611. Table References*

Links
<a href="https://citizenlab.org/2016/05/stealth-falcon/">https://citizenlab.org/2016/05/stealth-falcon/</a>

## ScarCruft

ScarCruft is a relatively new APT group; victims have been observed in several countries, including Russia, Nepal, South Korea, China, India, Kuwait and Romania. The group has several ongoing operations utilizing multiple exploits — two for Adobe Flash and one for Microsoft Internet Explorer.

ScarCruft is also known as:

- Operation Daybreak
- Operation Erebus

*Table 1612. Table References*

Links
<a href="https://securelist.com/blog/research/75082/cve-2016-4171-adobe-flash-zero-day-used-in-targeted-attacks/">https://securelist.com/blog/research/75082/cve-2016-4171-adobe-flash-zero-day-used-in-targeted-attacks/</a>

## Pacifier APT

Bitdefender detected and blocked an ongoing cyber-espionage campaign against Romanian institutions and other foreign targets. The attacks started in 2014, with the latest reported occurrences in May of 2016. The APT, dubbed Pacifier by Bitdefender researchers, makes use of malicious .doc documents and .zip files distributed via spear phishing e-mail.

Pacifier APT is also known as:

- Skipper
- Popeye

*Table 1613. Table References*

Links
<a href="http://download.bitdefender.com/resources/files/News/CaseStudies/study/115/Bitdefender-Whitepaper-PAC-A4-en-EN1.pdf">http://download.bitdefender.com/resources/files/News/CaseStudies/study/115/Bitdefender-Whitepaper-PAC-A4-en-EN1.pdf</a>

## HummingBad

This group created a malware that takes over Android devices and generates \$300,000 per month in fraudulent ad revenue. The group effectively controls an arsenal of over 85 million mobile devices around the world. With the potential to sell access to these devices to the highest bidder

*Table 1614. Table References*

Links
<a href="http://blog.checkpoint.com/wp-content/uploads/2016/07/HummingBad-Research-report_FINAL-62916.pdf">http://blog.checkpoint.com/wp-content/uploads/2016/07/HummingBad-Research-report_FINAL-62916.pdf</a>

## Dropping Elephant

Dropping Elephant (also known as “Chinastrats” and “Patchwork”) is a relatively new threat actor that is targeting a variety of high profile diplomatic and economic targets using a custom set of attack tools. Its victims are all involved with China’s foreign relations in some way, and are generally caught through spear-phishing or watering hole attacks.

Dropping Elephant is also known as:

- Chinastrats
- Patchwork
- Monsoon
- Sarit

*Table 1615. Table References*

Links
<a href="https://securelist.com/blog/research/75328/the-dropping-elephant-actor/">https://securelist.com/blog/research/75328/the-dropping-elephant-actor/</a>
<a href="http://www.symantec.com/connect/blogs/patchwork-cyberespionage-group-expands-targets-governments-wide-range-industries">http://www.symantec.com/connect/blogs/patchwork-cyberespionage-group-expands-targets-governments-wide-range-industries</a>

## Operation Transparent Tribe

Proofpoint researchers recently uncovered evidence of an advanced persistent threat (APT) against

Indian diplomatic and military resources. Our investigation began with malicious emails sent to Indian embassies in Saudi Arabia and Kazakstan but turned up connections to watering hole sites focused on Indian military personnel and designed to drop a remote access Trojan (RAT) with a variety of data exfiltration functions.

Table 1616. Table References

Links
<a href="https://www.proofpoint.com/sites/default/files/proofpoint-operation-transparent-tribe-threat-insight-en.pdf">https://www.proofpoint.com/sites/default/files/proofpoint-operation-transparent-tribe-threat-insight-en.pdf</a>

## Scarlet Mimic

Scarlet Mimic is a threat group that has targeted minority rights activists. This group has not been directly linked to a government source, but the group's motivations appear to overlap with those of the Chinese government. While there is some overlap between IP addresses used by Scarlet Mimic and Putter Panda, it has not been concluded that the groups are the same.

Table 1617. Table References

Links
<a href="https://attack.mitre.org/wiki/Groups">https://attack.mitre.org/wiki/Groups</a>
<a href="http://researchcenter.paloaltonetworks.com/2016/01/scarlet-mimic-years-long-espionage-targets-minority-activists/">http://researchcenter.paloaltonetworks.com/2016/01/scarlet-mimic-years-long-espionage-targets-minority-activists/</a>

## Poseidon Group

Poseidon Group is a Portuguese-speaking threat group that has been active since at least 2005. The group has a history of using information exfiltrated from victims to blackmail victim companies into contracting the Poseidon Group as a security firm.

Table 1618. Table References

Links
<a href="https://securelist.com/blog/research/73673/poseidon-group-a-targeted-attack-boutique-specializing-in-global-cyber-espionage/">https://securelist.com/blog/research/73673/poseidon-group-a-targeted-attack-boutique-specializing-in-global-cyber-espionage/</a>
<a href="https://attack.mitre.org/wiki/Groups">https://attack.mitre.org/wiki/Groups</a>

## DragonOK

Threat group that has targeted Japanese organizations with phishing emails. Due to overlapping TTPs, including similar custom tools, DragonOK is thought to have a direct or indirect relationship with the threat group Moafee. 2223 It is known to use a variety of malware, including Sysget>HelloBridge, PlugX, PoisonIvy, FormerFirstRat, NFlog, and NewCT.

DragonOK is also known as:

- Moafee

Table 1619. Table References

Links
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/wp-operation-quantum-entanglement.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/wp-operation-quantum-entanglement.pdf</a>
<a href="https://attack.mitre.org/wiki/Groups">https://attack.mitre.org/wiki/Groups</a>

## Threat Group-3390

Chinese threat group that has extensively used strategic Web compromises to target victims.

Threat Group-3390 is also known as:

- TG-3390
- Emissary Panda

Table 1620. Table References

Links
<a href="http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/">http://www.secureworks.com/cyber-threat-intelligence/threats/threat-group-3390-targets-organizations-for-cyberespionage/</a>
<a href="https://attack.mitre.org">https://attack.mitre.org</a>

## ProjectSauron

ProjectSauron is the name for a top level modular cyber-espionage platform, designed to enable and manage long-term campaigns through stealthy survival mechanisms coupled with multiple exfiltration methods. Technical details show how attackers learned from other extremely advanced actors in order to avoid repeating their mistakes. As such, all artifacts are customized per given target, reducing their value as indicators of compromise for any other victim. Usually APT campaigns have a geographical nexus, aimed at extracting information within a specific region or from a given industry. That usually results in several infections in countries within that region, or in the targeted industry around the world. Interestingly, ProjectSauron seems to be dedicated to just a couple of countries, focused on collecting high value intelligence by compromising almost all key entities it could possibly reach within the target area. The name, ProjectSauron reflects the fact that the code authors refer to 'Sauron' in the Lua scripts.

ProjectSauron is also known as:

- Strider
- Sauron

Table 1621. Table References

Links
<a href="https://securelist.com/analysis/publications/75533/faq-the-projectsauron-apt/">https://securelist.com/analysis/publications/75533/faq-the-projectsauron-apt/</a>



## APT 30

APT 30 is a threat group suspected to be associated with the Chinese government. While Naikon shares some characteristics with APT30, the two groups do not appear to be exact matches.

APT 30 is also known as:

- APT30

*Table 1622. Table References*

Links
<a href="https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf">https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf</a>
<a href="https://attack.mitre.org/wiki/Group/G0013">https://attack.mitre.org/wiki/Group/G0013</a>

## TA530

TA530, who we previously examined in relation to large-scale personalized phishing campaigns

## GCMAN

GCMAN is a threat group that focuses on targeting banks for the purpose of transferring money to e-currency services.

*Table 1623. Table References*

Links
<a href="https://securelist.com/blog/research/73638/apt-style-bank-robberies-increase-with-metel-gcman-and-carbanak-2-0-attacks/">https://securelist.com/blog/research/73638/apt-style-bank-robberies-increase-with-metel-gcman-and-carbanak-2-0-attacks/</a>

## Suckfly

Suckfly is a China-based threat group that has been active since at least 2014

*Table 1624. Table References*

Links
<a href="http://www.symantec.com/connect/blogs/suckfly-revealing-secret-life-your-code-signing-certificates">http://www.symantec.com/connect/blogs/suckfly-revealing-secret-life-your-code-signing-certificates</a>

## FIN6

FIN is a group targeting financial assets including assets able to do financial transaction including PoS.

*Table 1625. Table References*

Links
-------

## Libyan Scorpions

Libyan Scorpions is a malware operation in use since September 2015 and operated by a politically motivated group whose main objective is intelligence gathering, spying on influentials and political figures and operate an espionage campaign within Libya.

## TeamXRat

TeamXRat is also known as:

- CorporacaoXRat
- CorporationXRat

*Table 1626. Table References*

Links

<https://securelist.com/blog/research/76153/teamxrat-brazilian-cybercrime-meets-ransomware/>

## OilRig

Iranian threat agent OilRig has been targeting multiple organisations in Israel and other countries in the Middle East since the end of 2015.

*Table 1627. Table References*

Links

<http://researchcenter.paloaltonetworks.com/2016/05/the-oilrig-campaign-attacks-on-saudi-arabian-organizations-deliver-helminth-backdoor/>

## Volatile Cedar

Beginning in late 2012, a carefully orchestrated attack campaign we call Volatile Cedar has been targeting individuals, companies and institutions worldwide. This campaign, led by a persistent attacker group, has successfully penetrated a large number of targets using various attack techniques, and specifically, a custom-made malware implant codenamed Explosive .

*Table 1628. Table References*

Links

<https://www.checkpoint.com/downloads/volatile-cedar-technical-report.pdf>

## Malware reusers

Threat Group conducting cyber espionage while re-using tools from other teams; like those of Hacking Team, and vmprotect to obfuscate.

Malware reusers is also known as:

- Reuse team
- Dancing Salome

## TERBIUM

Microsoft Threat Intelligence identified similarities between this recent attack and previous 2012 attacks against tens of thousands of computers belonging to organizations in the energy sector. Microsoft Threat Intelligence refers to the activity group behind these attacks as TERBIUM, following our internal practice of assigning rogue actors chemical element names.

*Table 1629. Table References*

Links
<a href="https://blogs.technet.microsoft.com/mmcp/2016/12/09/windows-10-protection-detection-and-response-against-recent-attacks/">https://blogs.technet.microsoft.com/mmcp/2016/12/09/windows-10-protection-detection-and-response-against-recent-attacks/</a>

## Molerats

In October 2012, malware attacks against Israeli government targets grabbed media attention as officials temporarily cut off Internet access for its entire police force and banned the use of USB memory sticks. Security researchers subsequently linked these attacks to a broader, yearlong campaign that targeted not just Israelis but Palestinians as well. and as discovered later, even the U.S. and UK governments. Further research revealed a connection between these attacks and members of the so-called “Gaza Hackers Team.” We refer to this campaign as “Molerats.”

Molerats is also known as:

- Gaza Hackers Team
- Operation Molerats
- Extreme Jackal
- Moonlight

*Table 1630. Table References*

Links
<a href="https://www.fireeye.com/blog/threat-research/2013/08/operation-molerats-middle-east-cyber-attacks-using-poison-ivy.html">https://www.fireeye.com/blog/threat-research/2013/08/operation-molerats-middle-east-cyber-attacks-using-poison-ivy.html</a>
<a href="http://blog.vectranetworks.com/blog/moonlight-middle-east-targeted-attacks">http://blog.vectranetworks.com/blog/moonlight-middle-east-targeted-attacks</a>

## PROMETHIUM

PROMETHIUM is an activity group that has been active as early as 2012. The group primarily uses Truvasys, a first-stage malware that has been in circulation for several years. Truvasys has been involved in several attack campaigns, where it has masqueraded as one of server common computer utilities, including WinUtils, TrueCrypt, WinRAR, or SanDisk. In each of the campaigns,

Truvasys malware evolved with additional features—this shows a close relationship between the activity groups behind the campaigns and the developers of the malware.

PROMETHIUM is also known as:

- StrongPity

*Table 1631. Table References*

Links
<a href="https://blogs.technet.microsoft.com/mmpc/2016/12/14/twin-zero-day-attacks-promethium-and-neodymium-target-individuals-in-europe/">https://blogs.technet.microsoft.com/mmpc/2016/12/14/twin-zero-day-attacks-promethium-and-neodymium-target-individuals-in-europe/</a>
<a href="https://www.virusbulletin.com/conference/vb2016/abstracts/last-minute-paper-strongpity-waterhole-attacks-targeting-italian-and-belgian-encryption-users">https://www.virusbulletin.com/conference/vb2016/abstracts/last-minute-paper-strongpity-waterhole-attacks-targeting-italian-and-belgian-encryption-users</a>

## NEODYMIUM

NEODYMIUM is an activity group that is known to use a backdoor malware detected by Microsoft as Wingbird. This backdoor’s characteristics closely match FinFisher, a government-grade commercial surveillance package. Data about Wingbird activity indicate that it is typically used to attack individual computers instead of networks.

*Table 1632. Table References*

Links
<a href="https://blogs.technet.microsoft.com/mmpc/2016/12/14/twin-zero-day-attacks-promethium-and-neodymium-target-individuals-in-europe/">https://blogs.technet.microsoft.com/mmpc/2016/12/14/twin-zero-day-attacks-promethium-and-neodymium-target-individuals-in-europe/</a>

## Packrat

A threat group that has been active for at least seven years has used malware, phishing and disinformation tactics to target activists, journalists, politicians and public figures in various Latin American countries. The threat actor, dubbed Packrat based on its preference for remote access Trojans (RATs) and because it has used the same infrastructure for several years, has been analyzed by Citizen Lab researchers John Scott-Railton, Morgan Marquis-Boire, and Claudio Guarnieri, and Cyphort researcher Marion Marschalek, best known for her extensive analysis of state-sponsored threats.

*Table 1633. Table References*

Links
<a href="https://citizenlab.org/2015/12/packrat-report/">https://citizenlab.org/2015/12/packrat-report/</a>

## Cadelle

Symantec telemetry identified Cadelle and Chafer activity dating from as far back as July 2014, however, it’s likely that activity began well before this date. Command-and-control (C&C) registrant information points to activity possibly as early as 2011, while executable compilation times suggest early 2012. Their attacks continue to the present day. Symantec estimates that each team is made up

of between 5 and 10 people.

*Table 1634. Table References*

Links
<a href="https://www.symantec.com/connect/blogs/iran-based-attackers-use-back-door-threats-spy-middle-eastern-targets">https://www.symantec.com/connect/blogs/iran-based-attackers-use-back-door-threats-spy-middle-eastern-targets</a>

## Chafer

Symantec telemetry identified Cadelle and Chafer activity dating from as far back as July 2014, however, it's likely that activity began well before this date. Command-and-control (C&C) registrant information points to activity possibly as early as 2011, while executable compilation times suggest early 2012. Their attacks continue to the present day. Symantec estimates that each team is made up of between 5 and 10 people.

*Table 1635. Table References*

Links
<a href="https://www.symantec.com/connect/blogs/iran-based-attackers-use-back-door-threats-spy-middle-eastern-targets">https://www.symantec.com/connect/blogs/iran-based-attackers-use-back-door-threats-spy-middle-eastern-targets</a>

## PassCV

The PassCV group continues to be one of the most successful and active threat groups that leverage a wide array of stolen Authenticode-signing certificates. Snorre Fagerland of Blue Coat Systems first coined the term PassCV in a blog post. His post provides a good introduction to the group and covers some of the older infrastructure, stolen code-signing certificate reuse, and other connections associated with the PassCV malware. There are several clues alluding to the possibility that multiple groups may be utilizing the same stolen signing certificates, but at this time SPEAR believes the current attacks are more likely being perpetrated by a single group employing multiple publicly available Remote Administration Tools (RATs). The PassCV group has been operating with continued success and has already started to expand their malware repertoire into different off-the-shelf RATs and custom code. SPEAR identified eighteen previously undisclosed stolen Authenticode certificates. These certificates were originally issued to companies and individuals scattered across China, Taiwan, Korea, Europe, the United States and Russia. In this post we expand the usage of the term 'PassCV' to encompass the malware mentioned in the Blue Coat Systems report, as well as the APT group behind the larger C2 infrastructure and stolen Authenticode certificates. We'd like to share some of our findings as they pertain to the stolen certificates, command and control infrastructure, and some of the newer custom RATs they've begun development on.

*Table 1636. Table References*

Links
<a href="https://blog.cylance.com/digitally-signed-malware-targeting-gaming-companies">https://blog.cylance.com/digitally-signed-malware-targeting-gaming-companies</a>

## Sath-1 Müdafaa

A Turkish hacking group, Sath-1 Müdafaa, is encouraging individuals to join its DDoS-for-Points platform that features points and prizes for carrying out distributed denial-of-service (DDoS) attacks against a list of predetermined targets. Their DDoS tool also contains a backdoor to hack the hackers. So the overarching motivation and allegiance of the group is not entirely clear.

## Aslan Neferler Tim

Turkish nationalist hacktivist group that has been active for roughly one year. According to Domaintools, the group's site has been registered since December 2015, with an active Twitter account since January 2016. The group carries out distributed denial-of-service (DDoS) attacks and defacements against the sites of news organizations and governments perceived to be critical of Turkey's policies or leadership, and purports to act in defense of Islam

Aslan Neferler Tim is also known as:

- Lion Soldiers Team
- Phantom Turk

## Ayyıldız Tim

Ayyıldız (Crescent and Star) Tim is a nationalist hacking group founded in 2002. It performs defacements and DDoS attacks against the websites of governments that it considers to be repressing Muslim minorities or engaged in Islamophobic policies.

Ayyıldız Tim is also known as:

- Crescent and Star

## TurkHackTeam

Founded in 2004, Turkhackteam is one of Turkey's oldest and most high-profile hacking collectives. According to a list compiled on Turkhackteam's forum, the group has carried out almost 30 highly publicized hacking campaigns targeting foreign government and commercial websites, including websites of international corporations.

TurkHackTeam is also known as:

- Turk Hack Team

## Equation Group

The Equation Group is a highly sophisticated threat actor described by its discoverers at Kaspersky Labs as one of the most sophisticated cyber attack groups in the world, operating alongside but always from a position of superiority with the creators of Stuxnet and Flame

Table 1637. Table References

Links

[https://en.wikipedia.org/wiki/Equation\\_Group](https://en.wikipedia.org/wiki/Equation_Group)

## Greenbug

Greenbug was discovered targeting a range of organizations in the Middle East including companies in the aviation, energy, government, investment, and education sectors.

Table 1638. Table References

Links

<https://www.symantec.com/connect/blogs/greenbug-cyberespionage-group-targeting-middle-east-possible-links-shamoon>

## Gamaredon Group

Unit 42 threat researchers have recently observed a threat group distributing new, custom developed malware. We have labelled this threat group the Gamaredon Group and our research shows that the Gamaredon Group has been active since at least 2013. In the past, the Gamaredon Group has relied heavily on off-the-shelf tools. Our new research shows the Gamaredon Group have made a shift to custom-developed malware. We believe this shift indicates the Gamaredon Group have improved their technical capabilities.

Table 1639. Table References

Links

<http://researchcenter.paloaltonetworks.com/2017/02/unit-42-title-gamaredon-group-toolset-evolution>

## Hammer Panda

Hammer Panda is a group of suspected Chinese origin targeting organisations in Russia.

Hammer Panda is also known as:

- Zhenbao

Table 1640. Table References

Links

<http://www.darkreading.com/endpoint/chinese-cyberspies-pivot-to-russia-in-wake-of-obama-xi-pact/d/d-id/1324242>

## Infy

Infy is a group of suspected Iranian origin.

Infy is also known as:

- Operation Mermaid

*Table 1641. Table References*

Links

<https://www.blackhat.com/docs/us-16/materials/us-16-Guarnieri-Iran-And-The-Soft-War-For-Internet-Dominance-wp.pdf>

## Sima

Sima is a group of suspected Iranian origin targeting Iranians in diaspora.

*Table 1642. Table References*

Links

<https://www.blackhat.com/docs/us-16/materials/us-16-Guarnieri-Iran-And-The-Soft-War-For-Internet-Dominance-wp.pdf>

## Blue Termite

Blue Termite is a group of suspected Chinese origin active in Japan.

Blue Termite is also known as:

- Cloudy Omega

*Table 1643. Table References*

Links

<https://securelist.com/blog/research/71876/new-activity-of-the-blue-termite-apt/>

## Groundbait

Groundbait is a group targeting anti-government separatists in the self-declared Donetsk and Luhansk People's Republics.

*Table 1644. Table References*

Links

<http://www.welivesecurity.com/2016/05/18/groundbait>

## Longhorn

Longhorn has been active since at least 2011. It has used a range of back door Trojans in addition to zero-day vulnerabilities to compromise its targets. Longhorn has infiltrated governments and internationally operating organizations, in addition to targets in the financial, telecoms, energy, aerospace, information technology, education, and natural resources sectors. All of the



organizations targeted would be of interest to a nation-state attacker. Longhorn has infected 40 targets in at least 16 countries across the Middle East, Europe, Asia, and Africa. On one occasion a computer in the United States was compromised but, following infection, an uninstaller was launched within hours, which may indicate this victim was infected unintentionally.

*Table 1645. Table References*

Links
<a href="https://www.symantec.com/connect/blogs/longhorn-tools-used-cyberespionage-group-linked-vault-7">https://www.symantec.com/connect/blogs/longhorn-tools-used-cyberespionage-group-linked-vault-7</a>

## Callisto

The Callisto Group is an advanced threat actor whose known targets include military personnel, government officials, think tanks, and journalists in Europe and the South Caucasus. Their primary interest appears to be gathering intelligence related to foreign and security policy in the Eastern Europe and South Caucasus regions.

*Table 1646. Table References*

Links
<a href="https://www.f-secure.com/documents/996508/1030745/callisto-group">https://www.f-secure.com/documents/996508/1030745/callisto-group</a>

## APT32

Cyber espionage actors, now designated by FireEye as APT32 (OceanLotus Group), are carrying out intrusions into private sector companies across multiple industries and have also targeted foreign governments, dissidents, and journalists. FireEye assesses that APT32 leverages a unique suite of fully-featured malware, in conjunction with commercially-available tools, to conduct targeted operations that are aligned with Vietnamese state interests.

APT32 is also known as:

- OceanLotus Group
- Ocean Lotus
- APT-32
- APT 32

*Table 1647. Table References*

Links
<a href="https://www.fireeye.com/blog/threat-research/2017/05/cyber-espionage-apt32.html">https://www.fireeye.com/blog/threat-research/2017/05/cyber-espionage-apt32.html</a>

## SilverTerrier

As these tools rise and fall in popularity (and more importantly, as detection rates by antivirus vendors improve), SilverTerrier actors have consistently adopted new malware families and shifted to the latest packing tools available.

Table 1648. Table References

Links
<a href="https://www.paloaltonetworks.com/content/dam/pan/en_US/assets/pdf/reports/Unit_42/silverterrier-next-evolution-in-nigerian-cybercrime.pdf">https://www.paloaltonetworks.com/content/dam/pan/en_US/assets/pdf/reports/Unit_42/silverterrier-next-evolution-in-nigerian-cybercrime.pdf</a>

## WildNeutron

A corporate espionage group has compromised a string of major corporations over the past three years in order to steal confidential information and intellectual property. The gang, which Symantec calls Butterfly, is not-state sponsored, rather financially motivated. It has attacked multi-billion dollar companies operating in the internet, IT software, pharmaceutical, and commodities sectors. Twitter, Facebook, Apple, and Microsoft are among the companies who have publicly acknowledged attacks.

WildNeutron is also known as:

- Butterfly
- Morpho
- Sphinx Moth

Table 1649. Table References

Links
<a href="https://www.symantec.com/connect/blogs/butterfly-profiting-high-level-corporate-attacks">https://www.symantec.com/connect/blogs/butterfly-profiting-high-level-corporate-attacks</a>
<a href="https://securelist.com/71275/wild-neutron-economic-espionage-threat-actor-returns-with-new-tricks/">https://securelist.com/71275/wild-neutron-economic-espionage-threat-actor-returns-with-new-tricks/</a>
<a href="https://research.kudelskisecurity.com/2015/11/05/sphinx-moth-expanding-our-knowledge-of-the-wild-neutron-morpho-apt/">https://research.kudelskisecurity.com/2015/11/05/sphinx-moth-expanding-our-knowledge-of-the-wild-neutron-morpho-apt/</a>

## PLATINUM

PLATINUM has been targeting its victims since at least as early as 2009, and may have been active for several years prior. Its activities are distinctly different not only from those typically seen in untargeted attacks, but from many targeted attacks as well. A large share of targeted attacks can be characterized as opportunistic: the activity group changes its target profiles and attack geographies based on geopolitical seasons, and may attack institutions all over the world. Like many such groups, PLATINUM seeks to steal sensitive intellectual property related to government interests, but its range of preferred targets is consistently limited to specific governmental organizations, defense institutes, intelligence agencies, diplomatic institutions, and telecommunication providers in South and Southeast Asia. The group's persistent use of spear phishing tactics (phishing attempts aimed at specific individuals) and access to previously undiscovered zero-day exploits have made it a highly resilient threat.

Table 1650. Table References

Links
-------

<http://download.microsoft.com/download/2/2/5/225BFE3E-E1DE-4F5B-A77B-71200928D209/Platinum%20feature%20article%20-%20Targeted%20attacks%20in%20South%20and%20Southeast%20Asia%20April%202016.pdf>  
<https://blogs.technet.microsoft.com/mmpc/2016/04/26/digging-deep-for-platinum/>

## ELECTRUM

Dragos, Inc. tracks the adversary group behind CRASHOVERRIDE as ELECTRUM and assesses with high confidence through confidential sources that ELECTRUM has direct ties to the Sandworm team. Our intelligence ICS WorldView customers have received a comprehensive report and this industry report will not get into sensitive technical details but instead focus on information needed for defense and impact awareness.

*Table 1651. Table References*

Links
<a href="https://dragos.com/blog/crashoverride/CrashOverride-01.pdf">https://dragos.com/blog/crashoverride/CrashOverride-01.pdf</a>
<a href="https://www.welivesecurity.com/wp-content/uploads/2017/06/Win32_Industroyer.pdf">https://www.welivesecurity.com/wp-content/uploads/2017/06/Win32_Industroyer.pdf</a>

## FIN8

FIN8 is a financially motivated group targeting the retail, hospitality and entertainment industries. The actor had previously conducted several tailored spearphishing campaigns using the downloader PUNCHBUGGY and POS malware PUNCHTRACK.

*Table 1652. Table References*

Links
<a href="https://www.fireeye.com/blog/threat-research/2016/05/windows-zero-day-payment-cards.html">https://www.fireeye.com/blog/threat-research/2016/05/windows-zero-day-payment-cards.html</a>
<a href="https://www2.fireeye.com/WBNR-Know-Your-Enemy-UNC622-Spear-Phishing.html">https://www2.fireeye.com/WBNR-Know-Your-Enemy-UNC622-Spear-Phishing.html</a>
<a href="https://www.root9b.com/sites/default/files/whitepapers/PoS%20Malware%20ShellTea%20PoSlurp.pdf">https://www.root9b.com/sites/default/files/whitepapers/PoS%20Malware%20ShellTea%20PoSlurp.pdf</a>
<a href="http://files.shareholder.com/downloads/AMDA-254Q5F/0x0x938351/665BA6A3-9573-486C-B96F-80FA35759E8C/FEYE_rpt-mtrends-2017_FINAL2.pdf">http://files.shareholder.com/downloads/AMDA-254Q5F/0x0x938351/665BA6A3-9573-486C-B96F-80FA35759E8C/FEYE_rpt-mtrends-2017_FINAL2.pdf</a>

## El Machete

El Machete is one of these threats that was first publicly disclosed and named by Kaspersky here. We've found that this group has continued to operate successfully, predominantly in Latin America, since 2014. All attackers simply moved to new C2 infrastructure, based largely around dynamic DNS domains, in addition to making minimal changes to the malware in order to evade signature-based detection.

*Table 1653. Table References*

Links
<a href="https://securelist.com/blog/research/66108/el-machete/">https://securelist.com/blog/research/66108/el-machete/</a>

## Cobalt

A criminal group dubbed Cobalt is behind synchronized ATM heists that saw machines across Europe, CIS countries (including Russia), and Malaysia being raided simultaneously, in the span of a few hours. The group has been active since June 2016, and their latest attacks happened in July and August.

Cobalt is also known as:

- Cobalt group
- Cobalt gang

*Table 1654. Table References*

Links

<https://www.helpnetsecurity.com/2016/11/22/cobalt-hackers-synchronized-atm-heists/>

## Tool

threat-actor-tools is an enumeration of tools used by adversaries. The list includes malware but also common software regularly used by the adversaries..



Tool is a cluster galaxy available in JSON format at [this location](#) The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

### authors

Alexandre Dulaunoy - Florian Roth - Timo Steffens - Christophe Vandeplass

## Tinba

Banking Malware

Tinba is also known as:

- Hunter
- Zusy
- TinyBanker

*Table 1655. Table References*

Links

<https://thehackernews.com/search/label/Zusy%20Malware>

<http://blog.trendmicro.com/trendlabs-security-intelligence/the-tinbatinybanker-malware/>

# PlugX

Malware

PlugX is also known as:

- Backdoor.FSZO-5117
- Trojan.Heur.JP.juW@ayZZvMb
- Trojan.Inject1.6386
- Korplug
- Agent.dhwhf

*Table 1656. Table References*

Links
<a href="https://www.trendmicro.com/vinfo/us/threat-encyclopedia/web-attack/112/pulling-the-plug-on-plugx">https://www.trendmicro.com/vinfo/us/threat-encyclopedia/web-attack/112/pulling-the-plug-on-plugx</a>

# MSUpdater

Trojan (RAT) linked to current targeted attacks and others dating back to at least early 2009

*Table 1657. Table References*

Links
<a href="https://www.zscaler.com/pdf/whitepapers/msupdater_trojan_whitepaper.pdf">https://www.zscaler.com/pdf/whitepapers/msupdater_trojan_whitepaper.pdf</a>

# Lazagne

A password sthealing tool regularly used by attackers

*Table 1658. Table References*

Links
<a href="https://github.com/AlessandroZ/LaZagne">https://github.com/AlessandroZ/LaZagne</a>

# Poison Ivy

Poison Ivy is a RAT which was freely available and first released in 2005.

Poison Ivy is also known as:

- Backdoor.Win32.PoisonIvy
- Gen:Trojan.Heur.PT

Table 1659. Table References

Links
<a href="https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-poison-ivy.pdf">https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/rpt-poison-ivy.pdf</a>
<a href="https://www.f-secure.com/v-descs/backdoor_w32_poisonivy.shtml">https://www.f-secure.com/v-descs/backdoor_w32_poisonivy.shtml</a>

## SPIVY

In March 2016, Unit 42 observed this new Poison Ivy variant we've named SPIVY being deployed via weaponized documents leveraging CVE-2015-2545.

Table 1660. Table References

Links
<a href="http://researchcenter.paloaltonetworks.com/2016/04/unit42-new-poison-ivy-rat-variant-targets-hong-kong-pro-democracy-activists/">http://researchcenter.paloaltonetworks.com/2016/04/unit42-new-poison-ivy-rat-variant-targets-hong-kong-pro-democracy-activists/</a>

## Torn RAT

Torn RAT is also known as:

- Anchor Panda

Table 1661. Table References

Links
<a href="https://www.crowdstrike.com/blog/whois-anchor-panda/">https://www.crowdstrike.com/blog/whois-anchor-panda/</a>

## OzoneRAT

OzoneRAT is also known as:

- Ozone RAT
- ozonercp

Table 1662. Table References

Links
<a href="https://blog.fortinet.com/2016/08/29/german-speakers-targeted-by-spam-leading-to-ozone-rat">https://blog.fortinet.com/2016/08/29/german-speakers-targeted-by-spam-leading-to-ozone-rat</a>

## ZeGhost

ZeGhots is a RAT which was freely available and first released in 2014.

ZeGhost is also known as:

- BackDoor-FBZT!52D84425CDF2

- Trojan.Win32.Staser.ytq
- Win32/Zegost.BW

Table 1663. Table References

#### Links

<https://www.microsoft.com/security/portal/threat/encyclopedia/entry.aspx?Name=Backdoor%3aWin32%2fZegost.BW>

## Elise Backdoor

Trojan (RAT) linked to current targeted attacks and others dating back to at least early 2009

Elise Backdoor is also known as:

- Elise

Table 1664. Table References

#### Links

<http://thehackernews.com/2015/08/elise-malware-hacking.html>

## Trojan.Laziok

A new information stealer, Trojan.Laziok, acts as a reconnaissance tool allowing attackers to gather information and tailor their attack methods for each compromised computer.

Trojan.Laziok is also known as:

- Laziok

Table 1665. Table References

#### Links

<http://www.symantec.com/connect/blogs/new-reconnaissance-threat-trojanlaziok-targets-energy-sector>

## Slempo

Android-based malware

Slempo is also known as:

- GM-Bot
- SlemBunk
- Bankosy
- Acecard

Table 1666. Table References

Links
<a href="https://securityintelligence.com/android-malware-about-to-get-worse-gm-bot-source-code-leaked/">https://securityintelligence.com/android-malware-about-to-get-worse-gm-bot-source-code-leaked/</a>

## PWOBot

We have discovered a malware family named ‘PWOBot’ that is fairly unique because it is written entirely in Python, and compiled via PyInstaller to generate a Microsoft Windows executable. The malware has been witnessed affecting a number of Europe-based organizations, particularly in Poland. Additionally, the malware is delivered via a popular Polish file-sharing web service.

PWOBot is also known as:

- PWOLauncher
- PWOHTTPD
- PWOKeyLogger
- PWOMiner
- PWOPyExec
- PWOQuery

Table 1667. Table References

Links
<a href="http://researchcenter.paloaltonetworks.com/2016/04/unit42-python-based-pwobot-targets-european-organizations/">http://researchcenter.paloaltonetworks.com/2016/04/unit42-python-based-pwobot-targets-european-organizations/</a>

## Lost Door RAT

We recently came across a cyber attack that used a remote access Trojan (RAT) called Lost Door, a tool currently offered on social media sites. What also struck us the most about this RAT (detected as BKDR\_LODORAT.A) is how it abuses the Port Forward feature in routers.

Lost Door RAT is also known as:

- LostDoor RAT
- BKDR\_LODORAT

Table 1668. Table References

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/lost-door-rat-accessible-customizable-attack-tool/">http://blog.trendmicro.com/trendlabs-security-intelligence/lost-door-rat-accessible-customizable-attack-tool/</a>

## njRAT

njRAT is also known as:



- Bladabindi
- Jorik

Table 1669. Table References

Links
<a href="http://www.fidelisecurity.com/files/files/FTA_1009-njRAT_Uncovered_rev2.pdf">http://www.fidelisecurity.com/files/files/FTA_1009-njRAT_Uncovered_rev2.pdf</a>
<a href="https://github.com/kevthehermit/RATDecoders/blob/master/yaraRules/njRat.yar">https://github.com/kevthehermit/RATDecoders/blob/master/yaraRules/njRat.yar</a>

## NanoCoreRAT

NanoCoreRAT is also known as:

- NanoCore
- Nancrat
- Zurten
- Atros2.CKPN

Table 1670. Table References

Links
<a href="http://www.symantec.com/connect/blogs/nanocore-another-rat-tries-make-it-out-gutter">http://www.symantec.com/connect/blogs/nanocore-another-rat-tries-make-it-out-gutter</a>
<a href="https://nanocore.io/">https://nanocore.io/</a>

## Sakula

Sakula is also known as:

- Sakurel

Table 1671. Table References

Links
<a href="https://www.secureworks.com/research/sakula-malware-family">https://www.secureworks.com/research/sakula-malware-family</a>

## Hi-ZOR

Table 1672. Table References

Links
<a href="http://www.threatgeek.com/2016/01/introducing-hi-zor-rat.html">http://www.threatgeek.com/2016/01/introducing-hi-zor-rat.html</a>

## Derusbi

Derusbi is also known as:

- TROJ\_DLLSERV.BE

Table 1673. Table References

Links
<a href="http://www.novetta.com/wp-content/uploads/2014/11/Derusbi.pdf">http://www.novetta.com/wp-content/uploads/2014/11/Derusbi.pdf</a>
<a href="https://www.rsaconference.com/writable/presentations/file_upload/hta-w02-dissecting-derusbi.pdf">https://www.rsaconference.com/writable/presentations/file_upload/hta-w02-dissecting-derusbi.pdf</a>

## EvilGrab

EvilGrab is also known as:

- BKDR\_HGDER
- BKDR\_EVILOGE
- BKDR\_NVICM
- Wmonder

Table 1674. Table References

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/evilgrab-malware-family-used-in-targeted-attacks-in-asia/">http://blog.trendmicro.com/trendlabs-security-intelligence/evilgrab-malware-family-used-in-targeted-attacks-in-asia/</a>
<a href="http://researchcenter.paloaltonetworks.com/2015/06/evilgrab-delivered-by-watering-hole-attack-on-president-of-myanmars-website/">http://researchcenter.paloaltonetworks.com/2015/06/evilgrab-delivered-by-watering-hole-attack-on-president-of-myanmars-website/</a>

## Trojan.Naid

Trojan.Naid is also known as:

- Naid
- Mdmbot.E
- AGENT.GUNZ
- AGENT.AQUP.DROPPER
- AGENT.BMZA
- MCRAT.A
- AGENT.ABQMR

Table 1675. Table References

Links
<a href="https://www.symantec.com/connect/blogs/cve-2012-1875-exploited-wild-part-1-trojannaid">https://www.symantec.com/connect/blogs/cve-2012-1875-exploited-wild-part-1-trojannaid</a>
<a href="http://telussecuritylabs.com/threats/show/TSL20120614-05">http://telussecuritylabs.com/threats/show/TSL20120614-05</a>

## Moudoor

Backdoor.Moudoor, a customized version of Gh0st RAT

Moudoor is also known as:

- SCAR
- KillProc.14145

Table 1676. Table References

Links
<a href="http://www.darkreading.com/attacks-breaches/elite-chinese-cyberspy-group-behind-bit9-hack/d/d-id/1140495">http://www.darkreading.com/attacks-breaches/elite-chinese-cyberspy-group-behind-bit9-hack/d/d-id/1140495</a>
<a href="https://securityledger.com/2013/09/apt-for-hire-symantec-outs-hidden-lynx-hacking-crew/">https://securityledger.com/2013/09/apt-for-hire-symantec-outs-hidden-lynx-hacking-crew/</a>

## NetTraveler

APT that infected hundreds of high profile victims in more than 40 countries. Known targets of NetTraveler include Tibetan/Uyghur activists, oil industry companies, scientific research centers and institutes, universities, private companies, governments and governmental institutions, embassies and military contractors.

NetTraveler is also known as:

- TravNet
- Netfile

Table 1677. Table References

Links
<a href="https://securelist.com/blog/incidents/57455/nettraveler-is-back-the-red-star-apt-returns-with-new-tricks/">https://securelist.com/blog/incidents/57455/nettraveler-is-back-the-red-star-apt-returns-with-new-tricks/</a>

## Winnti

APT used As part of Operation SMN, Novetta analyzed recent versions of the Winnti malware. The samples, compiled from mid- to late 2014, exhibited minimal functional changes over the previous generations Kaspersky reported in 2013.

Winnti is also known as:

- Etso
- SUQ
- Agent.ALQHI

Table 1678. Table References

Links
<a href="https://securelist.com/blog/incidents/57455/nettraveler-is-back-the-red-star-apt-returns-with-new-tricks/">https://securelist.com/blog/incidents/57455/nettraveler-is-back-the-red-star-apt-returns-with-new-tricks/</a>

<https://kasperskycontenthub.com/wp-content/uploads/sites/43/vlpdfs/winnti-more-than-just-a-game-130410.pdf>

## Mimikatz

Ease Credential stealh and replay, A little tool to play with Windows security.

Mimikatz is also known as:

- Mikatz

*Table 1679. Table References*

Links
<a href="https://github.com/gentilkiwi/mimikatz">https://github.com/gentilkiwi/mimikatz</a>
<a href="https://researchcenter.paloaltonetworks.com/2017/07/unit42-twoface-webshell-persistent-access-point-lateral-movement/">https://researchcenter.paloaltonetworks.com/2017/07/unit42-twoface-webshell-persistent-access-point-lateral-movement/</a>

## WEBC2

Backdoor attributed to APT1

*Table 1680. Table References*

Links
<a href="https://github.com/gnaegle/cse4990-practical3">https://github.com/gnaegle/cse4990-practical3</a>
<a href="https://www.securestate.com/blog/2013/02/20/apt-if-it-aint-broke">https://www.securestate.com/blog/2013/02/20/apt-if-it-aint-broke</a>

## Pirpi

Symantec has observed Buckeye activity dating back to 2009, involving attacks on various organizations in several regions. Buckeye used a remote access Trojan (Backdoor.Pirpi) in attacks against a US organization's network in 2009. The group delivered Backdoor.Pirpi through malicious attachments or links in convincing spear-phishing emails.

Pirpi is also known as:

- Badey
- EXL

*Table 1681. Table References*

Links
<a href="http://www.symantec.com/connect/blogs/buckeye-cyberespionage-group-shifts-gaze-us-hong-kong">http://www.symantec.com/connect/blogs/buckeye-cyberespionage-group-shifts-gaze-us-hong-kong</a>

# RARSTONE

RARSTONE is a Remote Access Tool (RAT) discovered early 2013 by TrendMicro, it's characterized by a great affinity with the other RAT know as Plug is and was used in April for phishing campaigns that followed the dramatic attack to the Boston Marathon.

Table 1682. Table References

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/bkdr_rarstone-new-rat-to-watch-out-for/">http://blog.trendmicro.com/trendlabs-security-intelligence/bkdr_rarstone-new-rat-to-watch-out-for/</a>

# Backspace

Backspace is a Backdoor that targets the Windows platform. This malware is reportedly associated with targeted attacks against Association of Southeast Asian Nations (ASEAN) members (APT30).

Backspace is also known as:

- Lecna

Table 1683. Table References

Links
<a href="https://www2.fireeye.com/WEB-2015RPTAPT30.html">https://www2.fireeye.com/WEB-2015RPTAPT30.html</a>
<a href="https://www.fireeye.com/content/dam/fireeye-www/current-threats/pdfs/rpt-southeast-asia-threat-landscape.pdf">https://www.fireeye.com/content/dam/fireeye-www/current-threats/pdfs/rpt-southeast-asia-threat-landscape.pdf</a>

# XSControl

Backdoor user by he Naikon APT group

Table 1684. Table References

Links
<a href="https://securelist.com/analysis/publications/69953/the-naikon-apt/">https://securelist.com/analysis/publications/69953/the-naikon-apt/</a>
<a href="https://kasperskycontenthub.com/securelist/files/2015/05/TheNaikonAPT-MsnMM.pdf">https://kasperskycontenthub.com/securelist/files/2015/05/TheNaikonAPT-MsnMM.pdf</a>

# Neteagle

NETEAGLE is a backdoor developed by APT30 with compile dates as early as 2008. It has two main variants known as Scout and Norton.

Neteagle is also known as:

- scout
- norton

Table 1685. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0034">https://attack.mitre.org/wiki/Software/S0034</a>
<a href="https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf">https://www2.fireeye.com/rs/fireeye/images/rpt-apt30.pdf</a>

## Agent.BTZ

In November 2014, the experts of the G DATA SecurityLabs published an article about ComRAT, the Agent.BTZ successor. We explained that this case is linked to the Uroburos rootkit.

Agent.BTZ is also known as:

- ComRat

*Table 1686. Table References*

Links
<a href="https://blog.gdatasoftware.com/2015/01/23927-evolution-of-sophisticated-spyware-from-agent-btz-to-comrat">https://blog.gdatasoftware.com/2015/01/23927-evolution-of-sophisticated-spyware-from-agent-btz-to-comrat</a>

## Heseber BOT

RAT bundle with standard VNC (to avoid/limit A/V detection).

## Agent.dne

## Wipbot

Waterbug is the name given to the actors who use the malware tools Trojan.Wipbot (also known as Tavidig and Epic Turla)

Wipbot is also known as:

- Tavidig
- Epic Turla
- WorldCupSec
- TadjMakhal

*Table 1687. Table References*

Links
<a href="https://securelist.com/analysis/publications/65545/the-epic-turla-operation/">https://securelist.com/analysis/publications/65545/the-epic-turla-operation/</a>
<a href="https://www.symantec.com/content/en/us/enterprise/media/security_response/whitepapers/waterbug-attack-group.pdf">https://www.symantec.com/content/en/us/enterprise/media/security_response/whitepapers/waterbug-attack-group.pdf</a>

# Turla

Family of related sophisticated backdoor software - Name comes from Microsoft detection signature – anagram of Ultra (Ultra3 was a name of the fake driver).

Turla is also known as:

- Snake
- Uroburos
- Urouros

*Table 1688. Table References*

Links
<a href="https://www.first.org/resources/papers/tbilisi2014/turla-operations_and_development.pdf">https://www.first.org/resources/papers/tbilisi2014/turla-operations_and_development.pdf</a>

# Winexe

## Dark Comet

RAT initially identified in 2011 and still actively used.

## Cadelspy

Cadelspy is also known as:

- WinSpy

## CMStar

*Table 1689. Table References*

Links
<a href="http://researchcenter.paloaltonetworks.com/2016/03/digital-quartermaster-scenario-demonstrated-in-attacks-against-the-mongolian-government/">http://researchcenter.paloaltonetworks.com/2016/03/digital-quartermaster-scenario-demonstrated-in-attacks-against-the-mongolian-government/</a>

## DHS2015

DHS2015 is also known as:

- iRAT

*Table 1690. Table References*

Links
<a href="https://securelist.com/files/2015/02/The-Desert-Falcons-targeted-attacks.pdf">https://securelist.com/files/2015/02/The-Desert-Falcons-targeted-attacks.pdf</a>

# Gh0st Rat

Gh0st Rat is a well-known Chinese remote access trojan which was originally made by C.Rufus Security Team several years ago.

Gh0st Rat is also known as:

- Gh0stRat, GhostRat

*Table 1691. Table References*

Links

<http://download01.norman.no/documents/ThemanyfacesofGh0stRat.pdf>

# Fakem RAT

Fakem RAT makes their network traffic look like well-known protocols (e.g. Messenger traffic, HTML pages).

Fakem RAT is also known as:

- FAKEM

*Table 1692. Table References*

Links

<http://www.trendmicro.com/cloud-content/us/pdfs/security-intelligence/white-papers/wp-fakem-rat.pdf>

# MFC Huner

MFC Huner is also known as:

- Hupigon
- BKDR\_HUPIGON

*Table 1693. Table References*

Links

<http://blog.trendmicro.com/trendlabs-security-intelligence/japan-us-defense-industries-among-targeted-entities-in-latest-attack/>

# Blackshades

Blackshades Remote Access Tool targets Microsoft Windows operating systems. Authors were arrested in 2012 and 2014.

*Table 1694. Table References*

Links



<https://www.justice.gov/usao-sdny/pr/manhattan-us-attorney-and-fbi-assistant-director-charge-announce-charges-connection>

<https://blog.malwarebytes.org/intelligence/2012/06/you-dirty-rat-part-2-blackshades-net/>

## CHOPSTICK

backdoor used by apt28

CHOPSTICK is also known as:

- webhp
- SPLM
- (.v2 fysbis)

*Table 1695. Table References*

Links

<https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf>

## EVILTOSS

backdoor used by apt28

EVILTOSS is also known as:

- Sedreco
- AZZY
- ADVSTORESHELL
- NETUI

*Table 1696. Table References*

Links

<https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf>

## GAMEFISH

backdoor

GAMEFISH is also known as:

- Sednit
- Seduploader
- JHUHUGIT
- Sofacy

Table 1697. Table References

Links
<a href="https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf">https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf</a>

## SOURFACE

downloader - Older version of CORESHELL

SOURFACE is also known as:

- Sofacy

Table 1698. Table References

Links
<a href="https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf">https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf</a>

## OLDBAIT

credential harvester

OLDBAIT is also known as:

- Sasfis
- BackDoor-FDU
- IEChecker

Table 1699. Table References

Links
<a href="https://www.trendmicro.com/vinfo/us/threat-encyclopedia/malware/troj_sasfis.tl">https://www.trendmicro.com/vinfo/us/threat-encyclopedia/malware/troj_sasfis.tl</a>
<a href="https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf">https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf</a>

## CORESHELL

downloader - Newer version of SOURFACE

CORESHELL is also known as:

- Sofacy

Table 1700. Table References

Links
<a href="https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf">https://www2.fireeye.com/rs/848-DID-242/images/APT28-Center-of-Storm-2017.pdf</a>

## Havex RAT

Havex RAT is also known as:

- Havex

## KjW0rm

RAT initially written in VB.

*Table 1701. Table References*

Links
<a href="https://www.sentinelone.com/blog/understanding-kjw0rm-malware-we-dive-in-to-the-tv5-cyber-attack/">https://www.sentinelone.com/blog/understanding-kjw0rm-malware-we-dive-in-to-the-tv5-cyber-attack/</a>

## TinyTyphon

## Badnews

## LURK

## Oldrea

## AmmyAdmin

## Matryoshka

## TinyZBot

## GHOLE

## CWoolger

## FireMalv

## Regin

Regin (also known as Prax or WarriorPride) is a sophisticated malware toolkit revealed by Kaspersky Lab, Symantec, and The Intercept in November 2014. The malware targets specific users of Microsoft Windows-based computers and has been linked to the US intelligence gathering agency NSA and its British counterpart, the GCHQ. The Intercept provided samples of Regin for download

including malware discovered at Belgian telecommunications provider, Belgacom. Kaspersky Lab says it first became aware of Regin in spring 2012, but that some of the earliest samples date from 2003. The name Regin is first found on the VirusTotal website on 9 March 2011.

Regin is also known as:

- Prax
- WarriorPride

*Table 1702. Table References*

Links
<a href="https://en.wikipedia.org/wiki/Regin_(malware)">https://en.wikipedia.org/wiki/Regin_(malware)</a>

**Duqu**

**Flame**

**Stuxnet**

**EquationLaser**

**EquationDrug**

**DoubleFantasy**

**TripleFantasy**

**Fanny**

**GrayFish**

**Babar**

**Bunny**

**Casper**

**NBot**

# Tafacalou

# Tdrop

# Troy

# Tdrop2

# ZXShell

ZXShell is also known as:

- Sensode

*Table 1703. Table References*

Links
<a href="http://www.fireeye.com/blog/uncategorized/2014/02/operation-snowman-deputydog-actor-compromises-us-veterans-of-foreign-wars-website.html">http://www.fireeye.com/blog/uncategorized/2014/02/operation-snowman-deputydog-actor-compromises-us-veterans-of-foreign-wars-website.html</a>

# T9000

*Table 1704. Table References*

Links
<a href="http://researchcenter.paloaltonetworks.com/2016/02/t9000-advanced-modular-backdoor-uses-complex-anti-analysis-techniques/">http://researchcenter.paloaltonetworks.com/2016/02/t9000-advanced-modular-backdoor-uses-complex-anti-analysis-techniques/</a>

# T5000

T5000 is also known as:

- Plat1

*Table 1705. Table References*

Links
<a href="http://www.cylance.com/techblog/Grand-Theft-Auto-Panda.shtml">http://www.cylance.com/techblog/Grand-Theft-Auto-Panda.shtml</a>

# Taidoor

*Table 1706. Table References*

Links
<a href="http://www.symantec.com/connect/blogs/trojantaidoor-takes-aim-policy-think-tanks">http://www.symantec.com/connect/blogs/trojantaidoor-takes-aim-policy-think-tanks</a>

## Swisyn

Table 1707. Table References

Links

<http://labs.alienvault.com/labs/index.php/2013/latest-adobe-pdf-exploit-used-to-target-uyghur-and-tibetan-activists/>

## Rekaf

Table 1708. Table References

Links

<https://www.proofpoint.com/us/exploring-bergard-old-malware-new-tricks>

## Scieron

## SkeletonKey

Table 1709. Table References

Links

<http://www.secureworks.com/cyber-threat-intelligence/threats/skeleton-key-malware-analysis/>

## Skyipot

Table 1710. Table References

Links

<http://labs.alienvault.com/labs/index.php/2011/another-sykipot-sample-likely-targeting-us-federal-agencies/>

## Spindest

Table 1711. Table References

Links

<http://www.threatconnect.com/news/threatconnect-enables-healthy-networking-biomed-life-sciences-industry/>

## Preshin

## Oficla

## PCClient RAT

Table 1712. Table References

Links

<http://researchcenter.paloaltonetworks.com/2014/10/new-indicators-compromise-apt-group-nitro-uncovered/>

## Plexor

## Mongall

Table 1713. Table References

Links

<https://www.fireeye.com/blog/threat-research/2014/09/the-path-to-mass-producing-cyber-attacks.html>

## NeD Worm

Table 1714. Table References

Links

<http://www.clearskysec.com/dustysky/>

## NewCT

Table 1715. Table References

Links

<https://www.fireeye.com/blog/threat-research/2014/09/the-path-to-mass-producing-cyber-attacks.html>

## Nflog

Table 1716. Table References

Links

<https://www.fireeye.com/blog/threat-research/2014/09/the-path-to-mass-producing-cyber-attacks.html>

## Janicab

Table 1717. Table References

Links

<http://blog.avast.com/2013/07/22/multisystem-trojan-janicab-attacks-windows-and-macosx-via-scripts/>

## Jriplibot

Jriplibot is also known as:

- Jriplibot

*Table 1718. Table References*

Links

[http://www.symantec.com/content/en/us/enterprise/media/security\\_response/whitepapers/butterfly-corporate-spies-out-for-financial-gain.pdf](http://www.symantec.com/content/en/us/enterprise/media/security_response/whitepapers/butterfly-corporate-spies-out-for-financial-gain.pdf)

## Jolob

*Table 1719. Table References*

Links

[http://pwc.blogs.com/cyber\\_security\\_updates/2014/10/scanbox-framework-whos-affected-and-whos-using-it-1.html](http://pwc.blogs.com/cyber_security_updates/2014/10/scanbox-framework-whos-affected-and-whos-using-it-1.html)

## IsSpace

*Table 1720. Table References*

Links

<https://www.fireeye.com/blog/threat-research/2014/09/the-path-to-mass-producing-cyber-attacks.html>

## Emotet

Emotet is also known as:

- Geodo

*Table 1721. Table References*

Links

<https://securelist.com/analysis/publications/69560/the-banking-trojan-emotet-detailed-analysis/>

## Hoardy

Hoardy is also known as:

- Hoarde
- Phindolp



- BS2005

## Htran

*Table 1722. Table References*

Links

<http://www.secureworks.com/research/threats/htran/>

## HTTPBrowser

HTTPBrowser is also known as:

- TokenControl

*Table 1723. Table References*

Links

<https://www.threatstream.com/blog/evasive-maneuvers-the-wekby-group-attempts-to-evade-analysis-via-custom-rop>

## Disgufa

## Elirks

## Snifula

Snifula is also known as:

- Ursnif

*Table 1724. Table References*

Links

<https://www.circl.lu/pub/tr-13/>

## Aumlib

Aumlib is also known as:

- Yayih
- mswab
- Graftor

*Table 1725. Table References*

Links

<http://www.cybersquared.com/killing-with-a-borrowed-knife-chaining-core-cloud-service-profile-infrastructure-for-cyber-attacks>

## CTRat

*Table 1726. Table References*

Links

<http://www.fireeye.com/blog/technical/threat-intelligence/2014/07/spy-of-the-tiger.html>

## Emdivi

Emdivi is also known as:

- Newsripper

*Table 1727. Table References*

Links

<http://www.symantec.com/connect/blogs/operation-cloudyomega-ichitaro-zero-day-and-ongoing-cyberespionage-campaign-targeting-japan>

## Etumbot

Etumbot is also known as:

- Exploz
- Specfix
- RIPTIDE

*Table 1728. Table References*

Links

[www.arbornetworks.com/asert/wp-content/uploads/2014/06/ASERT-Threat-Intelligence-Brief-2014-07-Illuminating-Etumbot-APT.pdf](http://www.arbornetworks.com/asert/wp-content/uploads/2014/06/ASERT-Threat-Intelligence-Brief-2014-07-Illuminating-Etumbot-APT.pdf)[[www.arbornetworks.com/asert/wp-content/uploads/2014/06/ASERT-Threat-Intelligence-Brief-2014-07-Illuminating-Etumbot-APT.pdf](http://www.arbornetworks.com/asert/wp-content/uploads/2014/06/ASERT-Threat-Intelligence-Brief-2014-07-Illuminating-Etumbot-APT.pdf)]

## Fexel

Fexel is also known as:

- Loneagent

## Fysbis

*Table 1729. Table References*

Links

<http://researchcenter.paloaltonetworks.com/2016/02/a-look-into-fysbis-sofacys-linux-backdoor/>

## Hikit

*Table 1730. Table References*

Links

<https://blog.bit9.com/2013/02/25/bit9-security-incident-update/>

## Hancitor

Hancitor is also known as:

- Tordal
- Chanitor
- Pony

*Table 1731. Table References*

Links

<https://www.proofpoint.com/us/threat-insight/post/hancitor-ruckguy-reappear>

## Ruckguy

*Table 1732. Table References*

Links

<https://www.proofpoint.com/us/threat-insight/post/hancitor-ruckguy-reappear>

## HerHer Trojan

*Table 1733. Table References*

Links

<http://researchcenter.paloaltonetworks.com/2016/05/the-oilrig-campaign-attacks-on-saudi-arabian-organizations-deliver-helminth-backdoor/>

## Helminth backdoor

*Table 1734. Table References*

Links

<http://researchcenter.paloaltonetworks.com/2016/05/the-oilrig-campaign-attacks-on-saudi-arabian-organizations-deliver-helminth-backdoor/>

## HDRoot

Table 1735. Table References

Links
<a href="http://williamshowalter.com/a-universal-windows-bootkit/">http://williamshowalter.com/a-universal-windows-bootkit/</a>

## IRONGATE

Table 1736. Table References

Links
<a href="https://www.fireeye.com/blog/threat-research/2016/06/irongate_ics_malware.html">https://www.fireeye.com/blog/threat-research/2016/06/irongate_ics_malware.html</a>

## ShimRAT

Table 1737. Table References

Links
<a href="https://foxitsecurity.files.wordpress.com/2016/06/fox-it_mofang_threatreport_tlp-white.pdf">https://foxitsecurity.files.wordpress.com/2016/06/fox-it_mofang_threatreport_tlp-white.pdf</a>

## X-Agent

This backdoor component is known to have a modular structure featuring various espionage functionalities, such as key-logging, screen grabbing and file exfiltration. This component is available for Osx, Windows, Linux and iOS operating systems.

X-Agent is also known as:

- XAgent

Table 1738. Table References

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/pawn-storm-update-ios-espionage-app-found/">http://blog.trendmicro.com/trendlabs-security-intelligence/pawn-storm-update-ios-espionage-app-found/</a>
<a href="https://app.box.com/s/l7n781ig6n8wlf1aff5hgwbh4qoi5jqqq">https://app.box.com/s/l7n781ig6n8wlf1aff5hgwbh4qoi5jqqq</a>

## X-Tunnel

X-Tunnel is also known as:

- XTunnel

## Foozer

Table 1739. Table References

Links
-------

<a href="https://www.crowdstrike.com/blog/bears-midst-intrusion-democratic-national-committee/">https://www.crowdstrike.com/blog/bears-midst-intrusion-democratic-national-committee/</a>
---

## WinIDS

*Table 1740. Table References*

Links
-------

<a href="https://www.crowdstrike.com/blog/bears-midst-intrusion-democratic-national-committee/">https://www.crowdstrike.com/blog/bears-midst-intrusion-democratic-national-committee/</a>
---

## DownRange

*Table 1741. Table References*

Links
-------

<a href="https://www.crowdstrike.com/blog/bears-midst-intrusion-democratic-national-committee/">https://www.crowdstrike.com/blog/bears-midst-intrusion-democratic-national-committee/</a>
---

## Mad Max

*Table 1742. Table References*

Links
-------

<a href="https://www.arbornetworks.com/blog/asert/mad-max-dga/">https://www.arbornetworks.com/blog/asert/mad-max-dga/</a>
---

## Crimson

Crimson is malware used as part of a campaign known as Operation Transparent Tribe that targeted Indian diplomatic and military victims

*Table 1743. Table References*

Links
-------

<a href="https://www.proofpoint.com/sites/default/files/proofpoint-operation-transparent-tribe-threat-insight-en.pdf">https://www.proofpoint.com/sites/default/files/proofpoint-operation-transparent-tribe-threat-insight-en.pdf</a>
---

## Prikormka

Operation Groundbait based on our research into the Prikormka malware family. This includes detailed technical analysis of the Prikormka malware family and its spreading mechanisms, and a description of the most noteworthy attack campaigns.

*Table 1744. Table References*

Links
-------

<a href="http://www.welivesecurity.com/wp-content/uploads/2016/05/Operation-Groundbait.pdf">http://www.welivesecurity.com/wp-content/uploads/2016/05/Operation-Groundbait.pdf</a>
---

## NanHaiShu

This whitepaper details a malicious program we identify as NanHaiShu. Based on our analysis, the threat actor behind this malware targets government and private-sector organizations.

*Table 1745. Table References*

Links
<a href="https://www.f-secure.com/documents/996508/1030745/nanhaishu_whitepaper.pdf">https://www.f-secure.com/documents/996508/1030745/nanhaishu_whitepaper.pdf</a>

## Umbreon

Umbreon (sharing the same name as the Pokémon) targets Linux systems, including systems running both Intel and ARM processors, expanding the scope of this threat to include embedded devices as well.

*Table 1746. Table References*

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/pokemon-themed-umbreon-linux-rootkit-hits-x86-arm-systems/">http://blog.trendmicro.com/trendlabs-security-intelligence/pokemon-themed-umbreon-linux-rootkit-hits-x86-arm-systems/</a>

## Odinaff

Odinaff is typically deployed in the first stage of an attack, to gain a foothold onto the network, providing a persistent presence and the ability to install additional tools onto the target network. These additional tools bear the hallmarks of a sophisticated attacker which has plagued the financial industry since at least 2013–Carbanak. This new wave of attacks has also used some infrastructure that has previously been used in Carbanak campaigns.

*Table 1747. Table References*

Links
<a href="https://www.symantec.com/connect/blogs/odinaff-new-trojan-used-high-level-financial-attacks">https://www.symantec.com/connect/blogs/odinaff-new-trojan-used-high-level-financial-attacks</a>

## Hworm

Unit 42 has observed a new version of Hworm (or Houdini) being used within multiple attacks. This blog outlines technical details of this new Hworm version and documents an attack campaign making use of the backdoor. Of the samples used in this attack, the first we observed were June 2016, while as-of publication we were still seeing attacks as recently as mid-October, suggesting that this is likely an active, ongoing campaign.

Hworm is also known as:

- Houdini

*Table 1748. Table References*

Links
-------

<a href="http://researchcenter.paloaltonetworks.com/2016/10/unit42-houdinis-magic-reappearance/">http://researchcenter.paloaltonetworks.com/2016/10/unit42-houdinis-magic-reappearance/</a>
---

## Backdoor.Dripion

Backdoor.Dripion was custom developed, deployed in a highly targeted fashion, and used command and control servers disguised as antivirus company websites.

Backdoor.Dripion is also known as:

- Dripion

*Table 1749. Table References*

Links
-------

<a href="http://www.symantec.com/connect/blogs/taiwan-targeted-new-cyberespionage-back-door-trojan">http://www.symantec.com/connect/blogs/taiwan-targeted-new-cyberespionage-back-door-trojan</a>
---

## Adwind

Adwind is a backdoor written purely in Java that targets system supporting the Java runtime environment. Commands that can be used, among other things, to display messages on the system, open URLs, update the malware, download/execute files, and download/load plugins. A significant amount of additional functionality can be provided through downloadable plugins, including such things as remote control options and shell command execution.

Adwind is also known as:

- AlienSpy
- Frutas
- Unrecom
- Sockrat
- JSocket
- jRat
- Backdoor:Java/Adwind

*Table 1750. Table References*

Links
-------

<a href="https://securelist.com/blog/research/73660/adwind-faq/">https://securelist.com/blog/research/73660/adwind-faq/</a>
---

## Bedep

## Cromptui

# Dridex

Dridex is a strain of banking malware that leverages macros in Microsoft Office to infect systems. Once a computer has been infected, Dridex attackers can steal banking credentials and other personal information on the system to gain access to the financial records of a user.

Dridex is also known as:

- Cridex

*Table 1751. Table References*

Links
<a href="http://www.symantec.com/content/en/us/enterprise/media/security_response/whitepapers/dridex-financial-trojan.pdf">http://www.symantec.com/content/en/us/enterprise/media/security_response/whitepapers/dridex-financial-trojan.pdf</a>

# Fareit

# Gafgyt

# Gamarue

Gamarue is also known as:

- Andromeda

*Table 1752. Table References*

Links
<a href="https://blog.gdatasoftware.com/2015/03/24274-the-andromeda-gamarue-botnet-is-on-the-rise-again">https://blog.gdatasoftware.com/2015/03/24274-the-andromeda-gamarue-botnet-is-on-the-rise-again</a>

# Necurs

The Necurs botnet is a distributor of many pieces of malware, most notably Locky.

*Table 1753. Table References*

Links
<a href="https://en.wikipedia.org/wiki/Necurs_botnet">https://en.wikipedia.org/wiki/Necurs_botnet</a>

# Palevo

# Akbot

Akbot is also known as:

- Qbot



- Qakbot
- PinkSlipBot

Table 1754. Table References

Links
<a href="https://en.wikipedia.org/wiki/Akbot">https://en.wikipedia.org/wiki/Akbot</a>

## Upatre

Upatre is a Trojan downloader that is used to set up other threats on the victim's PC. Upatre has been used recently in several high profile Trojan attacks involving the Gameover Trojan.

## Vawtrak

Vawtrak is an information stealing malware family that is primarily used to gain unauthorised access to bank accounts through online banking websites.

Table 1755. Table References

Links
<a href="https://www.sophos.com/medialibrary/PDFs/technical%20papers/sophos-vawtrak-international-crimeware-as-a-service-tpna.pdf">https://www.sophos.com/medialibrary/PDFs/technical%20papers/sophos-vawtrak-international-crimeware-as-a-service-tpna.pdf</a>

## Empire

Empire is a pure PowerShell post-exploitation agent built on cryptologically-secure communications and a flexible architecture. Empire implements the ability to run PowerShell agents without needing powershell.exe, rapidly deployable post-exploitation modules ranging from key loggers to Mimikatz, and adaptable communications to evade network detection, all wrapped up in a usability-focused framework

Table 1756. Table References

Links
<a href="https://github.com/adaptivethreat/Empire">https://github.com/adaptivethreat/Empire</a>

## Explosive

Beginning in late 2012, a carefully orchestrated attack campaign we call Volatile Cedar has been targeting individuals, companies and institutions worldwide. This campaign, led by a persistent attacker group, has successfully penetrated a large number of targets using various attack techniques, and specifically, a custom-made malware implant codenamed Explosive.

Table 1757. Table References

Links
<a href="https://www.checkpoint.com/downloads/volatile-cedar-technical-report.pdf">https://www.checkpoint.com/downloads/volatile-cedar-technical-report.pdf</a>

## KeyBoy

The actors used a new version of “KeyBoy,” a custom backdoor first disclosed by researchers at Rapid7 in June 2013. Their work outlined the capabilities of the backdoor, and exposed the protocols and algorithms used to hide the network communication and configuration data

Table 1758. Table References

Links
<a href="https://citizenlab.org/2016/11/parliament-keyboy/">https://citizenlab.org/2016/11/parliament-keyboy/</a>
<a href="https://community.rapid7.com/community/infosec/blog/2013/06/07/keyboy-targeted-attacks-against-vietnam-and-india">https://community.rapid7.com/community/infosec/blog/2013/06/07/keyboy-targeted-attacks-against-vietnam-and-india</a>

## Yahoyah

The attacks in this case are associated with a campaign called Tropic Trooper, which has been active since at least 2011 and is known for heavily targeting Taiwan. One of the attacks used their known Yahoyah malware...

Yahoyah is also known as:

- W32/Seeav

Table 1759. Table References

Links
<a href="http://researchcenter.paloaltonetworks.com/2016/11/unit42-tropic-trooper-targets-taiwanese-government-and-fossil-fuel-provider-with-poison-ivy/">http://researchcenter.paloaltonetworks.com/2016/11/unit42-tropic-trooper-targets-taiwanese-government-and-fossil-fuel-provider-with-poison-ivy/</a>

## Tartine

Delphi RAT used by Sofacy.

## Mirai

Mirai (Japanese for "the future") is malware that turns computer systems running Linux into remotely controlled "bots", that can be used as part of a botnet in large-scale network attacks. It primarily targets online consumer devices such as remote cameras and home routers. The Mirai botnet has been used in some of the largest and most disruptive distributed denial of service (DDoS) attacks, including an attack on 20 September 2016 on computer security journalist Brian Krebs's web site, an attack on French web host OVH and the October 2016 Dyn cyberattack.

Mirai is also known as:

- Linux/Mirai

Table 1760. Table References

Links
-------

## BASHLITE

## BlackEnergy

BlackEnergy is a trojan which has undergone significant functional changes since it was first publicly analysed by Arbor Networks in 2007. It has evolved from a relatively simple DDoS trojan into a relatively sophisticated piece of modern malware with a modular architecture, making it a suitable tool for sending spam and for online bank fraud, as well as for targeted attacks. BlackEnergy version 2, which featured rootkit techniques, was documented by SecureWorks in 2010. The targeted attacks recently discovered are proof that the trojan is still alive and kicking in 2014. We provide a technical analysis of the BlackEnergy family, focusing on novel functionality and the differences introduced by new lite variants. We describe the most notable aspects of the malware, including its techniques for bypassing UAC, defeating the signed driver requirement in Windows and a selection of BlackEnergy2 plug-ins used for parasitic file infections, network discovery and remote code execution and data collection.

*Table 1761. Table References*

Links

<https://www.virusbulletin.com/conference/vb2014/abstracts/back-blackenergy-2014-targeted-attacks-ukraine-and-poland/>

## Trojan.Seaduke

Trojan.Seaduke is a Trojan horse that opens a back door on the compromised computer. It may also download potentially malicious files.

Trojan.Seaduke is also known as:

- Seaduke

*Table 1762. Table References*

Links

[https://www.symantec.com/security\\_response/writeup.jsp?docid=2015-031915-4935-99](https://www.symantec.com/security_response/writeup.jsp?docid=2015-031915-4935-99)

## Backdoor.Tinybaron

## Incognito RAT

## DownRage

DownRage is also known as:

- Carberplike

Table 1763. Table References

Links
<a href="https://labsblog.f-secure.com/2015/09/08/sofacy-recycles-carberp-and-metasploit-code/">https://labsblog.f-secure.com/2015/09/08/sofacy-recycles-carberp-and-metasploit-code/</a>
<a href="https://twitter.com/Timo_Steffens/status/814781584536719360">https://twitter.com/Timo_Steffens/status/814781584536719360</a>

## Chthonic

Table 1764. Table References

Links
<a href="https://www.proofpoint.com/us/threat-insight/post/threat-actors-using-legitimate-paypal-accounts-to-distribute-chthonic-banking-trojan">https://www.proofpoint.com/us/threat-insight/post/threat-actors-using-legitimate-paypal-accounts-to-distribute-chthonic-banking-trojan</a>

## GeminiDuke

GeminiDuke is malware that was used by APT29 from 2009 to 2012.

Table 1765. Table References

Links
<a href="https://attack.mitre.org/wiki/Software/S0049">https://attack.mitre.org/wiki/Software/S0049</a>

## Zeus

Trojan.Zbot, also called Zeus, is a Trojan horse that attempts to steal confidential information from the compromised computer. It may also download configuration files and updates from the Internet. The Trojan is created using a Trojan-building toolkit.

Zeus is also known as:

- Trojan.Zbot
- Zbot

Table 1766. Table References

Links
<a href="https://en.wikipedia.org/wiki/Zeus_(malware)">https://en.wikipedia.org/wiki/Zeus_(malware)</a>
<a href="https://www.symantec.com/security_response/writeup.jsp?docid=2010-011016-3514-99">https://www.symantec.com/security_response/writeup.jsp?docid=2010-011016-3514-99</a>

## Shifu

Shifu is a Banking Trojan first discovered in 2015. Shifu is based on the Shiz source code which incorporated techniques used by Zeus. Attackers use Shifu to steal credentials for online banking websites around the world, starting in Russia but later including the UK, Italy, and others.

Table 1767. Table References

Links
<a href="http://researchcenter.paloaltonetworks.com/2017/01/unit42-2016-updates-shifu-banking-trojan/">http://researchcenter.paloaltonetworks.com/2017/01/unit42-2016-updates-shifu-banking-trojan/</a>

## Shiz

The new variant of the Shiz Trojan malware targets mission-critical enterprise resource planning (ERP) applications — particularly SAP users.

Table 1768. Table References

Links
<a href="https://securityintelligence.com/tag/shiz-trojan-malware/">https://securityintelligence.com/tag/shiz-trojan-malware/</a>

## MM Core

Also known as “BaneChant”, MM Core is a file-less APT which is executed in memory by a downloader component. It was first reported in 2013 under the version number “2.0-LNK” where it used the tag “BaneChant” in its command-and-control (C2) network request. A second version “2.1-LNK” with the network tag “StrangeLove” was discovered shortly after.

MM Core is also known as:

- MM Core backdoor
- BigBoss
- SillyGoose
- BaneChant
- StrangeLove

Table 1769. Table References

Links
<a href="https://blogs.forcepoint.com/security-labs/mm-core-memory-backdoor-returns-bigboss-and-sillygoose">https://blogs.forcepoint.com/security-labs/mm-core-memory-backdoor-returns-bigboss-and-sillygoose</a>

## Shamoon

Shamoon,[a] also known as Distrack, is a modular computer virus discovered by Seculert[1] in 2012, targeting recent NT kernel-based versions of Microsoft Windows. The virus has been used for cyber espionage in the energy sector.[2][3][4] Its discovery was announced on 16 August 2012 by Symantec,[3] Kaspersky Lab,[5] and Seculert.[6] Similarities have been highlighted by Kaspersky Lab and Seculert between Shamoon and the Flame malware.[5][6]

Table 1770. Table References

Links
-------

## GhostAdmin

According to MalwareHunterTeam and other researchers that have looked at the malware's source code, GhostAdmin seems to be a reworked version of CrimeScene, another botnet malware family that was active around 3-4 years ago.

*Table 1771. Table References*

### Links

<https://www.bleepingcomputer.com/news/security/new-ghostadmin-malware-used-for-data-theft-and-exfiltration/>

## EyePyramid Malware

Two Italians referred to as the “Occhionero brothers” have been arrested and accused of using malware and a carefully-prepared spear-phishing scheme to spy on high-profile politicians and businessmen. This case has been called “EyePyramid”, which we first discussed last week. (Conspiracy theories aside, the name came from a domain name and directory path that was found during the research.)

*Table 1772. Table References*

### Links

<http://blog.trendmicro.com/trendlabs-security-intelligence/uncovering-inner-workings-eyepyramid/>

## LuminosityLink

LuminosityLink is a malware family costing \$40 that purports to be a system administration utility

*Table 1773. Table References*

### Links

<http://researchcenter.paloaltonetworks.com/2016/07/unit42-investigating-the-luminositylink-remote-access-trojan-configuration/>

## Flokibot

Floki Bot, described recently by Dr. Peter Stephenson from SC Magazine, is yet another bot based on the leaked Zeus code. However, the author came up with various custom modifications that makes it more interesting.

Flokibot is also known as:

- Floki Bot
- Floki

Table 1774. Table References

Links
<a href="https://www.arbornetworks.com/blog/asert/flokibot-flock-bots/">https://www.arbornetworks.com/blog/asert/flokibot-flock-bots/</a>
<a href="https://blog.malwarebytes.com/threat-analysis/2016/11/floki-bot-and-the-stealthy-dropper/">https://blog.malwarebytes.com/threat-analysis/2016/11/floki-bot-and-the-stealthy-dropper/</a>

## ZeroT

Most recently, we have observed the same group targeting military and aerospace interests in Russia and Belarus. Since the summer of 2016, this group began using a new downloader known as ZeroT to install the PlugX remote access Trojan (RAT) and added Microsoft Compiled HTML Help (.chm) as one of the initial droppers delivered in spear-phishing emails.

Table 1775. Table References

Links
<a href="https://www.proofpoint.com/us/threat-insight/post/APT-targets-russia-belarus-zerot-pluginx">https://www.proofpoint.com/us/threat-insight/post/APT-targets-russia-belarus-zerot-pluginx</a>

## StreamEx

Cylance dubbed this family of malware StreamEx, based upon a common exported function used across all samples 'stream', combined with the dropper functionality to append 'ex' to the DLL file name. The StreamEx family has the ability to access and modify the user's file system, modify the registry, create system services, enumerate process and system information, enumerate network resources and drive types, scan for security tools such as firewall products and antivirus products, change browser security settings, and remotely execute commands. The malware documented in this post was predominantly 64-bit, however, there are 32-bit versions of the malware in the wild.

Table 1776. Table References

Links
<a href="https://blog.cylance.com/shell-crew-variants-continue-to-fly-under-big-avs-radar">https://blog.cylance.com/shell-crew-variants-continue-to-fly-under-big-avs-radar</a>

## adzok

Remote Access Trojan

Table 1777. Table References

Links
<a href="https://github.com/kevthehermit/RATDecoders">https://github.com/kevthehermit/RATDecoders</a>

## albertino

Remote Access Trojan

Table 1778. Table References

Links
-------

<a href="https://github.com/kevthehermit/RATDecoders">https://github.com/kevthehermit/RATDecoders</a>
---

## arcom

Remote Access Trojan

*Table 1779. Table References*

Links
-------

<a href="https://github.com/kevthehermit/RATDecoders">https://github.com/kevthehermit/RATDecoders</a>
---

## blacknix

Remote Access Trojan

*Table 1780. Table References*

Links
-------

<a href="https://github.com/kevthehermit/RATDecoders">https://github.com/kevthehermit/RATDecoders</a>
---

## bluebanana

Remote Access Trojan

*Table 1781. Table References*

Links
-------

<a href="https://github.com/kevthehermit/RATDecoders">https://github.com/kevthehermit/RATDecoders</a>
---

## bozok

Remote Access Trojan

*Table 1782. Table References*

Links
-------

<a href="https://github.com/kevthehermit/RATDecoders">https://github.com/kevthehermit/RATDecoders</a>
---

## clientmesh

Remote Access Trojan

*Table 1783. Table References*

Links
-------

<a href="https://github.com/kevthehermit/RATDecoders">https://github.com/kevthehermit/RATDecoders</a>
---



# cybergate

Remote Access Trojan

*Table 1784. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

# darkcomet

Remote Access Trojan

*Table 1785. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

# darkrat

Remote Access Trojan

*Table 1786. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

# gh0st

Remote Access Trojan

*Table 1787. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

# greame

Remote Access Trojan

*Table 1788. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

# hawkeye

Remote Access Trojan

Table 1789. Table References

Links

<https://github.com/kevthehermit/RATDecoders>

## **javadropper**

Remote Access Trojan

Table 1790. Table References

Links

<https://github.com/kevthehermit/RATDecoders>

## **lostdoor**

Remote Access Trojan

Table 1791. Table References

Links

<https://github.com/kevthehermit/RATDecoders>

## **luxnet**

Remote Access Trojan

Table 1792. Table References

Links

<https://github.com/kevthehermit/RATDecoders>

## **pandora**

Remote Access Trojan

Table 1793. Table References

Links

<https://github.com/kevthehermit/RATDecoders>

## **poisonivy**

Remote Access Trojan

Table 1794. Table References

Links

<https://github.com/kevthehermit/RATDecoders>

# predatorpain

Remote Access Trojan

*Table 1795. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

# punisher

Remote Access Trojan

*Table 1796. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

# qratt

Remote Access Trojan

*Table 1797. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

# shadowtech

Remote Access Trojan

*Table 1798. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

# smallnet

Remote Access Trojan

*Table 1799. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

# spygate

Remote Access Trojan

*Table 1800. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

## template

Remote Access Trojan

*Table 1801. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

## tapaoux

Remote Access Trojan

*Table 1802. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

## vantom

Remote Access Trojan

*Table 1803. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

## virusrat

Remote Access Trojan

*Table 1804. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

## xena

Remote Access Trojan

*Table 1805. Table References*

Links

<https://github.com/kevthehermit/RATDecoders>

## xtreme

Remote Access Trojan

*Table 1806. Table References*

Links
-------

<a href="https://github.com/kevthehermit/RATDecoders">https://github.com/kevthehermit/RATDecoders</a>
---

## darkddoser

Remote Access Trojan

*Table 1807. Table References*

Links
-------

<a href="https://github.com/kevthehermit/RATDecoders">https://github.com/kevthehermit/RATDecoders</a>
---

## jspy

Remote Access Trojan

*Table 1808. Table References*

Links
-------

<a href="https://github.com/kevthehermit/RATDecoders">https://github.com/kevthehermit/RATDecoders</a>
---

## xrat

Remote Access Trojan

*Table 1809. Table References*

Links
-------

<a href="https://github.com/kevthehermit/RATDecoders">https://github.com/kevthehermit/RATDecoders</a>
---

## PupyRAT

Pupy is an opensource, cross-platform (Windows, Linux, OSX, Android) remote administration and post-exploitation tool mainly written in python.

*Table 1810. Table References*

Links
-------

<a href="https://github.com/n1nj4sec/pupy">https://github.com/n1nj4sec/pupy</a>
---

## ELF\_IMEIJ

Linux Arm malware spread via RFIs in cgi-bin scripts. This backdoor executes commands from a remote malicious user, effectively compromising the affected system. It connects to a website to send and receive information.

*Table 1811. Table References*

Links
<a href="https://www.trendmicro.com/vinfo/us/threat-encyclopedia/malware/elf_imeij.a">https://www.trendmicro.com/vinfo/us/threat-encyclopedia/malware/elf_imeij.a</a>

## KHRAT

KHRAT is a small backdoor that has three exports (functions), namely, K1, K2, and K3. K1 checks if the current user is an administrator. If not, it uninstalls itself by calling the K2 function.

*Table 1812. Table References*

Links
<a href="https://blogs.forcepoint.com/security-labs/trojanized-adobe-installer-used-install-dragonok%E2%80%99s-new-custom-backdoor">https://blogs.forcepoint.com/security-labs/trojanized-adobe-installer-used-install-dragonok%E2%80%99s-new-custom-backdoor</a>

## Trochilus

The Trochilus RAT is a threatening RAT (Remote Access Trojan) that may evade many anti-virus programs. The Trochilus RAT is currently being used as part of an extended threat campaign in South East Asia. The first appearance of the Trochilus RAT in this campaign, which has been active since August of 2015, was first detected in the summer of 2015. The Trochilus RAT is currently being used against civil society organizations and government computers in the South East Asia region, particularly in attacks directed towards the government of Myanmar.

*Table 1813. Table References*

Links
<a href="http://www.enigmasoftware.com/trochilusrat-removal/">http://www.enigmasoftware.com/trochilusrat-removal/</a>

## MoonWind

The MoonWind sample used for this analysis was compiled with a Chinese compiler known as BlackMoon, the same compiler used for the BlackMoon banking Trojan. While a number of attributes match the BlackMoon banking Trojan, the malware is not the same. Both malware families were simply compiled using the same compiler, and it was the BlackMoon artifacts that resulted in the naming of the BlackMoon banking Trojan. But because this new sample is different from the BlackMoon banking Trojan,

*Table 1814. Table References*

Links
-------

<http://researchcenter.paloaltonetworks.com/2017/03/unit42-trochilus-rat-new-moonwind-rat-used-attack-thai-utility-organizations/>

## Chrysaor

Chrysaor is spyware believed to be created by NSO Group Technologies, specializing in the creation and sale of software and infrastructure for targeted attacks. Chrysaor is believed to be related to the Pegasus spyware that was first identified on iOS and analyzed by Citizen Lab and Lookout.

Chrysaor is also known as:

- Pegasus
- Pegasus spyware

*Table 1815. Table References*

Links

<https://security.googleblog.com/2017/04/an-investigation-of-chrysaor-malware-on.html>

## Sathurbot

The trojan serves as a backdoor. It can be controlled remotely.

*Table 1816. Table References*

Links

[http://virusradar.com/en/Win32\\_Sathurbot.A/description](http://virusradar.com/en/Win32_Sathurbot.A/description)

<https://www.welivesecurity.com/2017/04/06/sathurbot-distributed-wordpress-password-attack/>

## AURIGA

The AURIGA malware family shares a large amount of functionality with the BANGAT backdoor. The malware family contains functionality for keystroke logging, creating and killing processes, performing file system and registry modifications, spawning interactive command shells, performing process injection, logging off the current user or shutting down the local machine. The AURIGA malware contains a driver component which is used to inject the malware DLL into other processes. This driver can also perform process and IP connection hiding. The malware family will create a copy of cmd.exe to perform its C2 activity, and replace the "Microsoft corp" strings in the cmd.exe binary with different values. The malware family typically maintains persistence through installing itself as a service.

*Table 1817. Table References*

Links

<http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html>

## BANGAT

The BANGAT malware family shares a large amount of functionality with the AURIGA backdoor. The malware family contains functionality for keylogging, creating and killing processes, performing filesystem and registry modifications, spawning interactive command shells, performing process injection, logging off the current user or shutting down the local machine. In addition, the malware also implements a custom VNC like protocol which sends screenshots of the desktop to the C2 server and accepts keyboard and mouse input. The malware communicates to its C2 servers using SSL, with self signed SSL certificates. The malware family will create a copy of cmd.exe to perform its C2 activity, and replace the "Microsoft corp" strings in the cmd.exe binary with different values. The malware family typically maintains persistence through installing itself as a service.

*Table 1818. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## BISCUIT

BISCUIT provides attackers with full access to an infected host. BISCUIT capabilities include launching an interactive command shell, enumerating servers on a Windows network, enumerating and manipulating process, and transferring files. BISCUIT communicates using a custom protocol, which is then encrypted using SSL. Once installed BISCUIT will attempt to beacon to its command/control servers approximately every 10 or 30 minutes. It will beacon its primary server first, followed by a secondary server. All communication is encrypted with SSL (OpenSSL 0.9.8i).

*Table 1819. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## BOUNCER

BOUNCER will load an extracted DLL into memory, and then will call the DLL's dump export. The dump export is called with the parameters passed via the command line to the BOUNCER executable. It requires at least two arguments, the IP and port to send the password dump information. It can accept at most five arguments, including a proxy IP, port and an x.509 key for SSL authentication. The DLL backdoor has the capability to execute arbitrary commands, collect database and server information, brute force SQL login credentials, launch arbitrary programs, create processes and threads, delete files, and redirect network traffic.

*Table 1820. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>



## CALENDAR

This family of malware uses Google Calendar to retrieve commands and send results. It retrieves event feeds associated with Google Calendar, where each event contains commands from the attacker for the malware to perform. Results are posted back to the event feed. The malware authenticates with Google using the hard coded email address and passwords. The malware uses the deprecated ClientLogin authentication API from Google. The malware is registered as a service dll as a persistence mechanism. Artifacts of this may be found in the registry.

*Table 1821. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## COMBOS

The COMBOS malware family is an HTTP based backdoor. The backdoor is capable of file upload, file download, spawning a interactive reverse shell, and terminating its own process. The backdoor may decrypt stored Internet Explorer credentials from the local system and transmit the credentials to the C2 server. The COMBOS malware family does not have any persistence mechanisms built into itself.

*Table 1822. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## COOKIEBAG

his family of malware is a backdoor capable of file upload and download as well as providing remote interactive shell access to the compromised machine. Communication with the Command & Control (C2) servers uses a combination of single-byte XOR and Base64 encoded data in the Cookie and Set-Cookie HTTP header fields. Communication with the C2 servers is over port 80. Some variants install a registry key as means of a persistence mechanism. The hardcoded strings cited include a string of a command in common with several other APT1 families.

COOKIEBAG is also known as:

- TROJAN.COOKIEBAG

*Table 1823. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## DAIRY

Members of this malware family are backdoors that provide file downloading, process listing,

process killing, and reverse shell capabilities. This malware may also add itself to the Authorized Applications list for the Windows Firewall.

*Table 1824. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## GETMAIL

Members of this family of malware are utilities designed to extract email messages and attachments from Outlook PST files. One part of this utility set is an executable, one is a dll. The malware may create a registry artifact related to the executable.

*Table 1825. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## GDOCUPLOAD

This family of malware is a utility designed to upload files to Google Docs. Nearly all communications are with docs.google.com are SSL encrypted. The malware does not use Google's published API to interact with their services. The malware does not currently work with Google Docs. It does not detect HTTP 302 redirections and will get caught in an infinite loop attempting to parse results from Google that are not present.

*Table 1826. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## GLOOXMAIL

GLOOXMAIL communicates with Google's Jabber/XMPP servers and authenticates with a hard-coded username and password. The malware can accept commands over XMPP that includes file upload and download, provide a remote shell, sending process listings, and terminating specified processes. The malware makes extensive use of the open source gloox library (<http://camaya.net/gloox/>, version 0.9.9.12) to communicate using the Jabber/XMPP protocol. All communications with the Google XMPP server are encrypted.

GLOOXMAIL is also known as:

- TROJAN.GTALK

*Table 1827. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

# GOGGLES

A family of downloader malware, that retrieves an encoded payload from a fixed location, usually in the form of a file with the .jpg extension. Some variants have just an .exe that acts as a downloader, others have an .exe launcher that runs as a service and then loads an associated .dll of the same name that acts as the downloader. This IOC is targeted at the downloaders only. After downloading the file, the malware decodes the downloaded payload into an .exe file and launches it. The malware usually stages the files it uses in the %TEMP% directory or the %WINDIR%\Temp directory.

GOGGLES is also known as:

- TROJAN.FOXY

*Table 1828. Table References*

Links

<http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html>

# GREENCAT

Members of this family are full featured backdoors that communicates with a Web-based Command & Control (C2) server over SSL. Features include interactive shell, gathering system info, uploading and downloading files, and creating and killing processes, Malware in this family usually communicates with a hard-coded domain using SSL on port 443. Some members of this family rely on launchers to establish persistence mechanism for them. Others contains functionality that allows it to install itself, replacing an existing Windows service, and uninstall itself. Several variants use %SystemRoot%\Tasks or %WinDir%\Tasks as working directories, additional malware artifacts may be found there.

*Table 1829. Table References*

Links

<http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html>

# HACKFASE

This family of malware is a backdoor that provides reverse shell, process creation, system statistics collection, process enumeration, and process termination capabilities. This family is designed to be a service DLL and does not contain an installation mechanism. It usually communicates over port 443. Some variants use their own encryption, others use SSL.

*Table 1830. Table References*

Links

<http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html>

## HELAUTO

This family of malware is designed to operate as a service and provides remote command execution and file transfer capabilities to a fixed IP address or domain name. All communication with the C2 server happens over port 443 using SSL. This family can be installed as a service DLL. Some variants allow for uninstallation.

*Table 1831. Table References*

Links

<http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html>

## KURTON

This family of malware is a backdoor that tunnels its connection through a preconfigured proxy. The malware communicates with a remote command and control server over HTTPS via the proxy. The malware installs itself as a Windows service with a service name supplied by the attacker but defaults to IPRIP if no service name is provided during install.

*Table 1832. Table References*

Links

<http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html>

## LIGHTBOLT

LIGHTBOLT is a utility with the ability to perform HTTP GET requests for a list of user-specified URLs. The responses of the HTTP requests are then saved as MHTML files, which are added to encrypted RAR files. LIGHTBOLT has the ability to use software certificates for authentication.

*Table 1833. Table References*

Links

<http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html>

## LIGHTDART

LIGHTDART is a tool used to access a pre-configured web page that hosts an interface to query a database or data set. The tool then downloads the results of a query against that web page to an encrypted RAR file. This RAR file (1.rar) is renamed and uploaded to an attacker controlled FTP server, or uploaded via an HTTP POST with a .jpg extension. The malware will execute this search once a day. The target webpage usually contains information useful to the attacker, which is updated on a regular basis. Examples of targeted information include weather information or ship coordinates.

*Table 1834. Table References*

Links
-------

<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>
---

## LONGRUN

LONGRUN is a backdoor designed to communicate with a hard-coded IP address and provide the attackers with a custom interactive shell. It supports file uploads and downloads, and executing arbitrary commands on the compromised machine. When LONGRUN executes, it first loads configuration data stored as an obfuscated string inside the PE resource section. The distinctive string thequickbrownfxjimpsvalzydg is used as part of the input to the decoding algorithm. When the configuration data string is decoded it is parsed and treated as an IP and port number. The malware then connects to the host and begins interacting with it over a custom protocol.

*Table 1835. Table References*

Links
-------

<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>
---

## MANITSME

This family of malware will beacon out at random intervals to the remote attacker. The attacker can run programs, execute arbitrary commands, and easily upload and download files. This IOC looks for both the dropper file and the backdoor.

*Table 1836. Table References*

Links
-------

<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>
---

## MAPIGET

This malware utility is a set of two files that operate in conjunction to extract email messages and attachments from an Exchange server. In order to operate successfully, these programs require authentication credentials for a user on the Exchange server, and must be run from a machine joined to the domain that has Microsoft Outlook installed (or equivalent software that provides the Microsoft 'Messaging API' (MAPI) service).

*Table 1837. Table References*

Links
-------

<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>
---

<a href="http://contagiodump.blogspot.com/2010/06/these-days-i-see-spike-in-number-of.html">http://contagiodump.blogspot.com/2010/06/these-days-i-see-spike-in-number-of.html</a>
---

## MINIASP

This family of malware consists of backdoors that attempt to fetch encoded commands over HTTP. The malware is capable of downloading a file, downloading and executing a file, executing

arbitrary shell commands, or sleeping a specified interval.

Table 1838. Table References

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## NEWSREELS

The NEWSREELS malware family is an HTTP based backdoor. When first started, NEWSREELS decodes two strings from its resources section. These strings are both used as C2 channels, one URL is used as a beacon URL (transmitting) and the second URL is used to get commands (receiving). The NEWSREELS malware family is capable of performing file uploads, downloads, creating processes or creating an interactive reverse shell.

Table 1839. Table References

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## SEASALT

The SEASALT malware family communicates via a custom binary protocol. It is capable of gathering some basic system information, file system manipulation, file upload and download, process creation and termination, and spawning an interactive reverse shell. The malware maintains persistence by installing itself as a service.

Table 1840. Table References

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## STARSYPOUND

STARSYPOUND provides an interactive remote shell over an obfuscated communications channel. When it is first run, it loads a string (from the executable PE resource section) containing the beacon IP address and port. The malware sends the beacon string "(SY)# <HOSTNAME>" to the remote system, where <HOSTNAME> is the hostname of the victim system. The remote host responds with a packet that also begins with the string "(SY)# cmd". This causes the malware to launch a new cmd.exe child process. Further communications are forwarded to the cmd.exe child process to execute. The commands sent to the shell and their responses are obfuscated when sent over the network.

Table 1841. Table References

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

# SWORD

This family of malware provides a backdoor over the network to the attackers. It is configured to connect to a single host and offers file download over HTTP, program execution, and arbitrary execution of commands through a cmd.exe instance.

Table 1842. Table References

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

# TABMSGSQL

This malware family is a full-featured backdoor capable of file uploading and downloading, arbitrary execution of programs, and providing a remote interactive command shell. All communications with the C2 server are sent over HTTP to a static URL, appending various URL parameters to the request. Some variants use a slightly different URL.

TABMSGSQL is also known as:

- TROJAN LETSGO

Table 1843. Table References

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

# TARSIP-ECLIPSE

The TARSIP malware family is a backdoor which communicates over encoded information in HTTPS headers. Typical TARSIP malware samples will only beacon out to their C2 servers if the C2 DNS address resolves to a specific address. The capability of TARSIP backdoors includes file uploading, file downloading, interactive command shells, process enumeration, process creation, process termination. The TARSIP-ECLIPSE family is distinguished by the presence of 'eclipse' in .pdb debug strings present in the malware samples. It does not provide a built in mechanism to maintain persistence.

Table 1844. Table References

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

# TARSIP-MOON

The TARSIP malware family is a backdoor which communicates over encoded information in HTTPS headers. Typical TARSIP malware samples will only beacon out to their C2 servers if the C2

DNS address resolves to a specific address. The capability of TARSIP backdoors includes file uploading, file downloading, interactive command shells, process enumeration, process creation, process termination. The TARSIP-MOON family is distinguished by the presence of 'moon' in .pdb debug strings present in the malware samples. It does not provide a built in mechanism to maintain persistence.

*Table 1845. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WARP

The WARP malware family is an HTTP based backdoor written in C++, and the majority of its code base is borrowed from source code available in the public domain. Network communications are implemented using the same WWW client library (w3c.cpp) available from [www.dankrusi.com/file\\_69653F3336383837.html](http://www.dankrusi.com/file_69653F3336383837.html). The malware has system survey functionality (collects hostname, current user, system uptime, CPU speed, etc.) taken directly from the BO2K backdoor available from [www.bo2k.com](http://www.bo2k.com). It also contains the hard disk identification code found at [www.winsim.com/diskid32/diskid32.cpp](http://www.winsim.com/diskid32/diskid32.cpp). When the WARP executing remote commands, the malware creates a copy of the `?%SYSTEMROOT%\system32\cmd.exe?` file as `'%USERPROFILE%\Temp\~ISUN32.EXE'`. The version signature information of the duplicate executable is zeroed out. Some WARP variants maintain persistence through the use of DLL search order hijacking.

*Table 1846. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WEBC2-ADSPACE

A WEBC2 backdoor is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. This family of malware is capable of downloading and executing a file. All variants represented here are the same file with different MD5 signatures. This malware attempts to contact its C2 once a week (Thursday at 10:00 AM). It looks for commands inside a set of HTML tags, part of which are in the File Strings indicator term below.

*Table 1847. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WEBC2-AUSOV

A WEBC2 backdoor is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between



the tags as commands. This malware family is a only a downloader which operates over the HTTP protocol with a hard-coded URL. If directed, it has the capability to download, decompress, and execute compressed binaries.

*Table 1848. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WEBC2-BOLID

A WEBC2 backdoor is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. This family of malware is a backdoor capable of downloading files and updating its configuration. Communication with the command and control (C2) server uses a combination of single-byte XOR and Base64 encoded data wrapped in standard HTML tags. The malware family installs a registry key as a persistence mechanism.

*Table 1849. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WEBC2-CLOVER

A WEBC2 backdoor is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. The family of malware provides the attacker with an interactive command shell, the ability to upload and download files, execute commands on the system, list processes and DLLs, kill processes, and ping hosts on the local network. Responses to these commands are encrypted and compressed before being POSTed to the server. Some variants copy cmd.exe to Updatasched.exe in a temporary directory, and then may launch that in a process if an interactive shell is called. On initial invocation, the malware also attempts to delete previous copies of the Updatasched.exe file.

*Table 1850. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WEBC2-CSON

A WEBC2 backdoor is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. Members of this family of malware act only as downloaders and droppers for other malware. They communicate with a hard-coded C2 server, reading commands embedded

in HTML comment fields. Some variants are executables which act upon execution, others are DLLs which can be attached to services or loaded through search order hijacking.

*Table 1851. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WEBC2-DIV

The WEBC2 malware family is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. The WEBC2-DIV variant searches for the strings "div safe:" and "balance" to delimit encoded C2 information. If the decoded string begins with the letter "J" the malware will parse additional arguments in the decoded string to specify the sleep interval to use. WEBC2-DIV is capable of downloading a file, downloading and executing a file, or sleeping a specified interval.

*Table 1852. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WEBC2-GREENCAT

A WEBC2 backdoor is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. This malware is a variant on the GREENCAT family, using a fixed web C2. This family is a full featured backdoor which provides remote command execution, file transfer, process and service enumeration and manipulation. It installs itself persistently through the current user's registry Run key.

*Table 1853. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WEBC2-HEAD

The WEBC2 malware family is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. The WEBC2-HEAD variant communicates over HTTPS, using the system's SSL implementation to encrypt all communications with the C2 server. WEBC2-HEAD first issues an HTTP GET to the host, sending the Base64-encoded string containing the name of the compromised machine running the malware.

*Table 1854. Table References*

Links
-------

<http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html>

## WEBC2-KT3

The WEBC2 malware family is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. The WEBC2-KT3 variant searches for commands in a specific comment tag. Network traffic starting with `*!Kt3+v|` may indicate WEBC2-KT3 activity.

*Table 1855. Table References*

Links

<http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html>

## WEBC2-QBP

The WEBC2 malware family is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. The WEBC2-QBP variant will search for two strings in a HTML comment. The first will be "2010QBP " followed by " 2010QBP/--". Inside these tags will be a DES-encrypted string.

*Table 1856. Table References*

Links

<http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html>

## WEBC2-RAVE

A WEBC2 backdoor is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. This family of malware will set itself up as a service and connect out to a hardcoded web page and read a modified base64 string from this webpage. The later versions of this malware supports three commands (earlier ones are just downloaders or reverse shells). The first commands will sleep the malware for N number of hours. The second command will download a binary from the encoded HTML comment and execute it on the infected host. The third will spawn an encoded reverse shell to an attacker specified location and port.

*Table 1857. Table References*

Links

<http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html>

## WEBC2-TABLE

The WEBC2 malware family is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data

between the tags as commands. The WEBC2-TABLE variant looks for web pages containing 'background', 'align', and 'bgcolor' tags to be present in the requested Web page. If the data in these tags are formatted correctly, the malware will decode a second URL and a filename. This URL is then retrieved, written to the decoded filename and executed.

*Table 1858. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WEBC2-TOCK

The WEBC2 malware family is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. The WEBC2-TABLE variant looks for web pages containing 'background', 'align', and 'bgcolor' tags to be present in the requested Web page. If the data in these tags are formatted correctly, the malware will decode a second URL and a filename. This URL is then retrieved, written to the decoded filename and executed.

*Table 1859. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WEBC2-UGX

A WEBC2 backdoor is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. Members of this family of malware provide remote command shell and remote file download and execution capabilities. The malware downloads a web page containing a crafted HTML comment that subsequently contains an encoded command. The contents of this command tell the malware whether to download and execute a program, launch a reverse shell to a specific host and port number, or to sleep for a period of time.

*Table 1860. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WEBC2-Y21K

A WEBC2 backdoor is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. Members of this family of backdoor malware talk to specific Web-based Command & Control (C2) servers. The backdoor has a limited command set, depending on version. It is primarily a downloader, but it classified as a backdoor because it can accept a limited command set, including changing local directories, downloading and executing additional files, sleeping, and connecting to a specific IP & port not initially included in the instruction set for the

malware. Each version of the malware has at least one hardcoded URL to which it connects to receive its initial commands. This family of malware installs itself as a service, with the malware either being the executable run by the service, or the service DLL loaded by a legitimate service. The same core code is seen recompiled on different dates or with different names, but the same functionality. Key signatures include a specific set of functions (some of which can be used with the OS-provided rundll32.exe tool to install the malware as a service), and hardcoded strings used in communication with C2 servers to issue commands to the implant.

*Table 1861. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## WEBC2-YAHOO

The WEBC2 malware family is designed to retrieve a Web page from a pre-determined C2 server. It expects the Web page to contain special HTML tags; the backdoor will attempt to interpret the data between the tags as commands. The WEBC2-YAHOO variant enters a loop where every ten minutes it attempts to download a web page that may contain an encoded URL. The encoded URL will be found in the pages returned inside an attribute named 'sb' or 'ex' within a tag named 'yahoo'. The embedded link can direct the malware to download and execute files.

*Table 1862. Table References*

Links
<a href="http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html">http://contagiodump.blogspot.lu/2013/03/mandiant-apt1-samples-categorized-by.html</a>

## HAYMAKER

HAYMAKER is a backdoor that can download and execute additional payloads in the form of modules. It also conducts basic victim profiling activity, collecting the computer name, running process IDs, %TEMP% directory path and version of Internet Explorer. It communicates encoded system information to a single hard coded command and control (C2) server, using the system's default User-Agent string.

*Table 1863. Table References*

Links
<a href="https://www.fireeye.com/blog/threat-research/2017/04/apt10_menuspass_grou.html">https://www.fireeye.com/blog/threat-research/2017/04/apt10_menuspass_grou.html</a>

## BUGJUICE

BUGJUICE is a backdoor that is executed by launching a benign file and then hijacking the search order to load a malicious dll into it. That malicious dll then loads encrypted shellcode from the binary, which is decrypted and runs the final BUGJUICE payload. BUGJUICE defaults to TCP using a custom binary protocol to communicate with the C2, but can also use HTTP and HTTPS if directed by the C2. It has the capability to find files, enumerate drives, exfiltrate data, take screenshots and provide a reverse shell.

Table 1864. Table References

Links
<a href="https://www.fireeye.com/blog/threat-research/2017/04/apt10_menuspass_grou.html">https://www.fireeye.com/blog/threat-research/2017/04/apt10_menuspass_grou.html</a>

## SNUGRIDE

SNUGRIDE is a backdoor that communicates with its C2 server through HTTP requests. Messages are encrypted using AES with a static key. The malware's capabilities include taking a system survey, access to the filesystem, executing commands and a reverse shell. Persistence is maintained through a Run registry key.

Table 1865. Table References

Links
<a href="https://www.fireeye.com/blog/threat-research/2017/04/apt10_menuspass_grou.html">https://www.fireeye.com/blog/threat-research/2017/04/apt10_menuspass_grou.html</a>

## QUASARRAT

QUASARRAT is an open-source RAT available at <https://github.com/quasar/QuasarRat> . The versions used by APT10 (1.3.4.0, 2.0.0.0, and 2.0.0.1) are not available via the public GitHub page, indicating that APT10 has further customized the open source version. The 2.0 versions require a dropper to decipher and launch the AES encrypted QUASARRAT payload. QUASARRAT is a fully functional .NET backdoor that has been used by multiple cyber espionage groups in the past.

Table 1866. Table References

Links
<a href="https://www.fireeye.com/blog/threat-research/2017/04/apt10_menuspass_grou.html">https://www.fireeye.com/blog/threat-research/2017/04/apt10_menuspass_grou.html</a>

## da Vinci RCS

Hacking Team's "DaVinci" Remote Control System is able, the company says, to break encryption and allow law enforcement agencies to monitor encrypted files and emails (even ones encrypted with PGP), Skype and other Voice over IP or chat communication. It allows identification of the target's location and relationships. It can also remotely activate microphones and cameras on a computer and works worldwide. Hacking Team claims that its software is able to monitor hundreds of thousands of computers at once, all over the country. Trojans are available for Windows, Mac, Linux, iOS, Android, Symbian and Blackberry.

da Vinci RCS is also known as:

- DaVinci
- Morcut

Table 1867. Table References

Links
-------

<http://surveillance.rsf.org/en/hacking-team/>

<https://wikileaks.org/hackingteam/emails/fileid/581640/267803>

<https://wikileaks.org/hackingteam/emails/emailid/31436>

## LATENTBOT

LATENTBOT, a new, highly obfuscated BOT that has been in the wild since mid-2013. It has managed to leave hardly any traces on the Internet, is capable of watching its victims without ever being noticed, and can even corrupt a hard disk, thus making a PC useless.

*Table 1868. Table References*

Links

[https://www.fireeye.com/blog/threat-research/2015/12/latentbot\\_trace\\_me.html](https://www.fireeye.com/blog/threat-research/2015/12/latentbot_trace_me.html)

[https://www.fireeye.com/blog/threat-research/2017/04/cve-2017-0199\\_useda.html](https://www.fireeye.com/blog/threat-research/2017/04/cve-2017-0199_useda.html)

## FINSPY

Though we have not identified the targets, FINSPY is sold by Gamma Group to multiple nation-state clients, and we assess with moderate confidence that it was being used along with the zero-day to carry out cyber espionage.

FINSPY is also known as:

- BlackOasis

*Table 1869. Table References*

Links

[https://www.fireeye.com/blog/threat-research/2017/04/cve-2017-0199\\_useda.html](https://www.fireeye.com/blog/threat-research/2017/04/cve-2017-0199_useda.html)

## RCS Galileo

HackingTeam Remote Control System (RCS) Galileo hacking platform

*Table 1870. Table References*

Links

<https://www.f-secure.com/documents/996508/1030745/callisto-group>

## EARLYSHOVEL

RedHat 7.0 - 7.1 Sendmail 8.11.x exploit

## EBBISLAND (EBBSHAVE)

root RCE via RPC XDR overflow in Solaris 6, 7, 8, 9 & 10 (possibly newer) both SPARC and x86

## **ECHOWRECKER**

remote Samba 3.0.x Linux exploit

## **EASYBEE**

appears to be an MDAemon email server vulnerability

## **EASYPI**

an IBM Lotus Notes exploit that gets detected as Stuxnet

## **EWOKFRENZY**

an exploit for IBM Lotus Domino 6.5.4 & 7.0.2

## **EXPLODINGCAN**

an IIS 6.0 exploit that creates a remote backdoor

## **ETERNALROMANCE**

a SMB1 exploit over TCP port 445 which targets XP, 2003, Vista, 7, Windows 8, 2008, 2008 R2, and gives SYSTEM privileges (MS17-010)

## **EDUCATEDSCHOLAR**

a SMB exploit (MS09-050)

## **EMERALDTHREAD**

a SMB exploit for Windows XP and Server 2003 (MS10-061)

## **EMPHASISMINE**

a remote IMAP exploit for IBM Lotus Domino 6.6.4 to 8.5.2

## **ENGLISHMANSDENTIST**

Outlook Exchange WebAccess rules to trigger executable code on the client's side to send an email to other users



## **EPICHERO**

0-day exploit (RCE) for Avaya Call Server

## **ERRATICGOPHER**

SMBv1 exploit targeting Windows XP and Server 2003

## **ETERNALSYNERGY**

a SMBv3 remote code execution flaw for Windows 8 and Server 2012 SP0 (MS17-010)

## **ETERNALBLUE**

SMBv2 exploit for Windows 7 SP1 (MS17-010)

## **ETERNALCHAMPION**

a SMBv1 exploit

## **ESKIMOROLL**

Kerberos exploit targeting 2000, 2003, 2008 and 2008 R2 domain controllers

## **ESTEEMAUDIT**

RDP exploit and backdoor for Windows Server 2003

## **ECLIPSEDWING**

RCE exploit for the Server service in Windows Server 2008 and later (MS08-067)

## **ETRE**

exploit for IMail 8.10 to 8.22

## **FUZZBUNCH**

an exploit framework, similar to MetaSploit

## **ODDJOB**

implant builder and C&C server that can deliver exploits for Windows 2000 and later, also not detected by any AV vendors

## PASSFREELY

utility which Bypasses authentication for Oracle servers

## SMBTOUCH

check if the target is vulnerable to samba exploits like ETERNALSYNERGY, ETERNALBLUE, ETERNALROMANCE

## ERRATICGOPHERTOUCH

Check if the target is running some RPC

## IISTOUCH

check if the running IIS version is vulnerable

## RPCOUTCH

get info about windows via RPC

## DOPU

used to connect to machines exploited by ETERNALCHAMPIONS

## FlexSpy

covert surveillance tools

## feodo

Unfortunately, it is time to meet 'Feodo'. Since august of this year when FireEye's MPS devices detected this malware in the field, we have been monitoring this banking trojan very closely. In many ways, this malware looks similar to other famous banking trojans like Zbot and SpyEye. Although my analysis says that this malware is not a toolkit and is in the hands of a single criminal group.

*Table 1871. Table References*

Links
<a href="https://www.fireeye.com/blog/threat-research/2010/10/feodosoff-a-new-botnet-on-the-rise.html">https://www.fireeye.com/blog/threat-research/2010/10/feodosoff-a-new-botnet-on-the-rise.html</a>

## Cardinal RAT

Palo Alto Networks has discovered a previously unknown remote access Trojan (RAT) that has been

active for over two years. It has a very low volume in this two-year period, totaling roughly 27 total samples. The malware is delivered via an innovative and unique technique: a downloader we are calling Carp uses malicious macros in Microsoft Excel documents to compile embedded C# (C Sharp) Programming Language source code into an executable that in turn is run to deploy the Cardinal RAT malware family. These malicious Excel files use a number of different lures, providing evidence of what attackers are using to entice victims into executing them.

*Table 1872. Table References*

Links
<a href="http://researchcenter.paloaltonetworks.com/2017/04/unit42-cardinal-rat-active-two-years/">http://researchcenter.paloaltonetworks.com/2017/04/unit42-cardinal-rat-active-two-years/</a>

## REDLEAVES

The REDLEAVES implant consists of three parts: an executable, a loader, and the implant shellcode. The REDLEAVES implant is a remote administration Trojan (RAT) that is built in Visual C++ and makes heavy use of thread generation during its execution. The implant contains a number of functions typical of RATs, including system enumeration and creating a remote shell back to the C2.

*Table 1873. Table References*

Links
<a href="https://www.us-cert.gov/ncas/alerts/TA17-117A">https://www.us-cert.gov/ncas/alerts/TA17-117A</a>

## Kazuar

Kazuar is a fully featured backdoor written using the .NET Framework and obfuscated using the open source packer called ConfuserEx. Unit 42 researchers have uncovered a backdoor Trojan used in an espionage campaign. The developers refer to this tool by the name Kazuar, which is a Trojan written using the Microsoft .NET Framework that offers actors complete access to compromised systems targeted by its operator. Kazuar includes a highly functional command set, which includes the ability to remotely load additional plugins to increase the Trojan's capabilities. During our analysis of this malware we uncovered interesting code paths and other artifacts that may indicate a Mac or Unix variant of this same tool also exists. Also, we discovered a unique feature within Kazuar: it exposes its capabilities through an Application Programming Interface (API) to a built-in webserver. We suspect the Kazuar tool may be linked to the Turla threat actor group (also known as Uroburos and Snake), who have been reported to have compromised embassies, defense contractors, educational institutions, and research organizations across the globe. A hallmark of Turla operations is iterations of their tools and code lineage in Kazuar can be traced back to at least 2005. If the hypothesis is correct and the Turla threat group is using Kazuar, we believe they may be using it as a replacement for Carbon and its derivatives. Of the myriad of tools observed in use by Turla Carbon and its variants were typically deployed as a second stage backdoor within targeted environments and we believe Kazuar may now hold a similar role for Turla operations.

*Table 1874. Table References*

Links
-------

<http://researchcenter.paloaltonetworks.com/2017/05/unit42-kazuar-multiplatform-espionage-backdoor-api-access/>

## Trick Bot

Many links indicate, that this bot is another product of the people previously involved in Dyreza. It seems to be rewritten from scratch – however, it contains many similar features and solutions to those we encountered analyzing Dyreza (read more).

Trick Bot is also known as:

- TrickBot
- TrickLoader

*Table 1875. Table References*

Links
<a href="https://blog.malwarebytes.com/threat-analysis/2016/10/trick-bot-dyrezas-successor/">https://blog.malwarebytes.com/threat-analysis/2016/10/trick-bot-dyrezas-successor/</a>
<a href="https://blog.fraudwatchinternational.com/malware/trickbot-malware-works">https://blog.fraudwatchinternational.com/malware/trickbot-malware-works</a>
<a href="https://securityintelligence.com/trickbot-is-hand-picking-private-banks-for-targets-with-redirection-attacks-in-tow/">https://securityintelligence.com/trickbot-is-hand-picking-private-banks-for-targets-with-redirection-attacks-in-tow/</a>

## Hackshit

Netskope Threat Research Labs recently discovered a Phishing-as-a-Service (PhaaS) platform named Hackshit, that records the credentials of the phished bait victims. The phished bait pages are packaged with base64 encoding and served from secure (HTTPS) websites with “.moe” top level domain (TLD) to evade traditional scanners. “.moe” TLD is intended for the purpose of ‘The marketing of products or services deemed’. The victim’s credentials are sent to the Hackshit PhaaS platform via websockets. The Netskope Active Platform can proactively protect customers by creating custom applications and a policy to block all the activities related to Hackshit PhaaS.

*Table 1876. Table References*

Links
<a href="https://resources.netskope.com/h/i/352356475-phishing-as-a-service-phishing-revamped">https://resources.netskope.com/h/i/352356475-phishing-as-a-service-phishing-revamped</a>

## Moneygram Adwind

*Table 1877. Table References*

Links
<a href="https://myonlinesecurity.co.uk/new-guidelines-from-moneygram-malspam-delivers-a-brand-new-java-adwind-version/">https://myonlinesecurity.co.uk/new-guidelines-from-moneygram-malspam-delivers-a-brand-new-java-adwind-version/</a>

# Banload

Banload has been around since the last decade. This malware generally arrives on a victim's system through a spam email containing an archived file or bundled software as an attachment. In a few cases, this malware may also be dropped by other malware or a drive-by download. When executed, Banload downloads other malware, often banking Trojans, on the victim's system to carry out further infections.

Table 1878. Table References

Links
<a href="https://researchcenter.paloaltonetworks.com/2016/03/banload-malware-affecting-brazil-exhibits-unusually-complex-infection-process/">https://researchcenter.paloaltonetworks.com/2016/03/banload-malware-affecting-brazil-exhibits-unusually-complex-infection-process/</a>
<a href="https://www.trendmicro.com/vinfo/us/threat-encyclopedia/malware/banload">https://www.trendmicro.com/vinfo/us/threat-encyclopedia/malware/banload</a>
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/banload-limits-targets-via-security-plugin/">http://blog.trendmicro.com/trendlabs-security-intelligence/banload-limits-targets-via-security-plugin/</a>
<a href="https://securingtomorrow.mcafee.com/mcafee-labs/banload-trojan-targets-brazilians-with-malware-downloads/">https://securingtomorrow.mcafee.com/mcafee-labs/banload-trojan-targets-brazilians-with-malware-downloads/</a>

# Smoke Loader

This small application is used to download other malware. What makes the bot interesting are various tricks that it uses for deception and self protection.

Smoke Loader is also known as:

- Dofoil

Table 1879. Table References

Links
<a href="https://blog.malwarebytes.com/threat-analysis/2016/08/smoke-loader-downloader-with-a-smokescreen-still-alive/">https://blog.malwarebytes.com/threat-analysis/2016/08/smoke-loader-downloader-with-a-smokescreen-still-alive/</a>

# LockPoS

The analyzed sample has a recent compilation date (2017-06-24) and is available on VirusTotal. It starts out by resolving several Windows functions using API hashing (CRC32 is used as the hashing function).

Table 1880. Table References

Links
<a href="https://www.arbornetworks.com/blog/asert/lockpos-joins-flock/">https://www.arbornetworks.com/blog/asert/lockpos-joins-flock/</a>

# Fadok

Win.Worm.Fadok drops several files. %AppData%\RAC\mls.exe or %AppData%\RAC\svcs.exe are instances of the malware which are auto-started when Windows starts. Further, the worm drops and opens a Word document. It connects to the domain wxanalytics[.]ru.

Fadok is also known as:

- Win32/Fadok

Table 1881. Table References

Links
<a href="https://www.microsoft.com/en-us/wdsi/threats/malware-encyclopedia-description?Name=Worm%3AWin32%2FFadok.A">https://www.microsoft.com/en-us/wdsi/threats/malware-encyclopedia-description?Name=Worm%3AWin32%2FFadok.A</a>
<a href="http://blog.talosintelligence.com/2017/06/threat-roundup-0602-0609.html">http://blog.talosintelligence.com/2017/06/threat-roundup-0602-0609.html</a>

# Loki Bot

Loki Bot is a commodity malware sold on underground sites which is designed to steal private data from infected machines, and then submit that info to a command and control host via HTTP POST. This private data includes stored passwords, login credential information from Web browsers, and a variety of cryptocurrency wallets.

Table 1882. Table References

Links
<a href="https://phishme.com/loki-bot-malware/">https://phishme.com/loki-bot-malware/</a>

# KONNI

Talos has discovered an unknown Remote Administration Tool that we believe has been in use for over 3 years. During this time it has managed to avoid scrutiny by the security community. The current version of the malware allows the operator to steal files, keystrokes, perform screenshots, and execute arbitrary code on the infected host. Talos has named this malware KONNI. Throughout the multiple campaigns observed over the last 3 years, the actor has used an email attachment as the initial infection vector. They then use additional social engineering to prompt the target to open a .scr file, display a decoy document to the users, and finally execute the malware on the victim's machine. The malware infrastructure of the analysed samples was hosted by a free web hosting provider: 000webhost. The malware has evolved over time. In this article, we will analyse this evolution:

Table 1883. Table References

Links
<a href="http://blog.talosintelligence.com/2017/05/konni-malware-under-radar-for-years.html">http://blog.talosintelligence.com/2017/05/konni-malware-under-radar-for-years.html</a>

# SpyDealer

Recently, Palo Alto Networks researchers discovered an advanced Android malware we've named "SpyDealer" which exfiltrates private data from more than 40 apps and steals sensitive messages from communication apps by abusing the Android accessibility service feature. SpyDealer uses exploits from a commercial rooting app to gain root privilege, which enables the subsequent data theft.

Table 1884. Table References

Links
<a href="https://researchcenter.paloaltonetworks.com/2017/07/unit42-spydealer-android-trojan-spying-40-apps/">https://researchcenter.paloaltonetworks.com/2017/07/unit42-spydealer-android-trojan-spying-40-apps/</a>

# CowerSnail

CowerSnail was compiled using Qt and linked with various libraries. This framework provides benefits such as cross-platform capability and transferability of the source code between different operating systems.

Table 1885. Table References

Links
<a href="https://securelist.com/cowersnail-from-the-creators-of-sambacry/79087/">https://securelist.com/cowersnail-from-the-creators-of-sambacry/79087/</a>

# Svpeng

In mid-July 2017, we found a new modification of the well-known mobile banking malware family Svpeng – Trojan-Banker.AndroidOS.Svpeng.ae. In this modification, the cybercriminals have added new functionality: it now also works as a keylogger, stealing entered text through the use of accessibility services.

Svpeng is also known as:

- trojan-banker.androidos.svpeng.ae

Table 1886. Table References

Links
<a href="https://securelist.com/a-new-era-in-mobile-banking-trojans/79198/">https://securelist.com/a-new-era-in-mobile-banking-trojans/79198/</a>

# TwoFace

While investigating a recent security incident, Unit 42 found a webshell that we believe was used by the threat actor to remotely access the network of a targeted Middle Eastern organization. The construction of the webshell was interesting by itself, as it was actually two separate webshells: an initial webshell that was responsible for saving and loading the second fully functional webshell. It is this second webshell that enabled the threat actor to run a variety of commands on the

compromised server. Due to these two layers, we use the name TwoFace to track this webshell. During our analysis, we extracted the commands executed by the TwoFace webshell from the server logs on the compromised server. Our analysis shows that the commands issued by the threat actor date back to June 2016; this suggests that the actor had access to this shell for almost an entire year. The commands issued show the actor was interested in gathering credentials from the compromised server using the Mimikatz tool. We also saw the attacker using the TwoFace webshell to move laterally through the network by copying itself and other webshells to other servers.

Table 1887. Table References

Links
<a href="https://researchcenter.paloaltonetworks.com/2017/07/unit42-twoface-webshell-persistent-access-point-lateral-movement/">https://researchcenter.paloaltonetworks.com/2017/07/unit42-twoface-webshell-persistent-access-point-lateral-movement/</a>

## IntrudingDivisor

Like TwoFace, the IntrudingDivisor webshell requires the threat actor to authenticate before issuing commands. To authenticate, the actor must provide two pieces of information, first an integer that is divisible by 5473 and a string whose MD5 hash is “9A26A0E7B88940DAA84FC4D5E6C61AD0”. Upon successful authentication, the webshell has a command handler that uses integers within the request to determine the command to execute - To complete

Table 1888. Table References

Links
<a href="https://researchcenter.paloaltonetworks.com/2017/07/unit42-twoface-webshell-persistent-access-point-lateral-movement/">https://researchcenter.paloaltonetworks.com/2017/07/unit42-twoface-webshell-persistent-access-point-lateral-movement/</a>

## JS\_POWMET

Attacks that use completely fileless malware are a rare occurrence, so we thought it important to discuss a new trojan known as JS\_POWMET (Detected by Trend Micro as JS\_POWMET.DE), which arrives via an autostart registry procedure. By utilizing a completely fileless infection chain, the malware will be more difficult to analyze using a sandbox, making it more difficult for anti-malware engineers to examine.

Table 1889. Table References

Links
<a href="http://blog.trendmicro.com/trendlabs-security-intelligence/look-js_powmet-completely-fileless-malware/">http://blog.trendmicro.com/trendlabs-security-intelligence/look-js_powmet-completely-fileless-malware/</a>

## EngineBox Malware

The main malware capabilities include a privilege escalation attempt using MS16-032 exploitation; a HTTP Proxy to intercept banking transactions; a backdoor to make it possible for the attacker to issue arbitrary remote commands and a C&C through a IRC channel. As it's being identified as a



Generic Trojan by most of VirusTotal (VT) engines, let's name it EngineBox— the core malware class I saw after reverse engineering it.

*Table 1890. Table References*

Links
<a href="https://isc.sans.edu/diary/22736">https://isc.sans.edu/diary/22736</a>

## Joao

Spread via hacked Aeria games offered on unofficial websites, the modular malware can download and install virtually any other malicious code on the victim's computer. To spread their malware, the attackers behind Joao have misused massively-multiplayer online role-playing games (MMORPGs) originally published by Aeria Games. At the time of writing this article, the Joao downloader was being distributed via the anime-themed MMORPG Grand Fantasia offered on [gf.ignitgames\[.\]to](http://gf.ignitgames[.]to).

*Table 1891. Table References*

Links
<a href="https://www.welivesecurity.com/2017/08/22/gamescom-2017-fun-blackhats/">https://www.welivesecurity.com/2017/08/22/gamescom-2017-fun-blackhats/</a>

## Fireball

Upon execution, Fireball installs a browser hijacker as well as any number of adware programs. Several different sources have linked different indicators of compromise (IOCs) and varied payloads, but a few details remain the same.

*Table 1892. Table References*

Links
<a href="https://www.cylance.com/en_us/blog/threat-spotlight-is-fireball-adware-or-malware.html">https://www.cylance.com/en_us/blog/threat-spotlight-is-fireball-adware-or-malware.html</a>

## ShadowPad

ShadowPad is a modular cyber-attack platform that attackers deploy in victim networks to gain flexible remote control capabilities. The platform is designed to run in two stages. The first stage is a shellcode that was embedded in a legitimate `nssock2.dll` used by Xshell, Xmanager and other software packages produced by NetSarang. This stage is responsible for connecting to “validation” command and control (C&C) servers and getting configuration information including the location of the real C&C server, which may be unique per victim. The second stage acts as an orchestrator for five main modules responsible for C&C communication, working with the DNS protocol, loading and injecting additional plugins into the memory of other processes.

*Table 1893. Table References*

Links
<a href="https://cdn.securelist.com/files/2017/08/ShadowPad_technical_description_PDF.pdf">https://cdn.securelist.com/files/2017/08/ShadowPad_technical_description_PDF.pdf</a>

## IoT\_reaper

IoT\_reaper is fairly large now and is actively expanding. For example, there are multiple C2s we are tracking, the most recently data (October 19) from just one C2 shows the number of unique active bot IP address is more than 10k per day. While at the same time, there are millions of potential vulnerable device IPs being queued into the c2 system waiting to be processed by an automatic loader that injects malicious code to the devices to expand the size of the botnet.

*Table 1894. Table References*

Links
<a href="http://blog.netlab.360.com/iot_reaper-a-rappid-spreading-new-iot-botnet-en/">http://blog.netlab.360.com/iot_reaper-a-rappid-spreading-new-iot-botnet-en/</a>

## FormBook

FormBook is a data stealer and form grabber that has been advertised in various hacking forums since early 2016.

*Table 1895. Table References*

Links
<a href="https://www.fireeye.com/blog/threat-research/2017/10/formbook-malware-distribution-campaigns.html">https://www.fireeye.com/blog/threat-research/2017/10/formbook-malware-distribution-campaigns.html</a>
<a href="https://www.arbornetworks.com/blog/asert/formidable-formbook-form-grabber/">https://www.arbornetworks.com/blog/asert/formidable-formbook-form-grabber/</a>

## Dimnie

Dimnie, the commonly agreed upon name for the binary dropped by the PowerShell script above, has been around for several years. Palo Alto Networks has observed samples dating back to early 2014 with identical command and control mechanisms. The malware family serves as a downloader and has a modular design encompassing various information stealing functionalities. Each module is injected into the memory of core Windows processes, further complicating analysis. During its lifespan, it appears to have undergone few changes and its stealthy command and control methods combined with a previously Russian focused target base has allowed it to fly under the radar up until this most recent campaign.

*Table 1896. Table References*

Links
<a href="https://researchcenter.paloaltonetworks.com/2017/03/unit42-dimnie-hiding-plain-sight/">https://researchcenter.paloaltonetworks.com/2017/03/unit42-dimnie-hiding-plain-sight/</a>