

MISP RESTSEARCH MODULE DEVELOPMENT

BUILDING A SIMPLE EXPORT MODULE FOR THE CORE

CIRCL / TEAM MISP PROJECT



13TH ENISA-EC3 WORKSHOP



MISP restSearch module development

2024-09-11

MISP RESTSEARCH MODULE DEVELOPMENT

BUILDING A SIMPLE EXPORT MODULE FOR THE CORE

CIRCL / TEAM MISP PROJECT



13TH ENISA-EC3 WORKSHOP



- Similar in scope to an **export module** of the MISP modules system
- Pros:
 - ▶ Can be used for composited data coming from a **filtered query**
 - ▶ Fast, **native approach**
 - ▶ Can be built to support **several scopes** (events, attributes, sightings)
- Cons...

2024-09-11

└ Building a native restSearch export

- Similar in scope to an **export module** of the MISP modules system
- Pros:
 - ▶ Can be used for composited data coming from a **filtered query**
 - ▶ Fast, **native approach**
 - ▶ Can be built to support **several scopes** (events, attributes, sightings)
- Cons...

BUILDING A NATIVE RESTSEARCH EXPORT

- Similar in scope to an **export module** of the MISP modules system
- Pros:
 - ▶ Can be used for composited data coming from a **filtered query**
 - ▶ Fast, **native approach**
 - ▶ Can be built to support **several scopes** (events, attributes, sightings)
- Cons...



MISP restSearch module development

2024-09-11

└ Building a native restSearch export

BUILDING A NATIVE RESTSEARCH EXPORT

- Similar in scope to an **export module** of the MISP modules system
- Pros:
 - ▶ Can be used for composited data coming from a **filtered query**
 - ▶ Fast, **native approach**
 - ▶ Can be built to support **several scopes** (events, attributes, sightings)
- Cons...



SO HOW DOES RESTSEARCH WORK?

- Standardised way of collecting **parameters**
- Using the parameters, a loop is started to **chunk and gradually build** our export data
- The chunk size depends on memory envelopes
- Each chunk is **converted piece by piece...**
- ... and subsequently are concatenated into a temporary file
- Once no more elements are left, the file is sent in the response

MISP restSearch module development

2024-09-11

└ So how does restSearch work?

- Standardised way of collecting parameters
- Using the parameters, a loop is started to **chunk and gradually build** our export data
 - The chunk size depends on memory envelopes
 - Each chunk is **converted piece by piece...**
 - ... and subsequently are concatenated into a temporary file
 - Once no more elements are left, the file is sent in the response

WHERE DOES THE MODULE SYSTEM COME INTO PLAY?

■ The export modules handle 5 tasks:

- ▶ Pass **meta-information** back to restSearch on the export format itself
- ▶ Add a **start segment** to the exported data
- ▶ Do the actual **conversion** from MISP's internal format to the desired export format
- ▶ Provide a **separator** for data chunks
- ▶ Have a **closing segment** for the returned data, based on the formats conventions

MISP restSearch module development

2024-09-11

└ Where does the module system come into play?

- The export modules handle 5 tasks:
 - ▶ Pass **meta-information** back to restSearch on the export format itself
 - ▶ Add a **start segment** to the exported data
 - ▶ Do the actual **conversion** from MISP's internal format to the desired export format
 - ▶ Provide a **separator** for data chunks
 - ▶ Have a **closing segment** for the returned data, based on the formats conventions

OUR LITTLE TRAINING MODULE: NIBBLER, THE EVER HUNGRY IDS/IPS



MISP restSearch module development

2024-09-11

└ Our little training module: Nibbler, the ever hungry IDS/IPS



- Simplistic tool with its **own proprietary format**
- Meant to mimic a typical **in-house tool**
- Lightweight scope, for simplicity's sake
- **pipe separated values**
- **VALUE | TYPE | DESCRIPTION | REFERENCE | ACTION**

2024-09-11

└ Nibbler

- Simplistic tool with its **own proprietary format**
- Meant to mimic a typical **in-house tool**
- Lightweight scope, for simplicity's sake
- **pipe separated values**
- **VALUE | TYPE | DESCRIPTION | REFERENCE | ACTION**

- Rules can be prepended by comments, each comment line starting with #
- Some characters have to be escaped in some custom, crazy ways
 - ▶ linebreaks: ##LINEBREAK##
 - ▶ commas: ##COMMA##
 - ▶ pipes: ##PIPE##

2024-09-11

└ Nibbler format - caveats

- Rules can be prepended by comments, each comment line starting with #
- Some characters have to be escaped in some custom, crazy ways
 - ▶ linebreaks: ##LINEBREAK##
 - ▶ commas: ##COMMA##
 - ▶ pipes: ##PIPE##

NIBBLER FORMAT

- **Value:** The actual indicator value
- **Type:** The format of the indicator
- **Description:** A quick description for analysts investigating the alert, why is this relevant
- **Reference:** A backreference that the analyst can use to find out more about the alert
- **Action:** What should Nibbler do if it trips over the value?

MISP restSearch module development

2024-09-11

└ Nibbler format

- **Value:** The actual indicator value
- **Type:** The format of the indicator
- **Description:** A quick description for analysts investigating the alert, why is this relevant
- **Reference:** A backreference that the analyst can use to find out more about the alert
- **Action:** What should Nibbler do if it trips over the value?

- IP
- Domain
- Hostname
- MD5
- SHA1
- SHA256
- Filename

2024-09-11

└ Supported types

- IP
- Domain
- Hostname
- MD5
- SHA1
- SHA256
- Filename

- ALERT - default behaviour, create an alert.
- BLOCK - block the action outright. Only set if the tag nibbler:block is present

2024-09-11

└ Supported values

- ALERT - default behaviour, create an alert.
- BLOCK - block the action outright. Only set if the tag nibbler:block is present

- Though we have types to map from MISP, in some cases several types map to a Nibbler type
- We've created a rough **mapping** (this is probably the most difficult task) in advance
- Some MISP types map to a Nibbler type directly
- **Composite** MISP types map to **2 Nibbler types** each

2024-09-11

└ Mapping the types to MISP

- Though we have types to map from MISP, in some cases several types map to a Nibbler type
- We've created a rough **mapping** (this is probably the most difficult task) in advance
- Some MISP types map to a Nibbler type directly
- **Composite** MISP types map to **2 Nibbler types** each

- ip-dst :: IP
- ip-src :: IP
- domain :: Domain
- domain|ip :: Domain, IP
- hostname :: Hostname
- md5 :: MD5
- sha1 :: SHA1
- sha256 :: SHA256
- filename|md5 :: Filename, MD5
- malware-sample :: Filename, MD5
- filename|sha1 :: Filename, SHA1
- filename|sha256 :: Filename, SHA256

2024-09-11

└ Mapping the types to MISP

- ip-dst :: IP
- ip-src :: IP
- domain :: Domain
- domain|ip :: Domain, IP
- hostname :: Hostname
- md5 :: MD5
- sha1 :: SHA1
- sha256 :: SHA256
- filename|md5 :: Filename, MD5
- malware-sample :: Filename, MD5
- filename|sha1 :: Filename, SHA1
- filename|sha256 :: Filename, SHA256

EXPORT MODULE SKELETON

```
<?php
class NibblerExport
{
    public $additional_params = array();
    public function handler(
        $data, $options = array()
    ) {}
    public function header(
        $options = array()
    ) {}
    public function footer() {}
    public function separator() {}
}
```

MISP restSearch module development

2024-09-11

└ Export module skeleton

EXPORT MODULE SKELETON

```
<?php
class NibblerExport
{
    public $additional_params = array();
    public function handler(
        $data, $options = array()
    ) {}
    public function header(
        $options = array()
    ) {}
    public function footer() {}
    public function separator() {}
}
```

```
public $additional_params = array(  
    'flatten' => 1  
);
```

2024-09-11

└ Additional parameters

```
public $additional_params = array(  
    'flatten' => 1  
);
```

ADDING OUR MAPPING

```
private $__mapping = array(  
    'ip-dst' => 'IP',  
    'ip-src' => 'IP',  
    'domain' => 'Domain',  
    'domain|ip' => ['Domain', 'IP'],  
    'hostname' => 'Hostname',  
    'md5' => 'MD5',  
    'sha1' => 'SHA1',  
    'sha256' => 'SHA256',  
    'filename|md5' => array('Filename', 'MD5'),  
    'malware-sample' => array('Filename', 'MD5'),  
    'filename|sha1' => array('Filename', 'SHA1'),  
    'filename|sha256' => array('Filename', 'SHA256')  
);
```

MISP restSearch module development

2024-09-11

└ Adding our mapping

```
private $__mapping = array(  
    'ip-dst' => 'IP',  
    'ip-src' => 'IP',  
    'domain' => 'Domain',  
    'domain|ip' => ['Domain', 'IP'],  
    'hostname' => 'Hostname',  
    'md5' => 'MD5',  
    'sha1' => 'SHA1',  
    'sha256' => 'SHA256',  
    'filename|md5' => array('filename', 'MD5'),  
    'malware-sample' => array('filename', 'MD5'),  
    'filename|sha1' => array('filename', 'SHA1'),  
    'filename|sha256' => array('filename', 'SHA256')  
);
```

```
public function header($options = array())
{
    return sprintf(
        "# Nibbler rules generated by MISP at %s\n",
        date('Y-m-d H:i:s')
    );
}
```

2024-09-11

└ Writing the start of the output

```
public function header($options = array())
{
    return sprintf(
        "# Nibbler rules generated by MISP at %s\n",
        date('Y-m-d H:i:s')
    );
}
```

```
public function footer()  
{  
    return "\n";  
}
```

2024-09-11

└ Footer function - how should the output end?

```
public function footer()  
{  
    return "\n";  
}
```

WHAT SEPARATES THE CHUNKS?

```
public function separator()  
{  
    return "\n";  
}
```

MISP restSearch module development

2024-09-11

└ What separates the chunks?

```
public function separator()  
{  
    return "\n";  
}
```

THE ACTUAL LEGWORK, THE HANDLER

```
public function handler($data, $options = array())
{
    if ($options['scope'] === 'Attribute') {
        $data['Attribute'][ 'AttributeTag' ] = $data['AttributeTag'];
        return $this->__convertAttribute($data['Attribute'], $data['Event']);
    }
    if ($options['scope'] === 'Event') {
        $result = array();
        foreach ($data['Attribute'] as $attribute) {
            $temp = $this->__convertAttribute($attribute, $data['Event']);
            if ($temp) $result[] = $temp;
        }
        return implode($this->separator(), $result);
    }
    return '';
}
```

MISP restSearch module development

2024-09-11

└ The actual legwork, the handler

```
public function handler($data, $options = array())
{
    if ($options['scope'] === 'Attribute') {
        $data['Attribute'][ 'AttributeTag' ] = $data['AttributeTag'];
        return $this->__convertAttribute($data['Attribute'], $data['Event']);
    }
    if ($options['scope'] === 'Event') {
        $result = array();
        foreach ($data['Attribute'] as $attribute) {
            $temp = $this->__convertAttribute($attribute, $data['Event']);
            if ($temp) $result[] = $temp;
        }
        return implode($this->separator(), $result);
    }
    return '';
}
```

BUILDING AN OPTIONAL INTERNAL CONVERTER FUNCTION

```
private function __convertAttribute($attribute, $eve
{
    if (empty($this->__mapping[$attribute['type']])) {
        // mapping not found - invalid type for nibbler
        return '';
    }
    if (is_array($this->__mapping[$attribute['type']])){
        // handle mappings for composites - slide
    } else {
        // handle simple mappings - slide
    }
    // return 1 or 2 lines, separated by separator()
    return implode($this->separator(), $result);
}
```

MISP restSearch module development

2024-09-11

└ Building an optional internal converter function

BUILDING AN OPTIONAL INTERNAL CONVERTER FUNCTION

```
private function __convertAttribute($attribute, $eve
{
    if (empty($this->__mapping[$attribute['type']])) {
        // mapping not found - invalid type for nibbler
        return '';
    }
    if (is_array($this->__mapping[$attribute['type']])){
        // handle mappings for composites - slide
    } else {
        // handle simple mappings - slide
    }
    // return 1 or 2 lines, separated by separator()
    return implode($this->separator(), $result);
}
```

```
$result[] = sprintf(  
    '%s|%s|%s|%s|%s',  
    $this->__escapeSpecialChars($attribute['value']),  
    $this->__mapping[$attribute['type']],  
    $event['uuid'],  
    $this->__escapeSpecialChars($event['info']),  
    'ALERT'  
);
```

2024-09-11

└ Handling the simple case

```
$result[] = sprintf(  
    '%s|%s|%s|%s',  
    $this->__escapeSpecialChars($attribute['value']),  
    $this->__mapping[$attribute['type']],  
    $event['uuid'],  
    $this->__escapeSpecialChars($event['info']),  
    'ALERT'  
);
```

HANDLING THE CASE FOR COMPOSITES

```
$attribute['value'] = explode(
    '|', $attribute['value']
);
foreach (array(0,1) as $part) {
    $result[] = sprintf(
        '%s|%s|%s|%s|%s',
        $this->__escapeSpecialChars(
            $attribute['value'][$part]
        ),
        $this->__mapping[$attribute['type']][$part],
        $event['uuid'],
        $this->__escapeSpecialChars($event['info']),
        'ALERT'
    );
}
```

MISP restSearch module development

2024-09-11

└ Handling the case for composites

HANDLING THE CASE FOR COMPOSITES

```
$attribute['value'] = explode(
    '|', $attribute['value']
);
foreach (array(0,1) as $part) {
    $result[] = sprintf(
        '%s|%s|%s|%s|%s',
        $this->__escapeSpecialChars(
            $attribute['value'][$part]
        ),
        $this->__mapping[$attribute['type']][$part],
        $event['uuid'],
        $this->__escapeSpecialChars($event['info']),
        'ALERT'
    );
}
```

PUTTING IT TOGETHER

```

private function __convertAttribute($attribute, $event) {
    if (empty($this->__mapping[$attribute['type']])) return '';
    $result = array();
    $attributes = array();
    if (is_array($this->__mapping[$attribute['type']]))) {
        $attribute['value'] = explode(' ', $attribute['value']);
        foreach (array(0,1) as $part) {
            $result[] = sprintf(
                '%s|%s|%s|%s',
                $this->__escapeSpecialChars($attribute['value'][$part]),
                $this->__mapping[$attribute['type']][$part],
                '/events/view/ . ' . $event['uuid'],
                $this->__escapeSpecialChars($event['info']),
                $this->__decideOnAction($attribute['AttributeTag'])
            );
        }
    } else {
        $result[] = sprintf(
            '%s|%s|%s|%s',
            $this->__escapeSpecialChars($attribute['value']),
            $this->__mapping[$attribute['type']],
            '/events/view/ . ' . $event['uuid'],
            $this->__escapeSpecialChars($event['info']),
            $this->__decideOnAction($attribute['AttributeTag'])
        );
    }
    return implode($this->separator(), $result);
}

```

MISP restSearch module development

2024-09-11

└ Putting it together

```

private function __convertAttribute($attribute, $event) {
    if (empty($this->__mapping[$attribute['type']])) return '';
    $result = array();
    $attributes = array();
    if (is_array($this->__mapping[$attribute['type']]))) {
        $attribute['value'] = explode(' ', $attribute['value']);
        foreach ($attribute['value'] as $part) {
            $result[] = sprintf(
                '%s|%s|%s|%s',
                $this->__escapeSpecialChars($attribute['value'][$part]),
                $this->__mapping[$attribute['type']][$part],
                '/events/view/ . ' . $event['uuid'],
                $this->__escapeSpecialChars($event['info']),
                $this->__decideOnAction($attribute['AttributeTag'])
            );
        }
    } else {
        $result[] = sprintf(
            '%s|%s|%s|%s',
            $this->__escapeSpecialChars($attribute['value']),
            $this->__mapping[$attribute['type']],
            '/events/view/ . ' . $event['uuid'],
            $this->__escapeSpecialChars($event['info']),
            $this->__decideOnAction($attribute['AttributeTag'])
        );
    }
    return implode($this->separator(), $result);
}

```

ADDING THE FUNCTION THAT DECIDES ON THE ACTION

```
private function __decideOnAction($attributeTags)
{
    foreach($attributeTags as $attributeTag) {
        if (
            $attributeTag['Tag'][ 'name' ] ===
            'nibbler:block'
        ) {
            return 'BLOCK';
        }
    }
    return 'ALERT';
}
```

MISP restSearch module development

2024-09-11

└ Adding the function that decides on the action

```
private function __decideOnAction($attributeTags)
{
    foreach($attributeTags as $attributeTag) {
        if (
            $attributeTag['Tag'][ 'name' ] ===
            'nibbler:block'
        ) {
            return 'BLOCK';
        }
    }
    return 'ALERT';
}
```

ADDING THE FUNCTION THAT DECIDES ON THE ACTION

FINALISING THE EXPORT MODULE... THE ESCAPING FUNCTION

```
private function __escapeSpecialChars($value)
{
    $value = preg_replace(
        "/\r|\n/", "##LINEBREAK##", $value
    );
    $value = preg_replace(
        "/ , /", "##COMMA##", $value
    );
    $value = preg_replace(
        "/ \| /", "##PIPE##", $value
    );
    return $value;
}
```

MISP restSearch module development

2024-09-11

└ Finalising the export module... The escaping function

FINALISING THE EXPORT MODULE... THE ESCAPING FUNCTION

```
private function __escapeSpecialChars($value)
{
    $value = preg_replace(
        "/\r|\n/", "##LINEBREAK##", $value
    );
    $value = preg_replace(
        "/ , /", "##COMMA##", $value
    );
    $value = preg_replace(
        "/ \| /", "##PIPE##", $value
    );
    return $value;
}
```

MODIFYING THE MISP CORE TO KNOW ABOUT THE EXPORT MODULE

- The **models** that we are targeting by scope (Event, Attribute) need to be updated
- They are located in **/var/www/MISP/app/Model/**
- The global variable **\$validFormats** houses all mappings
- Simply add a new line such as the following:
'nibbler' => array('nibbler', 'NibblerExport', 'nibbler')

MISP restSearch module development

2024-09-11

- └ Modifying the MISP core to know about the export module

- The **models** that we are targeting by scope (Event, Attribute) need to be updated
- They are located in **/var/www/MISP/app/Model/**
- The global variable **\$validFormats** houses all mappings
- Simply add a new line such as the following:
'nibbler' => array('nibbler', 'NibblerExport', 'nibbler')

MODIFYING THE MISP CORE TO KNOW ABOUT THE EXPORT MODULE

LET US TEST THE MODULE!

- Use the **rest client** to test it conveniently
- Both the event and attribute level restSearch function should work
- Simply set the **returnFormat** to nibbler, which should also show up as a valid export format

MISP restSearch module development

2024-09-11

└ Let us test the module!

- Use the **rest client** to test it conveniently
- Both the event and attribute level restSearch function should work
- Simply set the **returnFormat** to nibbler, which should also show up as a valid export format

REST CLIENT

HTTP method to use
POST

Relative path to query
/events/restSearch

Use full path - disclose my apikey Bookmark query
 Show result Skip SSL validation

HTTP headers
Authorization: ArSxnHf20foSapnOSyxfrljMdl9oLDnvmqvHK97q
Accept: application/json
Content-Type: application/json

HTTP body

```
{  
    "returnFormat": "nibbler",  
    "page": 1,  
    "limit": 4,  
    "type": ["ip-dst", "ip-src", "domain|ip", "hostname", "domain"]  
}
```

Run query

MISP restSearch module development

2024-09-11

└ REST client

REST CLIENT

HTTP method to use
POST

Relative path to query
/events/restSearch

Use full path - disclose my apikey Bookmark query
 Skip SSL validation

HTTP headers
Authorization: ArSxnHf20foSapnOSyxfrljMdl9oLDnvmqvHK97q
Accept: application/json
Content-Type: application/json

HTTP body
{"returnFormat": "nibbler", "page": 1, "limit": 4, "type": ["ip-dst", "ip-src", "domain|ip", "hostname", "domain"]}

Run query